

SYNTHETIC TEST FIXTURE. This document is original test data created for the bg-spec MCP server. It is not a Berlin Group publication and has no normative value.

## 1 Introduction

This document describes the account information interface of the synthetic Open Finance Framework version 2. Version 2 extends version 1.3 and keeps the version 1.3 interface available for existing TPPs.

## 2 Conventions

The key words MUST, MUST NOT, SHALL, SHALL NOT, SHOULD and MAY are to be interpreted as normative requirement levels. Statements without these key words are informative.

## 4.2 Read Transaction List

Call GET /accounts/{accountId}/transactions reads the transaction list of an addressed account.

The query parameter bookingStatus is mandatory. The ASPSP SHALL support the values booked, pending and both. The ASPSP MAY support the values information and all. If the value information is used, the ASPSP SHALL return standing order information instead of transactions.

The query parameter dateFrom is mandatory unless deltaList is used. The ASPSP SHALL reject a request without dateFrom with HTTP status 400 and error code FORMAT\_ERROR.

The ASPSP SHALL support the pagination of transaction lists. The TPP MAY limit the page size with the query parameter pageSize. The ASPSP SHALL return a link next when more entries exist.

The ASPSP SHALL return HTTP status 429 with error code ACCESS\_EXCEEDED when the access frequency limit of the consent is exceeded.

Each returned transaction MUST contain transactionAmount and bookingDate. The bookingDate is returned as date-time in version 2.



#### 4.3 Read Transaction Details

Call GET /accounts/{accountId}/transactions/{transactionId} reads the details of one transaction. The ASPSP SHALL return HTTP status 404 if the transactionId is unknown.

#### 4.4 Read Balance

Call GET /accounts/{accountId}/balances reads the balances of an account. The ASPSP SHALL return at least one balance of type closingBooked or interimAvailable.

## 5 Error Codes

FORMAT\_ERROR (400): the request does not match the syntax of the interface.

PERIOD\_INVALID (400): the requested period is outside the supported range.

CONSENT\_INVALID (401): the consent was created but is not valid for the addressed service.

ACCESS\_EXCEEDED (429): the access frequency limit of the consent is exceeded.