



openFinance API Framework Implementation Guidelines

Protocol Functions and Security Measures

Version 2.4.1

31 July 2026

Berlin Group License Notice

Berlin Group Specifications are published by the Berlin Group under the following license conditions:

- “Creative Commons Attribution-NoDerivatives 4.0 International Public License”



- This means that the Specification can be copied and redistributed in any medium or format for any purpose, even commercially, and when shared, that appropriate credit must be given, a link to the license must be provided, and indicated if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use. In addition, if you remix, transform, or build upon the Specification, you may not distribute the modified Specification.
- Any OpenAPI files offered by Berlin Group are bound by “Creative Commons Attribution 4.0 International Public License” and are allowed to be changed. However, please note that the normative reference still is the Implementation Guidelines document.
- Implementation of certain elements of this Specification may require licenses under third party intellectual property rights, including without limitation, patent rights. The Berlin Group or any contributor to the Specification is not, and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.
- Any right, title and interest in and to the copyright and all related rights in topic-related Scheme Rulebooks, belong to the respective Scheme Manager (amongst others, the European Payments Council AISBL - EPC).
- The Specification, including technical data, may be subject to export or import regulations in different countries. Any user of the Specification agrees to comply strictly with all such regulations and acknowledges that it has the responsibility to obtain licenses to export, re-export, or import (parts of) the Specification.

Contents

1	Introduction.....	1
1.1	From Core XS2A Interface to openFinance API	1
1.2	Protocol Functions supported by XS2A and openFinance API	3
1.3	Security Measures supported by XS2A and openFinance API	3
1.4	Document Structure.....	3
1.5	Document History	5
2	Character Sets and Notations.....	9
2.1	Character Set and Data Types	9
2.2	Notation.....	10
2.2.3	Notations used for Requests as well as Responses	11
2.2.4	Base64 Notations.....	12
2.2.5	Notion of a Transaction	13
2.2.6	Notion of a Transaction Resource and Service Resource ..	13
2.2.7	Notion of a Transaction Resource Variant.....	14
2.2.8	Notation for Access Methods	15
3	REST API Approach: Guiding Principles	17
3.1	Location of Message Parameters	17
3.2	API Structure	18
3.3	API Versioning.....	20
3.4	API Access Methods of Change Transaction Resource Requests.	20
3.5	API Request Header Parameter	22
3.5.1	Transaction Initiation Request Headers.....	23
3.5.2	Service Resource Creation Request Headers	23
3.5.3	Change Transaction Resource Request Headers	24
3.5.4	Client Brand Information Header	24
3.5.5	Signature related headers	25
3.5.6	Technical headers.....	25
3.6	Header Parameters for Idempotency	25
3.7	API Steering Process by Hyperlinks (HATEOAS)	26
3.8	Links in dedicated Responses	29

3.8.1	Links in Transaction Initiation and Change Transaction Resource Responses.....	29
3.8.2	Links in Service Resource Creation Response.....	31
3.9	HTTP Response Codes.....	31
3.10	Multi-channel access, Multi-API-Client access, Retrieval of Resources to be authorised, and Access Conflicts	34
3.11	Addressing resource variants during a Change Transaction Resource Process	35
3.11.1	Addressing resource variants via the If-Match Header	35
3.11.2	Retrieval of the changed version of a resource using the inChange query parameter.....	37
3.11.3	Withdrawal of Transaction Resource Changes that are not approved yet	40
3.11.4	General flow for addressing resource variants	40
3.12	Data Extensions by the ASPSP	41
3.13	Multicurrency Accounts	42
3.14	Interval Borders Including Rules.....	42
4	Error Handling	43
4.1	Responses in Error Cases.....	43
4.1.1	Header	43
4.1.2	Body	43
4.2	Additional Error Information	43
4.2.1	openFinance API Framework Specific Solution.....	44
4.2.2	Standardised Additional Error Information.....	45
5	Authentication of API Client and ASPSP at transport layer	48
5.1	TLS-secured connection established by API Client.....	48
5.2	TLS-secured connection established by ASPSP	49
5.3	Certificate Requirements on Redirect URIs	50
6	Signing HTTP request messages at the application level	51
6.1	Certificates to be used.....	51
6.2	Signing HTTP messages based on [RFC7515]	52
6.2.1	Extensions to the HTTP message	52
6.2.2	Building the extensions	53

6.2.3	Example.....	59
7	Security measures for securing (parts of) the message body	65
7.1	Signing the body.....	65
7.1.1	Variants for sending signature related data	66
7.1.2	Signature Profiles supported for signing the request body..	66
7.1.3	Explicit Authorisation Process (as defined in section 9).....	68
	Note: Above the JWS protected header is shown in pretty format. In the above example it is used without breaks and extra spaces.....	74
7.1.4	Signing the body using JAdES_JS	74
7.1.5	Signing the body using XAdES.....	78
7.1.6	Signing the body using EMV_AC	78
7.1.7	Signing the body using EUDIW	78
7.2	Encryption of (parts of) the body.....	78
7.2.1	Overview	79
7.2.2	Extension to the http message	80
7.2.3	How to build a JWE.....	82
7.2.4	JWE Example	85
7.2.5	How to build an EncryptedBody or EncryptedElementTag element.....	88
7.2.6	Exchange of certificates with public encryption keys	90
8	Strong customer authentication of a PSU	93
8.1	Optional Usage of OAuth2 for PSU Authentication or Authorisation	93
8.2	Header Parameter for PSU Context Data	94
8.3	Header Parameters for PSU Identification Data.....	96
8.4	Header Parameters for strong customer authentication	97
8.4.1	Request Header Parameters Steering SCA Approaches ...	97
8.4.2	Related Response Headers	99
8.5	Embedded SCA Approach.....	99
8.6	Decoupled SCA Approach.....	99
8.7	Redirect SCA Approach	100
8.8	OAuth SCA Approach.....	100

8.8.1	Authorization Request.....	101
8.8.2	Authorization Response	103
8.8.3	Access Token Request	104
8.8.4	Access Token Response.....	105
8.8.5	Refresh Token Grant Type.....	106
8.8.6	API Requests	106
8.9	ASPSP Channel SCA Approach.....	106
8.10	Signature SCA Approach.....	107
9	Authorisation Processes used commonly in all Services.....	108
9.1	Authorisation Endpoints.....	108
9.2	Transaction Cancellation Endpoints e.g. for Payments.....	111
9.3	Access Methods for Authorisations.....	112
9.4	Start Authorisation Process	115
9.4.1	Update PSU Data	128
9.4.2	Update PSU Data (Identification)	129
9.4.3	Update PSU Data (Authentication) in the Decoupled or Embedded Approach	133
9.4.4	Update PSU Data (Select Authentication Method)	140
9.5	Transaction Authorisation	147
9.6	GET Authorisation Sub-Resources Request.....	151
9.7	GET Authorisation Status Request.....	153
9.8	Confirmation Request Procedure.....	156
9.8.1	Confirmation Request Flow Examples for Payment Initiation	157
9.8.2	Retrieving the Confirmation Code in Redirect SCA approach	159
9.8.3	Confirmation Request Message Pre-Condition.....	162
9.8.4	Authorisation Confirmation Request Message.....	162
9.9	Update Resource with Debtor Account.....	166
9.10	Cancel an Authorisation Sub-resource Request	170
10	Payment Formats	173
10.1	Single Credit Transfers for Core PIS, RTP and Extended PIS	174
10.2	Repository for Single Credit Transfer and RTP	178



10.3	Bulk Credit Transfers	181
10.4	Multi Bulk Credit Transfers	183
10.5	RTP Bulk	183
10.6	Single SEPA Direct Debits	184
10.7	SEPA Direct Debit Bulk	187
10.8	SEPA Direct Debit Multi Bulk	189
11	Signing Baskets	190
11.1	Access Methods for Signing Baskets	190
11.2	Establish Signing Basket Request	190
11.3	Get Signing Basket Request	194
11.4	Get Signing Basket Status Request	196
11.5	Cancellation of Signing Baskets	198
12	Resource Status Notification	200
12.1	API Access Methods	200
12.2	HTTP Response Codes for Notifications	201
12.3	Implicit Subscription for Resource Status Notification	201
12.4	Communicate Notification URI of API Clients to the ASPSP	202
12.5	Resource Status Notification Message Flow	205
12.6	Push Resource Status with JSON encoding	205
13	Annex	210
13.1	List of tables	210
13.2	References	210
13.2.1	Documents of the NextGenPSD2 XS2A Framework	210
13.2.2	Documents of the openFinance API Framework	210
13.2.3	Further documents	211
13.3	Detailed Change Log	213
13.3.1	Changes from Version 2.0 to 2.1	213
13.3.2	Changes from Version 2.1 to 2.2	216
13.3.3	Changes from Version 2.2 to 2.3	217
13.3.4	Changes from Version 2.3 to 2.4	218
13.3.5	Changes from Version 2.4 to 2.4.1	223

1 Introduction

1.1 From Core XS2A Interface to openFinance API

With [PSD2] the European Union has published a directive on payment services in the internal market. Among others [PSD2] contains regulations on services to be operated by so-called Third Party Payment Service Providers (TPP) on behalf of a Payment Service User (PSU). These services are

- Payment Initiation Service (PIS) to be operated by a Payment Initiation Service Provider (PISP) TPP as defined by article 66 of [PSD2],
- Account Information Service (AIS) to be operated by an Account Information Service Provider (AISP) TPP as defined by article 67 of [PSD2], and
- Confirmation on the Availability of Funds Service (FCS) to be used by a Payment Instrument Issuing Service Provider (PIISP) TPP as defined by article 65 of [PSD2].

To implement these services (subject to PSU consent) a TPP needs to access the account of the PSU. The account is managed by another PSP called the Account Servicing Payment Service Provider (ASPSP). To support the TPP in accessing the accounts managed by an ASPSP, each ASPSP has to provide an "access to account interface" (XS2A interface). Such an interface has been defined in the Berlin Group NextGenPSD2 XS2A Framework.

This XS2A Framework now has been opened up to extended services. This interface is addressed in the following as **openFinance API**. This openFinance API differs from the XS2A interface in several dimensions:

- The extended services might not rely anymore solely on PSD2.
- Other important regulatory frameworks which apply are e.g. GDPR.
- The openFinance API can address different types of **API Clients** as access clients, e.g. TPPs regulated by an NCA according to PSD2, or corporates not regulated by an NCA.
- The extended services might require contracts between the access client and the ASPSP.
- While the client identification at the openFinance API can still be based on eIDAS certificates, they do not need to be necessarily PSD2 compliant eIDAS certificates.
- The extended services might require e.g. the direct involvement of the access client's bank for KYC processes.



Note: The notions of API Client and ASPSP are used because of the technical standardisation perspective of the openFinance API. These terms are analogous to "asset broker" and "asset holder" resp. in the work of the ERPB on a SEPA API access scheme.

Note: In implementations, the API services of several ASPSPs might be provided on an aggregation platform. Such platforms will be addressed in the openFinance API Framework as "API provider".

Note: At some places, the openFinance API Framework is still using the technical TPP notion also for the openFinance APIs, e.g. in redirection related header parameters. In this context, the TPP is not necessarily a licensed TPP as mentioned above, but for certain services may just be any "third party provider".

The following account access methods are covered by this framework:




Figure 1: Core XS2A interface and openFinance API

The ASPSP may restrict the access to the services offered at its openFinance API and require dedicated onboarding. The requirements for the rights to access to services offered at the openFinance API are out of scope of this document. These requirements are in detail in [oFA-IG-Adm].

In contrast to the services of the openFinance API the ASPSP has to offer access to the services of his core XS2A API to any TPP without any discrimination as long as the TPP has got the necessary licence to access a service as a PISP, AISP or PIISP from an NCA according to the regulations of [PSD2].

1.2 Protocol Functions supported by XS2A and openFinance API

The addressed services within the XS2A API and the openFinance API share many protocol functions. Such functions are defined in this Framework document and cover e.g.

- dynamic protocol steering by hyperlinks,
- how to address transaction authorisation resource,
- how to push resource status changes to API clients or
- how to handle protocol preferences of the API Clients.

Such generic protocol functions are explained only within this document. Service specifications using these functions then just refer to this openFinance API Framework documentation for better readability. For better readability, the document refers in most parts to the openFinance API Framework only instead of addressing both, the XS2A API and the openFinance API. Where needed, the two APIs are addressed separately.

1.3 Security Measures supported by XS2A and openFinance API

Specific API protocol functions are security measures to be supported by an API. XS2A and openFinance API according to the specifications of the Berlin Group support different security measures and approaches for the authentication of a PSU. Examples are the authentication of an API Client either at the transport level or the support of different approaches for the execution of a strong customer authentication of a PSU.

Some of these security measures and approaches for PSU authentication have to be supported by an API mandatorily, for other the support is an option for the ASPSP. In any case an API Client has to secure his access to an XS2A or openFinance API by a security measure or has to use a special approach for PSU authentication if requested by an ASPSP.

This document describes how different security measures and approaches for PSU authentication are supported by an XS2A or openFinance API. For each it is defined if the support at an XS2A API and/or at an openFinance API is mandatory (i.e. has to be supported by each ASPSP) or optional (i.e. the ASPSP can decide to support it or not). If special restrictions for values, parameters, variants, etc. for the support of a security measure exist, these are also described.

Please notice that this document contains only the specification of how security measures are supported by an API, but not the specification of the security measures itself.

1.4 Document Structure

This document specifies the Protocol Functions and Security Measures supported by an XS2A or openFinance API (if based on one of the Berlin Group specifications) in detail. It has to be considered in combination with any other Implementation Guidelines published by the Berlin




Group. A more abstract overview on these topics is given by the basic operational rules of the framework, cf. [oFA-OR-FW]. This document defines the following building bricks:

- Character sets and primitive data types supported by all services in Section 2.1
- Notations used within all services definitions and in the openFinance API Framework documentation in Section 2.2
- REST API principles within the openFinance API Framework in Section 3
- Error handling in Section 4
- Authentication of API Clients and ASPSP at transport layer in Section 5
- Signing messages on application layer in Section 6
- Signing message bodies in Section 7.1
- Encryption of message bodies in Section 7.2
- SCA Approaches supported in Section 8
- Authorisation processes supported in Section 9
- Introduction of the different payment formats and definition for SEPA and cross-border payment products supported in Section 10
- Signing basket function to group transactions for authorisation in Section 11
- Resource status notification function (formerly called Lean Push Service) in Section 12



This document fits into the overall structure of the documentation as follows:



1.5 Document History

Version	Change/Note	Approved
Version 2.0	Initial Version of the openFinance API Framework documentation.	2023-10-5 openFinance TF
Version 2.1	Enhancing the Framework by the SCA approach "ASPSP-Channels" when using asynchronous SCA procedures via e.g. the ASPSP online channels. Renaming some authorisation related HTTP headers to prepare the API Framework for direct access for corporates. Extending the embedded and decoupled SCA approach by an option to add the debtor account during the authorisation process, via an account selection process. Extending message signing routines by headers protecting the resources addressed.	

Version	Change/Note	Approved
	Errata and clarifications. Details are covered in the Annex of this document.	
Version 2.2	MaxXLength data structures have been clarified to have a minimum length of one character (in compliance with ISO20022). Improving the structure of the guidelines by introducing two different natures of services, one of which is related to transactions and the other is related to the creation of service resources. In more details, the description of a service resource, the header parameters of a service resource creation request and the links of the response of the service resource creation are correspondingly added. The header Client Brand Logging Information is restricted to Max140Text. The requirement not to restrict redirect URIs to TPP domains protected by the QWAC has been detailed. Some new features have been added to support the integration of a Verification of payee function into payment initiation APIs. The examples for signing messages is completely reworked in Section 6.2.3 New OAuth scope key words for document services and user management services have been added. Further detailed information is covered in the Annex in Section 13.3.2 of this document.	

Version	Change/Note	Approved
Version 2.3	Revision of Section 7.1 on signing the body of a message. Due to the fundamentally different approach of the process of signing the body (with JAdES_JS) that is now specified in detail, the specifications do no longer support the signing process relying on the signature profile XAdES that was included in this standard beforehand. Added a new section 10 on payment formats to be used by payment initiation services, where the different payment formats are introduced and SEPA and cross-border payment products are defined. Further detailed information is covered in the Annex in Section 13.3.3 of this document.	31 October 2025 openFinance TF
Version 2.4	Revision on the integration of the signature SCA approach in the framework for a better understanding. Improving the structure of the guidelines by introducing a new type and functionality of services, Change Transaction Resource Requests. These allow to update already authorised resources. The inclusion in the specification induces the usage of ETags and other technicalities to address the changed resource variants. Further and detailed information on the changes are covered in the Annex in Section 13.3.4 of this document.	19 March 2026 openFinance Taskforce

Version	Change/Note	Approved
Version 2.4.1	Full editorial revision of Sections 6 and 7 for clarification. Fixing errata. Further and detailed information on the changes are covered in the Annex in Section 13.3.4 of this document.	openFinance TF, 2026-07-07



2 Character Sets and Notations

This section introduces character sets and notations used throughout the openFinance API Framework.

2.1 Character Set and Data Types

HTTP body parameters

The character set within the openFinance API Framework for parameters transported in HTTP bodies is UTF 8 encoded. This specification is only using the basic data elements "String", "Boolean", "ISODateTime", "ISODate", "UUID", "Integer" (with a byte length of 32 bits), "Decimal Number" (with 18 total digits and 17 fraction digits) and ISO based code lists. For codes defined by ISO, a reference to the corresponding ISO standard is given on service specification or data dictionary level.

Max35Text, Max70Text, Max140Text, Max500Text, Max1000Text, Max2000Text are defining strings with a minimum of one and a maximum length of 35, 70, 140, 500, 1000 and 2000 characters respectively. Further lengths might also be used analogously.

ASPSPs will accept for strings at least the following character set:

a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
/ - ? : () . , ' +
Space

ASPSPs may accept further character sets for text fields like names, addresses, text. Corresponding information will be contained in the ASPSP documentation of the related service. ASPSPs might convert certain special characters of these further character sets, before forwarding e.g. submitted payment data.

For the usage of versions of UUIDs the following applies:

- for UUIDs generated by the server, no restrictions are defined in the framework,
- for UUIDs used on Header level (e.g. X-Request-Id), version 7 of UUIDs should be used, **RFU**: This will be mandated in a later version of the Framework.
- for UUIDs on body level, related payment schemes or API access schemes requirements apply.

Complex data types and code lists are defined in the data dictionary [oFA-DaD] or in related service specifications.

HTTP query and header parameters

Encoding follows the HTTP specification. Specific additions might be provided for HTTP parameters introduced specifically by this specification.

2.2 Notation

2.2.1 Notation for Requests

For API request calls, query parameters, HTTP header parameters and body content parameters are specified within this openFinance API Framework as follows:

Attribute	Type	Condition	Description
attribute tag	type of attribute	condition	description of the semantic of the attribute and further conditions.
<i><reference to attribute tags></i>		mandatory	In service specific implementation guidelines, some data models or formats may be included implicitly by referring to the data model. Then the reference is given in the table. This could lead to the inclusion of potentially multiple attributes which shall be used according to the condition specified in the reference.

The "Type" is referring to either basic or complex data types as introduced in Section 2.1.

The following conditions may be used when describing data to be submitted by the client:

- Optional: The attribute is supported by the server, usage is optional for the client. The server may ignore the parameter if mentioned in the "Description" column of the table above.
- Conditional: The attribute is supported by the server and might be mandated by
 - the server provider in its own documentation of the support of the related API or
 - by certain rules as defined in the "Description" column of the table above.
- Mandatory: The attribute is supported by the server and shall be used by the client.
- Optional if supported by API provider: It is optional for the server to support this attribute. If the server is supporting the attribute as indicated in its own documentation of the related service, it might be used by the client optionally. If the

server is not supporting the attribute, then the request is rejected when it is contained.

Remark: Please note that the conditions “Optional if supported by API provider” is used rarely in the openFinance API Framework.

2.2.2 Notation for Responses

For API call responses, parameters, HTTP header parameters and body content parameters are specified within the openFinance API Framework as follows:

Attribute	Type	Condition	Description
attribute tag	type of attribute	condition	description of the semantic of the attribute and further conditions.
<i><reference to attribute tags></i>		mandatory	In service specific implementation guidelines, some data models or formats may be included implicitly by referring to the data model. Then the reference is given in the table. This could lead to the inclusion of potentially multiple attributes which shall be used according to the condition specified in the reference.

The "Type" is referring to either basic or complex data types as introduced in Section 2.1.

The following conditions can be set on data to be provided by the server:

- Optional: The attribute is supported optionally by the server
- Conditional: The attribute is supported by the server under certain conditions as indicated in the “Description” column of the table above.
- Mandatory: The attribute is always supported by the server.

2.2.3 Notations used for Requests as well as Responses

The following additional conditions apply to both, requests from the client to the server as well as responses from the server to the client:

Attribute	Type	Condition	Description
		{Or	
		Or	

Attribute	Type	Condition	Description
		Or}	
		{Or – Optional	
		Or – Optional	
		Or – Optional}	

- {Or: The **first** element in a sequence of elements of which **exactly one** has to be included.
- Or: An element in a sequence of elements of which **exactly one** has to be included. The element is **neither the first nor the last** within this sequence.
- Or}: The **last** element in a sequence of elements of which **exactly one** has to be included.
- {Or – Optional: The **first** element in a sequence of elements of which **at most one** may be included.
- Or – Optional: An element in a sequence of elements of which **at most one** may be included. The element is **neither the first nor the last** within this sequence.
- Or – Optional}: The **last** element in a sequence of elements of which **at most one** may be included.

Note: Specifications for the openFinance API are accompanied by an openAPI interface description (as a yaml file). Within these openAPI descriptions, elements with conditions "{Or", "Or", "Or}", "{Or – Optional", "Or – Optional", "Or – Optional}" will be treated as (pure) optional elements at the moment. It is the responsibility of the implementer to ensure the additional checks.

2.2.4 Base64 Notations

Base64 encoding:

Base64 encoding according to [RFC4648].

Base64url encoding:

According to [RFC7515] base64 encoding using the URL- and filename-safe character set defined in Section 5 of [RFC4648], with all trailing '=' characters omitted (as

permitted by Section 3.2) and without the inclusion of any line breaks, whitespace, or other additional characters. Note that the base64url encoding of the empty octet sequence is the empty string. (See Appendix C of [RFC7515] for notes on implementing base64url encoding without padding.)

2.2.5 Notion of a Transaction

Transaction is used in two different contexts within this document respectively the openFinance API Framework:

- "Transaction" as meta description of a complex service interaction with the API to simplify the definitions in this document:
 - The notion of a transaction subsumes service interactions like payment initiation, consents for API interaction, subscriptions or signing baskets.
 - Such transactions are started by the API Client with a related initiation request, called throughout this document "Transaction Initiation Request", e.g. a
 - Payment Initiation Request,
 - Establish Consent Request,
 - Establish Signing Basket Request, or
 - Initiate Subscription Request.
 - The response to these initiations by the ASPSP is called "Transaction Initiation Response" throughout this document.
 - Transactions normally need to be authorised by the PSU by applying a Strong Customer Authentication (SCA).
 - Where transaction data is posted to the API, a related resource is created.
- Transaction as a banking transaction on an account:
 - Entries on an account are also addressed as transactions.

2.2.6 Notion of a Transaction Resource and Service Resource

Most of the technical POST requests supported in this API framework will lead to a generation of a resource with a related resource identification, which enables the API Client to address



the related object later on. This resource identification is called "resourceId" when specifying abstract service calls in this text, even if the actual attribute in the related service is called differently (e.g. paymentId for payment initiations). A prominent POST request is the Transaction Initiation Request defined above, where the object stored in the addressed so called "Transaction Resource" is part of a complex interaction with the API.

In some cases, a resource is created, but only some restricted API interaction features are supported for this resource like the push resource status function. Such a resource is called "Service Resource" in this document, the related requests are called "Service Resource Creation Request" throughout the openFinance API documentation.

Examples of Service Resource Creation Request in the openFinance API Framework e.g. are:

- Document Submission Request, or
- Request to Pay Request.

2.2.7 Notion of a Transaction Resource Variant

After a Transaction Resource is generated, certain API services initiate to change (some) parameters of the addressed resource (or an addressable sub-resource) while maintaining the resource's identification. Such related requests are referred to as "Change Transaction Resource Request" in the openFinance documentation. Examples of a Change Transaction Resource Request in the openFinance API Framework are:

- Standing Order Update Request, or
- Update on User Data Request.

The process of changing an existing resource usually needs to be authorised by the PSU by applying Strong Customer Authentication (SCA) at the API. Until the authorisation process of the changed resource is completed, the older but currently still authorised version of the resource remains valid. In essence, this means, that the openFinance API Framework needs to be able to handle several variants of a resource at the same time during the authorisation processes, which can take some time, specifically in cases where 4 eyes principles need to be involved.

In the framework, we differentiate these two variants using the following notation:

- The **active** version is the most recent authorised variant of the resource. This resource variant is also called valid.
- The **changed** version is the outcome of the most recent change/update process (initiated by a Change Transaction Resource Request) applied to the resource. This variant always differs from the active version and must be authorised by SCA to be applied by one or several PSU.

Note: Only the resource variant that is currently undergoing a Change Transaction Resource Process and that is not (fully) authorised is referred to as the changed version of the resource. Once the authorisation process is completed, this variant becomes the active version and until a new Change Transaction Resource Request is issued requesting to update this resource once more, there exists no changed version of the resource.

How to differentiate and address these two variants of the same resource technically by introducing ETags following standard web technology defined in [RFC 9110] is explained in Section 3.11 in detail.

2.2.8 Notation for Access Methods

All service definitions in the openFinance API Framework will come with an overview on the http access methods supported.

These access methods are denoted by the following tables:

Endpoints	Method	Condition	Description
service-endpoint	POST or GET or PUT or PATCH or DELETE	Mandatory or Optional or Conditional	Description and reference to the section, where the related access point is

The following definitions apply for such tables throughout the openFinance API Framework documentation:

- Endpoints: This is the endpoint name.
- Method: This is the HTTP method to be applied. The HTTP methods POST, GET, PUT, PATCH and DELETE are supported.
- Condition: The condition defines the condition for the ASPSP.
 - Mandatory: The access method shall be provided by the ASPSP
 - Optional: The access method may be provided by the ASPSP
 - Conditional: The access method shall be provided given certain conditions defined in the Description column.

Please note that the condition is given relative to the parent node of the path, i.e. the condition e.g. on a method on /service-endpoint/{resourceId} applies only if the endpoint /service-endpoint is supported at all.

- Description: Gives an overview on the method and potentially conditions for the method as well as a reference to the section in the document, where the method is described in detail.



3 REST API Approach: Guiding Principles

This section introduces some basic technical rules on how to implement the REST API approach within the openFinance API Framework.

3.1 Location of Message Parameters

The openFinance API Framework definitions follow the REST service approach. This approach allows to transport message parameters at different levels:

- message parameters as part of the HTTP level (HTTP header)
- message parameters by defining the resource path (URL path information) with additional query parameters and
- message parameters as part of the HTTP body.

The content parameters in the corresponding HTTP body will be encoded either in JSON or in XML syntax. XML syntax is only used where

- an ISO 20022 based payment initiation (pain.001 message) with the corresponding payment initiation report (pain.002 message) or
- ISO 20022 based account information message (camt.052, camt.053 or camt.054 message)

is contained.

As an exception, response messages might contain plain text format in account information messages to support MT940, MT941 or MT942 message formats related to transaction reports.

The parameters are encoded

- in spinal-case (small letters) on path level,
- in spinal-case (starting capital letters) on HTTP header level and
- in lowerCamelCase for query parameters and JSON based content parameters.

The following principle is applied when defining the API:

Message parameters as part of the HTTP header:

- Definition of the content syntax,
- Certificate and Signature Data where needed,

- PSU identification data (the actual data from the online banking frontend or access token),
- Protocol level data like Request Timestamps, Request/Transaction Identifiers or protocol preferences of the API Client.

Message parameters as part of the path level:

- All data addressing a resource:
 - Provider identification,
 - Service identification,
 - Payment product identification,
 - Account Information subtype identification,
 - Resource ID

Query Parameters:

- Additional information needed to process the GET request for filtering information,

Message parameters as part of the HTTP body:

- Business data content,
- PSU authentication data,
- Messaging Information
- Hyperlinks to steer the full TPP – ASPSP process

3.2 API Structure

The XS2A Interface resp. openFinance API is resource oriented. Resources can be addressed under the API endpoints

<https://{provider}/v2/{service}{?query-parameters}>

using additional content parameters {parameters}

where

- {provider} is the host and path of the related API, which is not further mentioned. The host or path may contain release version information of the ASPSP.

- v2 is denoting the final version 2.x of the related implementation guidelines within the openFinance API Framework.

NOTE: The addressed exact version of the Implementation Guidelines of the addressed service will be provided in a dedicated response header, cp. Section 3.3.

- {service} has the values consents, payments, bulk-payments, periodic-payments, accounts, card-accounts, signing-baskets or funds-confirmations for the XS2A Interface eventually extended by more information on product types like resource identification and request scope. For the openFinance API, more services are offered as provided in the extended service specifications of the openFinance API Framework.

Remark: It is strongly recommended that the related resourceId for identifying a dedicated resource is a UUID.

- {?query-parameters} are parameters detailing GET based access methods, e.g. for filtering content data
- {parameters} are content attributes defined in JSON or XML and transported in the http body encoding according to the following
 - XML encoding appears only when ISO 20022 pain.001 messages are transported when demanded by the ASPSP for the corresponding payment product
 - all other request bodies are encoded in JSON

Resources

The structure of the request/response is described according to the following categories

- Path: Attributes encoded in the Path, e.g. "payments/sepa-credit-transfers" for {resource}
- Query Parameters: Attributes added to the path after the "?" sign as process steering flags or filtering attributes for GET access methods. Query parameters of type Boolean shall always be used in a form query-parameter=true or query-parameter=false.
- Header: Attributes encoded in the HTTP header of request or response
- Request: Attributes within the content parameter set of the request
- Response: Attributes within the content parameter set of the response, defined in XML, text or JSON:

- XML encoding appears only, when camt.052, camt.053 or camt.054 messages (reports, notifications or account statements) or pain.002 payment status messages are transported. pain.002 messages will only be delivered for the GET Status Request, and only in cases where the payment initiation was performed by using pain.001 messages.
- Text encoding appears only, when MT940, MT941 or MT942 messages (reports, notifications or account statements) are transported.
- All other response bodies are encoded in JSON.

The HTTP response codes which might be used in the openFinance API Framework are specified in Section 3.8.1. This is not repeated for every API call definition.

Remark: For JSON based responses, this specification defines body attributes which are responded from ASPSP to API Clients following POST or PUT API calls. The ASPSP is free to return the whole addressed resource within the response, following usual REST methodologies.

3.3 API Versioning

For calls on a dedicated service, the ASPSP might use the following HTTP header in responses:

Attribute	Type	Condition	Description
X-Reference-API-Name	String	Optional	"Berlin Group openFinance API"
X-Reference-API-Document	String	Optional	The name of the Implementation Guideline document, where the service is based on, e.g. "Extended Payment Initiation Services".
X-Reference-API-Version	String	Optional	This is the exact version number of the openFinance API Framework Implementation Guidelines of the related service which is implemented, e.g. "2.1.3".

Note: The usage of these header parameters is recommended to use at least on root endpoints for an addressed service. It should be used independently of the http response code.

3.4 API Access Methods of Change Transaction Resource Requests

Change Transaction Resource Requests at the openFinance API Framework may be initiated by an API call using a POST, PUT or a PATCH command as access method. Change

Transaction Resource Initiations come with several instantiations and the way the changing process is proceeded differs depending on the access method of the initial API call, please cp. the table below. This is covered within this section as a basic building block for the openFinance API Framework V2.

A change resource function allows the API Client to update a resource within the openFinance API Framework. The addressed transaction resource must exist already and must be accessible by the requesting API Client via the API. The respective resource identification shall remain unaffected by this process. The API handling how to address the respective resource variants are given in Section 3.10.

Depending on the resource, the ASPSP and the related service specification, it might be mandated that only certain parameters of a resource are allowed to be updated by such a Change Transaction Resource Request. Any field that may not be changed generally via such a request is referred to as an **immutable field** in the framework documentation. Once the resource is created (e.g. by a Transaction Initiation Request or a Service Resource Creation Request), any API call trying a.o. to change the value of such an immutable field will be rejected at the API. The ASPSP shall provide a whitelist of all fields that may be updated/changed using a respective Change Transaction Resource Request via its discovery services, see [oFA-IG-Disc].

Remark: In conjunction with API synchronisation, the change resource process **should** achieve idempotency at least during the authorisation process as detailed in Section 3.6, i.e. if you re-send a PATCH command to the existing resource (with the same Request-ID), then you should receive the same answer, as before. If the new variant of the resource is already authorised, then this call could be rejected.

Method	Description
POST	This request addresses the creation of a sub-resource related to the addressed main resource. The path parameters of this request might include a sub-path specifying that the Change Transaction Resource Request only addresses a certain sub-resource of the addressed resource. The sub-resource might obtain some fields that values are inherited from the (main) resource, thus they are immutable fields of the sub-resource. If this Change Transaction Resource Request initiates the change of any of these fields, the API call will be denied.
PUT	This request rewrites the whole resource data. All fields of the addressed resource are replaced by the fields contained in this request's body. Any field not presented in this call will be removed from the resource. Any immutable fields of the resource must be provided in the request, carrying the same value as in the original resource, else this request will be rejected.

Method	Description
PATCH	This request updates the addressed resource partially. Any field of the resource not contained in the request body remains unchanged. The openFinance Framework supports two different approaches to apply a patch on a resource. If any immutable fields are contained in the Change Transaction Resource Request Body, the request will be rejected. The first approach is a general Patch message using a normal JSON request body and adds or replaces any field provided in the request body. As opposed to a PUT, any field that is not present in the request body remains unchanged. The second approach uses a dedicated content-type "application/json-patch+json" for the request body and follows the PATCH method specified in [RFC6902], also called a JSON Patch. A JSON Patch contains an array of patch operations in the request body that are subsequently applied to the resource as a single transaction, meaning if just a single patch operation fails, the entire request must be rejected, and the resource remains unchanged. Each patch operation is a JSON object that contains the following three fields: • "op": The operation requested to perform. The following values are supported in the openFinance Framework: "add", "replace" and "remove", • "path": the path to the location in the resource where the operation shall be applied to, and • "value": the value to use for the operation. This might contain a single attribute or a (layered) data structure as parameter so that complex/nested attributes can be addressed. This parameter must be used for the operations "add" and "replace" and may not be used for the operation "remove". When applicable, a service should prefer the JSON Patch over the first approach.

Both PATCH methods are functionally similar as both contain only the actual changes that should be applied on the resource and skip any fields that should not be changed. However, the content type of the request body is different for these methods and the JSON Patch according to [RFC6902] allows more precise changes and might avoid accidental deletion of fields in a multilayered structure.

3.5 API Request Header Parameter

The following headers are defined generically within this document and will be instantiated to service definitions explicitly only via the related OpenAPI files. Such lean documentation is intended to enhance the readability of the service definitions.

3.5.1 Transaction Initiation Request Headers

Transaction Initiation Request messages (cp. Section 2.2.5 for a definition) are specific within the openFinance API Framework. These initiation messages for a business transaction not only transport business related information, but also context data and data steering the usage of openFinance API Framework functions. These headers are defined within this document and will be instantiated to service definitions explicitly only via the related Open API files. Such lean documentation is intended to enhance the readability of the service definitions.

The openFinance API Framework foresees a.o. the following header parameters for Transaction Initiation Request messages

- PSU context data, cp. Section 8.2
- PSU identification data, cp. Section 8.3
- SCA Approach Preferences, cp. Section 8.4
- API Client Notification data, cp. Section 12
- Client Brand Information Header, see Section 3.5.4

The usage of the headers mentioned above might lead to the usage of specific header parameters in the Transaction Initiation Response, as defined in the sections above. These headers will not be referred anymore in the related service implementation guidelines, but only generically in this document and in the related yaml files. Others like OAuth2 authorization headers or API Contract IDs are still addressed explicitly in the service implementation guidelines.

The same headers (besides the Client Brand Information Header) also apply to Payment Cancellation Request messages.

3.5.2 Service Resource Creation Request Headers

Service Resource Creation Request messages (cp. Section 2.2.6 for definition) are differently specified among different services in the openFinance API Framework. Nevertheless, one could predict a usual set of header parameters that are required to create the corresponding resource. These parameters include a.o.:

- Client Brand Information Header, see Section 3.5.4
- API Client Notification data, cp. Section 12

These headers will not be referred anymore in the related service implementation guidelines, but only generically in this document and in the related yaml files. Others like OAuth2 authorization headers or API Contract IDs are still addressed explicitly in the service implementation guidelines.

3.5.3 Change Transaction Resource Request Headers

The Change Transaction Resource Request messages (cp. Section 2.2.6 for definition) yield a specific message type initiating a change/update of an existing resource via the openFinance API. These messages do not only transport the resource update related data but also context data and data steering the usage of openFinance API Framework functions. These headers will not be referred anymore in the related service implementation guidelines, but only generically in this document and assumed to be implicitly defined when an API call is referred to as a Change Transaction Resource Request. In the respective Open API files these parameters are given explicitly. The header parameters for Change Transaction Resource Request messages include a.o. the following:

- PSU context data, cp. Section 8.2
- PSU identification data, cp. Section 8.3
- SCA Approach Preferences, cp. Section 8.4
- API Client Notification data, cp. Section 12
- Client Brand Information Header, see Section 3.5.4
- If-Match Header, see Section 3.11

The usage of the headers mentioned above might lead to the usage of specific header parameters in the Change Transaction Resource Response. These headers will not be referred anymore in the related service implementation guidelines, but only generically in this document and in the related yaml files. Others like OAuth2 authorization headers or API Contract IDs are still addressed explicitly in the service implementation guidelines.

3.5.4 Client Brand Information Header

The following header may be used within all Transaction Initiation Requests or Service Resource Creation Requests:

Attribute	Type	Condition	Description
Client-Brand-Logging-Information	Max140Text	Optional	This header might be used by API Clients to inform the ASPSP about the brand used by the API Client towards the PSU. This information is meant for logging entries to enhance communication between ASPSP and PSU or ASPSP and API Client. This header might be ignored by the ASPSP.

3.5.5 Signature related headers

In addition, the following header parameters might be used in all API request headers, where applicable:

- Signature related headers in a message signing context, cp. Section 6
- Signature related headers in a signed transaction request context (SCA), cp. Section 9.4.

3.5.6 Technical headers

The http requests come with certain technical headers, which are not specifically addressed in this specification. One of these headers is the "date" header which is typically added automatically on http protocol level by the API Client system.

Please further note that the http message signing procedure defined in Section 6 specifies a dedicated timestamp for the openFinance API Framework which is protected itself by signing.

3.6 Header Parameters for Idempotency

All requests **and** responses in this API framework come with the unique X-Request-Id, a UUID in requests and responses. The X-Request-Id in the response equals the X-Request-Id in the related request.

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

The uniqueness implies the following:

A request B with the same X-Request-Id as request A should be responded as follows to achieve idempotency:

- If the business content of request B (e.g. path, query parameters, body and headers defined in this specification) equals the business content of request A and if the time deviation is not too high (implementation/request specific) and if potentially the internal state of the related resource has not changed in the meantime: The response message from the server to request B then also should equal the response message to request A.
- Otherwise the requested message should be rejected with a 40x response code.

3.7 API Steering Process by Hyperlinks (HATEOAS)

The services defined within the openFinance API Framework require several requests from the API Client towards the ASPSP. With the Transaction Initiation Request specified in each service, a resource presentation is generated by the ASPSP for the related business transaction, e.g. a payment resource or a consent resource for AIS access. The location header of the response will usually contain a link to the created resource.

In addition, the ASPSP can embed a hyperlink together with a "tag" for the semantics of this hyperlink into the response to these first requests and to all succeeding requests within the services. This hyperlink must be a URI reference as defined in [RFC3986](#) and can be either a relative link, which is recommend to save space, for the host starting e.g. with "/psd2/v2/payments/sepa-credit-transfers" or it can be a global link like <https://www.testbank.com/psd2/v2/payments/sepa-credit-transfers/asdf-asdf-asdf-1234>.

The global links might be needed in some circumstances, e.g. a re-direct. The tag of the hyperlink transports the functionality of the resource addressed by the link, e.g. "authorise-transaction". This link indicates that results of a SCA method are to be posted to the resource addressed by this link to authorise e.g. a payment.

The steering hyperlinks are transported in the "_links" data element of type Link, cp. the related data dictionary. It may contain one or several hyperlinks. Services might define additional hyperlinks before they are integrated mid-term to the overall data dictionary within the openFinance API Framework maintenance.

The "_links" data element may contain more hyperlinks than specified in the related call. In this case, this will be documented in the ASPSP's API documentation or the hyperlinks can be ignored by the API Client.

Some hyperlinks might require additional data in the same response body which are then needed when following this hyperlink. The following table gives an overview on these specific steering hyperlinks to explain interconnection with the data elements.

Hyperlink	Additional Link Related Data	Description
startAuthorisationWith PsuAuthentication	(challengeData)	The link to an endpoint where the authorisation of a transaction or of a transaction cancellation shall be started, where PSU authentication data shall be uploaded with the corresponding call. Remark: In rare cases the ASPSP will ask only for some dedicated ciphers of the passwords. This information is then transported to the TPP by using the

Hyperlink	Additional Link Related Data	Description
		"challenge" data element, normally used only in SCA context.
startAuthorisationWith EncryptedPsuAuthentication	(challengeData)	Same as startAuthorisationWith PsuAuthentication, but password is encrypted on application layer when uploaded.
updatePsuAuthentication	(challengeData)	The link to the authorisation sub resource, which needs to be updated by a PSU password and eventually the PSU identification if not delivered yet. Remark: In rare cases the ASPSP will ask only for some dedicated ciphers of the passwords. This information is then transported to the TPP by using the "challenge" data element, normally used only in SCA context.
updateEncryptedPsu Authentication	(challengeData)	Same as updatePsuAuthentication, but password is encrypted on application layer when uploaded.
startAuthorisationWith AuthenticationMethodSelection	scaMethods	This is a link to an endpoint where the authorisation of a transaction or of a transaction cancellation shall be started, where the selected SCA method shall be uploaded with the corresponding call.

Hyperlink	Additional Link Related Data	Description
selectAuthenticationMethod	scaMethods	This is a link to a resource, where the TPP can select the applicable strong customer authentication methods for the PSU, if there were several available authentication methods.
authoriseTransaction	challengeData, chosenScaMethod	A link to the resource, where a "Transaction Authorisation Request" can be sent to. This request transports the result of the SCA method performed by the customer, generating a response to the challenge data if provided earlier.
startAuthorisationWith TransactionAuthorisation	challengeData, chosenScaMethod	A link to an endpoint, where an authorisation of a transaction or a cancellation can be started, and where the response data for the challenge or a signature is uploaded in the same call for the transaction authorisation or transaction cancellation at the same time in the Embedded SCA Approach or the Signature SCA Approach.

3.8 Links in dedicated Responses

In the following, semantic links for dedicated response messages are defined. These links will not be specified anymore in related service implementation guidelines.

3.8.1 Links in Transaction Initiation and Change Transaction Resource Responses

The Transaction Initiation Response and the Change Transaction Resource Response messages may contain many hyperlinks to indicate the next steps to be taken to authorise the transaction resp. the changed resource variant. These hyperlinks are independent of the actual transaction initiated. This is why they are defined once here generically and are not repeated on Implementation Guideline level, but only in related OpenAPI files. The same applies to response messages of other transactions which might require authorisation, e.g. a Payment Cancellation Request.

Warning: Please note that within a Change Transaction Resource Response an ETag is included as header parameter, see Section 3.11. This ETag must be used in addition to the links to access the requested endpoint for the changed version of the resource, else only the active version is addressed (and depending on the link, the accesses might be denied).

Only for Change Transaction Resource Responses a link "changedVersion" as specified below is contained as links in the response body.

Attribute	Type	Condition	Description
_links	Links	Mandatory	A list of hyperlinks to be recognised by the API Client. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "scaRedirect": In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. "startAuthorisationWithPsuIdentification": The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while uploading the PSU identification data.

Attribute	Type	Condition	Description
			"startAuthorisationWithPsuAuthentication": The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while uploading the PSU authentication data. "startAuthorisationWithEncryptedPsuAuthentication": Same as startAuthorisationWithPsuAuthentication, but the authentication data need to be encrypted on application level while uploading. "startAuthorisationWithAuthenticationMethodSelection": The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" "startAuthorisationWithTransactionAuthorisation": The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while authorising the transaction e.g. by uploading an OTP received by SMS. "self": Only supported for Transaction Initiation Responses. The link to the transaction initiation resource created by this request. This link can be used to retrieve the resource data. "status": The link to retrieve the transaction status of the transaction resource. "scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation sub-resource has been already created. "changedVersion": Only supported for Change Transaction Resource Responses. The link

Attribute	Type	Condition	Description
			retrieves the changed variant of the resource using mandatorily the query parameter "?inChange=true" defined in Section 3.11.2, the ETag may not be included here. This query parameter must be provided already by the ASPSP.

3.8.2 Links in Service Resource Creation Response

The possible links in Service Resource Generation Responses vary depending on the service, nevertheless, the following table contains all minimum links defined so far for these dedicated response messages. These links will not be repeated in related service implementation guidelines.

Attribute	Type	Condition	Description
_links	Links	Mandatory	A list of hyperlinks to be recognised by the API Client. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "self": The link to the resource created by this request. This link can be used to retrieve the resource data. "status": The link to retrieve the status of the resource created by this request.

3.9 HTTP Response Codes

The HTTP response code is communicating the success or failure of an API Client request message. The 4XX HTTP response codes should only be given if the current request cannot be fulfilled, e.g. a payment initiation cannot be posted or account transactions cannot be retrieved. For further details on error handling cp. Section 4. A request to get the status of a transaction usually returns HTTP response code 200 since the actual request to retrieve the status succeeded, regardless if that transaction state is set to failure or not.

The openFinance API Framework supports the following HTTP response codes:

Status Code	Description
200 OK	GET Response Code POST, PUT, PATCH Response Code, if no new resource was created This return code is permitted if a request was repeated due to a time-out. The response in that case might be either a 200 or 201 code depending on the ASPSP implementation.
201 Created	POST response code where a Transaction Request was correctly performed and a related resource was created, which is addressable further on by the API Client.
202 Accepted	DELETE response code, where a transaction resource, e.g. a payment resource can be cancelled in general, but where a cancellation authorisation is needed in addition.
204 No Content	DELETE response code where a transaction resource, e.g. a consent resource was successfully deleted. The code indicates that the request was performed, but no content was returned.
400 Bad Request	Validation error occurred. This code will cover malformed syntax in request or incorrect data in payload.
401 Unauthorized	The API Client or the PSU is not correctly authorised to perform the request. Retry the request with correct authentication information.
403 Forbidden	Returned if the resource that was referenced in the path exists but cannot be accessed by the API Client or the PSU. This code should only be used for non-sensitive id references as it will reveal that the resource exists even though it cannot be accessed.
404 Not found	Returned if the resource or endpoint that was referenced in the path does not exist or cannot be referenced by the API Client or the PSU. When in doubt if a specific id in the path is sensitive or not, use the HTTP response code 404 instead of the HTTP response code 403.
405 Method Not Allowed	This code is only sent when the HTTP method (PUT, POST, PATCH, DELETE, GET etc.) is not supported on a specific endpoint. It has nothing to do with the related transaction data model. DELETE Response code in case of cancellation of a transaction resource, e.g. a payment resource, where the related transaction, e.g. a

Status Code	Description
	payment initiation cannot be cancelled due to legal or other operational reasons.
406 Not Acceptable	The ASPSP cannot generate the content that the API Client specified in the accept header.
408 Request Timeout	The server is still working correctly, but an individual request has timed out.
409 Conflict	The request could not be completed due to a conflict with the current state of the target resource. Usage Rule: In case of a PUT or PATCH Change Transaction Resource Request, if the request leads to a conflict between the parameters given in the body and the addressed resource or if the change of an immutable field was requested.
412 Precondition Failed	POST, PUT or PATCH response code: The request is rejected due to a precondition in the request header fields not being met. Usage rule: incorrect ETag used in the If-Match Header.
415 Unsupported Media Type	The API Client has supplied a media type which the ASPSP does not support.
422 Unprocessable Entity	POST, PUT or PATCH response code: The request is well-formed but rejected due to erroneous semantics. Usage rule: an ETag was specified in the If-Match and additionally the query parameter inChange was used in the request.
423 Locked	POST, PUT or PATCH response code: The resource is locked, e.g. due to an ongoing authorisation process and may not be changed e.g. by a Change Transaction Resource Request

In addition, application independent http response codes generated by the communication infrastructure are supported as well and not explicitly defined here.

3.10 Multi-channel access, Multi-API-Client access, Retrieval of Resources to be authorised, and Access Conflicts

The openFinance API Framework now supports several access channels, e.g. TPP channels and a corporate direct access channel. Resources might potentially be shared then by several channels, even if not yet fully authorised.

The introduction of resource access by several channels implies certain side conditions. First, it is up to the ASPSP which resources are shared via which channels supported by the openFinance API Framework and which access methods are applicable – this is a fundamental implementation decision how to “cut” implementations of the openFinance APIs in dedicated channels. For details, see [oFA-OR-FW].

An ASPSP could decide to share resources initiated via channel A, which are not yet fully authorised by related PSUs, also in channel B. To support the retrieval of such “open” transaction resources, the following access method applies:

- GET /resource-related-path?status={resourceStatus}

Where the following additional parameter applies:

Request Query Parameter

Attribute	Type	Condition	Description
status	String	Optional if supported by ASPSP	Filtering the list of all resources with a related resource status. The encoding of the addressed status depends on the addressed resources. The ASPSP might restrict which resource status (depending on the resource category) the API Client is allowed to use as filter in this query parameter.

Note: This query parameter applies potentially to all Transaction or Service resources.

If transaction resources are shared via different channels and/or API Clients, then the blocking of a resource for Change Transaction Resource Processes (e.g. after an authorisation process has been started for the addressed resource) will apply to all channels and/or API Clients at the same time to avoid ambivalent status of a resource, i.e. the actual status of the resource is a “global” status applicable to all channels and API Clients at the same time. This is comparable to “check-out” processes in data sharing platforms, if applied to the change resource procedures.

Note: Dedicated rules relevant for blocking resources cross channel are contained in [oFA-OR-FW].

Note: The deletion of a resource or the changed resource variant is not a Change Transaction Resource Process and can be initiated always using the respective DELETE request.

3.11 Addressing resource variants during a Change Transaction Resource Process

3.11.1 Addressing resource variants via the If-Match Header

For certain Change Transaction Resource Requests, an ETag, as described in [RFC 9110], functions as a unique identifier for a specific version of the resource is used in addition to the related resourceId. Its use is mandated for any modification of an existing resource initiated by a Change Transaction Resource Request message, or other access methods addressing the changed variant like retrievals for the resource status, until the related authorisation process of the changed variant is completed or the change is deleted.

For Change Transaction Resource Request using the PATCH or PUT access method, the API Call addresses an existing resource and request to change parts of or the whole resource. Such an update of the resource needs to be authorised before the changed variant of the resource becomes valid. If the Change Transaction Resource Request is accepted but the authorisation of the changed variant is still pending, this leads to two variants of a resource related to the same resourceId: the currently-still authorised resource, before the changes were applied, called the active version, and the updated resource, for which the authorisation process is not completed yet, called the changed version, cf. Section 2.2.6.

In the Change Transaction Resource Response, a unique identifier of the changed version of the resource is returned as a response header parameter, called an ETag and specified by the following:

Response Header parameter

Attribute	Type	Condition	Description
ETag	UUID	Mandatory	Unique identification of the changed resource variant that resulted from this request. It can be used together with the original resourceId to address the resource variant of the update, following [RFC 9110].

The ETag can be included in a request by using the following request header parameter:

Request Header parameter

Attribute	Type	Condition	Description
If-Match	UUID	Optional	If used, this field must obtain the ETag of the changed version of the resource. Otherwise, the request will be rejected. Note: in the [RFC 9110] this attribute is a comma separated list of several ETags. In the openFinance documentation only the usage of one ETag is supported. Warning: If this parameter is used, the query parameter <i>inChange</i> that is defined in Section 3.11.2 must not be used. If an API Client uses both the If-Match and the inChange parameter for the same API Call, the request is denied at the API using the HTTP response code 422 and the dedicated message code "ADDESSING_VARIANT_INVALID".

By referring to a specific ETag in an API request using the If-Match header field, the API Client imposes the following pre-conditions on the request:

- this request is to be executed on the changed variant of the resource referenced by the ETag, and
- this request is only to be executed if the changed resource variant referenced by the ETag is currently still the changed variant.

This is to avoid acting on a resource or a resource variant that has already been updated again, i.e. changes may only be addressed and applied to existing resource variants.

The If-Match parameter is supported for requests receiving the status or retrieving the resource data of the changed variant as well as for patching **further** changes or **initiating** the authorisation or deletion of the changed version.

Clarification:

- For any such Change Transaction Resource Services, there exist *at most* two different versions of the same resource. This implies, if a resource already obtains a changed version, an update request addressing the resource's active version must be rejected by the ASPSP.

If a request at the API does not refer to an ETag (i.e. does not include an If-Match header field), this request is always addressing the active version of the resource.

- Using the PATCH approach for Change Transaction Resource Requests, it is possible to update a resource multiple times, before authorising the changed version. Each changed version must obtain its own specific ETag.

The related Change Transaction Resource Requests must always address the currently *latest* version of the resource. This is either the active version if no changed version exists (yet), or the currently latest changed version, i.e. the changed variant that resulted from the latest Change Transaction Resource Request, if it exists. This is to avoid divergent revisions of one resource and to communicate that changes may only be initiated if they are applied to the latest version of the resource.

If an authorisation request or a Change Transaction Resource Request includes no ETag or an ETag referencing a changed resource variant that does not exist anymore as it was already updated by a Change Transaction Resource Request in the meantime again, then request must be rejected at the API with the HTTP response code 412. For details see [oFA-OR-FW].

- A Change Transaction Resource Request using the PUT access method does not support the usage of the If-Match header parameter. If the API Client intends to rewrite a changed version of a resource, the Client should first delete this changed version and then apply the related PUT command to the active version of the resource.
- Once the authorisation process of a changed variant has been initiated, any Change Transaction Resource Request addressing the changed version must be denied at the API using the response code 423. The changed resource variant remains locked until its authorisation is completed, or the (changed variant of the) resource gets deleted (e.g. all changes are withdrawn, see Section 3.11.3).

A more abstract overview on how the different resource versions are addressed and managed at the API including top-level information flows for the different processes of a Change Transaction Resource Process is detailed in [oFA-OR-FW].

3.11.2 Retrieval of the changed version of a resource using the inChange query parameter

The framework differs between the active version and changed version of a transaction resource, see Section 2.2.6 for the definition. Changes of a transaction resource which are not (fully) authorised yet are managed at the API via ETags and may be addressed via the additional If-Match header field, for details see Section 3.11.1. If multi-channel access to the resource is allowed e.g. in the direct access scenario, it is possible that changes are requested

by different users or API Clients, such that some API Clients are not aware of the latest changes and the related ETag of the changed version is not known.

To address the changed version of the resource and retrieve the corresponding ETag, an API Client can request to read the resource via the related GET request and including the query parameter "inChange" that is specified in the following. If this query parameter is used in a related request, the response must include the changed version, if it exists, and the corresponding ETag of the changed version must be included as header parameter.

Request Query Parameter

Attribute	Type	Condition	Description
inChange	Boolean	Optional	If "inChange=true", the API Client ask to retrieve the changed version of the addressed resource is requested. If it exists, the response shall include the related ETag as header parameter. If the resource does not obtain a changed version, the request is rejected. Warning: The "inChange" query parameter and the If-Match header field must not be used within the same call. If both parameters are used in the same request, the request will automatically be rejected at the API using the HTTP response code 422 and the dedicated message code "ADDESSING_VARIANT_INVALID".

If the ASPSP supports a multi-channel access to its APIs where Change Transaction Resource Requests may be issued, then this attribute must be supported.

Note: This parameter shall only be used if the ETag of the changed version is not known and it is only supported for the following types of GET requests:

- GET /resource-related-path
to filter an addressed list of resources such that the list presents only the resources that are currently undergoing a change process. For each resource in this list, a

hyperlink "changedVersion" is included which can be used by the API Client to retrieve the changed variant of the resource and to obtain the corresponding ETag.

The ASPSP must support the query parameter `inChange` for this API Call, if Change Transaction Resource processes are allowed for the related resource.

Additionally, the API Client may filter the list using the `resourceId` of a related service resource as query parameter. This can be used e.g. instead of the following option.

- `GET /resource-related-path/{resourceId}`

to retrieve the changed version of the addressed resource. The response provides the changed version of the resource together, its corresponding ETag in provided as header parameter.

The ASPSP may support the query parameter `inChange` for this API Call, if Change Transaction Resource processes are allowed for the related resource.

Then the ETag(s) obtained this way may be used to initiate further steps to authorise, to delete or to further update the changed variant of the addressed resource(s).

Note: For all other types of API calls, the changed resource must be addressed using the *If-Match* Request Header field as defined in Section 3.11.1.

If the changed version of an addressed resource is requested, in addition to the ETag given in the response header, the ASPSP should use the following header parameters (in case of multi-channel access to its APIs). These convey information on the last change process that led to the current changed version of the resource. Once the authorisation process of the changed version is completed, this data is no longer presented at the ASPSP's APIs.

Response Header Parameters

Attribute	Type	Condition	Description
<code>lastChangedBy</code>	Max140Text	Optional	This attribute contains the identifier of the PSU that initiated the latest Change Transaction Resource Request that initiated the latest update of the resource.
<code>lastChangedChannel</code>	String	Optional	This attribute contains the access channel that was used for the initiation of the latest update of the resource.
<code>lastChangedTimestamp</code>	ISODateTime	Optional	This attribute contains the timestamp of the Change Transaction Resource Request that initiated the latest update of the resource.

3.11.3 Withdrawal of Transaction Resource Changes that are not approved yet

It is possible to withdraw all the requested changes in the changed version as long as the changed version is not (fully) approved yet. Then the changed version of the resource gets cancelled, and the active version becomes the only version of the resource again. The deletion of the changed version might be restricted to certain API Clients or channels (e.g. the one who already gave approval). Once the authorisation process has started, a deletion request coming from a blocked API Client/channel will be denied using the HTTP response code 423 together with a message code informing the API Client that the access is blocked for this channel.

To initiate the withdrawal of changes, a DELETE request issuing the deletion of the changed version of the resource is issued. The If-Match header field must be used and must obtain the ETag of the changed version. This API call issues the deletion of the changed version of the resource; thus, all unapproved changes are withdrawn. The active version is not affected by this deletion. This deletion process of the changed variant shall be approved without SCA.

If the request is successful, the deletion of the changed version is executed, the active version remains unchanged by this process and the resource does not obtain a changed version at the moment. The ETag corresponding to the former changed version becomes invalid and its usage in an API call leads to a rejection of the request.

3.11.4 General flow for addressing resource variants

In general, the following flow for authorising a changing process and the respective commands for the different resource variants is given:

- `GET /resource-related-path/{resourceId}`
will retrieve the active variant of the resource as it obtains the currently authorised resource data.
Remark: If the resource related to the resourceId obtains a changed version, then the response body should include a hyperlink "changedVersion" to indicate the existence of this pending update of the resource.
- `GET /resource-related-path/{resourceId}?inChange=true`
and
`GET /resource-related-path/{resourceId}`
If-Match: ETag as returned by related Change Transaction Resource Response
are two API calls that will retrieve the changed version of the resource that is not (fully) authorised yet.

If the changed version of the resource contains changes that are not fully approved yet, it is not possible to request the deletion of the active version only. The following applies:

- `DELETE /resource-related-path/{resourceId}`

issues the deletion of the resource's active version. It is the ASPSP's decision if either both versions are deleted or if the request gets denied.

- `DELETE /resource-related-path/{resourceId}`
If-Match: ETag as returned by the latest Change Transaction Initiation Response

will delete the changed variant of the resource, in particular, the active variant of the resource remains unaffected by this deletion.

- `POST /resource-related-path/{resourceId}/authorisations`
If-Match: ETag as returned by related Change Transaction Resource Response

will initiate an explicit start of the authorisation of the changed version as defined in the openFinance API Framework. All succeeding authorisation calls must use the same If-Match header.

After the authorisation has been applied successfully by addressing the related authorisation resources, i.e. if the new resource variant has a final authorisation status (which can be different in different object categories), then:

- `GET /resource-related-path/{resourceId}`
will retrieve the new (now authorised) resource variant including the requested changes. The formerly active version of the resource is not retrievable via the openFinance API anymore.

Until a Change Transaction Resource Request addressing the resource is issued, there does not exist a changed variant of the resource.

3.12 Data Extensions by the ASPSP

The ASPSP might add more data attributes to response messages. Such extensions then shall be documented in the ASPSP's documentation of its XS2A interface. These data attributes can be either ignored by the API Client or can be interpreted as defined by the above mentioned documentation.

The ASPSP might add additional optional data attributes to be submitted, e.g. for setting up additional services. In addition, an ASPSP can ask the API Client for a submission of proprietary data in a second step via the "proprietaryData" hyperlink. This shall be published by the ASPSP in its documentation.

Remark: Before defining these additional proprietary data elements, the ASPSP is requested to submit the attribute description to the Berlin Group openFinance Taskforce, where it will be decided on a standardised approach for the related data attributes.

3.13 Multicurrency Accounts

Definition: A multicurrency account is an account which is a collection of different sub-accounts which are all addressed by the same account identifier like an IBAN by e.g. payment initiating parties. The sub-accounts are legally different accounts and they all differ in their currency, balances and transactions. An account identifier like an IBAN together with a currency always addresses uniquely a sub-account of a multicurrency account.

This specification supports to address multicurrency accounts either on collection or on sub-account level. The currency data attribute in the corresponding data structure "Account Reference" allows to build structures like

```
{"iban": "DE40100100103307118608"}
```

or

```
{"iban": "DE40100100103307118608",  
  "currency": "EUR"}
```

If the underlying account is a multicurrency account, then

- the first reference is referring to the collection of all sub-accounts addressable by this IBAN, and
- the second reference is referring to the euro sub-account only.

This interface specification is acting on sub-accounts of multicurrency accounts in exactly the same way as on regular accounts. This applies to payment initiation as well as to account information.

3.14 Interval Borders Including Rules

Data attributes for dates, amounts or other discrete data come sometimes with the suffix "To" or "From", e.g. "dateTo", "validTo" or "baseAmountFrom". These attributes always define intervals. In **all** such cases, the "From" and "To" is including the value at the addressed border of the addressed interval. That means, that e.g. "dateFrom": "2023-04-05" means, that the 5th April 2023 is included in the addressed interval.

4 Error Handling

This section introduces the error handling in the openFinance API Framework. API data structures as defined here will not be repeated in service specifications. Instantiations to the related services will only be provided via the related OpenAPI files.

4.1 Responses in Error Cases

In order to achieve a better readability, the service definitions in the openFinance API Framework specify responses in case of a positive processing result only. The following section gives specific rules for the case of a negative processing result applicable to all services.

4.1.1 Header

In general, the same rules regarding the presence of header elements apply for both positive and negative responses. An exception is made for cases, where an error occurred before functional processing. Examples for such error cases are general server errors (typically with 50x http response code) and – depending on the implementation – the validation of the certificate. In those error cases, the ASPSP may omit the specified headers. However, when functional processing has already taken place, the ASPSP is still required to include the mandated (and if applicable conditional) headers also in a negative response.

4.1.2 Body

All descriptions of body elements in the service documents only apply to cases with a positive response. The related attributes need also be provided in the body, where possible and applicable. In addition, the API shall offer additional error information as described in Section 4.2, when the API server is technically able to provide it.

4.2 Additional Error Information

If necessary, the ASPSP **might** communicate additional error information to the API Client within a request/response dialogue which results in 4xx or 5xx HTTP response codes, in some exemptions also for HTTP response code 2xx, see also Section 3.8.1 This specification offers two possibilities for ASPSPs to communicate additional error information. The ASPSP might choose one of the solutions. Note that the major additional error information is the detailed error code which is of type "Message Code" as defined in [oFA-DaD] is used in both variants of additional error information.

In cases, where no message code is defined for an HTTP response code, the additional error information is not used, since the messageCode is a mandatory subfield. In this case, the HTTP code gives sufficient information about the error situation.

4.2.1 openFinance API Framework Specific Solution

The openFinance API Framework offers a proprietary way to transport additional error information. In this solution, the additional error information is sent to the API Client using the data element `apiClientMessages` with the attribute category set to "ERROR". The attribute "code" indicates the error, and the attribute "path" the path of the element of the request message which provoked this error message, if applicable. It will further offer a free text field to describe the error context or actions to be taken to the API Client.

Usually, the usage of `apiClientMessages` accompanies a negative response. However, there are cases where the ASPSP sends a positive response but still includes an `apiClientMessages` attribute. This might occur, when the API Client sends a status request and the request itself is technically accepted but the requested status indicates some kind of banking processing issue/error or the requirement of additional action by the API Client or the PSU. In the same way, the requirement of additional actions can be indicated when (generally) accepting a payment initiation.

In addition, the response message might optionally contain a `_links` section containing a hyperlink to tell the API Client the next step to avoid further errors, cp. Section 3.7. This applies especially in case of PSU authentication errors where a resubmission of credentials by the API Client might be needed after new entering of credentials by the PSU.

Response Code

The HTTP response code is 4xx or 5xx as defined in Section 3.8.1 for response codes in case of errors.

Response Header

Attribute	Type	Condition	Description
Content-Type	String	Mandatory	The string application/json is used.

Response Body

Attribute	Type	Condition	Description
<code>apiClientMessages</code>	Array of Client Message Information	Optional	Error information
<code>_links</code>	Links	Optional	Should refer to next steps if the problem can be resolved e.g. for re-submission of credentials.

Example 1 (Access token not correct):

```
{ "apiClientMessages": [{  
    "category": "ERROR",  
    "code": "TOKEN_INVALID",  
    "text": "additional text information of the ASPSP up to 500  
characters"  
}]  
}
```

Example 2 (Password incorrect):

```
{ "apiClientMessages": [{  
    "category": "ERROR",  
    "code": "PSU_CREDENTIALS_INVALID",  
    "text": "additional text information of the ASPSP up to 500  
characters"  
}],  
  "_links": {  
    "updatePsuAuthentication": {"href": "/psd2/v2/payments/sepa-credit-  
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-  
a47d-4130-9999-a9c0ff861100"}  
  }  
}
```

4.2.2 Standardised Additional Error Information

In [RFC7807] a standardised definition of reporting error information is described. In the following, requirements of how to use this standardised error information reporting in the context of openFinance API Framework are defined.

RFU: This section might be replaced in future by [RFC9457] which is the successor of [RFC7807].

Response Code

The HTTP response code is 4xx or 5xx as defined in Section 3.8.1 for response codes in case of errors. However, with the same reasoning as in Section 4.2.1, Additional Error Information may also be included in certain responses with positive response codes.

Response Header

Attribute	Type	Condition	Description
Content-Type	String	Mandatory	The string application/problem+json is used.

Response Body

Attribute	Type	Condition	Description
type	Max70Text	Mandatory	A URI reference [RFC3986] that identifies the problem type. Remark for Future: These URI will be provided by openFinance API Framework in future. Meanwhile ASPSPs must NOT use https://berlingroup.com prefixes mentioned in the example.
title	Max70Text	Optional	Short human readable description of error type. Could be in local language. To be provided by ASPSPs.
status	Integer	Optional	HTTP response code generated by the server. If contained, this is more relevant as the actual http response code in the actual response, because it is introduced by the application server.
detail	Max500Text	Optional	Detailed human readable text specific to this instance of the error.
instance	Max256Text	Optional	This attribute is containing a JSON pointer (as defined in [RFC6901]) or XPath expression to indicate the path to an issue generating the error in the related request.
code	Message Code	Mandatory	Message code to explain the nature of the underlying error.
additionalErrors	Array of Error Information	Optional	Might be used if more than one error is to be communicated

Attribute	Type	Condition	Description
_links	Links	Optional	Should refer to next steps if the problem can be resolved e.g. for re-submission of credentials.

Example 1

```

HTTP/1.1 401 Unauthorized
Content-Type: application/problem+json
Content-Language: en
{
  "type": "https://berlingroup.com/error-codes/TOKEN_INVALID",
  "title": "The OAuth2 token is associated to the TPP but is not valid
for the addressed service/resource.",
  "detail": "additional text information of the ASPSP up to 500
characters ",
  "code": "TOKEN_INVALID",
  "additionalErrors": [ {
    "title": "The PSU-Corporate-ID cannot be matched by the
addressed ASPSP.",
    "detail": "additional text information of the ASPSP up to 500
characters",
    "code": "CORPORATE_ID_INVALID"
  }, ... ],
  "_links": { }
}

```

Example 2

The following example reflects a decline to a Bulk Payment request, where the first payment of the bulk contains an incorrect IBAN to identify the creditor account,

```

HTTP/1.1 400 Bad Request
Content-Type: application/problem+json
Content-Language: en
{
  "type": "https://berlingroup.com/error-codes/PAYMENT_FAILED",
  "title": "The payment initiation POST request failed during the initial
process. Additional information may be provided by the ASPSP.",
  "detail": "IBAN check failed.",
  "instance": "/creditTransfers/0/creditorAccount/iban"
  "code": "PAYMENT_FAILED",
  "_links": { }
}

```

5 Authentication of API Client and ASPSP at transport layer

The communication between an API Client and an ASPSP is always secured by using a TLS-secured connection. Client authentication is always used, i.e. a mutual authentication between the API Client and the ASPSP will be part of the setup of the TLS-secured connection.

TLS version 1.2 or higher has to be used. For the choice of cipher suite selections, NIST recommendations on the cryptographical strength should be followed. For ASPSPs, further cipher suite requirements of their national IT security agency or of a related API Access Scheme might apply.

Two TLS-secured connections have to be distinguished:

- TLS-secured connection established by the API Client (as TLS-client) to access the BG API provided by an ASPSP (as TLS-server) for usual API services defined by the XS2A Framework or the openFinance API Framework. See section 5.1.
- TLS-secured connection established by an ASPSP (as TLS-client) to access an API provided by an API Client (as TLS-server) for pushed-based services defined by the openFinance Framework. See section 5.2.

5.1 TLS-secured connection established by API Client

Support for this security measures is mandatory for any ASPSP and any API Client.

For all services offered at an XS2A API the TLS-secured connection has to be established by the API Client as TLS-client. The ASPSP acts as TLS-server in this case.

This is also true for most of the extended services offered at an openFinance API. Only for push-based extended services the TLS-secured connection has to be established by the ASPSP. See section 5.2 for this case.

For the case of an XS2A API:

The API Client has to establish the TLS-secured connection including client authentication, i.e. authentication of the API Client as TLS-client. For this authentication the API Client has to use a qualified certificate for website authentication (QWAC). This qualified certificate has to be issued by a qualified trust service provider according to the eIDAS regulation [eIDAS]. The content of the certificate has to be compliant with the requirements of [EBA-RTS] and the technical specification of ETSI [ETSI TS 119 495]. The certificate of the API Client has to indicate all roles the API Client is authorised to use (according to [PSD2] and [EBA-RTS]).

Remark: For getting a QWAC compliant with the requirements of [EBA-RTS] and [ETSI TS 119 495] the API Client has to get the necessary licence to access a service as a PISP, AISP or PIISP from an NCA according to the regulations of [PSD2].

For the case of an openFinance API:

The requirements for the certificate for website authentication to be used by the API Client for the client authentication as TLS-client will be defined by the ASPSP. In any case a QWAC of an API Client enabling him to access the XS2A API of an ASPSP can also be used by the API Client to access the openFinance API of the ASPSP.

In any case within the openFinance API Framework:

This specification does not define any further requirements for the certificates used by an ASPSP as TLS-server. Of course, the certificates should be compliant with general requirements defined by [RFC5280] and the best practise recommendations of the CA/Browser Forum.

If an ASPSP wants to support any push-based services it is recommended that the certificate of the ASPSP supports also the client authentication as TLS-client. See section 5.2 for further details.

5.2 TLS-secured connection established by ASPSP

Support for this security measures is conditional for an ASPSP and for an API Client. It shall be supported by an ASPSP if the ASPSP wants to offer pushed-based services. It shall be supported by an API Client if the API Client wants to use pushed-based services offered by an ASPSP.

For push-based extended services it is necessary that the TLS-secured connection is established by the ASPSP. In this case the ASPSP acts as TLS-client and the API Client as TLS-server.

The ASPSP **shall** use the same certificate for his authentication as TLS-client as he will use for his authentication as TLS-server as described in section 5.1. For this it is necessary that the certificate of the ASPSP supports also the client authentication, i.e. the certificate shall contain the field extendedKeyUsage with both attributes clientAuth and serverAuth.

The API Client **should** use the same QWAC for his authentication as TLS-server as he will use for his authentication as TLS-client as described in section 5.1.

The URIs which are provided by an API Client to an ASPSP for push-based services shall comply with the domain secured by the certificate of the API Client (used for his authentication as TLS-server), i.e. as contained in one of the fields CN or SubjectAltName of the certificate of the API Client. Please note that in case of example-TPP.com, a certificate entry Client-Notification-URI like

- <https://example-TPP.com/xs2a-client/v2/ASPSPidentification/mytransaction-id/notifications> or

- <https://push-server.example-TPP.com/xs2a-client/v2/ASPSPidentification/mytransaction-id/notifications>

would be compliant.

Wildcard definitions shall be taken into account for compliance checks by the ASPSP.

NOTE: The URI should be addressable by the ASPSP just by presenting his certificate for his authentication as TLS-client as part of the establishment of the TLS-secured connection. No further pre-steps of any kind should be mandated by the API Client.

5.3 Certificate Requirements on Redirect URIs

The TPP can provide several URIs to the ASPSP as parameters for succeeding protocol steps. For security reasons, it should be ensured that these URIs are secured by the TPP eIDAS QWAC used for identification of the TPP. The following applies:

URIs which are provided by TPPs in Client-Redirect-URI or Client-Nok-Redirect-URI should comply with the domain secured by the eIDAS QWAC certificate of the TPP in the field CN or SubjectAltName of the certificate. Please note that in case of example-TPP.com as certificate entry Client-Redirect-URI like

- www.example-TPP.com/xs2a-client/v2/ASPSPidentification/mytransaction-id or
- redirects.example-TPP.com/xs2a-client/v2/ASPSPidentification/mytransaction-id

would be compliant.

Wildcard definitions shall be taken into account for compliance checks by the ASPSP.

NOTE: In PSD2 compliance services, the ASPSP shall not reject requests if the provided URIs do not comply, if not mandated by applicable regulations. In premium services, ASPSPs may reject requests, if the provided URIs do not comply and if agreed in related contracts or if mandated by applicable regulations.

6 Signing HTTP request messages at the application level

Support for this security measure is optional for an ASPSP.

Support for this security measure is mandatory for an API Client. If an ASPSP requires signing an HTTP request message at the application level, the API Client shall sign the HTTP request message at the application level.

If required by an ASPSP, only the HTTP request message has to be signed at the application level by the API Client. HTTP response messages are not signed by the ASPSP if not stated otherwise explicitly in the ASPSP documentation.

Remark for Future: Future versions might also support explicit specification of signing HTTP response messages at the application level.

Signing of HTTP request messages at the application level used for push-based services is also possible. The ASPSP (or related API access scheme) decides if it signs an HTTP request message used for a pushed-based service at the application level.

Signing of an HTTP request message at the application level is always done using the signature profile based on JSON Web signature [RFC7515] adapted for signing HTTP request messages (taking [OBESign] as best practise approach into account). See section 6.2 for the description of this signature profile.

6.1 Certificates to be used

For the case of an XS2A API:

For signing an HTTP request message at the application level, the API Client has to use a qualified certificate for electronic seals (QSealC). This qualified certificate has to be issued by a qualified trust service provider according to the eIDAS regulation [eIDAS]. The content of the certificate has to be compliant with the requirements of [EBA-RTS] and the technical specification of ETSI [ETSI TS 119 495]. The certificate of the API Client has to indicate all roles the API Client is authorised to use (according to [PSD2] and [EBA-RTS]).

Remark: For getting a QSealC compliant with the requirements of [EBA-RTS] and [ETSI TS 119 495] the API Client has to get the necessary licence to access a service as a PISP, AISP or PIISP from an NCA according to the regulations of [PSD2].

For the case of an openFinance API:

The requirements for the certificate for signing HTTP request messages to be used by the API Client will be defined by the ASPSP. In any case a QSealC of an API Client enabling it to sign HTTP request messages for the XS2A API of an ASPSP can also be used by the API Client to sign HTTP request messages for the openFinance API of the ASPSP.

In any case of a BG API:

This specification does not define any further requirements for the certificates used by an ASPSP to sign HTTP request messages as part of a push-based service. Of course, the certificates should be compliant with the general requirements defined by [RFC5280].

6.2 Signing HTTP messages based on [RFC7515]

The following signature profile is compliant with the requirements of [RFC7515] (JSON Web Signature) and [ETSI TS 119 182-1] (JAdES profile of ETSI). It is based on the best practise approach defined by [OBESign].

6.2.1 Extensions to the HTTP message

6.2.1.1 Path

None.

6.2.1.2 Header parameter

The following parameters have to be added to the header of the HTTP request message:

Attribute	Type	Condition	Description
Digest	String	Conditional	Contains the hash value calculated over the content of the body of the HTTP request message. See section 6.2.2.1.
x-jws-signature	String	Conditional	JSON Web Signature with detached JWS Payload containing the base64url encoded JWS Protected Header and the base64url encoded JWS Signature Value (separated by ".."). See section 6.2.2.2.

Table 1: Header parameters for HTTP message signature according to [OBESign].

Remark on the row "condition":

If the HTTP request message has to be signed using this signature profile both attributes are mandatory.

Remark on the transport of the certificate:

The attribute TPP-Signature-Certificate used in former versions of the specifications for the transport of the certificate is not available for version 2 of the specification. Instead

the recommendations of [OBSign] are used for the transport of the certificate. These are summarized as follows:

- If the certificate used by the API Client to sign the HTTP request message is not already known by the ASPSP, the API Client shall include its certificate into the JWS Protected Header using the x5c parameter. See requirement 9 of [OBSign].
- If the certificate used by the API Client to sign the HTTP request message is already known by the ASPSP (by some prior arrangements out of scope of this specification) either one, but not both, of the parameters x5c (containing the certificate) or x5t#S256 (containing the fingerprint of the certificate using SHA 256) shall be included in the JWS Protected Header. See requirement 7 of [OBSign].
- The ASPSP may require that the certificate is always included in the JWS Protected Header using the x5c parameter.
- If the JWS Protected Header contains the x5t#S256 parameter (containing the fingerprint of the certificate using SHA 256), the JWS Protected Header may also contain the x5u parameter with further information to identify the certificate. See option 14 of [OBSign].

6.2.1.3 Message body

None.

6.2.2 Building the extensions

6.2.2.1 Attribute Digest

When an API Client includes a signature according to this signature profile, it must also include a "Digest" header as defined in [RFC3230]. The "Digest" Header contains a base64 encoded Hash of the message body. If the message does not contain a body, the "Digest" header must contain the hash of an empty byte list. The only hash algorithms that may be used to calculate the Digest within the context of this specification are SHA-256 and SHA-512 as defined in [RFC5843].

Remark: In the case of a multipart message the same method is used to calculate the digest, i.e. a hash of the entire message body is calculated including all parts of the multipart message as well as the separators.

6.2.2.2 Attribute x-jws-signature

The attribute x-jws-signature contains the JSON Web Signature in compact serialisation with a detached JWS Payload according to [RFC7515]. This consists of the following three concatenated elements:

Element	Type	Condition	Description
JWS Protected Header	String	Mandatory	Contains the base64url encoded JWS Protected Header.
Delimiter	String	Mandatory	Constant string "..". Note: Since the JWS Payload is detached, the delimiter "." appears twice in a row.
JWS Signature Value	String	Mandatory	Contains the base64url encoded JWS Signature Value.

Table 2: Elements of the JSON Web Signature according to [OBESign].

Note: In a base64url encoded string, the padding characters are omitted.

JWS Protected Header

The JWS Protected Header is a JSON structure which defines how the signature is created. It contains the following elements:

Attribute	Type	Condition	Description
typ	String	Mandatory	Fixed string "JOSE".
b64	Boolean	Mandatory	Parameter according to [RFC 7797] indicating whether the payload is base64url encoded or not. According to [OBESign] this parameter has to be included and set to "false", indicating that the payload is not base64url encoded. See Section 3 of [RFC 7797] for details about the b64 parameter.

Attribute	Type	Condition	Description
x5c	Array of strings	Conditional	Certificate used by the API Client to sign the HTTP request message according to [RFC7515]. This parameter may include the full certificate chain up to a trust anchor. See option 10 in [OBSign]. Each element of this array is the base64 (not base64url) encoded DER PKIX value of a certificate. The first certificate must contain the public key used to sign this JWS. Each subsequent certificate must be the one used to sign the preceding certificate. This parameter shall be part of the JWS Protected Header if the certificate is not already known by the ASPSP (by some prior arrangements out of scope of this specification). The ASPSP may require that this parameter is included. The ASPSP informs about this as part of the discovery API.
x5t#S256	String	Conditional	Fingerprint (Hash value) over the certificate of the API Client used for signing the request message. The fingerprint is the base64url encoded SHA 256 digest of the DER encoding of the certificate. This parameter shall be part of the JWS Protected Header if and only if the x5c parameter is not part of this JWS protected header.
x5u	String	Optional	A URI pointing to the resource where the X.509 signing certificate (with or without the certification path) may be retrieved from. This parameter may be part of the JWS Protected Header only if the x5t#S256 parameter is also part of the JWS Protected Header
crit	Array of strings	Mandatory	List of names of parameters of the JWS Protected Header which are marked critical. According to [OBSign] this parameter has to be included and has to contain the following list: ["b64", "sigT", "sigD"]

Attribute	Type	Condition	Description
			Other parameters shall not be marked critical for BG API.
sigT	DateTime	Mandatory	Claimed signing time. The time shall be UTC (ending in "Z") and shall indicate date and time with the resolution of one second.
sigD	JSON Object	Mandatory	This parameter shall contain the two properties "pars" and "mid". The property "pars" contains the ordered list of HTTP header parameters which are used to create the JWS Payload to be signed. The names of the HTTP header parameters shall be given lowercase in this list. The property "mid" identifies the mechanism used to identify the data to be signed. This property shall contain the fixed value "http://uri.etsi.org/19182/HttpHeaders_" For using this signature profile with BG API, the following restrictions concerning the property "pars" shall be considered: The list shall contain at least "digest" and "x-request-id". The list shall conditionally include if and only if the corresponding HTTP header is included in the HTTP-Request: • "api-contract-id" • "psu-id" • "psu-corporate-id" • "Client-Redirect-uri" The list may include additional HTTP header parameters.
alg	String	Mandatory	This parameter identifies the cryptographic algorithm used to create the JWS Signature Value. According to [OBESign] this parameter has to be included and shall not have the value "none".

Attribute	Type	Condition	Description
			Identifiers should be used (if possible) according to [RFC7518]. For using this signature profile with BG API, the following restrictions concerning the algorithm to be used shall be considered: The algorithm shall identify the same algorithm for the signature as described for the public key (Subject Public Key Info) in the certificate (already known by the ASPSP or contained in the element "x5c") of this Request. Otherwise, the request message shall be rejected.
aud	String	Mandatory	Parameter according to [RFC7519] containing the intended recipient of the signed request message. This specification defines the intended recipient by the uppercased HTTP method and the relative request URI starting with "/v2/" (including all query parameters of the request), separated by a single space character. Examples for the content of the aud parameter: "POST /v2/deferred-payments/sepa-credit-transfers" "GET /v2/deferred-payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/initiations?dateFrom=2024-04-15"

Table 3: Parameters of the JWS Protected Header according to [OBESign].

Remarks:

- The aud parameter according to [RFC7519] is an extension to [OBESign]. It is used to protect the method and the relative path of the HTTP-request by the signature, so that the ASPSP can verify that the request was intended for this URI by the signer.

- If the x5t#S256 parameter is used: For the current version the algorithm SHA 256 shall be used to calculate the hash value over the certificate. This might be enhanced to additional hash algorithms in future versions of this specification.
- If the x5t#S256 parameter is used: It is recommended that the relying party checks the hash value contained in X5t#S256 against the certificate of the API Client (already known to the ASPSP by some prior arrangements out of scope of this specification).
- Remark: If the x5t#S256 parameter is used, the hash value can be used as a key to identify a certificate/public key previously exchanged between API Client and ASPSP.
- For the sigD parameter, the RECOMMENDATION-23 of [OBEsign] is not followed, i.e. (request-target), Content-Type, Content-Encoding and Host may not be part of the sub-field pars.
- For the sigD parameter, the ASPSP may not require additional HTTP header parameters to be included. The API Client may decide which HTTP header parameters are included in the generation of the signature as long as the restrictions mentioned above are met.
- For the alg parameter, the ASPSP may introduce further restrictions about the algorithms to be used. Information will be given by the discovery API of the ASPSP.

JWS Signature Value

The signature shall be calculated according to [RFC7515] using the algorithm indicated by the alg parameter of the JWS Protected Header. The key to be used shall be the private key corresponding to the certificate (e.g. QSealC) of the API Client.

To calculate the signature, proceed as follows:

1. Encode the JSON object containing the JWS Protected Header into base64url. Remark: According to section 2.2.4 the trailing "=" padding characters are omitted in base64url encoding.
2. Collect the HTTP header parameters as indicated by the sub-field "pars" of the sigD parameter of the JWS Protected Header preserving the ordering of the HTTP header as defined in the field "pars" to form a string as follows:
 - a) For an HTTP header name contained in the field "pars" create the header field string by concatenating the lowercased header field name followed with a colon ':', a single ASCII space character, and the header field value. Any leading and trailing white spaces are removed. If there are multiple instances of the same header field, all header field values associated with the header field shall be



concatenated, separated by an ASCII comma and an ASCII space ', ', and used in the order in which they will appear in the transmitted HTTP message.

- b) Insert a line feed character after all but the last header field string.
- c) Concatenate the header field strings.

See 5.2.8.2 of [ETSI TS 119 182-1] for this procedure.

This concatenation of the header field strings will be used as the JWS Payload. Since "b64=false" is contained in the JWS Protected Header, the JWS Payload is not base64url encoded, see section 3 of [RFC 7797].

3. Prepare the signature input by combining the base64url encoded JWS Protected Header from step 1 with the result string of step 2, separated by ".".
4. Compute the JWS Signature value using the signature input from step 3 using the signature algorithm determined by the alg parameter of the JWS Protected Header.

6.2.3 Example

Disclaimer:

The following example is only an informative part of this specification. In this example the JWS Protected Header does not contain all elements according to section 6.2.2.2. The objective of this example is just to give an example for the different steps to build the signed HTTP message starting from a given HTTP message. It should not be taken as a reference point for implementations for signing HTTP messages. In addition, the sequence of steps shown in the example could be changed by a real implementation if the same result is produced. The RSA keys used in this example are 768 bits long, which is too short for real-world applications, but sufficient for illustrative purposes here. The certificate used in this example is a self-signed X.509 certificate, generated using the aforementioned RSA keys along with some additional data. Below we provide it in the PEM format.

Throughout this example we use the following X.509 certificate with the corresponding private key.

Private Key in PEM format	<pre> -----BEGIN RSA PRIVATE KEY----- MIIBYgIBAAJhAJdVM8+7UdWgAdvLNDpWth0Y/1rgxkN5zbFIg40CgIXfx4XrTavL lwFjC7vmg+yjCXPSmv569Gn24aYK+fyeNQY32QhLQssRaU2P8V3u7xgQpHPUHsul 0srZ2pG3Bp1UAwIBAwJgGTjkop84TkVVPKHeCbkeWi7VOdAhCz73nYwV7NXAHk/2 llHiAfdD1qXXSfvAp3CUBuGQc24xkEouDPiFcpA0nWZ+9nRmTGmcRgFBDDqldcib BdJowHxEpmTaaRkotgWvAjEAw+MXENWny6naL+7enr/DMav86hvXfZC3i91SX1cb /L5vQqRMtEu40sQ4XH3dWWinAjEAxcYhORAJPI/zKEj6rn02JCTiV3UFgwcIHasY tTf0yJ6TDkFdlHB+EbiDvqIO/8lFAjEAgpdktePFMnE8H/SUadUsy8f98Wfk/mB6 XT426j0Sgh701xgzIt014dglkv6TkPBvAjEA9lre2AXfbVMxYX8dFN5bW3sOk4D rK9avnIQeM/4hb8MtCuTuEr+tnsCfxbN/9uDAjEAwPFsVMxZVD5AQRt+3sg78RdI </pre>
---------------------------	--

Certificate (including the Public Key) in PEM format	<pre> BJOJiaqBNpJwAX2jIKvzr1SgtbvxnTERT7hVv12E -----END RSA PRIVATE KEY----- -----BEGIN CERTIFICATE----- MIIB5DCCAW6gAwIBAgIUFNihspmc7vzDwkYUfYdwpce2ElKQwDQYJKoZIhvcNAQEL BQAwUjELMAkGA1UEBhMCREUxDDAKBgNVBAGMA05SVzENMAsgA1UEBwwEQm9ubjEg MA4GA1UECgwHRXhxbXBSZTEUMBIGA1UEAwwLZXhhbXBsZS5jb20wHhcNMjcxMTEw MTEwMTEwWbcNMjgxMTEwMTEwMTEwXjBSMQswCQYDVQQGEwJERTEMMAoGA1UECwD TlJXMzQ0CwYDVQQHDAkzY25uMRAwDgYDVQQKDAFeGFTcGx1MRQwEgYDVQQDDAtl eGFTcGx1LmNvbTB6MA0GCSqGSIb3DQEBAQUAA2kAMGYCYQCXVVvPulHVoAHbyzQ6 VrYdGP9a4MZDec2xSIONAoC138eF60wLy5cH4wu750PsoWlZ0pr+evRp9uGmCvn8 njUGN9kiS0LLEW1Nj/Fd7u8YEKRz1B7LpdLK2dqRtwadVAMCAQMwDQYJKoZIhvcN AQELBQADYQBCX1mw+zKScRjY2/09CcBQ6GBa1I+FlGbV6z1xhP/WRsZD/VE2DBhs +1E+JKR5301A53uSmjUz6+PD0eoxw57U3D5eew308x8fd/M4dVe+eftAyculvO8Q q/xPzmX3Pw0= -----END CERTIFICATE----- </pre>
SHA-256 Fingerprint of certificate (base64)	<pre>8EFiLk4taJ0nLtxtvaZrnPxc74X4ePqJ0nvduvDcpxI=</pre>

Step 0: Take the HTTP message

Prepare the unsigned HTTP message.

```
POST /v2/payments/sepa-credit-transfers HTTP/1.1
Host: api.testbank.com
Content-Type: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Mon, 26 Oct 2020 11:24:37 GMT
```

```
{
  "instructedAmount": {"currency": "EUR", "amount": "123.50"},
  "debtorAccount": {"iban": "DE40100100103307118608"},
  "creditor": {"name": "Merchant123"},
  "creditorAccount": {"iban": "DE02100100109307118603"},
  "remittanceInformationUnstructured": ["Ref Number Merchant"]
}
```

Note: The request body is assumed to be a UTF-8 encoded, compact JSON, i.e. without any additional line breaks or spaces, which are only inserted here for better human-readability. However, the API client is free to format the JSON request body (including the ordering of the fields inside the JSON) anyway it likes, as long as the JSON content remains identical. When calculating the digest of the request body, the exact byte sequence as-is has to be taken into account.

Step 1: Create JWS Protected Header

Define the JWS header parameters which define how the signature is created:

"b64": false means don't base64url encode HTTP header data to be signed

"x5t#S256": SHA256 Fingerprint of signing certificate (base64url encoded, i.e. without padding "=" characters)

"crit": ["sigT", "sigD", "b64"]

"sigT": Claimed signing time

"sigD": Defines list of lower case HTTP Header fields to be signed

"alg": "RS256" Signature algorithm

The pretty printed JWS Protected Header reads:

```
{
  "b64": false,
  "x5t#S256": "8EFiLk4taJ0nLttxtvaZrnPxc74X4ePqJ0nvduvDcpxI",
  "crit": [ "sigT", "sigD", "b64"],
  "sigT": "2020-10-26T11:26:57Z",
  "sigD": {
    "pars": ["x-request-id", "digest"],
    "mId": "http://uri.etsi.org/19182/HttpHeaders"
  },
  "alg": "RS256"
}
```

Note: The JWS Protected Header is shown here in a pretty print layout. To keep the JWS Signature slim, it will be sent in the compact serialisation without any line breaks or extra spaces. Escape characters are not used.

The JWS Protected Header above given in compact serialisation reads base64url encoded (recall, that there are no padding characters in base64url encoding):

```
eyJiNjQiOmZhbnHNlLCJ4NXQjUzI1NiI6IjhfFRmlMazR0YUowbkx0eHR2YVpyb1B4Yzc0WDRlUHF
KMG52ZHV2RGNweEkiLCJjcml0IjpbInNpZlQiLCJzaWdEIiwYjY0Il0sInNpZlQiOiIyMDIwLT
EwLTI2VDEuOjI2OjU3WiIsInNpZ0QiOncicGFycyI6WyJ4LXJlcXVlc3QtaWQiLCJkaWdlc3QiX
SwibUlkIjoiaHR0cDovL3VyaS5ldHNpLm9yZy8xOTE4Mi9IdHRwSGVhZGVycyJ9LCJhbGciOiJS
UzI1NiJ9
```

Step 2: Compute Digest of HTTP Body

Calculate the SHA-256 hash of the HTTP Body "as it is" (i.e. payload without HTTP headers and following empty line).

Note: For simplicity, we assume that the request body from the above message is actually sent in the compact format, i.e. without any additional line breaks or spaces, and encoded using UTF-8:

Request body (UTF-8)	{ "instructedAmount":{"currency":"EUR","amount":"123.50"}, "debtorAccount":{"iban":"DE40100100103307118608"}, "creditor":{"name":"Merchant123"}, "creditorAccount":{"iban":"DE02100100109307118603"}, "remittanceInformationUnstructured":["Ref Number Merchant"] }
SHA-256 Hash of the body (base64)	hjZCHu8SHxtkXX0iQMBBaP2Z1zirR731ZXrcZznNI4w=
Value of the HTTP Header "digest"	SHA-256=hjZCHu8SHxtkXX0iQMBBaP2Z1zirR731ZXrcZznNI4w=

Step 3: Create JWS Payload: Collect HTTP Headers to be signed

Create the JWS Payload, that is the string containing the HTTP headers to be signed, as selected using the JWS Protected header parameter sigD, including the HTTP header "Digest".

```
x-request-id: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
digest: SHA-256=hjZCHu8SHxtkXX0iQMBBaP2Z1zirR731ZXrcZznNI4w=
```

Note: Recall from step 2.b) of the description of the JWS Signature Value at the end of section 6.2.2.2 that each line of the HTTP header ends with line feed character (0x0A), but not the last line.

Step 4: Prepare input for Signature Value Computation

Combine the Base64url encoded JWS Protected Header with the JWS Payload (the HTTP Header to be signed), separated by ".", to obtain the signature input:

```
eyJiNjQiOmZhbnHN1LCJ4NXQjUzI1NiI6IjhhFRmlMazR0YUowbX0eHR2YVpyb1B4Yzc0WDRlUHF  
KMG52ZHV2RGNweEkiLCJjcml0IjpbInNpZ1QiLCJzaWdEIiwYjY0I10sInNpZ1QiOiIyMDIwLT  
EwLTl2VDExOjI2OjU3WiIsInNpZ0QiOncicGFycyI6WyJ4LXJlcXVlc3QtaWQiLCJkaWdlc3QiX  
SwibUlkIjoiaHR0cDovL3VyaS5ldHNpLm9yZy8xOTE4Mi9IdHRwSGVhZGVycyJ9LCJhbGciOiJS  
UzI1NiJ9.x-request-id: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721  
digest: SHA-256=hjZCHu8SHxtkXX0iQMBBaP2Z1zirR731ZXrcZznNI4w=
```

Note: The signature input contains exactly one line break before "digest", encoded by the line feed character 0x0A. Other than this, there is no line break in the signature input.

Step 5: Compute JWS Signature Value

Compute the digital signature. As defined in the field “alg” of the JWS Protected Header, the RSA signature over the SHA-256 hash value of the signature input shall be computed.

The Base64url encoded RSA Signature of the example is:

```
PPxyBpcCP8wjDFEODS41c5Ob2G9ZTIfgdxdxqmVtsqpdE57273998pXnaS0HBbxcG0rIhWh
GRWIHi2umxmQOyp0Qiss4P1qqt8l0hv0ZUWWT9XAHBX0TOyLOcJwnxSrf
```

Step 6: Build JSON Web Signature

Compile the compact serialised representation of the JSON Web Signature (with detached JWS Payload) containing the Base64url encoded JWS Protected header and the JWS Signature Value, separated by “..”, i.e. twice the delimiter “.”.

```
eyJiNjQiOmZhbnHN1LCJ4NXQjUzI1NiI6IjhfFRmlMazR0YUowbkx0eHR2YVpyblB4Yzc0WDRlUHF
KMG52ZHV2RGNweEkiLCJjcm10IjpbInNpZ1QiLCJzaWdEIiwYjY0I10sInNpZ1QiOiIyMDIwLT
EwLTlI2VDExOjI2OjU3WiIsInNpZ0QiOmsicGFycyI6WyJ4LXJlcXVlc3QtaWQiLCJkaWdlc3QiX
SwibUlkIjoiaHR0cDovL3VyaS5ldHNpLm9yZy8xOTE4Mi9IdHRwSGVhZGVycyJ9LCJhbGciOiJS
UzI1NiJ9..PPxyBpcCP8wjDFEODS41c5Ob2G9ZTIfgdxdxqmVtsqpdE57273998pXnaS0HBbxcG
0rIhWhGRWIHi2umxmQOyp0Qiss4P1qqt8l0hv0ZUWWT9XAHBX0TOyLOcJwnxSrf
```

Step 7: Insert JSON Web Signature into HTTP Message to form HTTP Signed Message

The HTTP message as sent over the network with the JSON Web Signature inserted reads:

```
POST /v2/payments/sepa-credit-transfers HTTP/1.1
Host: api.testbank.com
Content-Type: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Mon, 26 Oct 2020 11:24:37 GMT
Digest: SHA-256= hjZCHu8SHxtkXX0iQMBBaP2Z1zirR731ZXrcZznNI4w=
x-jws-signature:
eyJiNjQiOmZhbnHN1LCJ4NXQjUzI1NiI6IjhfFRmlMazR0YUowbkx0eHR2YVpyblB4Yzc0WDRlUHF
KMG52ZHV2RGNweEkiLCJjcm10IjpbInNpZ1QiLCJzaWdEIiwYjY0I10sInNpZ1QiOiIyMDIwLT
EwLTlI2VDExOjI2OjU3WiIsInNpZ0QiOmsicGFycyI6WyJ4LXJlcXVlc3QtaWQiLCJkaWdlc3QiX
SwibUlkIjoiaHR0cDovL3VyaS5ldHNpLm9yZy8xOTE4Mi9IdHRwSGVhZGVycyJ9LCJhbGciOiJS
UzI1NiJ9..PPxyBpcCP8wjDFEODS41c5Ob2G9ZTIfgdxdxqmVtsqpdE57273998pXnaS0HBbxcG
0rIhWhGRWIHi2umxmQOyp0Qiss4P1qqt8l0hv0ZUWWT9XAHBX0TOyLOcJwnxSrf

{"instructedAmount": {"currency": "EUR", "amount": "123.50"},
"debtorAccount": {"iban": "DE40100100103307118608"},
"creditor": {"name": "Merchant123"},
```



```
"creditorAccount": {"iban": "DE02100100109307118603"},  
"remittanceInformationUnstructured": "Ref Number Merchant"  
}
```

Note: The request body does not contain any line breaks, nor spaces outside of strings.



7 Security measures for securing (parts of) the message body

7.1 Signing the body

The body of a request or response message may be signed by one or more responsible entities. Who is responsible for signing the body depends on the single use case. The following are possible examples:

- For a request message sent by an API Client to the openFinance API of an ASPSP the body may be signed by one or more PSU.
- For a response message to a request of an API Client the body may be signed by a responsible department or one or more responsible employees of the ASPSP.
- For a request message as part of a pushed-based service the body may be signed by a responsible department or one or more responsible employees of the ASPSP.

Remark:

- Signing the body of a request message for a signed payment request should not be confused with the signing of an HTTP request message according to section 6. Signing the HTTP message according to section 6 will authenticate the API Client sending the request message to openFinance API of the ASPSP. It will not authenticate the PSU and for this reason cannot substitute an SCA of the PSU.
- To distinguish the case of a request message with a signed body (indicating the consent of the PSU) from signed HTTP messages (indicating the proof of origin by the API Client) these request messages with signed bodies will be called in general **signed transaction requests**.
- For the current version, only signed transaction requests sent by the API Client are considered. Signed response messages and push-based request messages with signed body sent by the ASPSP will be described in detail in a future version.

For a signed transaction request further SCA procedures for the strong customer authentication of the PSU involved might not be necessary if the creation of the corresponding signatures is compliant with the requirements for an SCA according to [PSD2] and [EBA-RTS].

It is up to the ASPSP if it supports signed transaction initiation requests at its openFinance API. For some use cases an ASPSP might mandate that the body of a request message sent by an API Client has to be signed by one or more PSUs.

This specification does not define any requirements about the quality of the process to generate the signature for a signed transaction request. It is possible that the ASPSP will define further requirements for this as for example

- special algorithms to be used,
- key length to be used,
- quality of certificates to be used.

Different signature procedures and profiles based on asymmetric and symmetric cryptography will be supported in future by this specification. The phrase "signing a body" will be used regardless if the body will be secured by an electronic signature or an electronic seal based on asymmetric cryptography or by some kind of cryptogram based on symmetric cryptography, as for example an EMV cryptogram generated by a payment card.

7.1.1 Variants for sending signature related data

For a signed transaction request the data necessary for the signature verification has to be sent to the ASPSP by the API Client. The data to be sent for the verification depends on the signature procedure and profile used to create the signature.

For sending the data necessary for the signature verification to an ASPSP the openFinance API Framework currently supports only the **Explicit Authorisation Process** (as defined in section 9). In this case, the HTTP transaction initiation request contains only the request data in its body, while for each signature the necessary data for its verification is sent independently through an (explicit) authorization process. A detailed description is provided in section 7.1.3. Note that it is not necessary that the PSU-signatures needed for the authorisation of the transaction have to be already available at the time the API Client sends the initiation of the transaction to the openFinance API of the ASPSP. It is possible that the signature of a PSU needed for the authorisation of the transaction may be generated by the PSU after the initiation of the transaction. All PSU-signatures needed for the authorisation can be generated by the PSU and sent by the API Client to the openFinance API of the ASPSP at various times after the initiation of the transaction. It might also be that the signatures are applied via different technical API Clients. For this reason, these signatures will be called **distributed signatures**.

RFU: In the future further variants of signed transaction requests might be added to the openFinance API Framework (e.g., multipart HTTP messages transporting all signatures needed for authorising the related transaction).

7.1.2 Signature Profiles supported for signing the request body

The parameters used to indicate and confirm that the authorisation of a transaction request will be done by signatures are defined in the Start Authorisation Process Request and Response in Section 9.4. "Client-SCA-Approach-Preference" and "ASPSP-SCA-Approach" must obtain the value "signature" and the conditional parameters "Body-Sig-Profile-

Preference" and " Body-Sig-Profile-Accepted" must be used to request resp. confirm the signature profile which will be used for the authorisation.

Body-Sig-Profile:

The parameters Body-Sig-Profile-Preference and Body-Sig-Profile-Accepted indicate the signature profile to be used for signing the message body.

Currently the following values are supported by this specification:

JAdES_JS	The body is signed based on [RFC7515] using JWS JSON Serialization taking the requirements of [ETSI TS 119 182-1] for JAdES into account.
XAdES	FOR FUTURE USE ONLY (The body is signed based on [W3C XMLSig] taking the requirements of [ETSI EN 319 132-1] for XAdES into account).
EMV_AC	FOR FUTURE USE ONLY (The body (or parts of it) is secured using an EMV AC cryptogram).
EUDIW	FOR FUTURE USE ONLY (The body (or parts of it) is secured using an EUDI Wallet).

Table 4: Supported signature profiles.

For the beginning, only JAdES_JS will be supported by this specification. Future versions of the specification may support further values for the signature profile.

EMV_AC may be added only if the API will be used in future also for payments, where the SCA of the PSU is based on an EMV_AC cryptogram generated by a payment card of the PSU.

EUDIW will be added only if the EUDI Wallet will be used in future for the authorisation of transactions.

XAdES and the usage of Associated Signature Container (ASiC) will be integrated in future as soon as this requirement has been submitted to the Task Force by a member of the Berlin Group.

Remark:

For signed transaction requests, not all header parameters as defined by section 3.5 may be applicable.

7.1.3 Explicit Authorisation Process (as defined in section 9)

In the case of explicit authorisation, it is assumed that the HTTP Transaction Initiation Request contains only the request data in its body. It is posted to the usual endpoint for the corresponding transaction to be initiated.

The required data for the verification of the signatures is sent separately using the explicit authorisation process. The explicit authorisation process has to be executed for each signature necessary for the authorisation of the transaction. The following picture gives an overview:




Table 5: Flow for signed transaction request with explicit authorisation

Remark:

The above picture and the following description are based on the simplified one-step authorisation process consisting of a single POST request. If required, the longer two-step authorisation process, where the start of authorisation process and the sending of the signature data are split into a POST and a PUT request can be used by the API Client. The ASPSP has to decide whether the one- or two-step authorisation process has to be used by the API client.

7.1.3.1 Requesting the data to be signed

The API client needs to fetch the exact byte sequence to be signed over by the ASPSP to generate a signature that can be verified and to start the authorisation process (see Section

9.4). The specification of the API call to fetch the exact byte sequence to sign is given in this Subsection. Please note that this call might filter some of the data to be signed from the technical resource data.

Note: The request to receive the data that is to be signed is only needed if the signer does not know the byte sequence, i.e. the serialisation format of the body data, to be signed.

Call

```
GET /v2/{resource-path}/{resourceId}?toBeSigned=true HTTP/1.1
Host: api.testbank.com
```

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/{product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /consents {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.

Query Parameters

Attribute	Condition	Description
toBeSigned	Optional if supported by ASPSP	toBeSigned=true The API Client requests the exact representation of the resource, which needs to be signed, e.g. leaving out attributes which had been added by the ASPSP.

Attribute	Condition	Description
		This query parameter is not supported if signatures are not supported as SCA mechanism.

Request Header

No special Request Headers.

Request Body

None.

Response Code

HTTP response code equals 200.

Response Header

No special Response Headers.

Response Body

The body contains the transaction or payment data to be signed “as it is”, i.e. represented as the exact byte sequence that should be signed over.

7.1.3.2 Authorisation process

With the link "startAuthorisationWithTransactionAuthorisation" sent by the ASPSP in the response body to the transaction initiation request, the API Client can start the authorisation process by sending signature data. For details on this please see Section 9.5.

Note: This step has to be repeated by the API Client for each signature of a PSU needed for the authorisation of the transaction.

Note: For the creation of the signature the PSU has to use the signature profile as indicated by the ASPSP with the Body-Sig-Profile-Accepted parameter added to the response message of the transaction initiation.

7.1.3.3 Remark on the two-step variant

In the above section the simplified one-step authorisation process is described. If required, the longer two-step authorisation process, where the start of authorisation process and the sending of the signature data are split into a POST and a PUT request can be used by the API Client.

7.1.3.4 Example

The following example shows the use case "signing a payment transaction" using JSON Web Signature according to [RFC7515]

Step 1: Creating the payment resource

Request:

```
POST /v2/payments/sepa-credit-transfers HTTP/1.1
Host: api.testbank.com
Content-Type: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
PSU-IP-Address: 192.168.8.78
Date: Mon, 26 Oct 2020 11:24:37 GMT
Client-SCA-Approach-Preference: "signature"
Body-Sig-Profile-Preference: "JAdES_JS"

{
  "instructedAmount": {"currency": "EUR", "amount": "123.50"},
  "debtorAccount": {"iban": "DE40100100103307118608"},
  "creditor": {"name": "Merchant123"},
  "creditorAccount": {"iban": "DE02100100109307118603"},
  "remittanceInformationUnstructured": ["Ref Number Merchant"]
}
```

Response:

```
HTTP/1.1 201 Created
ASPSP-SCA-Approach: signature
Body-Sig-Profile-Accepted: JAdES_JS
Content-Type: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

{
  "paymentId": "3d9a81b3-a47d-4130-8765-a9c0ff861100",
  "transactionStatus": "RCVD",
  "links": {
    "startAuthorisationWithTransactionAuthorisation": {
      "href": "/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations"
    }
  }
}
```

Step 2. Fetching the payment resource as it should be signed.

Note: This step is optional.

Request:

```
GET /v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-
a9c0ff861100?toBeSigned=true HTTP/1.1
Host: api.testbank.com
X-Request-ID: 123e4567-e89b-12d3-a456-426614174000
Accept: application/json
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
X-Request-ID: 123e4567-e89b-12d3-a456-426614174000

{
  "instructedAmount": {"currency": "EUR", "amount": "123.50"},
  "debtorAccount": {"iban": "DE40100100103307118608"},
  "creditor": {"name": "Merchant123"},
  "creditorAccount": {"iban": "DE02100100109307118603"},
  "remittanceInformationUnstructured": ["Ref Number Merchant"]
}
```

Note: The response body contains the byte sequence to be signed. Thus, the response body must be signed exactly as it is, eventually including all invisible formatting characters.

Step 3. Submit the signature

Request:

```
POST /v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-
a9c0ff861100/authorisations HTTP/1.1
Host: api.testbank.com
X-Request-ID: e7c8e990-5e3f-4c3f-9b7a-04c6ea843bd3
Content-Type: application/json
```

```
{
  "signatureData": {
    "protected": "eyJhbGciOiJSUzI1NiIsIng1YyI6WyJNSU1CNURDQ0FXNmBd0lCQWdJVUZOSW
hzcG1jN3Z6RHdrWVVMWWR3cGMyRWxLUXdEUUV1KS29aSWh2Y05BUUVMQlFBd1VqRUxNQWtHQTFVR
UJoTUNSRVV4RERBS0JnTlZCQWdNQTA1U1Z6RU5NQXNHQTFVURUJ3d0VRbTl1YmpFUU1BNEdBMVVF
Q2d3SFJYAGhiWEJzWlRFVU1CSUdBMVVFQXN3d3R5YAGhiWEJzWlM1amIyMHdIaGNOTWpjeE1URXh
NVEV4TVRFfEdoY05Namd4TVRFd01URXhNVEV4V2pCU01Rc3dDUVlEVlFRR0V3SkVSVEVNTUFvR0
```



```

ExVUVDQXdEVGxKWE1RMHdDd11EVlFRSERBUkNiMjV1TVJBd0RnWURWUVFLREFkRmVHRnRjR3hsT
VJRd0VnWURWUVFEREF0bGVHRnRjR3hsTG1OdmJUQjZnQTBHQ1Nxr1NjYjNEUUVQCQVFVQUEya0FN
R1lDWVFDWFZWdlB1MUhWb0FIYnl6UTZWcllkr1A5YTRNwRlYzJ4U0lPTkFvQzEzOGVGNjB3THk
1Y0g0d3U3NW9Qc293bHowcHirZXZScDl1R21Ddm44bmpVR045a0lTMExMRVdsTmovRmQ3dThZRU
tSejFCN0xwZExLMMRxUnR3YWRWQU1DQVFNd0RRWUPLb1pJaHZjTkFRRUxCUUFEWVFCQ1gxbXcre
mtTQ3JKWTIvbz1DY0JRNkdCYTFJK0ZsR2JWNnoxGhQLldSc1pEL1ZFMkRCaHMrBEUrSktSNTNP
MUE1M3VTbWpVejYrUEQwZW94dzU3VTNENWVldzNPOHg4ZmQvTTRkVmUrZWZ0QXljdWx2TzhRcS9
4UHptWDNQdzA9Il0sInNpZ1QiOiIyMDIwLTUwLTI2VDExOjI2OjU3WiIsInN1YiI6IjNkOWE4MW
IzLWE0N2QtNDEzMzY1LWE5YzBmZjg2MTEwMCJ9",
"signature": "ND2HOiK8njIS4POik4Pl09dY9vWysdctFVrD_qSJ-
Sm3KCbMdGzzrtmzHBz9Me121t2mYN7ymcOsdWR8t7pDLF-A6lzoTgGxq0-
9f07sAifGOEkEnb2V_YPgLTkX4-JW"
}
}

```

Response:

HTTP/1.1 201 Created

X-Request-ID: e7c8e990-5e3f-4c3f-9b7a-04c6ea843bd3

Content-Type: application/json

```

{
  "authorisationId": "550e8400-e29b-41d4-a716-446655440000",
  "scaStatus": "finalised"
}

```

Remark: For convenience we reproduce here the JWS protected header and the certificate data used in the above example.

Throughout this example we use the following RSA key pair and X.509 certificate. Note that the same certificate is used in Example 6.2.3 and all disclaimers mentioned there apply here as well.

Private Key in PEM format	<pre> -----BEGIN RSA PRIVATE KEY----- MIIBBygIBAAJhAJdVW8+7UdWgAdvLNDpWth0Y/1rgxkN5zbFIg40CgLXfx4XrTAvL lwfjC7vmg+yjCXPsmv569Gn24aYK+fyeNQY32QhLQssRaU2P8V3u7xgQpHPUHsU 0srZ2pG3Bp1UAwIBAwJgGTjkop84TkVVPkHeCbkeWi7VodAhCz73nYwV7NXAHk/2 llHiAfdD1qXSFvAp3CBUbGQc24xkEouDPiFcpA0nWZ+9nRmTGmcRgFBDDqldcib BdJowHxEpmTaaRkotgWvAjEAw+MXENWny6naL+7enr/DMav86hvXfZC3i91SX1cb /L5vQqRMtEu40sQ4XH3dWWinAjEAxcYhORAJPI/zKEj6rn02JCTiV3UFGwcIHAsY tTf0yJ6TDkFdlHB+EbiDvqI0/8lFAjEAgpdktePFMnE8H/SUadUsy8f98Wfk/mB6 XT426j0SqH701xgzIt014dglkv6TkPBvAjEA91re2AXfbVMxYX8dFN5bW3sOk4D rK9avnIQeM/4hb8MtCuTuEr+tnsCfxbN/9uDAjEAwPFsVMxZVD5AQRt+3sg78RdI BJ0JiaqBNpJwAX2jIKvzr1SgtbvxnTERT7hVv12E -----END RSA PRIVATE KEY----- </pre>
---------------------------	--

Certificate (including the Public Key) in PEM format	<pre> -----BEGIN CERTIFICATE----- MIIB5DCCAW6gAwIBAgIUFNHspmc7vzDwkYUfYdwpc2ElKQwDQYJKoZIhvcNAQEL BQAwUjELMAkGA1UEBhMCREUxDDAKBgNVBAGMA05SVzENMA5GA1UEBwwEQm9ubjEQ MA4GA1UECgwHRXhhbXBsZTEUMBIGA1UEAwwLZXhhbXBsZS5jb20wHhcNMjcMTEx MTEwMTEwWhcNMjcMTExMTEwMTEwWjBSMQswCQYDVQQLGwJERTEEMMAoGA1UECAwD TlJXMQ0wCwYDVQQHDARCB25uMRAwDgYDVQQKDAdFeGFtcGx1MRQwEgYDVQQDDAt1 eGFtcGx1LmNvbTB6MA0GCsGCSiB3DQEBAAQUAA2kAMGYCYQCXVVvPu1HV0AHbyzQ6 VrYdGP9a4MZDec2xSIONAoC138eF60wLy5cH4wu75oPsowlz0pr+evRp9uGmCvn8 njUGN9kIS0LLEWlNj/Fd7u8YEKRz1B7LpdLK2dqRtwadVAMCAQMwDQYJKoZIhvcN AQELBQADYQBCX1mw+zkSCrJY2/o9CcBQ6GBa1I+FlGbV6z1xhP/WRsZD/VE2DBhs +1E+JKR5301A53uSmjUz6+PD0eoxw57U3D5eew308x8fd/M4dVe+eftAyculvO8Q q/xPzmX3Pw0= -----END CERTIFICATE----- </pre>
--	--

JWS Protected Header in pretty format:

```

{
  "alg": "RS256",
  "x5c": [
    ["MIIB5DCCAW6gAwIBAgIUFNHspmc7vzDwkYUfYdwpc2ElKQwDQYJKoZIhvcNAQELBQAwUjELMAkGA1UEBhMCREUxDDAKBgNVBAGMA05SVzENMA5GA1UEBwwEQm9ubjEQMA4GA1UECgwHRXhhbXBsZTEUMBIGA1UEAwwLZXhhbXBsZS5jb20wHhcNMjcMTExMTEwMTEwWhcNMjcMTExMTEwMTEwWjBSMQswCQYDVQQLGwJERTEEMMAoGA1UECAwDTlJXMQ0wCwYDVQQHDARCB25uMRAwDgYDVQQKDAdFeGFtcGx1MRQwEgYDVQQDDAt1eGFtcGx1LmNvbTB6MA0GCsGCSiB3DQEBAAQUAA2kAMGYCYQCXVVvPu1HV0AHbyzQ6VrYdGP9a4MZDec2xSIONAoC138eF60wLy5cH4wu75oPsowlz0pr+evRp9uGmCvn8njUGN9kIS0LLEWlNj/Fd7u8YEKRz1B7LpdLK2dqRtwadVAMCAQMwDQYJKoZIhvcNAQELBQADYQBCX1mw+zkSCrJY2/o9CcBQ6GBa1I+FlGbV6z1xhP/WRsZD/VE2DBhs+1E+JKR5301A53uSmjUz6+PD0eoxw57U3D5eew308x8fd/M4dVe+eftAyculvO8Qq/xPzmX3Pw0="],
    "sigT": "2020-10-26T11:26:57Z",
    "sub": "3d9a81b3-a47d-4130-8765-a9c0ff861100"
  ]
}

```

7.1.4 Note: Above the JWS protected header is shown in pretty format. In the above example it is used without breaks and extra spaces. Signing the body using JAdES_JS

Only detached JWS signatures in the sense of appendix F of [RFC7515] shall be used. Moreover, only JWS JSON Serialisation using the flattened syntax according to section 7.2.2 of [RFC7515] shall be used.

Notes:

- The flattened syntax will be used since all needed signatures are transported in different steps as single signature to the authorisation endpoint.
- If more than one signature is needed for the authorisation, these signatures are considered as independent signatures and not as counter signatures. If one signature has to be protected by another signatures, counter signatures as described in section 5.3.2 of [ETSI TS 119 182-1] shall be used.

Each flattened detached JWS is the following JSON structure:

Element	Type	Condition	Description
protected	String	Mandatory	Base64URL encoded JWS Protected Header. BASE64URL(UTF8(JWS Protected Header))
header	String	Optional	Content of the JWS Unprotected Header.
signature	String	Mandatory	Base64URL encoded JWS Signature. BASE64URL(JWS Signature)

Table 6: JSON structure of a JWS

For this JWS the element "payload" (with the value BASE64URL(JWS Payload)) is omitted as mandated by appendix F of [RFC7515] for detached signatures. Though, of course, this element is used for the generation and verification of the signature.

Note: [RFC7515] assumes JWS Payload and JWS Signature to be in binary form and JWS Protected Header and JWS Unprotected Header to be strings.

JWS Protected Header

The JWS Protected Header is mandatory, i.e. the element protected shall be part of the JWS. It shall contain at least the following sub elements:

Element	Type	Condition	Description
alg	String	Mandatory	Identifier of the algorithm used for the creation of the signature according to [RFC7518]. Examples: RS256, PS256

Element	Type	Condition	Description
x5c	Array of String	{Or	The "x5c" (X.509 certificate chain) Header Parameter contains the X.509 public key certificate or certificate chain corresponding to the key used to generate the signature. The certificate or certificate chain is represented as a JSON array of certificate value strings. Each string in the array is a base64-encoded (not base64url-encoded) DER PKIX certificate value. The certificate containing the public key corresponding to the key used to generate the signature MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one. The recipient MUST validate the certificate chain according to RFC 5280 and consider the certificate or certificate chain to be invalid if any validation failure occurs.
x5u	String	Or	The "x5u" (X.509 URL) Header Parameter is a URI that refers to a resource for the X.509 public key certificate or certificate chain corresponding to the key used to generate the signature. The identified resource MUST provide a representation of the certificate or certificate chain that conforms to RFC 5280 in PEM-encoded form, with each certificate delimited as specified in Section 6.1 of RFC 4945. The certificate containing the public key used to generate the signature MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one. The protocol used to acquire the resource MUST provide integrity protection; an HTTP GET request to retrieve the certificate MUST use TLS; and the identity of the server MUST be validated, as per Section 6 of RFC 6125.
x5t#S256	String	Or}	SHA-256 hash value of the certificate corresponding to the key used to generate the signature.
sigT	DateTime	Mandatory	Claimed signing time. The time shall be UTC (ending in "Z") and shall indicate date and time to the second.

Element	Type	Condition	Description
sub	String	Conditional	Id of the resource (e.g. paymentId, consentId etc) received by the API client in the response to the transaction initiation request. This element shall be included if the id of the resource to be protected already exists.
jti	String	Conditional	Unique identifier of this signature according to [RFC7519]. This element shall not be included if the element sub is included.

Table 7: JSON structure of a JWS Protected Header

Remarks:

- The ASPSP can mandate algorithms to be supported for the creation of a signature.
- One of the elements x5u, x5c, and x5t#S256 shall be contained in the JWS Protected Header.
- The ASPSP may define further restriction for the content of the elements x5u, x5c, and x5t#S256. For example, the ASPSP may require that the element x5c is contained and that this element contains only the certificate itself but not the complete certificate chain.
- Only one of the elements sub and jti shall be contained in the JWS Protected Header.
- Further elements defined in section 5.1 and 5.2 of [ETSI TS 119 182-1] may be included. The ASPSP may define additional requirement on these elements, i.e. that an element shall be included or that an element shall not be included.
- All additional requirements defined by the ASPSP have to be described by the ASPSP specific documentation.
- It depends on the (security) policy of the ASPSP which of these elements and how these elements are verified by the ASPSP.

JWS Unprotected Header

The JWS Unprotected Header is optional, i.e. the element “header” may be missing. If the element “header” exists in the JWS, it shall contain only one sub element “etsiU” according to section 5.3.1 of [ETSI TS 119 182-1].

If a signature A has to be secured by another signature B, i.e. a counter signature according to [ETSI TS 119 182-1], the JWS representing the counter signature B shall be enclosed in the unprotected header of the JWS representing the signature A. In this case the sub element “etsiU” of the element “header” (containing the JWS unprotected header) shall contain the element “sigC” containing the JWS representing the counter signature.

JWS Signature

The signature is calculated over the string

$$\text{ASCII}(\text{BASE64URL}(\text{UTF8}(\text{JWS Protected Header})) \parallel '.' \parallel \text{BASE64URL}(\text{JWS Payload}))$$

using the private key corresponding to the certificates prescribed by the elements x5c, x5u, or x5t#S256, and using the algorithm identified by the element alg.

Note: Recall that [RFC7515] assumes JWS Payload to be in binary form. In our case this is the UTF8 encoded JSON structure as it send by the ASPSP’s server using the “toBeSigned” parameter.

7.1.5 Signing the body using XAdES

RFU: Not supported for the current version of the openFinance Framework. Support will be added as part of future versions.

7.1.6 Signing the body using EMV_AC

RFU: Not supported for the current version of the openFinance Framework. Support will be added as part of future versions.

7.1.7 Signing the body using EUDIW

RFU: Not supported for the current version of the openFinance Framework. Support will be added as part of future versions.

7.2 Encryption of (parts of) the body

Parts of a body or the complete body of a request or response message can be encrypted, if the body is JSON or XML encoded.

For the support of the encryption of (parts of) the body of a message the following holds.

- An ASPSP may support the encryption or decryption of (parts of) the body of a request or response message optionally.
- An ASPSP shall encrypt (parts of) a response message to be sent to an API Client only if the API Client accepts encrypted (parts of the) message bodies.

- An ASPSP shall encrypt (parts of) a request message to be sent to an API Client as part of a pushed-based service only if the API Client accepts encrypted (parts of the) message bodies.
- An API Client shall support the encryption of (parts of) a body of a request message to be sent to an ASPSP.
- An API Client shall encrypt (parts of) the body of a request message to be sent to an ASPSP if this is requested by an ASPSP.
- An API Client may support the decryption of (parts of) a body of a response message receive from an ASPSP optionally.
- For pushed-based services: An API Client may support the decryption of (parts of) a body of a request message receive from an ASPSP or the encryption of (parts of) a body of a response message to be sent to an ASPSP optionally.

Remark:

API access schemes may define further requirements.

7.2.1 Overview

Encryption of (part of) the body of an http (request or response) message will be based on the specification of

- JSON Web Encryption ([RFC7516]) for the case of JSON encoded bodies,
- XML Encryption [XML ENC] for the case of XML encoded bodies.

For JSON encryption:

- If the complete body of the message will be encrypted the complete plain text content of the body will be replaced by a JWE data structure representing the encrypted (and integrity) protected content of the body.
- If only an attribute of a body of the message will be encrypted the plain text content of this attribute will be replaced by a JWE data structure representing the encrypted (and integrity protected) content of the attribute.

For XML encryption:

- If the complete body of the message will be encrypted the complete plain text content of the body will be replaced by an XML element representing the encrypted (and integrity protected) content of the body.

- If only an element of a body of the message will be encrypted the plain text content of this element will be replaced by an XML element representing the encrypted (and integrity protected) content of the element.

Remark: The protection of the integrity of the encrypted content depends on the algorithm used for the encryption. If A256GCM is used the integrity of the content is protected in addition to the encryption of the content.

Only key encryption will be used as key management mode. A randomly generated CEK (content encryption key) is used for the encryption of the plain text using a symmetric encryption algorithm. A public key of the receiver is used for the encryption of the CEK using an asymmetric encryption algorithm.

For the current version of this specification only the following encryption algorithms may be used (see also [RFC7518] and [XML ENC]):

- A256GCM/AES256-GCM: Symmetric AES using the Galois/Counter mode of operation for the encryption of the plain text. For this the CEK shall be a 256-bit AES key.
- RSAES-OAEP: Asymmetric RSA with OAEP padding for the encryption of the CEK. MGF1 with SHA-1 mask generation function shall be used.

For JSON encryption only JWE Compact Serialisation according to section 3.1 of [RFC7516] is used.

Remark: It is possible that an ASPSP or a scheme mandates the support and usage of further encryption algorithms.

7.2.2 Extension to the http message

7.2.2.1 Path

None.

7.2.2.2 Query parameters

None.

7.2.2.3 Header parameters

If (parts of) the body contains encrypted information the following header parameters may be added to the header of the HTTP request or response message:

Attribute	Type	Condition	Description
Body-Enc-Profile	String	Conditional	Indicates the encryption profile used for the encryption of (parts of) the body.
Body-Enc-List	List of names	Optional	Contains a List of names of data elements/ attributes of the body which contain encrypted information.

Table 8: Header parameters to indicate the encryption of (parts of) the body.

Body-Enc-Profile

This parameter indicates the profile used for the encryption of (parts of) the message body. Currently only the values

- JWE_CS for "JSON Web Encryption using Compact Serialization" and
- XML_ENC for "XML Encryption" are supported.

Future versions of the specification may support further values for the encryption profile.

Note: This header parameter shall exist if encryption of the body or parts of the body is used.

Body-Enc-List

This parameter indicates which of the data elements/attributes of the body contain encrypted content. Example: ["password"]. If this parameter equals ["BODY"], the complete body of the message will be encrypted.

Note, that the body might also contain encrypted fields even if this parameter is missing. For example, the name of a data element/attribute may by itself indicate that the content is encrypted, like for example the attribute encryptedPassword.

7.2.2.4 Body

If the header parameter Body-Enc-List contains the name of a data element/attribute of the message body or if the name of a data element/attribute indicates that the content has to be encrypted, the plain text content of this data element/attribute has to be exchanged by

- (in the case of JSON encoding) the JWE built over the plain text content of that data element/attribute as described in section 7.2.3, or

- (in the case of XML encoding) the EncryptedElementTag element build based on the plain text content of that element as described in section 7.2.5.

If the header parameter Body-Enc-List equals ["BODY"] the plain text of the complete body has to be exchanged by

- (in the case of JSON encoding) the JWE built using the complete plain text content of the message body as described in section 7.2.3, or
- (in the case of XML encoding) the EncryptedBody element build based on the plain text XML body as described in section 7.2.5.

For JSON encoding encryption can only be used for special attributes for which the message definition allows strings without further restrictions.

For XML encoding encryption can only be used for special elements for which the message definition allows the EncryptedElementTag element as content without further restrictions.

7.2.3 How to build a JWE

For the current version of this specification only Compact Serialisation according to section 3.1 of [RFC7516] is used. In this case the JWE is a string built by the concatenation of the following base64url encoded elements:

BASE64URL(UTF8(JWE Protected Header)) || '.' ||

BASE64URL(JWE Encrypted KEY) || '.' ||

BASE64URL(JWE Initialisation Vector) || '.' ||

BASE64URL(JWE Ciphertext) || '.' ||

BASE64URL(Authentication Tag)

The single elements are built as follows:

JWE Protected Header

The JWE Protected Header is a JSON structure with the following elements:

Element	Type	Condition	Description
alg	String	Mandatory	Algorithm to be used for the encryption of the content encryption key (CEK). For the current version of this specification only the value RSAES-OAEP is supported.

Element	Type	Condition	Description
enc	String	Mandatory	Algorithm to be used for the encryption of the plain text using the CEK. For the current version of this specification only the value A256GCM is supported.
x5c	JSON Array	{Or	The "x5c" (X.509 certificate chain) Header Parameter contains the X.509 public key certificate or certificate chain corresponding to the key used to encrypt the CEK. The certificate or certificate chain is represented as a JSON array of certificate value strings. Each string in the array is a base64-encoded (not base64url-encoded) DER PKIX certificate value. The certificate containing the public key corresponding to the key used to the encrypt the CEK MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one. The recipient MUST validate the certificate chain according to RFC 5280 and consider the certificate or certificate chain to be invalid if any validation failure occurs.
X5u	URI	Or}	The "x5u" (X.509 URL) Header Parameter is a URI that refers to a resource for the X.509 public key certificate or certificate chain corresponding to the key used to encrypt the CEK. The identified resource MUST provide a representation of the certificate or certificate chain that conforms to RFC 5280 in PEM-encoded form, with each certificate delimited as specified in Section 6.1 of RFC 4945. The certificate containing the public key used to encrypt the CEK MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one. The protocol used to acquire the resource MUST provide integrity protection; an HTTP GET request to retrieve the certificate MUST use TLS; and the identity of the server MUST be validated, as per Section 6 of RFC 6125.

Table 9: JSON structure of a JWE Protected Header.

Remarks:

- One of the elements x5u or x5c shall be contained in the JWE Protected Header.
- The ASPSP may define further restriction for the content of the elements x5u and x5c. For example, the ASPSP may require that the element x5c is contained and that this element contains only the certificate itself but not the complete certificate chain. These additional requirements have to be described by the ASPSP specific documentation.

JWE Encrypted Key

The sender of the message shall generate a random content encryption key (CEK). This CEK shall be usable with the algorithm indicated by the element "enc" as part of the JWE protected header.

For the current version of this specification the CEK shall be a 256-bit AES key.

The JWE Encrypted Key equals the encrypted CEK with the algorithm indicated by the element "alg" as part of the JWE protected header using the public key of the receiver of the message. JWE Initialisation Vector

The sender of the message shall generate a random JWE Initialisation Vector. This initialisation vector shall be usable with the algorithm indicated by the element "enc" as part of the JWE protected header.

For the current version of this specification the JWE Initialisation Vector shall be a 96 bit long random value. JWE Ciphertext

The plain text of the complete body or of the data element/attribute of the body has to be encrypted with the CEK using the encryption algorithm given by the element "enc" of the JWE Protected Header. For the current version of this specification only A256GCM is supported, i.e. the Galois/Counter mode of operation [GCMencryp]. By this the plain text is not only encrypted but also integrity protected.

For the Galois/Counter mode of operation "additional authenticated data" (AAD) is needed. This is defined by the following:

$$\text{AAD} = \text{ASCII}(\text{BASE64URL}(\text{UTF8}(\text{JWE Protected Header})))$$

JWE Authentication Tag

The output of the Galois/Counter mode of operation of the AES algorithm delivers not only the ciphertext but also a 128-bit long authentication tag. This 128-bit output has to be used as JWE Authentication Tag.



7.2.4 JWE Example

Assume a request that contains the request headers

```
Body-Enc-Profile: JWE_CS
Body-Enc-List: "[\"psuData.password\"]"
```

And the request body:

```
{
  "psuData": {
    "password": "topSecret!"
  },
  "authenticationMethodId": "myAuthenticationID"
}
```

Thus, the field *psuData.password* shall be encrypted and its value replaced by a JWE object.

In this example, the RSAES-OAEP algorithm is used to encrypt the CEK and A256GCM to encrypt the message. The JWE Protected Header reads then, using a certificate with a 2048-bit RSA key:

```
{
  "alg" : "RSAES-OAEP",
  "enc" : "A256GCM",
  "x5c" : [
    "MIIDQDCCAiiGAWIBAgIUHZkszryIWtfJzrjogCnf8CsBQ0cwDQYJKoZIhvcNAQELBQAwKTEncMCUGA1UEAwweRXhhbXBsZSBSU0FFUy1PQUVQIENlcnRpZmljYXRlMB4XDTE2MDcxNDEyMzM0NloXDTE2MDcxMTEyMzM0NlowKTEncMCUGA1UEAwweRXhhbXBsZSBSU0FFUy1PQUVQIENlcnRpZmljYXRlMIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAu9Rq1NTnsKATbkM3yzB37wUSIad1CLpBGm3Zjp5USCNMM1DAJ/WwY2t4US7uc4ehq5UYec3DtXaWSfyfthMoaSIyCpyBp7NdRHtdl3mZJoKZOvyOslss3luzzIjRQWm+FOTKozEZR8Nuh5h95KXLRjsngjFyyIyuVeT0kq7RR119PEyDAeonKHSh0f0tdUnsn+yoVYhtYveD0zp4CgGVOfPMAESiyAtt681T2deW5iPtDu4CJ24mZsSHlBNIXcDwFc5QPrvKhY9cQMbu7Nx3zvQYxL9T7LrQAN+7E7zobzH/IkuljmYnGYVWonzX+1Kn49KMM4K5RkRCT79vovjIQIDAQABo2AwXjAdBgNVHQ4EFgQURvAi/QdKaOh3pL6k1RwDX0Eb4ngwHwYDVR0jBBGwFoAURvAi/QdKaOh3pL6k1RwDX0Eb4ngwDwYDVR0TAQH/BAUwAwEB/zALBgNVHQ8EBAMCBDAwDQYJKoZIhvcNAQELBQADggEBACzno34yT2uWcOMc2jy89vOG3Xmshs88hpwW0RCdBEiwd1A6s4VSlyDuTjW8cK7NDM3meIE/J8LU2dEhs4+kRoYURpaSRqtBxJuBgxURVoD08otvR9CfdGMYq2CPItJ24HEU6QD91KvAfFMWFeYNRGOACAIcBCB2Aj9qzzqYSffcomuT40FMLc+7w792505i0JnqX0M9ogc6oFb+ziAW8GTJPMsU7NuFAxoJsPmkEKAcZj+ZkrmElpRZwGkpyGMwKlB1tds0MG1qunvqq+jSD3Cl0njbJoC8YRRP9hlo9IRplPIanTU9WhXo5X1557ud5HtMkkUXV2sOxnF1wWA+uEE="]
  ]
}
```

This object reads in compact form and base64url encoded:

eyJhbGciOiJSU0FFUy1PQUVQIiwizW5jIjoiQTI1NkdDTSIsIng1YyI6WyJNSU1CNURDQ0FXNmdb01CQWdJVUZOSWhzcG1jN3Z6RHdrWVVmWWR3cGMvRWxLUXdEUUV1KS29aSW2Y05BUUVMQ1FBd1VqRUxNQWtHQTFVRUJoTUNSRVV4RERBS0JnTlZCQWdNQTA1U1Z6RU5NQXNHQTFVRUJ3d0VRbTl1YmpFUU1BNEdBmVVFQ2d3SFJYaGhiWEJzWlRFVU1CSUdBmVVFQX3dTFpYaGhiWEJzWlMlamIyMHdIaGNO TWpjeE1URXhNVEV4TVRFfEdoY05Namd4TVRFd01URXhNVEV4V2pCU01Rc3dDUV1EV1FRR0V3SkVSEVNTUFvR0ExVUVDQXdeVGxKWE1RMHdDd1lEV1FRSERBUkNiMjV1TVJBd0RnWURWUVFLREFkRmVRnRjR3hsTVJRd0VnWURWUVFEREF0bGVHRnRjR3hsTG1OdmJUQjZnQTBHQ1Nxr1NjYjNEUUVQVFQUEya0FNR1lDWVFDWFZWdlB1MUhWb0FIYn16UTZWcllkR1A5YTRNWkR1YzJ4U01PTkFvQzEzOGVGNjB3THk1Y0g0d3U3NW9Qc293bHowcHIrZXZScDl1R21Ddm44bnpVR045a0lTMExMRVdsTmovRmQ3dThZRUtSejFCN0xwZExLMmRxUnR3YWRWQU1DQVFNd0RRWUpLb1pJaHZjTkFRRUxCUUFEWVFCQ1gbXcremtTQ3JKWTIvbz1DY0JRNkdCYTFJK0ZsR2JWNnoxeGhQLldSc1pEL1ZFMkRCaHMrbEUrSkNTNPMUE1M3VTbWpVeJYrUEQwZW94dzU3VTNENWVldzNPOHg4ZmQvTTRkVmUrZWZ0QXljdWx2TzhRcS94UHptWDNQdzA9I119

The following AES-256 key (given in hexadecimal representation) is used as CEK:

f604e0076d51bfeed13bc62c2329b8f6a809bbb5260f5c6f0e6eba441a4a2e4

and reads encrypted with the example certificate given in the JWE Protected Header above (base64url encoded):

hW46qozvo8mIs_nmJjKoktx0LErnBMn6eazu0YXG6FjD3syXKY_syf50wa5NRdKG7GATDbZW7rh0nBRvl3RGgLxpuM3ZHD_jiPkeN8SLDhYvZ7hesdjoeEZYd6nGU8fC-5GGpoY3uWxYXo9jLz-6wgQt
iuWwMlRIjqhFpNj5ht1CUiwAHcfPt5F7ARdSAsR-Hdi9RJcjhgI2mb408MO0G8Hq7LDe8H1n5tRMlkjsDFK_5gU-dMJ7uxTCE5G8HL1ShU79hI-zq1eL4GO4D1Jfm02zGs40Fb6Vn9RvNzJjCBSMGkj9eefrLxEqCaWvFCtDqxS4oD7YuKfawo3Rrn09-w

Note, that the cipher is non-deterministic, i.e. when encrypting the same CEK with the same certificate, the outcome will be different cipher.

The initialisation vector used in this example is (base64url encoded):

r50zuVJ4bnwmJBXH

Using these parameters and the base64url encoded JWS Protected Header as AAD, the JWE Ciphertext is (base64url encoded)

4AGrTHnM8Z7cfw

and the authentication tag is (base64url encoded)

Kld8 J1ditTiEetDrHwVaw

Combining everything together, the request message with the value of “password” replaced by the JWE (in compact serialisation) is

Body-Enc-Profile: JWE CS

Body-Enc-List: "[\\"psuData.password\\"]"

```
{
  "psuData": {
    "password":
```

"eyJhbGciOiJSU0FFUy1PQUVQIiwiaWZwZW5jIjoiQTI1NkdDTSI8Ing1YyI6WyJNSU1CNURDQ0FXNm
dB

d01CQWdJVUZOSWhzcG1jN3Z6RHdrWVvmWWR3cGMyRWxLUXdEUVlKS29aSWh2Y05BUUVMQ1FBd1V
q

RUxN9WtHQTFVRUJ0TUNSRVV4RERBS0JnTlZCQWdNQTA1U1Z6RU5NQXNHQTFVRUJ3d0VRbTl1Ymp
F

UU1BNEdBmVVFQ2d3SFJYaGhiWEJzWlRFVU1CSudBMVVFQXd3TFpYaGhiWEJzWlMlamIyMHdIaGN
O

TWpjjeE1URXhNVEV4TVRFeFdoY05Namd4TVRfFd01URXhNVEV4V2pCU01Rc3dDUVlEVlFRR0V3Skv
S

VEVNTUFvR0ExVUVDQXdEVGxKWE1RMHdDdl1lEVlFRSERBUkNiMjV1TVJBd0RnWURWUVFLREFkRmV
H

RnRjR3hsTVJRd0VnWURWUVFEREF0bGVHRnRjR3hsTG1OdmJUQjZnQTBHQ1N×R1NJYjNEUUVQCQVF
V

QUEya0FNR11DWVDFWfZWd1B1MUhWb0FIYn16UTZWc11kR1A5YTRNWkR1YzJ4U01PTkFvQzEzOGV
G

```

NjB3THk1Y0g0d3U3NW9Qc293bHowcHIrZXZScDl1R21Ddm44bmpVR045a0lTMExMRVdsTmovRmQ
3

dThZRUtSejFCN0xwZExLMmRxUnR3YWRWQU1DQVFNd0RRWUpLb1pJaHZjTkFRRUxCUUFEWVFCQ1g
x

bXcremtTQ3JKWTIvbz1DY0JRNkdCYTFJK0ZsR2JWNnoxGhQLldSc1pEL1ZFmKRCaHMrbEUrSkt
S

NTNPMUE1M3VTbWpVeJYrUEQwZW94dzU3VTNENWVldzNPOHg4ZmQvTTRkVmUrZWZ0QX1jdWx2Tzh
R

cS94UHptWDNQdzA9Il19.hW46qozvo8mIs_nmJjKoktx0LErnBMn6eazu0YXG6FjD3syXKY_syf
5

0wa5NRdKG7GATDbZW7rh0nBRvl3RGgLxpuM3ZHD_jiPkeN8SLDhYvZ7hesdjoeEZYd6nGU8fC-
5G

    GpoY3uWxYXo9jLz-6wgQtIUWwMlRIjqhFpNj5ht1CUiwAHcfPt5F7ARdSAsR-
Hdi9RJcjhgI2mb4
    08MO0G8Hq7LDe8H1n5tRMlkjsDFK_5gU-dMJ7uxTCE5G8HL1ShU79hI-
zq1eL4GO4DlJfM02zGs4
    0Fb6Vn9RvNzJjCBSMGkj9eefrLxEqCaWvFCtDqxS4oD7YuKfawo3Rrn09-
w.r9kzuVJ4bnwmJBXH
    .4AGrTHnM8Z7cfw.Kld8_JlditTiEetDrHwVaw"
  },
  "authenticationMethodId": "myAuthenticationID"
}

```

7.2.5 How to build an EncryptedBody or EncryptedElementTag element

If the complete body has to be encrypted the corresponding encrypted body has the following content:

```

<EncryptedBody>
  <EncryptedData>
    See below
  </EncryptedData>
  <EncryptedKey ID="ID_CEK">
    See below
  </EncryptedKey>
</EncryptedBody>

```

Table 10: Elements of an encrypted XML message body

If an element with the tag `ElementTag` has to be encrypted the corresponding encrypted element has the following content:

```
<EncryptedElementTag>
  <EncryptedData>
    See below
  </EncryptedData>
  <EncryptedKey ID="ID_CEK">
    See below
  </EncryptedKey>
</EncryptedElementTag>
```

Table 11: Elements of an encrypted XML element with tag `ElementTag`

Element `EncryptedData`

This element contains the encrypted data and shall contain the following:

```
<EncryptedData>
  <EncryptionMethod Algorithm="URI_encryptionAlgorithm" />
  <KeyInfo>
    <RetrivalMethod URI="#ID_CEK"
      Type="http://www.w3.org/2001/04/xmlenc#EncryptedKey" />
  </KeyInfo>
  <CipherData>
    <CipherValue>
      Base 64 coded cipher value of the encrypted content
    </CiperValue>
  </CipherData>
</EncryptedData>
```

`URI_encryptionAlgorithm` identifies the (symmetric encryption) algorithm which has been used for the calculation of the cipher value using the symmetric CEK (content encryption key). This CEK can be retrieved from the element `EncryptedKey` identified by `"ID=ID_CEK"`.

`URI_encryptionAlgorithm` = <http://www.w3.org/2009/xmlenc11#aes256-gcm> has to be supported, i.e. AES encryption with 256-bit CEK using the Galois/Counter mode of operation for the encryption of the plain text. An ASPSP can mandate the usage of another algorithm.

Element EncryptedKey

This element contains the encrypted CEK (content encryption key) and shall contain the following:

```
<EncryptedKey ID="ID_CEK">
  <EncryptionMethod Algorithm="URI_CEK_encryptionAlg" />
  <KeyInfo>
    <X509Data>
      <X509Certificate>
        base64 coded X.509 encryption certificate
      </X509Certificate>
    </X509Data>
  </KeyInfo>
  <CipherData>
    <CipherValue>
      Base 64 coded cipher value of the encrypted CEK
    </CipherValue>
  </CipherData>
</EncryptedKey>
```

URI_CEK_encryptionAlg identifies the (asymmetric encryption) algorithm which has been used for the calculation of the cipher value of the CEK using the public key of the receiver of the message. X.509 certificate identifying this public key is contained in the sub-element KeyInfo.

URI_CEK_encryptionAlg = <http://www.w3.org/2001/04/xmlenc#rsa-oeap-mgf1p> has to be supported, i.e. RSA-OAEP encryption using MGF1 with SHA-1 mask generation function. An ASPSP can mandate the usage of another algorithm.

The element X509Data shall contain the X.509 certificate containing the public key of the receiver of the message used to encrypt the CEK.

7.2.6 Exchange of certificates with public encryption keys

For the encryption of (parts of) the body of an HTTP-message it is necessary that the sender of the message knows the public key of the receiver of the message to be used to encrypt the CEK to be used for the encryption of the content. This public key has to be exchanged as part

of a corresponding certificate over this public key. The openFinance API Framework supports two different mechanisms to exchange these encryption certificates.

Exchange of the certificate within an attribute of a message body:

A message may contain the following attribute if the sender of this message wishes that the receiver of this message will encrypt (parts of) the body of following messages:

Attribute	Type	Condition	Description
encryptionCertificate	String	Optional	The certificate to be used by the receiver for encryption of (parts of) the body of a following message

The attribute encryptionCertificate contains the X.509 public key certificate or certificate chain corresponding to the public key to be used to encrypt the CEK for the encryption of (parts of) the body of following messages. The certificate or certificate chain is represented as a JSON array of certificate value strings. Each string in the array is a base64-encoded (**not** base64url-encoded) DER PKIX certificate value. The certificate containing the public key corresponding to the key used to encrypt the CEK **MUST** be the first certificate. This **MAY** be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one.

The ASPSP may define further restrictions such that this attribute may contain only the certificate of the public key itself but not a certificate chain.

Exchange using a special link to the certificate:

The "_links" attribute of a message may contain the following special link if the sender of this message wishes that the receiver of this message will encrypt (parts of) the body of following messages:

Attribute	Type	Condition	Description
_links	String	Optional	May contain the following special link: "encryptionCertificates": {"href":...}

The href-link is an URI that refers to a resource for the X.509 public key certificate or certificate chain corresponding to the public key to be used to encrypt the CEK for the encryption of (parts of) the body of following messages. The identified resource **MUST** provide a representation of the certificate or certificate chain that conforms to RFC 5280 in PEM-encoded form, with each certificate delimited as specified in Section 6.1 of RFC 4945. The certificate containing the

public key to be used for the encryption of the CEK MUST be the first certificate. This MAY be followed by additional certificates, with each subsequent certificate being the one used to certify the previous one.



8 Strong customer authentication of a PSU

Remark: The term PSU is used for the user of a services even in the case of services which are not related to a payment service.

8.1 Optional Usage of OAuth2 for PSU Authentication or Authorisation

The XS2A API respectively the openFinance APIs will allow an ASPSP to implement OAuth2 as a support for the authorisation of the PSU towards the API Client for several services. In this case, the API Client will be the client, the PSU the resource owner and the ASPSP will be the resource server in the abstract OAuth2 model.

This specification supports two ways of integrating OAuth2. The first support is an authentication of a PSU in a pre-step, translating this authentication into an access token to be used at the XS2A interface or openFinance API afterwards. This usage of OAuth2 will be referred to in this specification as "if OAuth2 has been used as PSU authentication". Further details shall be defined in the documentation of the ASPSP of this XS2A interface or openFinance API.

Remark: When implementing the OAuth pre-step, the requirements on e.g. registration steps or no mandatory two SCA application in specific PIS only scenarios as defined by [EBA-OP2] should be recognised by the ASPSP.

The second option to integrate OAuth2 is an integration as an OAuth2 SCA Approach to be used for authorisation of transactions. In all services, OAuth2 will in this option be used in an integrated way, by using the following steps:

Integrated OAuth for the authorisation of transactions which are reflected as resources in the related services endpoints of the API:

- 1.) The transaction data is posted to the corresponding service endpoint of the XS2A API resp. the openFinance API. This service endpoint might be extended by a product-type, e.g. sepa-credit-transfers in the case of the /payments endpoint.
- 2.) The OAuth2 protocol is used with the "Authorization Code Grant" flow to get the authorisation of the PSU for the related transaction, while using the "scope" attribute in OAuth2 to refer to the data from Step 1.).
- 3.) The corresponding transaction is then automatically initiated by the ASPSP after a successful authorisation by the PSU, if no further interaction between API Client and ASPSP is required.

NOTE: For AIS services, the API Client needs to get a consent resource authorised first via the routine described above. The API Client then can use the access token received during the OAuth2 protocol to access the related accounts endpoint for authorised account information for the validity period of the authorised consent resp. the validity period of the technical access token.

For Step 2.), details are described in Section 8.8.

When using OAuth2, the XS2A API or openFinance API calls will work with an access token instead of using the PSU credentials.

8.2 Header Parameter for PSU Context Data

The following data elements are forwarding information about the interface between PSU and API Client to enhance the risk management procedures of the ASPSP integrated into SCA resp. SCA exemption procedures. It is **strongly recommended** to send these data elements within all Transaction Initiation Requests, that involve PSU authentication, e.g. in Payment Initiation Requests.

Header parameters as defined in this section will not be repeated in the implementation guidelines of service specifications to enhance document readability, but the implementation guidelines will refer to this document in the relevant sections. However, the detailed specifications of service calls via the related OpenAPI files will still contain all applicable headers.

The only exception is where conditions other than "optional" apply on specific request messages, e.g. for the PSU IP Address. More details might be provided in the data overview within service definitions.

Attribute	Format	Condition	Description
PSU-IP-Address	String	Conditional	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. Conditions will be defined within service specifications, If applicable.
PSU-IP-Port	String	Optional	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.
PSU-Accept	String	Optional	The forwarded IP Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.
PSU-Accept-Charset	String	Optional	see above
PSU-Accept-Encoding	String	Optional	see above
PSU-Accept-Language	String	Optional	see above

Attribute	Format	Condition	Description
PSU-User-Agent	String	Optional	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.
PSU-Http-Method	String	Optional	HTTP method used at the PSU – TPP interface, if available. Valid values are: • GET • POST • PUT • PATCH • DELETE
PSU-Device-ID	String	Optional	UUID (Universally Unique Identifier) or IMEI for a device, which is used by the PSU, if available. UUID/IMEI identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.
PSU-Geo-Location	Geo Location	Optional	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.

Note: Information about the interface between PSU and API Client might be used by the ASPSP as input for his fraud detection and risk management systems. Some ASPSPs use this information also to exclude certain authentication methods (for example some ASPSPs do not allow to receive an OTP by SMS on the same smartphone used also for the transaction itself). In addition, the ASPSP might need to receive specific device related information to be able to support an optimised app-2-app redirection procedure for the API Client. For these reasons it is highly recommended that an API Client includes all of this information in the related Transaction Initiation Request messages. Missing information may result in an assessment of the user device as not useable for the authentication method or in a classification of the current transaction as a "higher risk transaction" e.g. due to session attacks. By this, the probability of a rejection of that transaction due to the result of fraud detection and/or risk management might be increased.

Remark: These requirements do not apply in a "direct access" scenario, where no third party provider is involved and where the ASPSP can detect the related information directly from the then PSU/ASPSP interface.

8.3 Header Parameters for PSU Identification Data

The openFinance API Framework supports the transmission of PSU identification data within request parameters for all Transaction Initiation Request messages. The ASPSP might mandate these elements, which then needs to be reflected in the related ASPSP documentation.

Header parameters as defined in this section will not be repeated in the implementation guidelines of service specifications to enhance document readability, but the implementation guidelines will refer to this document in the relevant sections. However, the detailed specifications of service calls via the related OpenAPI files will still contain all applicable headers.

Attribute	Type	Condition	Description
PSU-ID	Max140Text	Conditional	Client ID of the PSU in the ASPSP client interface. Might be mandated in the ASPSP's documentation. It might be contained even if an Oauth2 based authentication was performed in a pre-step. In this case the ASPSP might check whether PSU-ID and token match, according to ASPSP documentation.
PSU-ID-Type	Max35Text	Conditional	Type of the PSU-ID; needed in scenarios where PSUs have several PSU-IDs as access possibility. In this case, the mean and use are then defined in the ASPSP's documentation.
PSU-Corporate-ID	Max140Text	Conditional	Identification of a Corporate in the Online Channels Might be mandated in the ASPSP's documentation. Only used in a corporate context.
PSU-Corporate-ID-Type	Max35Text	Conditional	This is describing the type of the identification needed by the ASPSP to identify the PSU-Corporate-ID content as used in online channels. Typically, this is a proprietary definition. Mean and use is defined in the ASPSP's documentation. Only used in a corporate context.

Note: If the ASPSP is mandating PSU identification related attributes, then the ASPSP needs to assure to be compliant with related sections from [EBA-OP2] if PSD2 compliance related services are addressed.

Note: The ASPSP might support special characters for PSU identification in their client interfaces. To support this on API level, the recommended character set for PSU identification related header parameters is ISO8859-1 based. In addition to the plain ISO8859-1 encoding following the HTTP specification, the ASPSP might offer a Base64 encoding. In the latter variant, this results in the following expression:

```
=?ISO-8859-1?B?<Base64 coded ISO-8859-1 String>?=
```

An UTF-8 encoding of header parameters used by the API Client thus might lead to rejections with Message Code PSU_CREDENTIALS_INVALID.

Deviations from these recommendations should be documented in detail by the ASPSP.

8.4 Header Parameters for strong customer authentication

Header parameters as defined in this section will not be repeated in the implementation guidelines of service specifications to enhance document readability, but the implementation guidelines will refer to this document in the relevant sections. However, the detailed specifications of service calls via the related Open API files will still contain all applicable headers.

8.4.1 Request Header Parameters Steering SCA Approaches

The following request headers might be used by an API Client in a Transaction Initiation Request or Change Transaction Resource Request to communicate SCA preferences to the ASPSP for transaction authorisation.

Attribute	Type	Condition	Description
Client-SCA-Approach-Preference	Max35Text	Optional	A comma separated list of attributes, where the first entry will have a higher priority than the next or to every SCA Approach which is not indicated at all, e.g. "decoupled, redirect, embedded" or "decoupled". The possible SCA approaches are: EMBEDDED

Attribute	Type	Condition	Description
			• DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE This attribute may be ignored by the ASPSP.
Body-Sig-Profile-Preference	Max35Text	Conditional	Indicates the preferred signature profile used for signing (parts of) the body. Shall be used if the list of preferred SCA approach includes "signature".
Client-Redirect-URI	String	Conditional	URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach. See Section 8.7 for further requirements on this header. It is recommended to always use this header field.
Client-Nok-Redirect-URI	String	Optional	If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the Client-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP. See Section 8.7 for further requirements on this header.
Client-Explicit-Authorisation-Preferred	Boolean	Optional	If it equals "true", the API Client prefers to start the authorisation process separately, e.g. because of the usage of a signing basket or because of asynchronous authorisation. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality or if asynchronous authorisation is not supported. If it equals "false" or if the parameter is not used, there is no preference of the API Client. This especially indicates that the API Client assumes a direct authorisation of the transaction in the next step, without using a signing basket.

8.4.2 Related Response Headers

The following header is used by the ASPSP to transmit decisions of the chosen SCA Approach to the third party.

Attribute	Type	Condition	Description
ASPSP-SCA-Approach	String	Conditional	This data element must be contained, if the SCA Approach is already fixed. Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE The OAuth SCA approach will be subsumed by REDIRECT.
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

8.5 Embedded SCA Approach

The Embedded SCA Approach is defined as the scenario where all PSU credentials are transmitted via the XS2A API resp. the openFinance API. PSU identification data are transported using the related header parameters as defined in Section 8.3. After a Transaction Initiation Request and Response, an authorisation sub-resource is either implicitly generated by the ASPSP or needs to be explicitly created by the API Client in a next step, cp. Section 9.1.

The API calls to create an authorisation sub-resource as well as the API calls to transmit PSU credentials to the related authorisation resource within an Embedded SCA Approach are defined in Section 9.4 and Section 9.5. The specific functions to be used will always be indicated by related hyperlinks presented by the ASPSP before.

8.6 Decoupled SCA Approach

The Decoupled SCA Approach differs from the Embedded SCA Approach by using an ASPSP authentication app for the strong customer authentication and dynamic linking if applicable. The app is used by the PSU also for authentication of transaction in the online channels. Since the XS2A API resp. the openFinance API is not involved in this app authentication, no authentication specific API support is defined in this case.

NOTE: A more standardised security profile based on re-direct like the FAPI CIBA profile are not supported yet by the openFinance API Framework.

As a hybrid between Embedded and Decoupled SCA approach, the ASPSP might require the PSU to transmit a first factor (a password) first via the XS2A API resp. the openFinance API and only afterwards authentication with a second factor via the Decoupled Approach. The transmission of the password is handled as in the Embedded SCA Approach via the related authorisation sub resource and the API calls defined in Section 9.4. Such an implementation would still be called a Decoupled SCA Approach in the openFinance API Framework.

8.7 Redirect SCA Approach

In the Redirect SCA Approach, the TPP will at some point receive a "scaRedirect" link in the response from the ASPSP. The link leads to an authorisation page related to the transaction to be authorised and to the TPP must redirect the PSU agent to that link as a next step. When accessing the page, the PSU will authenticate himself with the related PSU credentials, review the presented information of the transaction and can finalise the authorisation from there. When the authorisation has been finalised by the PSU, the PSU agent is redirected again by the ASPSP to the Client-Redirect-URI, which has been submitted within the related Transaction Initiation Request. If the authorisation was not successful, the ASPSP may use the Client-Nok-Redirect-URI submitted in the same call, if supported.

Refer to Section 5.3 for requirements on TPP redirection links.

NOTE: The "scaRedirect" link may include query parameters. Due to definitions for a potential later confirmation flow, cp. Section 9.8.2.2, ASPSPs shall not include a query parameter named "state" in their "scaRedirect" links. Such a parameter is reserved for the TPP to be used for session control.

Remark for Future: For migration reasons, this specification mandates the TPP to keep the Client-Redirect-URI used within all authorisation processes for a specific transaction during the lifecycle of this transaction constant. This might be removed in the next version of the specification.

8.8 OAuth SCA Approach

The OAuth SCA approach is similar to the redirect SCA approach but the redirection to the authentication server of the ASPSP is embedded into the OAuth2 protocol, for details see [oFA-OR-FW]. The OAuth2 protocol as used optionally for this API is defined in [RFC6749]. In this section, additional requirements on the protocol are defined. The related protocol shall be used by the TPP, if the ASPSP is transmitting the link of type "scaOAuth".

NOTE: A more standardised security profile based on re-direct like the FAPI PAR profile are not supported yet by the openFinance API Framework.

The requirements on the data exchange between the TPP and the OAuth Server of the ASPSP regarding the transport layer are identical to the data exchange requirements between TPP and the XS2A Interface resp. the openFinance API, cp. Section 5 .

Note: Specifically, the requirements on using MTLS also apply to the usage of the OAuth2 protocol. However, the general requirements on the application layer such as e.g. signing of Requests (see Section 6) do not apply to the OAuth2 messages.

The response type "code" and the grant types "authorization_code" and "refresh_token" are recommended by this specification. It is further strongly recommended to TPPs and ASPSPs to follow the security best practices defined in [OA-SecTop].

Note: In case of the OAuth SCA Approach, the TPP has to generate in addition a nonce for the challenge parameter. This has also to be bound to the session of the user agent.

The ASPSP is required to provide API Clients with configuration data conforming to the "OAuth 2.0 Authorisation Server Metadata" specification and potentially oAuthAdditionalParameters.

8.8.1 Authorization Request

For the "authorization request" (see [RFC6749], section 4.1.1) to the OAuth2authorization endpoint provided in the Server Metadata, the following parameters are defined:

Query Parameters

Attribute	Condition	Description
response_type	Mandatory	"code" is recommended as response type.
client_id	Mandatory	organizationIdentifier as provided in the eIDAS certificate. PSD2 related access clients, the organizationIdentifier attribute shall contain information using the following structure in the presented order: - "PSD" as 3 character legal person identity type reference; - 2 character ISO 3166 country code representing the NCA country; - hyphen-minus "-" and - 2-8 character NCA identifier (A-Z uppercase only, no separator) - hyphen-minus "-" and - PSP identifier (authorization number as specified by NCA).

Attribute	Condition	Description
		For the usage in the context of premium services, a related API Access Scheme might define other requirements.
scope	Mandatory	PIS: The scope is the reference to the payment resource in the form "PIS:<paymentId>". Cancel-PIS: The scope is the reference to the payment cancellation in the form "Cancel-PIS:<paymentId>". Note: Cancel-PIS is an optional scope which the ASPSP can decide to use (whether it does must be specified in the ASPSP documentation). If they do so, it must also be used by the TPP for payment cancellation, and the PIS scope then refers only to payment authorisation. AIS: The scope is the reference to the consent resource for account access in the form "AIS:<consentId>" PIIS: The scope is the reference to the consent resource for granting consent to confirmation of funds in the form "PIIS:<consentId>". Signing Basket Services: The scope is the reference to the signing basket resource for authorisation of a bundle of access functions in the form "SB:<basketId>". Subscriptions: The scope is the reference to the subscription resource or subscription entry sub-resource in the form "SUB:<subscriptionId>" resp. "SUB-E"<subscriptionId>-<entryId>" Mandate Services: The scope is the reference to the mandate resource in the form "MAN:<resoruceld>", where the resoruceld is the resource identification of the related mandate. Document or RTP Services: The scope is the reference to the consent resource for document services in the form "DOC:<consentId>".

Attribute	Condition	Description
		User Services: The scope is the reference to the consent resource for user parameter access in the form "USR:<userResourceId>." Note: The resource ids chosen by the ASPSP need to be unique to avoid resource conflicts during the SCA process.
state	Mandatory	A dynamical value set by the TPP and used to prevent XSRF attacks.
redirect_uri	Mandatory	the URI of the TPP where the OAuth2 server is redirecting the PSU's user agent after the authorization.
code_challenge	Mandatory	PKCE challenge according to cryptographic [RFC7636] used to prevent code injection attacks.
code_challenge_method	Optional	Code verifier transformation method, is "S256" or "plain". "S256" is recommended by this specification.

Example

```
GET /authorize?response_type=code&client_id=PSDES-BDE-3DFD21 &
scope=ais%3A3d9a81b3-a47d-4130-8765-a9c0ff861100+offline_access&
state= S8NJ7uqk5fY4EjNvP_G_FtyJu6pUsvH9jsYni9dMAJw&
redirect_uri=https%3A%2F%2Fclient%2Eexample%2Ecom%2Fcb&
code_challenge_method="S256"
code_challenge=5c305578f8f19b2dcdb6c3c955c0aa709782590b4642eb890b97e43917cd
0f36 HTTP/1.1
Host: api.testbank.com
```

8.8.2 Authorization Response

The Authorization Response (see [RFC6749], section 4.1.2) of the ASPSP will deliver the following data:

Remark: As the request is not sent by the TPP but the PSU user agent, it will not be secured by the TPP's QWAC.

http Response Code

302

Query Parameters

Attribute	Condition	Description
Location:	Mandatory	redirect URI of the API Client
code	Mandatory	Authorisation code
state	Mandatory	Same value as for the request.

Example

HTTP/1.1 302 Found

Location: `https://client.example.com/cb`
`?code=Sp1xl0BeZQQYbYS6WxSbIA`
`&state=S8NJ7uqk5fY4EjNvP_G_FtyJu6pUsvH9jsYni9dMAJw`

8.8.3 Access Token Request

As described in [RFC6749], section 4.1.3, the TPP sends a POST request to the token endpoint in order to exchange the authorization code provided in the authorization response for an access token and, optionally, a refresh token. The following parameters are used:

Request Parameters

Attribute	Condition	Description
grant_type	Mandatory	"authorization_code" is recommended as response type.
client_id	Mandatory	cp. Definition in Section 8.8.1
code	Mandatory	Authorization code from the authorization response
redirect_uri	Mandatory	the exact uri of the TPP where the OAuth2 server redirected the user agent to for this particular transaction
code_verifier	Mandatory	PKCE verifier according to cryptographic [RFC7636] used to prevent code injection attacks.

Example

```
POST /token HTTP/1.1
Host: https://api.testbank.com
Content-Type: application/x-www-form-urlencoded
client_id=PSDES-BDE-3DFD21
&grant_type=authorization_code
&code=Sp1xl0BeZQQYbYS6WxSbIA
&redirect_uri=https%3A%2F%2Fclient%2Eexample%2Ecom%2Fcb
&code_verifier=7814hj4hjai87qqhjz9hahdeu9qu771367647864676787878
```

The TPP is authenticated during this request by utilising "OAuth 2.0 Mutual TLS Client Authentication and Certificate Bound Access Tokens" (see [RFC 8705]) in conjunction with the TPP's eIDAS certificate.

8.8.4 Access Token Response

The ASPSPS responds with the following parameters:

Response Parameters

Attribute	Condition	Description
access_token	Mandatory	Access Token bound to the scope as requested in the authorisation request and confirmed by the PSU.
token_type	Mandatory	Set to "Bearer"
expires_in	Optional	The lifetime of the access token in seconds
refresh_token	Optional	Refresh Token, which can be utilised to obtain a fresh access tokens in case the previous access token expired or was revoked. Especially useful in the context of AIS.
scope	Mandatory	the scope of the access token

Example

HTTP/1.1 200 OK

```
Content-Type: application/json
Cache-Control: no-store
```

Pragma: no-cache

```
{
  "access_token": "SlAV32hkKG",
  "token_type": "Bearer",
  "expires_in": 3600,
  "refresh_token": "tGzv3JokF0XG5Qx2TlKWIA",
  "scope": "exampleScope"
}
```

8.8.5 Refresh Token Grant Type

The ASPSP may issue refresh tokens at its discretion, e.g. if an AISP uses the standard scope value "offline_access" or if the recurringIndicator is set to true.

8.8.6 API Requests

When using the OAuth SCA approach, subsequent API requests are being authorised using the respective OAuth Access Token. The Access Token is sent to the API using the "Authorization" Header and the "Bearer" authorization scheme as defined in RFC 6750.

This is an example API request

```
GET /psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-
a9c0ff861100/status HTTP/1.1
Host: https://api.testbank.com
Authorization: Bearer SlAV32hkKG
```

8.9 ASPSP Channel SCA Approach

The ASPSP might offer to authorise a transaction **not** within the session

- started with the first resource data submission of the ASPSP within a Transaction Initiation procedure, or
- started with the POST /authorisations request

but instead later in other authorisation channels of the ASPSP like the online channels.

This SCA approach is addressed by the API Client by using the term "ASPSP-CHANNEL" in the attribute "Client-SCA-Approach-Preference".¹

¹ This SCA approach is added to support extended services, where asynchronous SCA approaches are provided. This is not supposed to be supported for compliance services under PSD2 which cover synchronous authorisation processes only.

NOTE: The new ASPSP-SCA-Approach "ASPSP-CHANNEL" might be changed later on dynamically to e.g. "Redirect" by the API Client in case of re-starting the authorisation procedure explicitly via the API. It just sticks to "ASPSP-SCA-Approach", if the related transaction is authorised in a different authorisation channel of the ASPSP (e.g. online channel).

8.10 Signature SCA Approach

The Signature SCA Approach is defined to be the SCA approach, where the PSU is providing a digital signature on transaction data submitted to the ASPSP. After a Transaction Initiation Request and Response, an authorisation sub-resource is either implicitly generated by the ASPSP or needs to be explicitly created by the API Client in a next step, cp. Section 9.1.

The API calls to create an authorisation sub-resource as well as the API calls to transmit the digital signature to the related authorisation resource within a Signature SCA Approach are defined in Section 7.1.3.2 and Sections 7.1.4 to 7.1.7. The specific functions to be used will always be indicated by related hyperlinks presented by the ASPSP before.



9 Authorisation Processes used commonly in all Services

Many business transactions need authorisation processes to be initiated via the openFinance API resp. the XS2A API. Authorisation processes include PSU authentication supported in the openFinance API Framework via the different SCA approaches as defined in Section 8. A very specific business transaction is a cancellation process for a transaction resource via the API where in some cases (e.g. payment initiation) also an authorisation process via SCA by the PSU might be mandated.

These authorisations are reflected in the openFinance API Framework in two perspectives:

- The impact of an authorisation process on an existing transaction resource, which will lead to new sub-resources of the addressed transaction resource as defined in Section 9.1 and 9.2.
- The impact on access methods for the related authorisation or cancellation authorisation endpoints as defined in Section 9.3 ff.

The description in this section is generic by defining the access methods in detail but abstractly. The related endpoints will not be documented in the implementation guidelines of service specification to enhance document readability. However, detailed specifications including the authorisation endpoints will be available via the related OpenAPI files.

Remark: The API design differs across the various SCA approaches (Embedded, Signature, Redirect, OAuth2 or Decoupled, cp. Section 8), but mostly between the Embedded and Signature SCA Approaches and all other approaches, since these two SCA approaches demand the support of the full SCA complexity within the API itself. For that reason, all data or processes which are only needed for the Embedded SCA Approach and the Signature SCA Approach are shown in a light blue background, to increase the readability of the specification.

9.1 Authorisation Endpoints


The openFinance API Framework is supporting dedicated authorisation endpoints in order to handle transaction authorisation by PSUs. These authorisation endpoints are supporting the following features in a common structured way

- multiple level SCA, where a transaction needs an authorisation by more than one PSU, e.g. in a corporate context,
- signing of a group of transactions with one SCA, as it is offered by ASPSPs today in online banking, cp. the definition of signing baskets in Section 10
- signing of a group of transactions with multi-level SCA, where this group of transactions need an authorisation by more than one PSU, e.g. in a corporate context.

To support this, the resources resulting from the submission of transaction data, like payment data or consent data are separated from authorisation (sub-)resources. For example, payment which needs to be signed n times then will end up in a payment resource with n SCA (sub-)resources in a normal successful process.

The optional function of grouping several transactions for one common authorisation process is supported by the signing-baskets endpoint, which might be offered by the ASPSP. If this function is offered by an ASPSP, the API Client can first submit transaction data without starting the authorisation. After having grouped the related transaction resources by using a grouping command through the signing-baskets endpoint, the authorisation then can be started by authorising this basket content. This results in a basket resource with the corresponding authorisation sub-resource.

The following picture gives an overview on the abstract data model for the different scenarios in the example of a payment:



Remark: When offering the signing basket function, the ASPSP might restrict the grouping e.g.

- to payments as such,
- to individual payments,
- to the same payment product.

This restriction on groupings will then be detailed in the ASPSP's documentation.

Note: The grouping of transaction is only a "signing vehicle", bundling authorisation processes for the grouped transactions. The authorisation rules for transactions can be very complex in a corporate context. The signing basket gets the status of being fully authorised as soon as all grouped transactions have been successfully authorised by the applied SCA mechanism. A transaction with less authorisation requirements might then be authorised earlier than the whole signing basket and also already processed. In addition, single transactions of the signing basket could be authorised with additional SCAs directly on transaction level, depending on the implementations of the ASPSPs – the signing basket is a non-exclusive mechanism to bundle authorisations. Current implementations of this functionality differ in Europe, specifically in a corporate context. For this reason, more complex functionality as DELETE processes on partially authorised signing baskets are not supported yet.

Remark for Future: The upcoming versions of the specification might implement more advanced functionality of the signing basket function and cancellation processes around it.

Optimisation process for the submission of e.g. single payments

The general model introduced above requires the API Client to start two sub-processes when initiating a transaction. For example, in a payment initiation of a sepa credit transfer this would result in

```
POST /payments/sepa-credit-transfers {payment data}
```

which is generating the payment resource and returns paymentId as a resource identification.

```
POST /payments/sepa-credit-transfers/paymentId/authorisations
```

is then starting the authorisation process with creating an authorisation sub-resource and returning an authorisationId for addressing this sub-resource in the following.

Applying this requirement to all authorisations of transactions e.g. in the Redirect SCA Approach would significantly augment the calls on the resulting API. For this reason, this specification still enables the ASPSP to directly start e.g. a Redirect SCA processing after the submission of transaction data, like e.g. a payment or a consent, if no other data from the API Client has to be submitted anyhow. In this case, the ASPSP will create the related authorisation sub-resources automatically and will give access to these sub-resources to the API Client by returning corresponding hyperlinks, cp. Section 3.7. As a consequence, the authorisation status would still be provided by submitting the command

```
GET /payments/sepa-credit-transfers/paymentId/authorisations/authorisationId,
```

where the authorisation resource with identification authorisationId has been created by the ASPSP implicitly.

9.2 Transaction Cancellation Endpoints e.g. for Payments

The openFinance API Framework is supporting the cancellation of strongly protected resources, like payment initiations or payment authorisations by PISPs. This process is divided into two steps:

1. DELETE the corresponding resource.
2. Start an authorisation process for the cancellation by the PSU where needed by submitting a


`POST payments/sepa-credit-transfers/paymentId/cancellation-
authorisations`

command.


The second step might be omitted, where a dedicated authorisation of the cancellation is not foreseen by the ASPSP. The need to authorise the cancellation will be communicated by sending corresponding hyperlinks to the API Client, cp. Section 3.7.

In the two-step approach, this cancellation process will be handled by cancellation-authorisation sub-resources in analogy to the actual authorisations. The authorisation sub-resources will stay unchanged. The following picture shows the changes on resource level in case of a scheduled payment:


Data model for a scheduled single payment with one SCA



Data model for a scheduled single payment which has been cancelled, where a customer authorisation was needed for cancellation



Data model for a scheduled single payment which has been cancelled, where no dedicated customer authorisation was needed for cancellation



The corresponding original authorisation sub-resources stay unchanged.

For transactions, where a multilevel SCA is needed for authorisation, also a multilevel SCA might be needed for cancellation, depending on ASPSP role management. In equivalence to authorisation, the model would then be extended by more cancellation sub-resources.

NOTE: The logic of cancellation sub resources will apply also to other transactions, where a cancellation via the API Client requires a cancellation authorisation by the PSU.

9.3 Access Methods for Authorisations

Processes on starting authorisations, update PSU identification or PSU authentication data and explicit authorisation of transactions by using SCA are very similar in all services. The API calls supporting these processes are described in the following independently from the service/endpoint. These processes usually are used following a hyperlink of the ASPSP. The usage is defined at the beginning of the following sections. The API access methods are provided only in a schematic way in this document. The related OpenAPI files will provide the actual access methods by instantiating the term {resource-path}/{resourceId} with the addressed service, product types, where applicable, and the correct resource identification.

Thus, the following API access methods are supported for authorisation processes.

Endpoints/Resources	Method	Condition	Description
{resource-path}/{resourceId}/authorisations	POST	Mandatory	Create an authorisation sub-resource and start the authorisation process, might in addition transmit authentication and authorisation related data. This method is iterated n times for an n times SCA authorisation in a corporate context, each creating an own authorisation sub-endpoint for the corresponding PSU authorising the transaction. The ASPSP might make the usage of this access method unnecessary in case of only one SCA process needed, since the related authorisation resource might be automatically created by the ASPSP after the submission of the resource data with the first POST {resource-path} call. Section 9.4.
{resource-path}/{resourceId}/authorisations	GET	Mandatory	Read a list of all authorisation sub-resources IDs which have been created. Section 9.6.

Endpoints/Resources	Method	Condition	Description
{resource-path}/{resourceId}/authorisations/{authorisationId}	PUT	Mandatory for Embedded SCA Approach and Signature SCA Approach, Conditional for other approaches	Update data on the authorisation resource if needed. It may authorise a payment within the Embedded SCA Approach or Signature SCA Approach where needed. Independently from the SCA Approach it supports e.g. the selection of the authentication method and a non-SCA PSU authentication. Section 9.4.1, Section 9.5.
{resource-path}/{resourceId}/authorisations/{authorisationId}	PUT	Conditional for Redirect or OAuth SCA Approach	Update the authorisation resource with a confirmation code to counter potential session attacks, where supported by ASPSPs. Section 9.8.
{resource-path}/{resourceId}/authorisations/{authorisationId}	GET	Mandatory	Read the SCA status of the authorisation. Section 9.7.
{resource-path}/{resourceId}/authorisations/{authorisationId}	DELETE	Optional	Cancel the authorisation resource if the authorisation of the underlying resource is not completed yet. Section 9.10

Endpoints/Resources	Method	Condition	Description
{resource-path}/{resourceId}/cancellation-authorisations	POST	Optional	Starts the authorisation of the cancellation of the addressed resource with resource identification resourceId if mandated by the ASPSP (i.e. the DELETE access method is not sufficient) and if applicable to the related service, and received in product related timelines (e.g. before end of business day for scheduled payments of the last business day before the scheduled execution day). NOTE: Such a cancellation authorisation for now only applies to payments. But the openFinance API Framework allows to apply it to any other service. Section 9.4.
{resource-path}/{resourceId}/cancellation-authorisations	GET	Optional	Retrieve a list of all created cancellation authorisation sub-resources. If the POST command on this endpoint is supported, then also this GET method needs to be supported. Section 9.6.
{resource-path}/{resourceId}/cancellation-authorisations/{authorisationId}	PUT	Mandatory for Embedded SCA Approach, Signature SCA Approach, Conditional for other approaches	Update data on the cancellation authorisation resource if needed. It may authorise a cancellation of the payment within the Embedded SCA Approach or Signature SCA Approach where needed. Independently from the SCA Approach it supports e.g. the selection of the authentication method and a non-SCA PSU authentication. Section 9.4.1 and Section 9.5.

Endpoints/Resources	Method	Condition	Description
{resource-path}/{resourceId}/cancellation-authorisations/{authorisationId}	GET	Mandatory	Read the SCA status of the cancellation authorisation. Section 9.7.
{resource-path}/{resourceId}/cancellation-authorisations/{authorisationId}	DELETE	Optional	Cancel the authorisation resource if the authorisation of the underlying resource is not completed yet. Section 9.10

Remark for Future: The PUT HTTP methods might be adapted to technical PATCH methods in a future version of the specification. A corresponding decision will reflect current market practices and the work in ISO TC68/SC9/WG2 on Financial API services.

9.4 Start Authorisation Process

Usage

If the further processing of a resource reflecting a business transaction (e.g. a payment) requires an authorisation of one or more PSUs, each authorisation is represented by an authorisation sub-resource of that resource, cp. also Section 9.1 for the example of payment initiation. This transaction resource has been created after the submission of Transaction Initiation Request, cp. Section 2.2.5.

In some cases, an authorisation by the PSU is required, when an already existing and authorised resource is to be cancelled. Currently, the only occasion of that situation is the cancellation of a payment. In such a case, a "Transaction Cancellation Request" (with corresponding "Transaction Cancellation Response") has been sent by the API Client for an already existing resource. This leads to a situation, where a "Cancellation-Authorisation" will be created to represent the authorisation of the cancellation of the existing resource by the PSU. Therefore, the Cancellation-Authorisation resources also are sub-resources of the "Transaction" resource itself, cp. Section 9.2.

The "start authorisation process" is the process which creates a new authorisation or cancellation-authorisation sub-resource. The related sub-resource is reflecting the PSU authentication steps as authorisation process or cancellation authorisation process of the PSU. Please note that all the processes and conditions are identical for authorisations and cancellation-authorisations. The only difference appears in their respective names and effects

on the underlying resource. The "start authorisation process" appears in the following scenarios:

- The ASPSP has indicated with a "startAuthorisation" hyperlink in the preceding Transaction Initiation Response, Transaction Cancellation Response or a Change Transaction Resource Request that an explicit start of the authorisation process is needed by the API Client. The "startAuthorisation" hyperlink can transport more information about data which needs to be uploaded by using the extended forms
 - "startAuthorisationWithPsuIdentification",
 - "startAuthorisationWithPsuAuthentication",
 - "startAuthorisationWithEncryptedPsuAuthentication",
 - "startAuthorisationWithAuthentciationMethodSelection"
 - "startAuthorisationWithTransactionAuthorisation".
- The related business transaction or business transaction cancellation cannot yet be executed since a multilevel SCA is mandated.

Call

POST /v2/{resource-path}/{resourceId}/{authorisation-category}

Starts an authorisation process or a cancellation authorisation process for the business transaction reflected by the resource identified with resourceId, depending on the authorisation category `authorisations` or `cancellation-authorisations`.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/{product-type}, where • {service} stands for the service type of the related business transaction, e.g. /payments or /consents • {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.

Attribute	Type	Description
authorisation-category	String	The following two categories are supported: <code>authorisations</code>: used in case of an authorisation of the related business transaction. <code>cancellation-authorisations</code>: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
If-Match	UUID	Optional if supported by the ASPSP	If used, this field must contain the ETag of the changed variant of the resource.
PSU-ID	String	Conditional	Client ID of the PSU in the ASPSP client interface. Shall be transmitted if this Request is indicated by "startAuthorisationWithPsuIdentification" or "startAuthorisationWithPsuAuthentication" or "startAuthorisationWithEncryptedPsuAuthentication" and this field has not yet been transmitted before.
PSU-ID-Type	String	Conditional	Type of the PSU-ID, needed in scenarios where PSUs have several PSU-IDs as access possibility. Shall be transmitted in this case, if this Request is indicated by "startAuthorisationWithPsuIdentification" or "startAuthorisationWithPsuAuthentication" or

Attribute	Type	Condition	Description
			"startAuthorisationWithEncryptedPsuAuthentication" and this field has not yet been transmitted before.
PSU-Corporate-ID	String	Conditional	Identification of a Corporate in the Online Channels. Shall be transmitted if this Request is indicated by "startAuthorisationWithPsuIdentification" or "startAuthorisationWithPsuAuthentication" or "startAuthorisationWithEncryptedPsuAuthentication" and this field has not yet been transmitted before, and only where generally needed in a corporate context.
PSU-Corporate-ID-Type	String	Conditional	This is describing the type of the identification needed by the ASPSP to identify the PSU-Corporate-ID content. Shall be transmitted if this Request is indicated by "startAuthorisationWithPsuIdentification". or "startAuthorisationWithPsuAuthentication" or "startAuthorisationWithEncryptedPsuAuthentication" and this field has not yet been transmitted before. Mean and use is defined in the ASPSP's documentation. Only used in a corporate context.
Authorization	String	Conditional	Bearer Token. Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in a preceding AIS service in the same session.
Client-SCA-Approach-Preference	String	Optional	A comma separated list of attributes, where the first entry will have a higher priority than the next or to every SCA Approach which is not indicated at all, e.g. "decoupled, redirect, embedded" or "decoupled". The possible SCA approaches are: • EMBEDDED • DECOUPLED

Attribute	Type	Condition	Description
			• REDIRECT • ASPSP-CHANNEL • SIGNATURE This attribute may be ignored by the ASPSP.
Body-Sig-Profile-Preference	Max35Text	Conditional	Indicates the preferred signature profile used for signing (parts of) the body. Shall only be used for signed transaction requests.
Client-Redirect-URI	Max35Text	Conditional	URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach, specifically when Client-Redirect-Preferred equals "true". See Section 5.3 for further requirements on this header. This field may be ignored by the ASPSP for migration reasons. For this reason, the same Client-Redirect-URI as used when creating the related resource shall be provided by the TPP. This specifically applies to the authorisation of a payment cancellation, where the same Client-Redirect-URI as for the corresponding payment initiation shall be used. This applies also to multilevel SCA, where the Client-Redirect-URI for all authorisation processes for one transaction shall be equal. It is recommended to always use this header field. Remark for Future: The condition on keeping the Client-Redirect-URI equal during a transaction lifecycle might be removed in the next version of the specification.
Client-Nok-Redirect-URI	String	Optional	If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the Client-Redirect-URI in case of a negative result of the redirect SCA method. This may be ignored by the ASPSP. See Section 5.3 for further requirements on this header.

Attribute	Type	Condition	Description
			The same condition as for Client-Redirect-URI on keeping the URI equal during a transaction lifecycle applies also to this header.

Remark:

- Client-SCA-Approach-Preference set to “signature” indicates only that an electronic signature in the mathematical sense of the word is used for SCA. This does not distinguish between a signature by a natural person or by a legal entity.
- Which kind of signatures are accepted and any quality requirements for signatures/ certificates to be used are determined by the (security) policy of the ASPSP.

Request Body

No request body.

Note: If the hyperlinks in the following extended forms are used in the Transaction Initiation Response message or Transaction Cancellation Response message before, additional conditions on request body parameters apply as indicated in the following:

- "startAuthorisationWithPsuIdentification": Cp. Section 9.4.2
- "startAuthorisationWithPsuAuthentication": Cp. Section 9.4.3
- "startAuthorisationWithEncryptedPsuAuthentication": Cp. Section 9.4.3.
- "startAuthorisationWithAuthenticationMethodSelection": Cp. Section 9.4.4.
- "startAuthorisationWithTransactionAuthorisation": Cp. Section 9.5.

The differences in the calls then are only whether to use a POST command to create the authorisation sub-resource and update the specified data at the same time or to use a PUT command to update the specified data to an already created authorisation sub-resource.

Response Code

HTTP response code equals 201.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
ETag	UUID	Conditional	Must be included if the request header used the If-Match header field and then this parameter must carry the same value as given in the request
ASPSP-SCA-Approach	String	Conditional	Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE OAuth will be subsumed by the value REDIRECT
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

Response Body

Attribute	Type	Condition	Description
transactionFees	Amount	Optional	Might be used by the ASPSP to transport the total transaction fee relevant for the underlying payments in case of a payment resource. This field includes the entry of the currencyConversionFees if applicable.

Attribute	Type	Condition	Description
currencyConversionFees	Amount	Optional	Might be used by the ASPSP to transport specific currency conversion fees related to the initiated credit transfer in case of a payment resource id.
estimatedTotalAmount	Amount	Optional	The amount which is estimated to be debited from the debtor account in case of a payment resource. Note: This amount includes fees.
estimatedInterbankSettlementAmount	Amount	Optional	The estimated amount to be transferred to the payee in case of a payment resource.
scaStatus	SCA Status	Mandatory	
authorisationId	String	Mandatory	Unique resource identification of the created authorisation or cancellation authorisation sub-resource.
originalTransactionInformationAndVopStatus	Array of Original Transaction Information and VOP Status	Conditional	VOP result information. Will be provided, if - an account/owner name match was requested and performed, - the result was not yet provided and the related code in the interbank VOP service was "CMTC", "NMTC" or "NOAP".

Attribute	Type	Condition	Description
scaMethods	Array of Authentication Objects	Conditional	This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods. Depending on the risk management of the ASPSP this choice might be offered before or after the PSU has been identified with the first relevant factor, or if an access token is transported. If this data element is contained, then there is also a hyperlink of type "selectAuthenticationMethod" contained in the response body. These methods shall be presented towards the PSU for selection by the API Client.
oAuthAdditionalParameters	OAuth Additional Parameters	Optional	If supported by the ASPSP, the API Client needs to follow these data when relying on the OAuth2 SCA approach
chosenSca Method	Authentication Object	Conditional	This data element is only contained in the response if the ASPSP has chosen the Embedded SCA Approach or the Signature SCA Approach, if the PSU is already identified e.g. with the first relevant factor or alternatively an access token, if SCA is required and if the authentication method is implicitly selected.
challengeData	Challenge	Conditional	It is contained in addition to the data element "chosenScaMethod" if challenge data is needed for SCA. In rare cases this attribute is also used in the context of the "updatePsuAuthentication" or "updateEncryptedPsuAuthentication" link.

Attribute	Type	Condition	Description
_links	Links	Mandatory	A list of hyperlinks to be recognised by the API Client. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "scaRedirect": In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser.

Attribute	Type	Condition	Description
			"scaOAuth": In case of a SCA OAuth2 Approach, the ASPSP is transmitting the URI where the configuration of the Authorisation Server can be retrieved. The configuration follows the OAuth 2.0 Authorisation Server Metadata specification. "confirmation": Might be added by the ASPSP if either the "scaRedirect" or "scaOAuth" hyperlink is returned in the same response message. This hyperlink defines the URL to the resource which needs to be updated with • a confirmation code as retrieved after the plain redirect authentication process with the ASPSP authentication server or • an access token as retrieved by submitting an authorization code after the integrated OAuth based authentication process with the ASPSP authentication server.

Attribute	Type	Condition	Description
			"updatePsuIdentification": The link to the authorisation or cancellation authorisation sub-resource, where PSU identification data needs to be uploaded. "updatePsuAuthentication": The link to the authorisation or cancellation authorisation sub-resource, where PSU authentication data needs to be uploaded. "updateEncryptedPsuAuthentication": The link to the authorisation or cancellation authorisation sub-resource, where encrypted PSU authentication data needs to be uploaded "selectAuthenticationMethod": The link to the authorisation or cancellation authorisation sub-resource, where the selected authentication method needs to be uploaded. This link is contained under exactly the same conditions as the data element "scaMethods" "authoriseTransaction": The link to the authorisation or cancellation authorisation sub-resource, where the authorisation data has to be uploaded, e.g. the TOP received by SMS.

Attribute	Type	Condition	Description
			"scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.
psuMessage	Max500Text	Optional	

Note: If the hyperlinks in the following extended forms are used in the Transaction Initiation Response or Transaction Cancellation Response message before, additional response parameters apply as indicated in the following:

- In case of "startAuthorisationWithPsuIdentification": Cp. Section 9.4.2
- In case of: "startAuthorisationWithPsuAuthentication": Cp. Section 9.4.3
- In case of: "startAuthorisationWithEncryptedPsuAuthentication": Cp. Section 9.4.3
- In case of: "startAuthorisationWithAuthenticationMethodSelection": Cp. Section 9.4.4.
- In case of "startAuthorisationWithTransactionAuthorisation": Cp. Section 9.5

Example

Request

POST <https://api.testbank.com/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations>
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
PSU-ID: PSU-1234

Response

HTTP/1.x 201 CREATED
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
ASPSP-SCA-Approach: DECOUPLED
Date: Sun, 06 Aug 2017 15:05:47 GMT

```
Location:          https://www.testbank.com/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100
Content-Type:      application/json
{
  "scaStatus": "received",
  "authorisationId": "3d9a81b3-a47d-4130-9999-a9c0ff861100",
  "psuMessage": "Please use your BankApp for transaction authorisation.",
  "_links": {
    "scaStatus": {"href": "/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100"}
  }
}
```

9.4.1 Update PSU Data

Independent of the SCA approach, the ASPSP might offer to select the SCA method before the SCA approach is defined, because e.g. the SCA Approach to be chosen might depend on the SCA method.

- A specific Update PSU Data Request is applicable for
 - the selection of authentication methods (see section 9.4.4), before choosing the actual SCA approach.

Depending on the SCA approach, different further PSU Data needs to be updated:

- Decoupled SCA Approach: A specific Update PSU Data Request is only applicable for
 - adding the PSU Identification (see section 9.4.2) or a PSU Authentication (see section 9.4.3, if not provided yet in the related Transaction Initiation Request and if no OAuth2 access token is used, or
 - the selection of authentication methods (see section 9.4.4).
- Embedded SCA Approach: The Update PSU Data Request might be used
 - to add credentials as a first factor authentication data of the PSU (see section 9.4.3) and
 - to select the authentication method (see section 9.4.4).

These different Update PSU Data Requests are differentiated in the following sub sections.

9.4.2 Update PSU Data (Identification)

This call is used, when in the preceding call the hyperlink of type "updatePsuIdentification" was contained, e.g. in case of a Decoupled Approach in the response and is now followed by the TPP.

Call

```
PUT /v2/{resource-path}/{resourceId}/{authorisation-
category}/{authorisationId}
```

Updates the addressed authorisation sub-resource data on the server by PSU data, if requested by the ASPSP.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /consents {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: - authorisations: used in case of an authorisation of the related business transaction. - cancellation-authorisations: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
If-Match	UUID	Optional if supported by the ASPSP	If used, this field must contain the ETag of the changed variant of the resource.
PSU-ID	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP in the related response
PSU-ID-Type	String	Conditional	Type of the PSU-ID, needed in scenarios where PSUs have several PSU-IDs as access possibility.
PSU-Corporate-ID	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP in the related response. This field is relevant only in a corporate context.
PSU-Corporate-ID-Type	String	Conditional	Might be mandated by the ASPSP in addition if the PSU-Corporate-ID is contained.

Request Body

No request body.

Response Code

HTTP response code is 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Attribute	Type	Condition	Description
ETag	UUID	Conditional	Must be included if the request header used the If-Match header field and then this parameter must obtain the same value as given in the request parameter
ASPSP-SCA-Approach	String	Conditional	Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE OAuth will be subsumed by the value REDIRECT
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

Response Body

Attribute	Type	Condition	Description
transactionFees	Amount	Optional	Might be used by the ASPSP to transport the total transaction fee relevant for the underlying payments. This field includes the entry of the currencyConversionFees if applicable.
currencyConversion Fees	Amount	Optional	Might be used by the ASPSP to transport specific currency conversion fees related to the initiated credit transfer.
estimatedTotalAmount	Amount	Optional	The amount which is estimated to be debted from the debtor account. Note: This amount includes fees.
estimatedInterbank SettlementAmount	Amount	Optional	The estimated amount to be transferred to the payee.

Attribute	Type	Condition	Description
scaMethods	Array of Authentication Objects	Conditional	Might be contained, if several authentication methods are available. (name, type)
_links	Links	Mandatory	A list of hyperlinks to be recognised by the TPP. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.
			"selectAuthenticationMethod": This is a link to a resource, where the TPP can select the applicable second factor authentication methods for the PSU, if there are several available authentication methods and if the PSU is already sufficiently authenticated.. If this link is contained, then there is also the data element "scaMethods" contained in the response body
scaStatus	SCA Status	Mandatory	
psuMessage	Max500Text	Optional	

Example

Request

```
PUT https://api.testbank.com/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
PSU-ID:                PSU-1234
```

Response

```
HTTP/1.x 200 OK
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
ASPS-SCA-Approach:     DECOUPLED
Date:                  Sun, 06 Aug 2017 15:05:47 GMT
Content-Type:          application/json
{
  "scaStatus": "psuIdentified",
  "psuMessage": "Please use your BankApp for transaction Authorisation.",
  "_links": {
    "scaStatus": { "href": "/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/
authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100" }
  }
}
```

9.4.3 Update PSU Data (Authentication) in the Decoupled or Embedded Approach

This call is used, when in the preceding call the hyperlink of type "updatePsuAuthentication", "updateEncryptedPsuAuthentication", or was contained in the response and is followed by the API Client.

Call

```
PUT /v2/{resource-path}/{resourceId}/{authorisation-
category}/{auhtorisationId}
```

Updates the addressed authorisation sub-resource data on the server by PSU data, if requested by the ASPSP.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type, where

Attribute	Type	Description
		{service} stands for the service type of the related business transaction, e.g. /payments or /consents {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: - authorisations: used in case of an authorisation of the related business transaction. - cancellation-authorisations: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Note: The openFinance API Framework allows ASPSPs to mandate a payload encryption to protect the password contained in the payload.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
If-Match	UUID	Optional if supported	If used, this field must contain the ETag of the changed variant of the resource.

Attribute	Type	Condition	Description
		by the ASPSP	
PSU-ID	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP in the related response
PSU-ID-Type	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP in the related response
PSU-Corporate-ID	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP in the related response. This field is relevant only in a corporate context.
PSU-Corporate-ID-Type	String	Conditional	Contained if not yet contained in a preceding request, and mandated by the ASPSP documentation. Might be mandated by the ASPSP in addition if the PSU-Corporate-ID is contained.

Request Body

Attribute	Type	Condition	Description
psuData	PSU Credentials	Mandatory	The password, or encryptedPassword, subfield is used, depending on encryption requirements of the ASPSP as indicated in the corresponding hyperlink contained in the preceding response message of the ASPSP. The related encryption requirements are defined in Section 7.2.

Response Code

HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
ETag	UUID	Conditional	Must be included if the request header used the If-Match header field and then this parameter must obtain the same value as given in the request parameter
ASPSP-SCA-Approach	String	Conditional	Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE OAuth will be subsumed by the value REDIRECT
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

Response Body

Attribute	Type	Condition	Description
originalTransactionInformationAndVopStatus	Array of Original Transaction Information and VOP Status	Conditional	VOP result information. Will be provided, if • an account/owner name match was requested and performed, • the result was not yet provided and • the related code in the interbank VOP service was "CMTC", "NMTC" or "NOAP".

Attribute	Type	Condition	Description
chosenScaMethod	Authentication Object	Conditional	A definition of the provided SCA method is contained, if only one authentication method is available, and if the Embedded SCA approach is chosen by the ASPSP.
challengeData	Challenge	Conditional	Challenge data might be contained, if only one authentication method is available, and if the Embedded SCA approach is chosen by the ASPSP.
scaMethods	Array of Authentication Objects	Conditional	Might be contained, if several authentication methods are available. (name, type)
accounts	Array of Account Details	Conditional	Provided, if the PSU account reference has not been provided in the related resource data submission and if more than one account is available.
_links	Links	Conditional	A list of hyperlinks to be recognised by the TPP. Might be contained, if several authentication methods are available for the PSU. Type of links admitted in this response: "updateAdditionalPsuAuthentication" The link to the payment initiation or account information resource, which needs to be updated by an additional PSU password. This link is only contained in rare cases, where such additional passwords are needed for PSU authentications. "updateAdditionalEncryptedPsuAuthentication" The link to the payment initiation or account information resource, which needs to be updated by an additional encrypted PSU password. This link is only contained in rare cases, where such additional passwords are needed for PSU authentications.

Attribute	Type	Condition	Description
			"updateResourceByDebtorAccountResource" The link to the business resource which needs an update by any potential debtor account delivered in the "accounts" attribute above. "selectAuthenticationMethod": This is a link to a resource, where the TPP can select the applicable second factor authentication methods for the PSU, if there were several available authentication methods. This link is only contained, if the PSU is already identified or authenticated with the first relevant factor or alternatively an access token, if SCA is required and if the PSU has a choice between different authentication methods. If this link is contained, then there is also the data element "scaMethods" contained in the response body "authoriseTransaction": The link to the resource, where the "Transaction Authorisation Request" is sent to. This is the link to the resource which will authorise the transaction by checking the SCA authentication data within the Embedded SCA approach or the Signature SCA Approach. "scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.
scaStatus	SCA Status	Mandatory	
psuMessage	Max500Text	Optional	

NOTE: In case of an incorrect password, the ASPSP informs the TPP via the message code PSU_CREDENTIALS_INVALID. The TPP then needs to ask the PSU for re-entering the password. The newly entered password needs to be updated to the same path. It is recommended that the ASPSP is informing the TPP about this by adding a `_links` section in the additional error information and presenting a corresponding `updatePsuAuthentication` or `updateEncryptedPsuAuthentication` hyperlink. In case an incorrect password is entered too often, the ASPSP will at least put the related resource to a "Rejected" status. The ASPSP might inform the PSU via `psuMessages` about further impact.

NOTE: If an account list is provided for the selection of an account via the access method defined in Section 9.9, then the status of the related payment resource will be moved from "RCVD" to "PNDG", to indicate that further data needs to be provided on resource level, before the authorisation can be completed. In addition, the ASPSP should provide a status reason code, providing more information on the pending reason.

Example

Request in case of Embedded Approach

```
PUT https://api.testbank.com/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
PSU-ID:                PSU-1234
{
  "psuData": {
    "password": "start12"
  }
}
```

Response in case of the embedded approach

```
HTTP/1.x 200 OK
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
ASPSP-SCA-Approach:    EMBEDDED
Date:                  Sun, 06 Aug 2017 15:05:47 GMT
Content-Type:          application/json

{
  "scaStatus": "psuAuthenticated",
  "_links": {
    "authoriseTransaction": {"href": "/psd2/v2/payments/sepa-credit-
transfers/3A3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100"}
  }
}
```

9.4.4 Update PSU Data (Select Authentication Method)

This call is used, when in the preceding call the hyperlink of type "selectAuthenticationMethod" was contained in the response and was followed by the TPP.

Call

```
PUT /v2/{resource-path}/{resourceId}/{authorisation-
category}/{authorisationId}
```

Updates the addressed authorisation sub-resource data on the server by PSU data, if requested by the ASPSP.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where • {service} stands for the service type of the related business transaction, e.g. /payments or /consents • {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.

Attribute	Type	Description
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: • <code>authorisations</code>: used in case of an authorisation of the related business transaction. • <code>cancellation-authorisations</code>: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Query Parameters

No specific query parameters.

Response Code

The HTTP response code equals 200.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
If-Match	UUID	Optional if supported by the ASPSP	If used, this field must contain the ETag of the changed variant of the resource.

Request Body

Attribute	Type	Condition	Description
-----------	------	-----------	-------------

authentication MethodId	String	Mandatory	The authentication method ID as provided by the ASPSP.
----------------------------	--------	-----------	--

Response Code

HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
ETag	UUID	Conditional	Must be included if the request header used the If-Match header field and then this parameter must obtain the same value as given in the request parameter
ASPSP-SCA-Approach	String	Optional	Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE OAuth will be subsumed by the constant REDIRECT
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

Response Body

Attribute	Type	Condition	Description
originalTransaction InformationAndVopStatus	Array of Original Transaction Information	Conditional	VOP result information. Will be provided, if

Attribute	Type	Condition	Description
	and VOP Status		- an account/owner name match was requested and performed, - the result was not yet provided and the related code in the interbank VOP service was "CMTTC", "NMTC" or "NOAP".
chosenSca Method	Authentication object	Conditional	A definition of the provided SCA method is contained, if the Embedded SCA approach is chosen by the ASPSP.
challengeData	Challenge	Conditional	Challenge data might be contained, if the Embedded SCA approach is chosen by the ASPSP.

_links	Links	Conditional	A list of hyperlinks to be recognised by the TPP. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Remark: This method can be applied before or after PSU identification. This leads to many possible hyperlink responses. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "scaRedirect": In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. "scaOAuth": In case of a SCA OAuth2 Approach, the ASPSP is transmitting the URI where the configuration of the Authorisation Server can be retrieved. The configuration follows the OAuth 2.0 Authorisation Server Metadata specification. "confirmation": Might be added by the ASPSP if either the "scaRedirect" or "scaOAuth" hyperlink is returned in the same response message. This hyperlink defines the URL to the resource which needs to be updated with • a confirmation code as retrieved after the plain redirect authentication process with the ASPSP authentication server or
--------	-------	-------------	---

Attribute	Type	Condition	Description
			an access token as retrieved by submitting an authorization code after the integrated OAuth based authentication process with the ASPSP authentication server.

Attribute	Type	Condition	Description
			"updatePsuIdentification": The link to the authorisation or cancellation authorisation sub-resource, where PSU identification data needs to be uploaded. "updatePsuAuthentication": The link to the authorisation or cancellation authorisation sub-resource, where PSU authentication data needs to be uploaded. "updateEncryptedPsuAuthentication": The link to the authorisation or cancellation authorisation sub-resource, where encrypted PSU authentication data needs to be uploaded. "authoriseTransaction": The link to the authorisation or cancellation authorisation sub-resource, where the authorisation data has to be uploaded, e.g. the TOP received by SMS. "scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.
scaStatus	Sca Status	Mandatory	
psuMessage	Max500Text	Optional	

Example

Request in case of Embedded Approach

```
PUT https://api.testbank.com/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100
X-Request-ID:          asdfoeljkasdfoelkjasdf-123479093
```

```
{
  "authenticationMethodId": "myAuthenticationID"
}
```

Response in case of the embedded approach

```
HTTP/1.x 200 OK
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
ASPS-SCA-Approach:     EMBEDDED
Date:                  Sun, 06 Aug 2017 15:05:47 GMT
Content-Type:          application/json
```

```
{
  "scaStatus": "scaMethodSelected",
  "chosenScaMethod": {
    "authenticationType": "SMS_OTP",
    "authenticationMethodId": "myAuthenticationID"},
  "challengeData": {
    "otpMaxLength": "6",
    "otpFormat": "integer"},
  "_links": {
    "authoriseTransaction": {"href": "/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100"}
  }
}
```

9.5 Transaction Authorisation

This call is only used in case of an Embedded SCA Approach or a Signature SCA Approach.

Call

```
PUT /v2/{resource-path}/{resourceId}/{authorisation-
category}/{authorisationId}
```

Transmit response data to the challenge for SCA checks by the ASPSP.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /consents {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: - authorisations: used in case of an authorisation of the related business transaction. - cancellation-authorisations: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Query Parameter

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Attribute	Type	Condition	Description
If-Match	UUID	Optional if supported by the ASPSP	If used, this field must contain the ETag of the changed variant of the resource.
Authorization	String	Conditional	Is contained only, if the optional OAuth Pre-Step was performed.

Request Body

Attribute	Type	Condition	Description
scaAuthenticationData	String	{Or	SCA authentication data, depending on the chosen authentication method. If the data is binary, then it is base64 encoded.
signatureData	String	Or}	Data needed for the verification of the signature (e.g. JWS for JSON signatures)

Note: Content and format of the Signature data depend on the signature profile used to create the signature. This shall correspond to the profile indicated by the special parameter Body-Sig-Profile-Accepted added by the ASPSP to the transaction initiation response message. See section 7.1.4 for a description how the data has to be created if JSON_JS is used as signature profile.

Response Code

HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
ETag	UUID	Conditional	Must be included if the request header used the If-Match header field and then this parameter must obtain the same value as given in the request parameter

Response Body

Attribute	Type	Condition	Description
scaStatus	SCA Status	Mandatory	Result of the verification of the signature data for the signature SCA approach or of the authentication data in case of the embedded SCA approach
_links	Links	Conditional	A list of hyperlinks to be recognised by the TPP. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.

If a signature has been verified by the ASPSP successfully, the scaStatus is set to finalised.

Note: This scaStatus reflects the verification status of this single signature or authentication data.

NOTE: In case of incorrect scaAuthenticationData or incorrect signatureData, the ASPSP informs the TPP via the message code PSU_CREDENTIALS_INVALID. The TPP then needs to ask the PSU for re-entering the authentication data by repeating the SCA method first. Depending on the implementation of the corresponding SCA method, the TPP needs

- either to re-start the full authorisation process by generating a new authorisation sub-resource, e.g. in case of an SMS OTP,
- or to submit newly generated authentication data generated on a customer device to the same path as the first time, and where no new challenge data from the ASPSP is needed, e.g. in case of a CHIP OTP.

The ASPSP is informing the TPP about this by adding a _links section in the additional error information and presenting a corresponding startAuthorisation, or transactionAuthorisation hyperlink. In case an incorrect OTP is entered too often, the ASPSP will at least put the related resource to a "Rejected" status. The ASPSP might inform the PSU via psuMessages about further impact.

Example

Request

```
PUT https://api.testbank.com/psd2/v2/payments/sepa-credit-transfers/
3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-
9999-a9c0ff861100
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
{
  "scaAuthenticationData": "123456"
}
```

Response in case of the embedded approach

Response Code 200

Response Body

```
{
  "scaStatus": "finalised",
  "_links": {
    "scaStatus": { "href": "/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100" }
  }
}
```

9.6 GET Authorisation Sub-Resources Request

Call

GET /v2/{resource-path}/{resourceId}/{authorisation-category}

Will deliver an array of resource identifications of all (explicitly and implicitly) generated authorisation or cancellation authorisation sub-resources.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /consents

Attribute	Type	Description
		{product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: - authorisations: used in case of an authorisation of the related business transaction. - cancellation-authorisations: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}

Query Parameters

No specific query parameters defined.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in the current business transaction or in a preceding AIS service in the same session, if no such OAuth2 SCA approach was chosen in the current PIS transaction.

Request Body

No request body.

Response Code

The HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
authorisationIds	Array of String	Mandatory	An array of all authorisationIds connected to the related business transaction.

Example

Request

```
GET https://api.testbank.com/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations
Accept: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7723
Date: Sun, 06 Aug 2017 15:04:07 GMT
```

Response

```
HTTP/1.x 200 Ok
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7723
Date: Sun, 06 Aug 2017 15:04:08 GMT
Content-Type: application/json

{
  "authorisationIds": ["3d9a81b3-a47d-4130-9999-a9c0ff861100"]
}
```

9.7 GET Authorisation Status Request

Call

```
GET /v2/{resource-path}/{resourceId}/{authorisation-
category}/{authorisationId}
```

Checks the SCA status of an authorisation or cancellation authorisation sub-resource.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /consents {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: - authorisations: used in case of an authorisation of the related business transaction. - cancellation-authorisations: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in the current PIS transaction or in a preceding AIS service in the same session, if no

Attribute	Type	Condition	Description
			such OAuth2 SCA approach was chosen in the current PIS transaction.

Query Parameters

No specific query parameters defined.

Request Body

No request body.

Response Code

The HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
scaStatus	SCA Status	Mandatory	This data element is containing information about the status of the SCA method applied.
psuName	Max140Text	Optional	Name of the PSU ² In case of a corporate account, this might be the person acting on behalf of the corporate.
_links	Links	Optional	Should refer to next steps if the problem can be resolved via the interface e.g. for re-submission of credentials.
apiClientMessages	Array of Client	Optional	Messages to the TPP on operational issues.

² Usage is following the mandate resulting from EBA Q&A 2020_5165.

Attribute	Type	Condition	Description
	Message Information		

Example

Request

```
GET https://api.testbank.com/psd2/v2/payments/sepa-credit-
transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-
a47d-4130-9999-a9c0ff861100
```

```
Accept: application/json
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 06 Aug 2017 15:04:07 GMT
```

Response

```
HTTP/1.x 200 Ok
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 06 Aug 2017 15:04:08 GMT
Content-Type: application/json
```

```
{
  "scaStatus": "finalised"
}
```

9.8 Confirmation Request Procedure

The Confirmation Request Procedure is technically an optional extension of the authorisation process in case of the Redirect or OAuth SCA Approach. Its purpose is to prevent Cross-Site-Request-Forgery attacks (XSRF attacks) following the approach presented in [XS2A-SecB], chapter 3. Further details motivating the extension are also presented there.

The Confirmation Request is used, when in the preceding response the hyperlink of type "confirmation" was contained. This may (only) happen, if a redirection or OAuth SCA approach has been applied.

The processes connected to the Confirmation Request differ in details depending on whether the authorization has taken place using a Redirect approach that **does not involve the OAuth** protocol (described as "**Redirect SCA Approach**" in the following) or a Redirect Approach that **makes use of the OAuth protocol ("OAuth SCA Approach")**. Before the call can be submitted by the TPP, an authorization code (in case of the OAuth SCA Approach),

respectively a confirmation code (in case of the Redirect SCA Approach) needs to be retrieved by the TPP after the SCA processing in a redirect to the ASPSP authentication server.

- In case of the OAuth SCA Approach, the overall procedure to receive the related authorization code and the access token successfully is described in Section
- In case of the Redirect SCA Approach, the procedure to retrieve the confirmation code is described in Section 9.8.2. The actual Confirmation Request Message is described in Section 9.8.4 for both the OAuth2 SCA Approach and the Redirect SCA Approach after having defined the pre-conditions in both approaches in Section 9.8.3


Due to the complexity of the process, flows are added below for payment initiation as an example before specifying the related requests in detail.

9.8.1 Confirmation Request Flow Examples for Payment Initiation

9.8.1.1 Redirect SCA Approach: Explicit Start of the Authorisation Process with Confirmation

If the ASPSP supports the Redirect SCA Approach, the message flow within the payment initiation service is simple. The Payment Initiation Request is followed by an explicit request of the TPP to start the authorisation. This is followed by a redirection to the ASPSP SCA authorisation site. An authorisation confirmation request is requested by the TPP after the session is re-directed to the TPP's system and after the TPP's control on session fixation. In

the end, a payment status request might be needed by the TPP to control the exact status of the payment initiation.




9.8.1.2 OAuth2 SCA Approach: Implicit Start of the Authorisation Process with Confirmation

If the ASPSP supports the OAuth2 SCA Approach, the flow is very similar to the Redirect SCA Approach with implicit start of the Authorisation Process. Instead of redirecting the PSU directly to an authentication server, the OAuth2 protocol is used for the transaction authorisation process. An authorisation confirmation request is required for the TPP in this scenario after the session is re-redirected to the TPP's system and after the TPP's control on session fixation.

the end, a payment status request might be needed by the TPP to control the exact status of the payment initiation.

Remark: The OAuth2 SCA Approach with explicit start of the Authorisation Process is treated analogously.



It is further recommended for ASPSPs and TPPs in this case to follow the Security Best Practice definitions as defined in [OA-SecTop]

9.8.2 Retrieving the Confirmation Code in Redirect SCA approach

In the Confirmation Request Flow, the TPP will receive the confirmationCode as a query parameter in the HTTP request from the PSU agent that redirects the PSU back to the TPP after successful authorisation.

9.8.2.1 Preparation of the Confirmation Request Flow

Any authorisation process always involves the PSU directly and therefore requires a session between the PSU and the TPP. To support the Confirmation Request flow that might occur during the session between PSU and TPP, the TPP needs to fix the session of the PSU agent (browser or mobile app) on its server with a nonce, where part of it is a unique state parameter.

Before redirecting the PSU agent to send the authorization request (see section 9.8.2.2) to the ASPSP authorisation website, the TPP shall

- create a one-time use token to prevent XSRF attacks to be conveyed to the ASPSP in the query parameter state and,
- bind this value to the current session in the user (PSU) agent.

The confirmationCode is then retrieved from the response of the HTTP request of the PSU agent as described in following sub-section.

9.8.2.2 Redirecting the PSU agent (Authorisation Request)

To prepare the Confirmation Request flow, the TPP shall add the generated token to prevent XSRF attacks (see section 9.8.2.1) as an additional query parameter to that URI.

Additional Query Parameter in the PSU Authorisation Request (GET command)

Attribute	Type	Condition	Description
state	string	mandated	state parameter as defined by the TPP as a unique parameter to counter XSRF attacks and bound to the PSU/TPP session.

As a consequence of this requirement, it follows that ASPSPs shall not include a query parameter named "state" in their "scaRedirect" links.

Example

If the TPP received "scaRedirect" link containing the URI "https://authserver.testbank.com" only, the TPP shall forward the PSU agent to send a request

```
GET https://authserver.testbank.com?state=1234567er
```

If the TPP received "scaRedirect" link containing the URI "https://authserver.testbank.com?bankProvidedQueryParameter=A" the TPP shall forward the PSU agent to send a request

GET

https://authserver.testbank.com?bankProvidedQueryParameter=A&state=1234567er

Response from the ASPSP Redirecting the PSU Agent back to the TPP

If the customer authentication via a Redirect SCA Approach ultimately fails, the customer is redirected to the URI assigned by the TPP in header field "Client-Nok-Redirect-URI". In this case, the business transaction / cancellation will anyhow not be authorised based in the current flow. Therefore no additional steps are required from the TPP. The last part of this paragraph as well as the whole sections 9.8.3 to 9.8.4 only apply, if SCA has been successful.

After the customer authentication via SCA has taken place on the ASPSP server, the ASPSP responds to the PSU agent redirecting it to the URI provided by the TPP in the header "Client-Redirect-URI". To support the Confirmation Request flow, the ASPSP shall add the received query parameter "state" and a unique confirmationCode bound to the authorisation resource . The confirmationCode will only be contained if SCA has been successfully performed. Redirection is done by sending an HTTP response code 302 and a location header containing the URI to which the PSU is redirected. This would result in a response from the ASPSP to the PSU agent as described in the follows:

Response Code

The HTTP response code equals 302.

Response Header

Attribute	Type	Condition	Description
Location	String	Mandatory	The ASPSP's Authorization server must create the content of the Location Header in the following Form: [Client-Redirect-URI]?confirmationCode=[confirmation code]&state=[state] Where [Client-Redirect-URI] is the value of the "Client-Redirect-URI" header of the underlying request from the TPP

Attribute	Type	Condition	Description
			[confirmationCode] is the ASPSP's confirmation code as described above [state] is the value of query parameter "state" from the PSU authorisation request

Remark: In case of the OAuth SCA approach, the PSU agent is forwarded similarly to the `redirect_uri` as defined in OAuth2 protocol. This redirection will also include a parameter `state` and – instead of the "confirmationCode" a parameter "code".

Example in case of Redirect SCA Approach

`http 302`

Location: `www.example-TPP.com/xs2a-client/v2/ASPSPidentification/mytransaction-id?state=1234567er&confirmationCode=2256ffgh`

9.8.3 Confirmation Request Message Pre-Condition

When the PSU is again redirected to the TPP as described above, the TPP will receive the additional query parameters "state" and "confirmationCode". The TPP must check whether the state parameter is linked to the current session as described in Section 9.8.2. If the check is positive then the TPP further processes

- within context of the OAuth SCA Approach with retrieving the access Bearer token as described in Section 8.8.3 of this document and then proceed as described in Section 9.8.4.
- within context of the Redirect SCA Approach directly as described in Section 9.8.4.

If the check fails, the transaction must be stopped by the TPP and the above defined request messages shall not be used.

9.8.4 Authorisation Confirmation Request Message

Call

`PUT /v2/{resource-path}/{resourceId}/{authorisation-category}/{authorisationId}`

In case of the Redirect SCA approach, this call updates the addressed authorisation or cancellation authorisation data on the ASPSP server by a confirmation code.

In case of the OAuth2 SCA approach, this call updates the addressed authorisation or cancellation authorisation data on the ASPSP server with the OAuth2 access token, after having sent the related attribute "code" to the token server, cp. Section 8.8.3.

Both calls shall only be performed if requested by the ASPSP via the related hyperlink "confirmation" and if the related checks by the TPP as defined in Section 9.8.3 have been successful.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type}, where • {service} stands for the service type of the related business transaction, e.g. /payments or /consents • {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: • <code>authorisations</code>: used in case of an authorisation of the related business transaction. • <code>cancellation-authorisations</code>: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Authorization Bearer Token as retrieved by the TPP in case the OAuth SCA Approach as described in Section 8.8.4

Request Body

Attribute	Type	Condition	Description
confirmationCode	String	Conditional	Confirmation code as retrieved by the TPP within the Redirect SCA Approach as described in Section 9.8.2

Response Code

HTTP response code is 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
scaStatus	SCA Status	Mandatory	Value "finalised" if the transaction authorisation/cancellation authorisation and confirmation was successful. Value "failed" if the transaction authorisation/cancellation authorisation or confirmation was not successful.
_links	Links	Mandatory	A list of hyperlinks to be recognised by the TPP. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "status": The link to retrieve the status of the corresponding transaction resource.
psuMessage	Max512Text	Optional	

Example for OAuth SCA solution

Request

PUT <https://api.testbank.com/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100>

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Authorization: Bearer 1234567

Response

HTTP/1.x 200 OK

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 06 Aug 2017 15:05:47 GMT

Content-Type: application/json

```
{
  "scaStatus": "finalised",
  "_links": {
    "status": {"href": "/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/status"}
  }
}
```

Example for redirect solution

Request

```
PUT https://api.testbank.com/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
{"confirmationCode": "2256ffgh"}
```

Response

```
HTTP/1.x 200 OK
X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 06 Aug 2017 15:05:47 GMT
Content-Type: application/json
{
  "scaStatus": "finalised",
  "_links": {
    "status": {"href": "/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/status"}
  }
}
```

9.9 Update Resource with Debtor Account

The following method is used to update a payment related resource by an account which is associated to a PSU, and which needs to be received from the ASPSP first in the response of the "Update PSU Data with Authentication Request", cp. Section 9.4.3.

Remark: This procedure might be offered by the ASPSP in decoupled or embedded SCA channels to support "noManualbanEntry" requirements from regulators for payment initiation.

Call

```
PUT /v2/{resource-path}/{resourceId}
```

Updates the addressed resource by an account related to the PSU.

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/{product-type}, where {service} stands for the service type of the related business transaction, e.g. /payments or /mandates {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments
resourceId	String	Resource identification of the related payment initiation or mandate submission.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Request Body

Attribute	Type	Condition	Description
debtorAccount	Account Resource Reference	Mandatory	The resourceId of the account as provided in the response defined in Section 9.4.3 shall be used as the technical account reference.

NOTE: The support of this feature mandates the ASPSP to support UUIDs in the attributes resourceId of the data type "account details".

Response Code

HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
ASPSP-SCA-Approach	String	Optional	Possible values are: • EMBEDDED • DECOUPLED • REDIRECT • ASPSP-CHANNEL • SIGNATURE OAuth will be subsumed by the constant REDIRECT
Body-Sig-Profile-Accepted	String	Conditional	Confirms the signature profile to be used by a PSU for signing the body. Shall only be used for a response message for signed transaction requests.

Response Body

Attribute	Type	Condition	Description
chosenScaMethod	Authentication Object	Conditional	A definition of the provided SCA method is contained, if only one authentication method is available, and if the Embedded SCA approach is chosen by the ASPSP.
challengeData	Challenge	Conditional	Challenge data might be contained, if only one authentication method is available, and if the Embedded SCA approach is chosen by the ASPSP.
scaMethods	Array of Authentication Objects	Conditional	Might be contained, if several authentication methods are available. (name, type)

Attribute	Type	Condition	Description
_links	Links	Conditional	A list of hyperlinks to be recognised by the TPP. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. Remark: All links can be relative or full links, to be decided by the ASPSP. Remark: This method can be applied before or after PSU identification. This leads to many possible hyperlink responses. Type of links admitted in this response, (further links might be added for ASPSP defined extensions): "selectAuthenticationMethod": This is a link to a resource, where the TPP can select the applicable second factor authentication methods for the PSU, if there were several available authentication methods. This link is only contained, if the PSU is already identified or authenticated with the first relevant factor or alternatively an access token, if SCA is required and if the PSU has a choice between different authentication methods. If this link is contained, then there is also the data element "scaMethods" contained in the response body "authoriseTransaction": The link to the authorisation or cancellation authorisation sub-resource, where the authorisation data has to be uploaded, e.g. the TOP received by SMS. "scaStatus": The link to retrieve the scaStatus of the corresponding authorisation sub-resource. "transactionFees": The link is to the status resource. This link is only added in case fee information is available via the status resource.

Attribute	Type	Condition	Description
psuMessage	Max500Text	Optional	

9.10 Cancel an Authorisation Sub-resource Request

With this call the API Client can cancel an explicitly or implicitly generated authorisation or cancellation authorisation sub-resource. This underlying transaction resource for which the authorisation is provided may not be fully authorised, yet. Else this call must be rejected.

Remark: This API Call shall be used only when the ASPSP allows a limited amount of authorisation resource, e.g. in a multilevel SCA approach, and some SCA is still missing but the creation of a new authorisation sub-resource, see Section 9.4, is rejected by the ASPSP due to reaching the maximum number of authorisation resources for this authorisation process. Then the API Client may use this Call to delete an authorisation resource for which SCA was not completed.

Remark: It is recommended for the ASPSP to allow the creation of as many authorisation resources as requested by the API Client as long as the resource is not fully authorised yet.

Call

```
DELETE /v2/{resource-path}/{resourceId}/{authorisation-  
category}/{authorisationId}
```

Path Parameters

Attribute	Type	Description
resource-path	String	This resource path can be a one-level parameter {service} or a two-level parameter {service}/product-type, where • {service} stands for the service type of the related business transaction, e.g. /payments or /consents • {product-type} stands for the product-type of the related business transaction where applicable, e.g. sepa-credit-transfers in the case of payments or account-access in case of consents.

Attribute	Type	Description
resourceId	String	Resource identification of the related payment initiation, signing basket, consent, subscription or other related business transaction resource.
authorisation-category	String	The following two categories are supported: • <code>authorisations</code>: used in case of an authorisation of the related business transaction. • <code>cancellation-authorisations</code>: used in case of the cancellation authorisation of the related business transaction. Used only if applicable to the addressed {service}
authorisationId	String	Resource identification of the related authorisation sub-resource.

Query Parameters

No specific query parameters defined.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in the current business transaction or in a preceding AIS service in the same session, if no such OAuth2 SCA approach was chosen in the current PIS transaction.

Request Body

No request body.

Response Code

The HTTP response code equals 204.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

No response body.

Example

Request

Delete `https://api.testbank.com/psd2/v2/payments/sepa-credit-transfers/3d9a81b3-a47d-4130-8765-a9c0ff861100/authorisations/3d9a81b3-a47d-4130-9999-a9c0ff861100`

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7723
Date: Sun, 06 Aug 2017 15:04:07 GMT

Response

HTTP/1.x 204 no content


X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7723
Date: Sun, 06 Aug 2017 15:04:08 GMT

10 Payment Formats

For core payment products in the European market, this document is defining JSON structures, which will be supported by all ASPSPs

- offering the corresponding payment products to their customers in Version 2.x of the openFinance API Framework and
- providing JSON based payment endpoints.

At the same time, the ASPSP may offer in addition more extensive JSON structures for the same payment products since they might offer these extensions also in their online banking system.



In addition, the specifications for Extended Payment Initiation Services as well as for Request-to-Pay Services given in the respective Implementation Guidelines will mandate the support of more data elements within the openFinance API context, which is already reflected in the subsequent chapters.

For domestic AIS/PIS definitions concerning (payment) formats for domestic elements, please refer to [oFA-DomDef].

10.1 Single Credit Transfers for Core PIS, RTP and Extended PIS

The following describes the data model to be used under `/v2/payments/{credit-transfer-product}`, `/v2/requests-for-payments/{credit-transfer-product}` and `/v2/{extended-payment-services}/{credit-transfer-product}` for certain standard products.

- The "Data Element" column in the table below contains the name of the data element defined in the respective row.
- The "Type" column defines the data type of the respective data element. The document [oFA-DaD] contains all data types together with their definitions used in this framework.
- The other columns are defined for specific services by the following:
 - The columns "SCT Core", "SCT inst Core", "Target2 Core" and "Cross-border CT Core" yield the standard products used for the core compliance services, i.e. the PSD2 complaint services integrated into the new architecture and/or data modelling of the openFinance API Framework. The services are detailed in [oFA-IG-Com].
 - The column "RTP all products" determines the related request-to-pay data model for all payment products. The respective services are described in [oFA-IG-RTP].
 - The column "Extended PIS all products" describes the data model for the extended payment initiation services for all payment products. The respective services are described in [oFA-IG-XPIS].

If the respective implementation guidelines of a service describe a derivation from the generalized specification of the data model given here, then one has to follow the specification given in the service-specific implementation guidelines.

- The general data type of attributes need sometimes to be restricted further, since the related product is not supporting the full data structure. This leads to an [n] in the Type definition requires a further instantiation of the data type by the payment product, which is then indicated in the related column, e.g. by using "Optional[1]" for stating: Optional Usage of this attribute of Type Payment Identification1, where Payment Identification is the full data structure. If there is no instantiation number provided in the product column, then the full data structure applies.

- The notation [a..b] in an entry only applies to arrays and says how many array entries are supported (minimum and maximum). The notation "Optional [1..1]" is following OpenAPI definition for JSON formats and translates into [0..1] for XML format definitions.
- The notation "n.a." ("not applicable") allows ASPSPs or communities of ASPSPs to make this data element optional in their implementations of the related product in further refinements.
- The notation, e.g. "Optional[1]" for an data element with type definition "Type[1]" allows ASPSP or communities of ASPSPs to extend the data model by using all related data type definitions type[n] with a broader scope, e.g. change the entry to "Optional[2]" for the paymentIdentification.
- On all levels, where an element xxxCode and xxxProprietary is offered, only one of the attribute is usable. This will be reflected in OpenAPI files by using the "{Or" and "Or}" in cases where exactly one of the Elements is to be included in the message and "{Or – Optional" and "Or – Optional}" in case where at most one of the elements is to be included in the message.
- For all SEPA payment schemes, it is noted that party name fields have a maximum length of 70 characters, even if the below data dictionary allows 140 characters technically, due to ISO20022 definitions, which might be used for non-SEPA payment schemes. Due to this inconsistency, ASPSP might either reject messages, where the related party name fields use more than 70 characters, or automatically shorten the related party name fields to 70 characters respectively.

NOTE: Please note, that this specification might provide an overview on payment functions and might offer some guidance to which functions are definitely premium payment services. Nevertheless, the openFinance API Framework cannot define the exact scope of what is mandated by the legislation. It is up to the ASPSP to define the exact scope of a PSD2 compliant API.

Data Element	Type	SCT Core	SCT inst Core	Target2 Core	Cross-border CT Core	RTP all products	Extended PIS all products
paymentIdentification	Payment Identification[n]	Optional[1]	Optional[1]	Optional[1]	n.a.	Optional	Optional
instructionPriority	Priority Code	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
serviceLevelCode	Service Level Code	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
localInstrumentCode	External Local Instrument Code	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.

Data Element	Type	SCT Core	SCT inst Core	Target2 Core	Cross-border CT Core	RTP all products	Extended PIS all products
localInstrumentProprietary	Max35Text	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
categoryPurposeCode	Category Purpose Code	n.a.	n.a.	n.a.	n.a.	Optional	Optional
categoryPurposeProprietary	Max35Text	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
chargeBearer	Charge Bearer	n.a.	n.a.	Optional	Conditional ³	n.a.	n.a.
debtorAccount	Account Reference[n]	Mand [1] ⁴	Mand[1] ⁴	Mand[1] ⁴	Mand[1] ⁴	Optional ⁵	Mand ⁴
chargesAccount	Account Reference[n]	n.a.	n.a.	n.a.	Optional[3]	n.a.	n.a.
debtor	Party Description[n]	n.a.	n.a.	n.a.	n.a.	Optional	Optional
ultimateDebtor	Party Description[n]	n.a.	n.a.	n.a.	n.a.	Optional[1]	Optional[1]
instructedAmount	Amount	Mandatory	Mandatory	Mandatory	Mandatory	Mandatory	Mandatory
currencyOfTransfer	Currency Code	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
exchangeRateInformation	Payment Exchange Rate	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
intermediaryAgent1	Agent Description[n]	n.a.	n.a.	n.a.	Optional[1]	n.a.	n.a.
intermediaryAgent2	Agent Description[n]	n.a.	n.a.	n.a.	Conditional[1]	n.a.	n.a.
creditorAccount	Account Reference[n]	Mandatory[1]	Mandatory[1]	Mandatory[1]	Mandatory[1]	Mandatory[1]	Mandatory[1]

³ This field might be mandated by ASPSPs generally or depending of default usage definitions of the ASPSP.

⁴ ASPSPs might change the condition on the debtor account for SEPA payments to optional as one way to fulfil the requirement according to item 36 of the EBA Opinion of June 2020

⁵ Either debtor account or debtor entry shall be provided.

Data Element	Type	SCT Core	SCT inst Core	Target2 Core	Cross-border CT Core	RTP all products	Extended PIS all products
creditorAgent	Agent Description[n]	Optional[1]	Optional[1]	Optional[1]	Conditional[1] ⁶	Optional[1]	Optional[1]
creditor	Party Description[n]	Mandatory[1]	Mandatory[1]	Mandatory[1]	Mandatory[1]	Mandatory	Mandatory
ultimateCreditor	Party Description[n]	Optional[1]	Optional[3]	Optional[1]	Optional[2]	Optional	Optional
purposeCode	Purpose Code	n.a.	n.a.	n.a.	n.a.	Optional	Optional
purposeProprietary	Max35 Text	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
remittanceInformation Unstructured	Array of Max140Text	Optional [1..1]	Optional [1..1]	Optional [1..1]	Optional [1..1]	Optional [1..1]	Optional [1..1]
remittanceInformation Structured	Array of Remittance	n.a.	n.a.	n.a.	n.a.	Optional [1..1]	Optional [1..1]
enclosedFile	Array of Enclosed File	n.a.	n.a.	n.a.	n.a.	Optional [1..1]	n.a.
requestedExecution Date	ISODate	n.a.	n.a.	n.a.	n.a.	Optional	Optional
requestedExecution DateTime	ISODateTime	n.a.	n.a.	n.a.	n.a.	(only if SCT INST)	(only if SCT inst)
regulatory Reporting	Array of Regulatory Reporting	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
additionalRequestInformation⁷	Additional Request Information	n.a.	n.a.	n.a.	n.a.	Optional	Conditional ⁸

⁶ This field might be mandated by ASPSPs generally or depending of the creditor's address' country.

⁷ Only applicable for request to pay services and extended payment services.

⁸ Must be used for all kinds of deferred payments and single and multiple pre-authorised payment. It is not supported for other Extended Payment Initiation Services.

10.2 Repository for Single Credit Transfer and RTP

The following table describes the full payment data model as a repository for product definitions.

Data Element	Type	Condition	Description
paymentIdentification	Payment Identification	Optional	Set of elements used to reference a payment instruction.
paymentMethod	Credit Transfer Payment Method Code	Optional	Specifies the means of payment that will be used to move the amount of money. Usage: Only used for cross-border transactions. If no paymentMethod is explicitly stated, paymentMethod will be interpreted as "TRF" (Credit Transfer).
instructionPriority	Priority Code	Optional	Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.
serviceLevelCode	Service Level Code	Optional	Agreement under which or rules under which the transaction should be processed, provided as a code.
localInstrumentCode	External Local Instrument Code	{Or - Optional	Agreement under which or rules under which the transaction should be processed, provided in proprietary encoding.
localInstrumentProprietary	Max35Text	Or – Optional}	User community specific instrument, provided in proprietary encoding.
categoryPurposeCode	Category Purpose Code	{Or – Optional	Specifies the high level purpose of the instruction based on a set of pre-defined categories; provided as code.
categoryPurposeProprietary	Max35Text	Or – Optional}	Specifies the high level purpose of the instruction based on a set of pre-defined categories; provided in proprietary encoding.
chargeBearer	Charge Bearer	Optional	Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Data Element	Type	Condition	Description
debtorAccount	Account Reference	Optional	Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.
chargesAccount	Account Reference3	Optional	Account used to process charges associated with a transaction.
debtor	Party Description	Optional	Party that owes an amount of money to the (ultimate) creditor.
ultimateDebtor	Party Description	Optional	Ultimate party that owes an amount of money to the (ultimate) creditor. Restriction to the schema are applied depending on the product, see 10.1.
instructedAmount	Amount	Mandatory	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.
currencyOfTransfer⁹	Currency Code	Optional	Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.
exchangeRateInformation	Payment Exchange Rate	Optional	Set of elements used to provide details on the currency exchange rate and contract.
creditorAccount	Account Reference1	Optional	Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.
creditorAgent	Agent Description	Optional	Financial institution servicing an account for the creditor.
creditor	Party Description	Optional	Party to which an amount of money is due.
ultimateCreditor	Party Description	Optional	Ultimate party to which an amount of money is due.
purposeCode	Purpose Code	Optional	Underlying reason for the payment transaction, provided as a code.

⁹ This is a data element to indicate a diverging interbank transaction currency.

Data Element	Type	Condition	Description
purposeProprietary	Max35Text	Optional	Underlying reason for the payment transaction, provided as proprietary encoding.
remittanceInformation Unstructured	Array of Max140Text	{Or -Optional	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.
remittanceInformation Structured	Array of Remittance	Or – Optional}	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.
enclosedFile	Array of Enclosed File	Optional	If the RTP includes a document, then this parameter contains the information about the attached document.
requestedExecution Date	ISODate	{Or -Optional	Date at which the initiating party requests the clearing agent to process the payment.
requestedExecution Date Time	ISODateTime	Or – Optional}	Date and time at which the initiating party requests the clearing agent to process the payment.
regulatoryReporting	Array of Regulatory Reporting	Optional	Information needed due to regulatory and statutory requirements.
additionalRequest Information¹⁰	Additional Request Information	Optional	Request related information which is not directly linked to the payment transaction.

¹⁰ Only applicable for request to pay services and extended payment services.

10.3 Bulk Credit Transfers

The following table displays the data model to be used under `/v2/bulk-payments/{credit-transfer-product}`. Further restrictions on data attribute types, inherited from Section 10.1 might apply.

Data Element	Type	Condition	Description
paymentInformationId	Max35Text	mandatory	Unique identification as assigned by the sending party to unambiguously identify this bulk payment. This attribute may be used by ASPSPs or communities as an optional field.
paymentMethod	Credit Transfer Payment Method Code	Optional	Specifies the means of payment that will be used to move the amount of money. Usage: Only used for cross-border transactions. If no paymentMethod is explicitly indicated, paymentMethod will be interpreted as "TRF" (Credit Transfer).
batchBooking	Boolean	optional	If this element equals true, the PSU prefers only one booking entry. If this element equals false, the PSU prefers individual booking of all contained individual transactions. The ASPSP will follow this preference according to contracts agreed on with the PSU.
numberOfTransactions	Integer	Mandatory	Number of individual transactions contained in the related bulk.
controlSum	Max35Text	Mandatory	Total of all individual amounts included in the group, irrespective of currencies.
serviceLevelCode	Service Level Code	Optional	
chargeBearer	Charge Bearer	Optional	
categoryPurposeCode	Category Purpose Code	{Or – Optional}	
categoryPurposeProprietary	Max35Text	Or – Optional}	
localInstrumentCode	Local Instrument Code	{Or – Optional}	
localInstrumentProprietary	Max35Text	Or – Optional}	
debtor	Party Description	Optional	
ultimateDebtor	Party Description	Optional	
debtorAccount	Account Reference	mandatory	
debtorAgent	Agent Description 2	n.a.	

Data Element	Type	Condition	Description
chargesAccount	Account Reference 3	Optional	Account used to process charges associated with a transaction.
requestedExecutionDate	ISODate	{Or – optional	If contained, the payments contained in this bulk will be executed at the addressed date. This field may not be used together with the field requestedExecutionTime.
requestedExecutionDateTime	ISODateTime	Or – optional}	If contained, the payments contained in this bulk will be executed at the addressed Date/Time. This field may not be used together with the field requestedExecutionDate.
creditTransfers	Array of Credit Transfer Bulk Entry	mandatory	The Credit Transfer Bulk Entry is a type which follows the JSON formats for the supported products for single payments, see Section 10.1, excluding the data elements • debtorAccount, • debtor • debtorAgent • requestedExecutionDate, • requestedExecutionDateTime. These data elements may not be contained in any bulk entry. In addition, the following entries will be allowed for every single entry, if not used already on bulk level: chargeBearer chargesAccount categoryPurposeCode categoryPurposeProprietary serviceLevelCode localInstrumentCode localInstrumentProprietary ultimateDebtor In addition, the attributes purposeCode remittanceInformationStructured are always available on entry level if supported by the related payment product.

Example

```
{
  "paymentInformationId": "bulk-payment 123",
  "batchBooking": true,
  "numberOfTransactions": 2,
  "controlSum": "12345.01",
  "debtorAccount": {"iban": "DE40100100103307118608"},
  "requestedExecutionDate": "2018-08-01",
  "creditTransfers": [{JSON based payment initiation 1}, {JSON based payment initiation 2}]
}
```

10.4 Multi Bulk Credit Transfers

Data model to be used under `/v2/multi-bulk-payments/{credit-transfer-product}`.

Data Element	Type	Condition	Description
messageId	Max35Text	mandatory	Unique identification as assigned by the sending party to unambiguously identify this bulk payment. This attribute may be used by ASPSPs or communities as an optional field.
creationDateTime	ISODateTime	Mandatory	
numberOfTransactions	Integer	Mandatory	Number of individual transactions contained in the related bulk.
controlSum	Max35Text	Mandatory	Total of all individual amounts included in the group, irrespective of currencies.
initiatingParty	Party Description1	Mandatory	Party that initiates the payment.
payments	Array of Credit Transfer Bults	Mandatory	This is an array of credit transfer bulks, as defined in Section 10.3.

10.5 RTP Bulk

The following table displays the data model to be used under `/v2/bulk-requests-for-payments/{credit-transfer-product}`.

Data Element	Type	Condition	Description
paymentInformationId	Max35Text	Mandatory	Unique identification as assigned by the sending party to unambiguously identify this bulk. This attribute may be used by ASPSPs or communities as an optional field.
numberOfTransactions	Integer	Mandatory	Number of individual transactions contained in the related bulk.
controlSum	Max35Text	Mandatory	Total of all individual amounts included in the group, irrespective of currencies.
chargeBearer	Charge Bearer	Optional	
serviceLevelCode	Service Level Code	Optional	For SCT not used, only defined to support non SEPA RTP schemes
categoryPurposeCode	Category Purpose Code	{Or – Optional	
categoryPurposeProprietary	Max35Text	Or – Optional}	For SCT not used, only defined to support non SEPA RTP schemes
localInstrumentCode	Local Instrument Code	{Or – Optional	For SCT not used, only defined to support non SEPA RTP schemes
localInstrumentProprietary	Max35Text	Or – Optional}	For SCT not used, only defined to support non-SEPA RTP schemes
requestedExecutionDate	ISODate	Optional	
creditor	Party Description	Mandatory	

Data Element	Type	Condition	Description
creditorAccount	Account Reference1	mandatory	
creditorAgent	Agent Description1	optional	
ultimateCreditor	Party Description	optional	
rtps	Array of RTP Bulk Entry	mandatory	The RTP Bulk Entry is a type which follows the JSON formats for the supported products for single RTP, see Section 10.1, excluding the data elements • creditorAccount, • creditor • creditorAgent These data elements may not be contained in any bulk entry. In addition, the following entries will be forbidden for every single entry, if they are used already on bulk level: chargeBearer requestedExecutionDate ultimateCreditor categoryPurposeCode categoryPurposeProprietary serviceLevelCode localInstrumentCode localInstrumentProprietary In addition, the attributes purposeCode remittanceInformationStructured are always available on entry level if supported by the related payment product.

Example

```
{
  "paymentInformationId": "bulk-request-to-pay 123",
  "numberOfTransactions": 2,
  "controlSum": "12345.01",
  "creditor": {
    "name": "RTP beneficiary's name"
  },
  "creditorAccount": {
    "iban": "DE40100100103307118608"
  },
  "rtps": [
    {JSON based RTP 1},
    {JSON based RTP 2}
  ]
}
```

10.6 Single SEPA Direct Debits

The following table describes the full direct debit data model as a repository for product definitions. Currently, the model is intended to be only used for SEPA Direct Debits. However, some extension of the data model are made to enable adoptions for other schemas in a structured way.

Data Element	Type	Condition	Description
paymentIdentification	Payment Identification1	Optional	Set of elements used to reference a payment instruction.
requestedCollectionDate	ISO Date		
creditor	Party Description2	Optional	Party that owes an amount of money to the (ultimate) creditor.
creditorAccount	Account Reference2	Optional	Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.
creditorAgent	AgentDescription2	Optional	Only BIC allowed
creditorSchemeId	Party Description3	Optional	Id: Creditor-Identifier (CI) only allowed if not present on transaction level "schemeNameProprietary" : "SEPA"
serviceLevelCode	Service Level Code	Optional	Agreement under which or rules under which the transaction should be processed, provided as a code. Remark: SEPA Direct Debit (SDD) scheme requires "SEPA"
localInstrumentCode	Local Instrument Code	{Or - Optional	Agreement under which or rules under which the transaction should be processed, provided in proprietary encoding. Remark: Within the SDD scheme, only "CORE" or "B2B" are used
localInstrumentProprietary	Max35Text	Or – Optional}	Remark: Within the SDD scheme, usage of this element is not supported.
sequenceType	Sequence Type Code	Optional	Remark: For SDD, only "FNAL", "FRST", "OOF" or "RCUR" is used
categoryPurposeCode	Category Purpose Code	Optional	Specifies the high level purpose of the instruction based on a set of pre-defined categories; provided as code.

Data Element	Type	Condition	Description
instructedAmount	Amount	Optional	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.
chargeBearer	Charge Bearer	Optional	Specifies which party/parties will bear the charges associated with the processing of the payment transaction.
directDebitTransaction	Direct Debit Transaction	Optional	Provides information specific to the direct debit mandate.
ultimateCreditor	Party Description1	Optional	Ultimate party that owes an amount of money to the (ultimate) creditor.
debtorAgent	Agent Description1	Optional	Financial institution servicing an account for the debtor. Remark: Within the SDD scheme only subelement "bicfi" of "financialInstitutionId" is used.
debtor	Party Description	Optional	Party to which an amount of money is due. Remark: Within the SDD scheme only subelements "name" and "postalAddress" are used. Usage of "postalAddress" is further restricted to "country" and at most two entries in "adressLines".
debtorAccount	Account Reference2	Optional	Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.
ultimateDebtor	Party Description1	Optional	Ultimate party to which an amount of money is due. Remark: Within the SDD scheme only subelement "name" is restricted to 70 characters.
purposeCode	Purpose Code	Optional	Underlying reason for the payment transaction, provided as a code.
remittanceInformationUnstructured	Array of Max140Text	{Or - Optional	Remark: Within the SDD scheme not more than one item is included in the array.

Data Element	Type	Condition	Description
remittanceInformationStructured	Array of Remittance	Or – Optional}	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

10.7 SEPA Direct Debit Bulk

The following table displays the data model to be used under /v2/bulk-payments/sepa-direct-debits.

Data Element	Type	Condition	Description
paymentInformationId	Max35Text	mandatory	Unique identification as assigned by the sending party to unambiguously identify this bulk payment. This attribute may be used by ASPSPs or communities as an optional field.
batchBooking	Boolean	optional	If this element equals true, the PSU prefers only one booking entry. If this element equals false, the PSU prefers individual booking of all contained individual transactions. The ASPSP will follow this preference according to contracts agreed on with the PSU.
numberOfTransactions	Integer	Mandatory	Number of individual transactions contained in the related bulk.
controlSum	Max35Text	Mandatory	Total of all individual amounts included in the group, irrespective of currencies.
serviceLevelCode	Service Level Code	Optional	Remark: SDD scheme requires "SEPA"
localInstrumentCode	Local Instrument Code	{Or – Optional	Agreement under which or rules under which the transaction should be processed, provided in proprietary encoding. Remark: Within the SDD scheme, only "CORE" or "B2B" is used
localInstrumentProprietary	Max35Text	Or – Optional}	Remark: Within the SDD scheme, usage of this element is not supported.
sequenceType	Sequence Type Code	Optional	Remark: For SDD, only "FNAL", "FRST", "OOF" or "RCUR" is used
categoryPurposeCode	Category Purpose Code	Optional	
requestedCollectionDate	ISODate	Mandatory	
creditor	Party Description2	Optional	Remark: Within the SDD scheme, only subelements "name" and "postalAddress" are supported.
creditorAccount (incl. type)	Account Reference2	mandatory	Remark: Within the SDD scheme, subelement "iban" is mandatory and

Data Element	Type	Condition	Description
			apart from "iban" only "currency" supported.
creditorAgent	Agent Description2	optional	Remark: Within the SDD scheme, only subelement "bicfi" is supported.
ultimateCreditor	Party Description1	optional	
chargeBearer	Charge Bearer	optional	Remark: Within the SDD scheme, only value "SLEV" is supported.
creditorSchemeld	Party Description3	Optional	Remark: Within the SDD the following requirements apply: PrivateID Other Id: Creditor-Identifier (CI) "schemeNameProprietary" : "SEPA"
directDebits	Array of Direct Debit Bulk Entry	mandatory	Direct Debit Bulk Entry is a type which follows the JSON formats for the supported products for single payments, see Section 10.1, excluding the data elements • creditorAccount, • creditor • icreditorAgent • requestedCollectionDate, These data elements may not be contained in any bulk entry. In addition, the following entries will only be allowed for every single entry, if not used already on bulk level: chargeBearer categoryPurposeCode categoryPurposeProprietary serviceLevelCode localInstrumentCode localInstrumentProprietary sequenceType ultimateCreditor In addition, the attributes purposeCode remittanceInformationStructured are always available on entry level if supported by the related payment product.

Example

```
{
  "paymentInformationId": "bulk-direct-debit 123",
  "batchBooking": true,
  "numberOfTransactions": 2,
  "controlSum": "12345.01",
  "creditorAccount": {"iban": "DE40100100103307118608"},
  "requestedCollectionDate": "2018-08-01",
  "directDebits":
    [{JSON based direct debit 1}, {JSON based direct debit 2}]
}
```

10.8 SEPA Direct Debit Multi Bulk

Data model to be used under /v2/multi-bulk-payments/sepa-direct-debits .

Data Element	Type	Condition	Description
messageId	Max35Text	mandatory	Unique identification as assigned by the sending party to unambiguously identify this bulk payment. This attribute may be used by ASPSPs or communities as an optional field.
creationDateTime	ISODateTime	mandatory	
numberOfTransactions	Integer	Mandatory	Number of individual transactions contained in the related bulk.
controlSum	Max35Text	Mandatory	Total of all individual amounts included in the group, irrespective of currencies.
initiatingParty	Party Description1	Mandatory	Party that initiates the payment.
directDebitBulks	Array of Direct Debit Bulks	Mandatory	This is an array of direct Debit bulks, as defined in Section 2.6.

11 Signing Baskets

The signing basket is a function of the openFinance API Framework to bundle several transactions for authorisation. The SCA is then covering all transactions within the signing basket simultaneously. The ASPSP offering this service can restrict the bundling of transactions to certain transaction types, e.g. payments only.

Remark: Resources that are undergoing a change process as described in Section 3.4 for which authorisation of the changed variant is still needed, may not be bundled in a signing basket.

11.1 Access Methods for Signing Baskets

Please note that the Establish Signing Basket Request is one instantiation of the Transaction Initiation Request as introduced in Section 2.2.5, i.e. the notion of authorisation sub resources and related access methods do also apply here but are specified generically in Section 9.

The following access methods are provided for signing baskets:

Endpoints	Method	Condition	Description
signing-baskets	POST	Optional	Creates a signing basket resource, where all transactions to be signed will be addressed within the body. Section 11.2
signing-baskets/{basketId}	GET	Mandatory	Retrieve the content of a signing basket resource. Section 11.3
signing-baskets/{basketId}/status	GET	Mandatory	Retrieve the signing basket status Section 11.4
signing-baskets/{basketId}	DELETE	Optional	Remove an existing signing basket. The transactions contained in the basket are not impacted by this call. Section 11.5

11.2 Establish Signing Basket Request

POST /v2/[signing-baskets/](#)

Generates a signing basket

NOTE: Please note that the Establish Signing Basket Request is one instantiation of the Transaction Initiation Request as introduced in Section 2.2.5, i.e. all related header

parameters regarding PSU context, PSU Identification etc. will apply but will not be described in detail here. The related Open API files will offer all header parameters in detail.

Path Parameters

None.

Query Parameters

No Query Parameter

Request Header

Attribute	Type	Condition	Description
Content-Type	String	Mandatory	application/json
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Bearer Token. Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in an preceding AIS service in the same session.
Consent-ID	String	Optional	This data element may be contained, if the signing basket transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS one off consent, which was performed prior to this bulk signing.
PSU-IP-Address	String	Mandatory	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.

Request Body

Attribute	Type	Condition	Description
paymentIds	Array of Max70Text	Optional	A non-empty array of paymentIds.
consentIds	Array of Max70Text	Optional	A non-empty array of consentIds.
subscriptionIds	Array of Max70Text	Optional	A non-empty array of subscriptionIds.

Attribute	Type	Condition	Description
subscriptionEntryIds	Array of Max70Text	Optional	A non-empty array of subscriptionEntryIds.
mandateResourceIds	Array of Max70Text	Optional	A non-empty array of mandateResourceIds

The body shall contain at least one entry.

Response Code

The HTTP response code equals 201.

Response Header

Attribute	Type	Condition	Description
Location	String	Mandatory	Location of the created resource (if created)
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
transactionStatus	Transaction Status	Mandatory	The non-payment related values might be used like RCVD or ACTC. For a list of all transactionStatus codes permitted for signing baskets, cp. Section 11.4.
basketId	Max70Text	Mandatory	resource identification of the generated signing basket resource.
scaMethods	Array of Authentication Objects	Conditional	This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods. Depending on the risk management of the ASPSP this choice might be offered before or after the PSU has been identified with the first relevant factor, or if an access token is transported. If this data element is contained, then there is also a hyperlink of type "startAuthorisationWith

Attribute	Type	Condition	Description
			AuthenticationMethodSelection" contained in the response body. These methods shall be presented towards the PSU for selection by the TPP.
chosenScaMethod	Authentication Object	Conditional	This data element is only contained in the response if the ASPSP has chosen the Embedded SCA Approach or the Signature SCA Approach, if the PSU is already identified e.g. with the first relevant factor or alternatively an access token, if SCA is required and if the authentication method is implicitly selected.
challengeData	Challenge	Conditional	It is contained in addition to the data element "chosenScaMethod" if challenge data is needed for SCA.
			In rare cases this attribute is also used in the context of the "startAuthorisationWithPsuAuthentication" link.
_links	Links	Mandatory	A list of hyperlinks to be recognised by the API Client. The actual hyperlinks used in the response depend on the dynamical decisions of the ASPSP when processing the request. The potential links for this response message are generically defined in Section 3.8.1 for all Transaction Initiation Response messages which applies also to the Establish Signing Basket Response. These links will also be contained in the related Open API files. Remark: All links can be relative or full links, to be decided by the ASPSP.
psuMessage	Max500Text	Optional	Text to be displayed to the PSU
apiClientMessages	Array of Client Message Information	Optional	Messages to the API Client on operational issues.

Example

Request

POST <https://api.testbank.com/psd2/v2/signing-baskets>

```

Content-Type:          application/json
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
PSU-IP-Address:        192.168.8.78
PSU-GEO-Location:      GEO:52.506931;13.144558
PSU-User-Agent:        Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
Date:                  Sun, 06 Aug 2017 15:02:37 GMT

```

```

{
  "paymentIds": ["3d9a81b3-a47d-4130-8765-a9c0ff861100", "3d9a81b3-a47d-4130-8765-a9c0ff861100"]
}

```

Response (always with explicit authorisation start)

```

HTTP/1.x 201 Created
X-Request-ID:          99391c7e-ad88-49ec-a2ad-99ddcb1f7721
ASPSP-SCA-Approach:    REDIRECT
Date:                  Sun, 06 Aug 2017 15:02:42 GMT
Location:              https://www.testbank.com/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100
Content-Type:          application/json

```

```

{
  "transactionStatus": "RCVD",
  "basketId": "3d9a81b3-a47d-4130-8766-a9c0ff861100",
  "_links": {
    "self": {"href": "/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100"},
    "status": {"href": "/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100/status"},
    "startAuthorisation": {"href": "/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100/authorisations"}
  }
}

```

11.3 Get Signing Basket Request

Call

GET /v2/[signing-baskets/{basketId}](#)

Returns the content of a signing basket object.

Path Parameters

Attribute	Type	Description
basketId	String	ID of the corresponding signing basket object.

Query Parameters

No specific query parameter.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in the current PIS transaction or in a preceding AIS service in the same session, if no such OAuth2 SCA approach was chosen in the current signing basket transaction.

Request Body

No request body.

Response Code

The HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
paymentIds	Array of Max70Text	Optional	A non-empty array of paymentIds.
consentIds	Array of Max70Text	Optional	A non-empty array of consentIds.
subscriptionIds	Array of Max70Text	Optional	A non-empty array of subscriptionIds.
subscriptionEntryIds	Array of Max70Text	Optional	A non-empty array of subscriptionEntryIds.

Attribute	Type	Condition	Description
mandateResourceIds	Array of Max70Text	Optional	A non-empty array of mandateResourceIds.
transactionStatus	Transaction Status	Mandatory	Only the not explicitly payment related codes like RCVD, PATC, ACTC, RJCT are used. For a list of all transactionStatus codes permitted for signing baskets, cp. Section 11.4.
_links	Links	Optional	The ASPSP might integrate hyperlinks to indicate next (authorisation) steps to be taken.

Example

Request

GET <https://api.testbank.com/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100>

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 06 Aug 2017 15:05:46 GMT

Response

HTTP/1.x 200 Ok

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 06 Aug 2017 15:05:47 GMT

Content-Type: application/json

```
{
  "paymentIds": ["3d9a81b3-a47d-4130-8765-a9c0ff861100", "3d9a81b3-a47d-4130-8765-a9c0ff861110"],
  "transactionStatus": "ACTC"
}
```

11.4 Get Signing Basket Status Request

Call

GET /v2/[signing-baskets/{basketId}](#)/status

Returns the status of a signing basket object.

Path Parameters

Attribute	Type	Description
basketId	String	ID of the corresponding signing basket object.

Query Parameters

No specific query parameter.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based authentication was performed in a pre-step or an OAuth2 based SCA was performed in the current PIS transaction or in a preceding AIS service in the same session, if no such OAuth2 SCA approach was chosen in the current signing basket transaction.

Request Body

No request body.

Response Code

The HTTP response code equals 200.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

Attribute	Type	Condition	Description
transactionStatus	Transaction Status	Mandatory	Only the codes RCVD, PATC, ACTC, CANC and RJCT are supported for signing baskets.

Example

Request

GET <https://api.testbank.com/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100/status>

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 06 Aug 2017 15:05:49 GMT

Response

HTTP/1.x 200 Ok

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 06 Aug 2017 15:05:51 GMT
Content-Type: application/json

```
{
  "transactionStatus": "ACTC"
}
```

11.5 Cancellation of Signing Baskets

A cancellation of a Signing Basket is only permitted where no (partial) authorisation has been applied for the Signing Basket.

Call

DELETE /v2/signing-baskets/{basketId}

Deletes a created signing basket if it is not yet (partially) authorised.

Path Parameters

Attribute	Type	Description
basketId	String	Contains the resource-ID of the signing basket to be deleted.

Query Parameters

No specific query parameters.

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.
Authorization	String	Conditional	Is contained only, if an OAuth2 based SCA has been used in a pre-step.

Request Body

No Request Body.

Response Code

The HTTP response code is 204 in case of successful deletion.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Response Body

No Response Body

Example

Request

```
DELETE https://api.testbank.com/psd2/v2/signing-baskets/3d9a81b3-a47d-4130-8766-a9c0ff861100
X-Request-ID      99391c7e-ad88-49ec-a2ad-99ddcb1f7757
Date              Sun, 13 Aug 2017 17:05:37 GMT
```

Response

```
HTTP/1.x 204 No Content
X-Request-ID:      99391c7e-ad88-49ec-a2ad-99ddcb1f7757
Date:              Sun, 13 Aug 2017 17:05:38 GMT
```

12 Resource Status Notification

The openFinance API Framework is supporting a resource status notification function, formally specified in an alone standing document as Resource Status Notification Service before. This is now covered within this section as a basic building block for the openFinance API Framework V2.

This resource status notification function allows ASPSP to push status changes of a resource created by the API Client within the openFinance API Framework. The API Client needs to register for receiving such notification messages for every resource where such a function is envisaged. This registration is steered by the API Client by adding certain headers within the related Transaction Initiation Request message, which creates the addressed resource.

The related header parameters as defined in Section 12.4 will not be repeated on service implementation guideline level, but will still be contained in OpenAPI files as an instantiation to service specifications.

The resource status notification function is an optional feature within the openFinance API Framework, i.e. a related registration by the API Client might be ignored by the ASPSP. Requirements on TLS support for the actual push function (turning the ASPSP into a technical http client towards the API Client) are defined in Section 5.2.

12.1 API Access Methods

The following table gives an overview on the HTTP access methods supported by the notification API endpoints of the API Client for receiving notification messages on resource status changes by the ASPSP.

Endpoint	Method	Condition	Description
<Client-Notification-URI>	POST	Conditional	Notification initiated by ASPSP, endpoint provided by the API Client. This command posts notification content to the provided endpoint. This access method shall be supported by the API Client if a Client-Notification-URI is provided by the API Client in a previous call to the XS2A Interface or openFinance API of the ASPSP.

12.2 HTTP Response Codes for Notifications

The HTTP response code is communicating the success or failure of an API Client request message. The 4XX HTTP response codes should only be given if the current request cannot be fulfilled, e.g. the syntax of the body content is not correct.

This specification supports the following HTTP response codes for the Client Notification API:

Status Code	Description
200 OK	POST for a notification
400 Bad Request	Validation error occurred. This code will cover malformed syntax in request or incorrect data in payload.
401 Unauthorized	The API Client or the PSU is not correctly authorized to perform the request. Retry the request with correct authentication information.
403 Forbidden	Returned if the resource that was referenced in the path exists but cannot be accessed by the ASPSP. This code should only be used for non-sensitive id references as it will reveal that the resource exists even though it cannot be accessed.
404 Not found	Returned if the endpoint that was referenced in the path does not exist or cannot be referenced by the ASPSP. When in doubt if a specific id in the path is sensitive or not, use the HTTP response code 404 instead of the HTTP response code 403.
405 Method Not Allowed	This code is only sent when the HTTP method (PUT, POST, DELETE, GET etc.) is not supported on a specific endpoint.
408 Request Timeout	The server is still working correctly, but an individual request has timed out.
415 Unsupported Media Type	The ASPSP has supplied a media type which the API Client does not support.
500 Internal Server Error	Internal server error occurred.
503 Service Unavailable	The API Client server is currently unavailable. Generally, this is a temporary state.

12.3 Implicit Subscription for Resource Status Notification

This section describes how an API Client is registering for the resource status notification function within the Transaction Initiation Request message, e.g. a Payment Initiation Message or an Establish Consent Request message.

NOTE: The notification services will also be available for cancellation processes which require SCA based authentication of PSUs. These services will then be supported by the ASPSP if requested before by the API Client for the related resource initiation process. So, the "notification service" support function is stored within the created resource.

12.4 Communicate Notification URI of API Clients to the ASPSP

Call

Any POST command

- creating a resource (potentially to be authorised) within the openFinance API Framework.

Creates a corresponding resource in the ASPSP server.

Path Parameters

No specific requirements for the subscription of the resource status notification function.

Query Parameters

No specific requirements for the subscription of the resource status notification function.

Request Header

The following table contains only the request headers which have to be supported by the TPP or the API Client more generally in addition to headers defined API request.

Attribute	Type	Condition	Description
Client-Notification-URI	String	Optional	URI for the Endpoint of the Client API to which the status of the resource should be sent. This header field may be ignored by the ASPSP if the resource status push function is not supported for the related API client.
Client-Notification-Content-Preferred	String	Optional	The string has the form status=X1, ..., Xn where Xi is one of the constants SCA, PROCESS, LAST, MAJOR and where constants are not repeated. The usage of the constants supports the following semantics: SCA: A notification on every change of the scaStatus attribute for all related authorisation processes is preferred by the API Client.

Attribute	Type	Condition	Description
			PROCESS: A notification on all changes of resource status attributes is preferred by the API Client. LAST: Only a notification on the last resource status after its full authorisation is preferred by the API Client. MAJOR: A notification on the resource status after partial and full authorisation and in addition every resource status change after the authorisation. This header field may be ignored, if the ASPSP does not support the resource notification push function for the related API Client. Service implementation guidelines will provide more information.

NOTE: If only one of the two notification headers is presented, the ASPSP will ignore the related header, since no clear preference is provided by the API Client or no notification URI is provided.

Request Body

No specific requirements.

Response Code

No specific requirements

Response Header

The following table contains only the response headers which have to be supported by the ASPSP in addition to headers defined for the corresponding response of the related API service if the resource status push function is supported.

Attribute	Type	Condition	Description
ASPSP-Notification-Support	Boolean	Conditional	true if the ASPSP supports the resource status push function for the created resource. false if the ASPSP supports resource status push function in general, but not for the current request. One of the reasons of no support is that the API Client had not explicitly asked for the function in the request.


Attribute	Type	Condition	Description
			Not used, if the resource status notification function is generally not supported by the ASPSP. Shall be supported if the ASPSP generally supports the resource status notification function.
ASPSP-Notification-Content	String	Conditional	The string has the form status=X1, ..., Xn where Xi is one of the constants SCA, PROCESS, LAST, MAJOR and where constants are not repeated. The usage of the constants supports the following semantics: SCA: Notification on every change of the scaStatus attribute for all related authorisation processes is provided by the ASPSP for the related resource. PROCESS: Notification on all changes of the resource status attributes is provided by the ASPSP for the related resource. LAST: Only a notification on the last resource status after its full authorisation is provided by the ASPSP for the related resource. MAJOR: A notification on the last resource status after its partial and full authorisation and in addition every resource status change after the authorisation provided by the ASPSP for the related resource. This field shall be provided if the ASPSP-Notification-Support =true. The ASPSP might consider the notification content as preferred by the TPP, but can also respond independently of the preferred request.

Response Body

No specific requirements.

12.5 Resource Status Notification Message Flow

The following flow shows the simple request and response flow for a resource status notification function:



Remark: In case, where the ASPSP is only pushing a status hyperlink to the API Client, the API Client needs to check the resource status after step 2.) before informing e.g. the PSU.

12.6 Push Resource Status with JSON encoding

Call

POST <Client-Notification-URL>

Creates a Resource Notification on the API Client server.

Path Parameters

No Path Parameter

Query Parameters

No Query Parameter

Request Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the request, unique to the call, as determined by the initiating party.

Request Body

Attribute	Type	Condition	Description
paymentId	Max70Text	{Or	This shall be contained, if the push notification is about a payment or RTP initiation.
consentId	Max70Text	Or	This shall be contained if the push notification is about establishing a consent.
subscriptionId	Max70Text	Or	This shall be contained if the push notification is about establishing a subscription.
basketId	Max70Text	Or	This shall be contained if the push notification is about signing a basket.
mandateResourceId	UUID	Or	This shall be contained if the push notification is about establishing a mandate.
documentResourceId	UUID	Or}	This shall be contained, if the push notification is about a document submission.
entryId	Max70Text	{Or – Optional	This may be used if the status relates to an entry of an RTP bulk.
subscriptionEntryId	Max70Text	Or – Optional}	This may be used if the status relates to an entry of a subscription.
authorisationId	Max70Text	{Or - Optional	This attribute should be contained if the push notification is about a specific SCA status.
cancellationId	Max70Text	Or - Optional}	This attribute should be contained if the push notification is about a specific SCA status of a cancellation authorisation sub-resource.
transactionStatus	Transaction Status	{Or Optional	This attribute might be contained if the related resource contains a transaction status which has changed.

Attribute	Type	Condition	Description
consentStatus	Consent Status	Or Optional	This attribute might be contained if the consent status of the addressed resource has changed.
subscriptionStatus	Subscription Status	Or Optional	This attribute might be contained if the subscription status of the addressed resource has changed.
subscriptionEntryStatus	Subscription Entry Status	Or Optional	This attribute might be contained if the subscription entry status of the addressed resource has changed.
mandateStatus	Mandate Status	Or optional	This attribute might be contained if the mandate status of the addressed resource has changed.
documentStatus	Document Status	Or optional}	This attribute might be contained if the document status of the addressed resource has changed.
scaStatus	SCA Status	Optional	This attribute might be contained if the authorisation status of the addressed authorisation resource has changed.
requestStatus	Request Status	Optional	The status of the related request to pay transaction. To be delivered by the API Server if not agreed otherwise.
reasonCode	Status Reason Code	{Or Optional	Additional information on the reason for e.g. rejecting the request
reasonProprietary	Max35Text	Or Optional}	Proprietary additional information on the reason for e.g. rejecting the request.
debtorDecision DateTime	ISO Date Time	Optional	The date and time when the PSU has decided on accepting/rejecting the related request.
acceptedAmount	Amount	Optional	Contained only if the accepted amount deviates from the instructed amount.
acceptanceDateTime	ISODateTime	Optional	Contained only if the agreed requested execution date deviates

Attribute	Type	Condition	Description
			from the requested execution date in the request.
acceptedPaymentInstrument	Max105Text	Optional	“SCT” or “SCT inst” as default values.
statusIdentification	Max35Text	Optional	Reference added by the debtor.
_links	Links	Optional	The following link types are supported.
			scaStatus This shall be contained if the related SCA status is not reported at the same time by the scaStatus attribute. The API Client then needs to get the scaStatus by a GET command using this hyperlink.
			status This shall be contained if the related consent or transaction status is not reported at the same time. The API Client then needs to get the resource status by a GET command using this hyperlink.

HTTP Response Code

200

Remark: All response codes which do not equal 200 are ignored by the ASPSP. The notification will not be repeated.

Response Header

Attribute	Type	Condition	Description
X-Request-ID	UUID	Mandatory	ID of the corresponding request, unique to the call, as determined by the initiating party.

Response Body

No Response Body

**Example
Request**

POST https://notifications.testclient.com/v2/transaction-12345

Content-Type: application/json

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 06 Aug 2017 15:02:37 GMT

```
{
  "paymentId": "3d9a81b3-a47d-4130-8765-a9c0ff861100",
  "transactionStatus": "ACFC"
}
```

Response

HTTP/1.x 200

Content-Type: application/json

X-Request-ID: 99391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 06 Aug 2017 15:04:08 GMT



13 Annex

13.1 List of tables

TABLE 1: HEADER PARAMETERS FOR HTTP MESSAGE SIGNATURE ACCORDING TO [OBESIGN].	52
TABLE 2: ELEMENTS OF THE JSON WEB SIGNATURE ACCORDING TO [OBESIGN].	54
TABLE 3: PARAMETERS OF THE JWS PROTECTED HEADER ACCORDING TO [OBESIGN].	57
TABLE 4: SUPPORTED SIGNATURE PROFILES.	67
TABLE 5: FLOW FOR SIGNED TRANSACTION REQUEST WITH EXPLICIT AUTHORISATION	68
TABLE 6: JSON STRUCTURE OF A JWS	75
TABLE 7: JSON STRUCTURE OF A JWS PROTECTED HEADER	77
TABLE 8: HEADER PARAMETERS TO INDICATE THE ENCRYPTION OF (PARTS OF) THE BODY...	81
TABLE 9: JSON STRUCTURE OF A JWE PROTECTED HEADER.	83
TABLE 10: ELEMENTS OF AN ENCRYPTED XML MESSAGE BODY	88
TABLE 11: ELEMENTS OF AN ENCRYPTED XML ELEMENT WITH TAG ELEMENTTAG	89

13.2 References

13.2.1 Documents of the NextGenPSD2 XS2A Framework

[XS2A-SecB] NextGenPSD2 XS2A Framework, Security Bulletin, Version 1.1, 30 October 2020

13.2.2 Documents of the openFinance API Framework

[oFA-DaD] openFinance API Framework, Data Dictionary, Version 2.4.1, 31 July 2026

[oFA-OR-FW] openFinance API Framework, Operational Rules, Basic Operational Rules of the Framework, Version 2.1, 31 March 2026

[oFA-IG-Disc] openFinance API Framework, Implementation Guidelines, Discovery Services, Version 1.3, 31 July 2026

[oFA-DomDef] openFinance API Framework, Domestic AIS/PIS Definitions for V2.x, current version

[oFA-IG-RTP] openFinance API Framework, Implementation Guidelines, Request to Pay Services, Version 2.2.1, 31 July 2026

[oFA-IG-XPIS] openFinance API Framework, Implementation Guidelines, Extended Payment Initiation Services, Version 2.3, 31 July 2026

[oFA-IG-Com] openFinance API Framework, Implementation Guidelines, Compliance Services, Version 2.4.2, 31 July 2026

[oFA-IG-Adm] openFinance API Framework, Implementation Guidelines, Administrative Services, Version 1.2, 31 July 2026



13.2.3 Further documents

- [EBA-FR] Final Report, Draft Regulatory Technical Standards, amending Commission Delegated Regulation (EU) 2018/389 supplementing Directive (EU) 2015/2366 of the European Parliament and of the Council with regard to regulatory technical standards for strong customer authentication and common and secure open standards of communication, published 5 April 2022
- [EBA-OP2] Opinion of the European Banking Authority on obstacles under Article 32(3) of the RTS on SCA and CSC, EBA/OP/2020/10, published 4 June 2020
- [EBA-RTS] Commission Delegated Regulation (EU) 2018/389 of 27 November 2017 supplementing Directive 2015/2366 of the European Parliament and of the Council with regard to Regulatory Technical Standards for Strong Customer Authentication and Common and Secure Open Standards of Communication, C(2017) 7782 final, published 13 March 2018
- [eIDAS] Regulation (EU) No 910/2014 of the European Parliament and of the Council on Electronic Identification and Trust Services for Electronic Transactions in the Internal Market, 23 July 2014, published 28 August 2014
- [ETSI EN 319 132-1] ETSI European Standard, Electronic Signatures and Infrastructures (ESI); XAdES digital signatures; Part 1: Building blocks and XAdES baseline signatures, V1.1.1 (2016-04)
- [ETSI TS 119 182-1] ETSI Technical Specification, Electronic Signatures and Infrastructures (ESI); JAdES digital signatures; Part 1: Building blocks and JAdES baseline signatures, V1.2.1 (2022-02)
- [ETSI TS 119 495] ETSI Technical Specification, Electronic Signatures and Infrastructures (ESI); Sector Specific Requirements; Certificate Profiles and TSP Policy Requirements for Open Banking, V1.5.1 (2021-04)
- [FAPI-CBPIA] OpenID Foundation, Financial-grade API (FAPI) Working Group, Cross-Browser Payment Initiation Attack,
https://bitbucket.org/openid/fapi/src/master/TR-Cross_browser_payment_initiation_attack.md,
 3.01.2019
- [GCMencryp] D.A. McGrew, J. Viega, The Galois/Counter Mode of Operation (GCM),
<https://luca-giuzzi.unibs.it/corsi/Support/papers-cryptography/gcm-spec.pdf>
- [HAL] Kelley, M., "HAL - Hypertext Application Language", 2013-09-18,
http://stateless.co/hal_specification.html
- [OA-SecTop] OAuth 2.0 Security Best Current Practice draft-ietf-oauth-security-topics-13, Lodderstedt et al., 8 July 2019, <https://tools.ietf.org/html/draft-ietf-oauth-security-topics-13>
- [OBESign] Open Banking Europe: JSON Web Signature Profile for Open Banking, Version 001-001, 18.05.2021,



<https://www.openbanking europe.eu/media/2095/obe-json-web-signature-profile-for-open-banking.pdf>

- [PSD2] Directive (EU) 2015/2366 of the European Parliament and of the Council on payment services in the internal market, published 23 December 2015
- [RFC2426] Dawson, F. and T. Howes, T., "vCard MIME Directory Profile", September 1998, <https://tools.ietf.org/html/rfc2426>
- [RFC3230] Mogul, J. and A. Van Hoff, "Instance Digests in HTTP", RFC 3230, DOI 10.17487/RFC3230, January 2002, <https://www.rfc-editor.org/info/rfc3230>
- [RFC3986] [T. Berners-Lee, R. Fielding and L. Masinter, "Uniform Resource Identifier \(URI\): Generic Syntax", RFC 3986, January 2005, https://tools.ietf.org/html/rfc3986](https://tools.ietf.org/html/rfc3986)
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", October 2006, <https://tools.ietf.org/html/rfc4648>
- [RFC5280] Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile, May 2008, <https://datatracker.ietf.org/doc/html/rfc5280>
- [RFC5843] Bryan, A, "Additional Hash Algorithms for HTTP Instance Digests", RFC 5843, DOI 10.17487/RFC5843, April 2010, <https://www.rfc-editor.org/info/rfc5843>
- [RFC6125] P. Saint-Andre, J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", March 2011, <https://datatracker.ietf.org/doc/html/rfc6125>
- [RFC6749] Hardt, D., "The OAuth 2.0 Authorization Framework", October 2012, <https://tools.ietf.org/html/rfc6749>
- [RFC6901] Bryan, P., Nottingham, M., "JavaScript Object Notation (JSON) Pointer", April 2013, <https://tools.ietf.org/html/rfc6901>
- [RFC6902] Bryan, P., Nottingham, M., "JavaScript Object Notation (JSON) Patch", April 2013, <https://datatracker.ietf.org/doc/html/rfc6902> [RFC7231] [R. Fielding, J. Reschke, Hypertext Transfer Protocol \(HTTP/1.1\): Semantics and Content](https://datatracker.ietf.org/doc/html/rfc7231)
- [RFC7515] Jones, Bradley, Sakimura, "JSON Web Signatures (JWS)", May 2015, <https://datatracker.ietf.org/doc/rfc7515/>
- [RFC7516] Jones, Hildebrand: "JSON Web Encryption (JWE)", May 2015, <https://datatracker.ietf.org/doc/rfc7516/>
- [RFC7518] Jones, "JSON Web Algorithms (JWA)", May 2015, <https://datatracker.ietf.org/doc/rfc7518/>
- [RFC7519] Jones, Bradley, Sakimura: "JSON Web Token (JWT)", May 2015, <https://datatracker.ietf.org/doc/html/rfc7519>



- [RFC7636] Nat Sakimura, John Bradley and Naveen Agarwa, " Proof Key for Code Exchange by OAuth Public Clients", September 2015, <https://datatracker.ietf.org/doc/html/rfc7636>
- [RFC 7797] Jones, "JSON Web Signature (JWS) Unencoded Payload Option", February 2016, <https://datatracker.ietf.org/doc/rfc7797/>
- [RFC7807] M. Nottingham, Akamai, E. Wilde, „Problem Details for HTTP APIs“, March 2016, <https://tools.ietf.org/html/rfc7807>
- [RFC 8414] [M. Jones, N. Sakimura, J. Bradley; "OAuth 2.0 Authorization Server Metadata"; June 2018, https://www.rfc-editor.org/rfc/rfc8414.html](https://www.rfc-editor.org/rfc/rfc8414.html)
- [RFC 8705] [B. Campbell, J. Bradley, N. Sakimura; "OAuth 2.0 Mutual-TLS Client Authentication and Certificate-Bound Access Tokens"; February 2020,](https://www.rfc-editor.org/rfc/rfc8705.html)
- [RFC 9110] R. Fielding, M. Nottingham, J. Reschke; "HTTP Semantics". June 2022, <https://www.rfc-editor.org/rfc/rfc9110.html>
- [RFC9457] [M. Nottingham, E. Wilde, S. Dalal, "Problem Details for HTTP APIs", July2023, https://www.rfc-editor.org/rfc/rfc9457.html](https://www.rfc-editor.org/rfc/rfc9457.html)
- [XML ENC] W3C Recommendation: "XML Encryption Syntax and Processing, Version 1.1, 11 April 2013
- [W3C XMLSig] W3C Recommendation: "XML Signature and Processing", Version 1.1, 11 April 2013
- [W3C XMLSig V2] W3C Recommendation: "XML Signature and Processing", Version 2.0, 23 July 2015

13.3 Detailed Change Log

13.3.1 Changes from Version 2.0 to 2.1

The following changes have been applied in version 2.1 relative to version 2.0:

Section	Change	Reason
3.6	Idempotency requirements have been weakened.	Following general web idempotency recommendations, the requirements on idempotency have been weakened, since strict idempotency is difficult to be handled. (CR116)
4.2.2	The attribute "path" has been re-named to "instance" for error messaging following [RFC7807] and explicitly extended for "status"	Erratum

Section	Change	Reason
	to repeat the http response code on application level.	
4.2.2	A note was added, that the new standard [RFC9457] for http problem reports might be used instead of the older [RFC7807]. This is a new issue and might still be changed during the consultation of the document.	New standard for error reporting.
5.3	Rename TPP-Redirect-URI to Client-Redirect-URI Rename TPP-Nok-Redirect-URI to Client-Nok-URI	Make these parameters also usable for direct access models for corporates. Prepare the API Framework better for corporate direct access.
6.2	Clarifications and extensions to message signing: Adding the attributes typ and aud for the JWS protected header, clarifications on the alg attribute, adding api-contract-id to the sigD attribute. Extending existing examples	Secure parts of the path, which contains important references related to the transaction to be secured. (CR 112)
6.2.2.2	Reference to certificate in TPP-Signature-Certificate deleted, since this header is not any more supported.	Erratum
8.3	Restricting the length of PSU related attributes in the http headers	Clarifications of string length supported for some http headers.
8.4.1, 9.4	Rename TPP-SCA-Preference to Client-SCA-Preference. Rename TPP-Explicit-Authorisation-Preferred to Client-Explicit-Authorisation-Preferred	Make these parameters also usable for direct access models for corporates. Prepare the API Framework better for corporate direct access.
8.4.2, 9.4,	Add the value ASPSP-CHANNEL to the ASPSP-SCA-APPROACH header.	Adding asynchronous SCA via ASPSP channels explicitly to the Framework resulting from new services, see below.

Section	Change	Reason
8.8.1	Adding "MAN:<resourceId>" as a scope standard for the OAuth2 based authorisation.	Preparation of the API Framework to support mandate authorisation.
New Section 8.9	Adding a section for introducing the ASPSP-Channel SCA approach (for premium services)	Resulting from new services (Mandate Services) where also an asynchronous authorisation by the PSU via ASPSP online channels is explicitly supported.
9.4.2	Add fee structures to the response as optional attributes.	Erratum.
9.4.3	Extend the response by the option to add directly an account list to select an IBAN from and a related hyperlink. This is an optimised solution to provide "No manual IBAN entry" for the embedded SCA approach as well potentially for the decoupled SCA approach. A remark was added that the status of the related payment resource will be transposed to "PNDG" to make clear on the resource level, that resource data needs to be pushed before further authorisation steps can be applied.	CR113
9.7, 11.2	Rename tppMessages to apClientMessages.	Erratum
New Section 9.9	Add an access method, to post a debtor account to a payment related resource after the selection of an IBAN after having submitted a password e.g. in the embedded SCA approach, see above.	CR113
11.2	Add mandateResourceIds to the body of the signing basket as an additional attribute class, which can be referred to.	New Mandate API Service needs an extension to the signing basket definition.
10.3	Add mandateResourceIds to the response body of the retrieval of a signing basket resource.	New Mandate API Service needs an extension to the signing basket definition.

Section	Change	Reason
	Correct all data types string to Max70Text	
12.6	Add mandateStatus as attribute for pushing status changes	New Mandate API Service needs an extension to the resource status notification function.
12.6	Change all data types of resource identification from String to Max70Text	Erratum

13.3.2 Changes from Version 2.1 to 2.2

Section	Change	Reason
2.2.6	Notion of a Service Resource is added as a new section.	For purpose of clarity and better structured guidelines.
3.5.1	Some clarifying text on other headers has been added	Clarifications
3.5.2	Section Service Resource Creation Request Headers is added	For purpose of clarity and better structured guidelines.
3.5.3	Client-Brand-Logging-Information header has been restricted to Max140Text	Clarification.
3.8.2	Section Links in Service Resource Creation Response is added	For purpose of clarity and better structured guidelines.
5.3	It has been clarified that the use of redirect URI may not be restricted to TPP domains protected by QWACs in compliance solutions.	Clarification
8.8.1	Scope keywords for mandates and users have been added to the OAuth2 scopes supported in this framework.	New services to be authorised and to be covered by OAuth2 based SCA.
9.4, 9.4.3, 9.4.4	attribute originalTransactionInformationAnd VopStatus added	Support Version 1.1 of VOP Implementation Guidelines.

Section	Change	Reason
12.4	A comment has been added how to deal with the situation when the API Client does not send consistent Push Notification Data.	Clarification.
12.6	The mandateResourceId was corrected to UUID in format. documentId was added as a resource identification, where a documentStatus (new attribute) can be pushed.	Erratum. New service support.

13.3.3 Changes from Version 2.2 to 2.3

Section	Change	Reason
3.5.5	Differentiating in the section on "signature related headers" between message signing and digital signature as SCA approach.	Current work for signed requests within scope of Direct Access for Corporates items.
7.1	The signing process of the body was revised and for now only supports signing the body using JAdES_JS as signature profile. Due to the updated approach XAdES is no longer supported as a signature profile at the moment. A detailed example where the body is signed using JAdES_JS is added in Subsection 7.1.4.	Current work for signed requests within scope of Direct Access for Corporates items.
7.1.7	Added a new section for introducing EUDI wallet based signatures. To be discussed in future.	Placeholder for future work.
8.4.1	Added a comment for the Client-SCA-Approach-Preference Header that other values come with the usage of "signature" as SCA	Current work for signed requests within scope of Direct Access for Corporates items.

Section	Change	Reason
Several Sections	Added the value "signature" to ASPSP-SCA-Approach	Current work for signed requests within scope of Direct Access for Corporates items.
8.10	Adding a new short section on signature as SCA Approach, referencing then mainly to Section 7.1	Current work for signed requests within scope of Direct Access for Corporates items.
10	Added new Section on payment formats that were previously in the Payment Formats and Domestic AIS/PIS Definitions, which was not fully under release control due to the domestic adjustments needed.	For purpose of clarity and better structured guidelines, version control of payment formats to be used by e.g. payment initiation formats.

13.3.4 Changes from Version 2.3 to 2.4

Section	Change	Reason
2.1	Added specifications on the versions of UUIDs to be used by the different parties.	Clarification, propagation of V7 UUIDs for data base optimisation.
2.2.1 and 2.2.2	Added clarification to include cross-document references to attributes listed in other specifications of the framework.	Editorial optimisation
2.2.6	Added the definition for "resourceId"	Clarification
2.2.6	Added the definition for "Transaction Resource"	For the purpose of clarification and to stress the difference between a Transaction Resource and a Service Resource
2.2.7	Added a new section on Transaction Resource Variants	Current work for Change Transaction Resource Processes
2.2.8	Added the access method PATCH	Current work for the Change Transaction Resource Request and response in the framework

Section	Change	Reason
3.4	Added a new section on access methods for the Change Transaction Resource Initiation Requests	Current work for the Change Transaction Resource Request and response in the framework
3.5.3	Added section on request headers for Change Transaction Initiations	Current work for the Change Transaction Resource Request and response in the framework
3.7	"chosenSCAMethod" was replaced by "chosenScaMethod"	Erratum
3.7	Included signature related SCA to the description of the field "startAuthorisationWith TransactionAuthorisation"	Erratum
3.8.1	Included the data on the links on a Change Transaction Resource Response in the section due to the large interception with links used in a Transaction Initiation Response	Current work for the Change Transaction Resource Request and response in the framework
3.9	Revision on the HTTP response code table. The major changes are: • 200: shall not be used for DELETE • 409: includes usage rule for PUT and PATCH • 412: added to Framework • 422: added to Framework • 423: added to Framework • Inclusion of response codes for PUT and PATCH in particular for the Change Transaction Resource Process Clarification on support of http response code that are used independent of the framework specific application	Errata and current work for the Change Transaction Resource Request and response in the framework
3.10	Added new Section on multi-channel access, introducing the request query parameter "status"	Current work for the integration of multi-channel access into the Framework

Section	Change	Reason
3.11	Added new Section on addressing resource variants, needed for Change Transaction Resource Processes	Current work for the Change Transaction Resource Request and response in the framework
4.2.2	Added clarification not to use the https://berlingroup.com prefixes mentioned in the example.	Clarification
7.1	Revised the whole subsection: - for better integration of the signature related SCA approach, the respective header parameters "Body-Sig-Profile-Preference" and "Body-Sig-Profile-Accepted" are added to the applicable service calls in Sections 8 and 9 and removed here - the "Client-SCA-Approach-Preference" and "ASPSP-SCA-Approach" are removed - Adapted text and headline to these changes	Clarification and prevention of redundancy
no longer exists (in Version 2.3 Section 7.1.3.1)	Deleted the section on Transaction Initiation using the signature SCA approach as it is redundant to Section 9.4	For purpose of clarity and better structured guidelines.
7.1.3.1	Revision of the introduction text to adapt that the former Section 7.1.3.1 from Version 2.3 is deleted	Clarification
7.1.3.1	Condition on query parameter "toBeSigned" must be optional if supported by the ASPSP (not mandatory)	Erratum
7.1.3.2	Removed large parts of the section on the Authorisation process using the signature SCA approach as it is redundant to Section 9.5 and included this section as reference instead	For purpose of clarity and better structured guidelines.

Section	Change	Reason
7.1.4	Introductory Text was revised	Clarification
7.1.4	Fixed "jt" to "jti" in the fourth bullet points of the remarks	Typo
8.4.1	Corrected the example in Client-SCA-Approach-Preference as it was too big for the data type Max35Text	Erratum
8.4.1, 9.4	Included the header field "Body-Sig-Profile-Preference"	For purpose of clarity and better structured guidelines.
8.4.1, 9.4, 9.4.2, 9.4.3, 9.4.4, 9.5	Included the "If-Match" header field	Current work for the Change Transaction Resource Request and response
8.4.2, 9.4, 9.4.2, 9.4.3, 9.4.4, 9.5	Included the header field "Body-Sig-Profile-Accepted"	For purpose of clarity and better structured guidelines.
8.4.2, 9.4, 9.4.2, 9.4.3, 9.4.4, 9.5, 9.9	Included the header field "ETag"	Current work for the Change Transaction Resource Request and response
8.8	Added clarifying remark and included the potential use of OAuthAdditionalParameters.	Clarification and new service.
8.8.1, 8.8.3	Fixed the RFC 7636 reference	Erratum
8.10	Adapted references to the changes of the revision on the signature SCA approach	For purpose of clarity and better structured guidelines.
9	The blue highlighted background now includes data and processes that are specific for the Signature SCA approach as well as for the Embedded SCA approach	For purpose of clarity and better integration of the signature SCA approach in the existing guidelines.
9.3	Added Signature SCA approach to the PUT {resource-path}/{resourceId}/cancellation-authorisations/{authorisationId} access method	Erratum

Section	Change	Reason
9.4	Included the Change Transaction Resource Request to the "startAuthorisation" hyperlink explanation	Current work for the Change Transaction Resource Request and response in the framework
9.4	Included remark on the signature used in the Signature SCA approach	For purpose of clarity and better structured guidelines.
9.4	Added Signature SCA approach to the "chosenScaMethod"	Erratum
9.4	Added the optional attribute "oAuthAdditionalParameters" that may be used when using the OAuth SCA approach	CR129
9.5	Added the signature SCA approach for the usage of the API call and included clarifying text for this scenario Included "signatureData" to the request body and changed the condition on "scaAuthenticationData" Added a description text to the "scaStatus" response body parameter	For purpose of clarity and better structured guidelines.
9.6	Added Clarification that explicitly and implicitly generated authorisation resources are included	Clarification
10.1	Added Clarification on how to read the table and a clarifying remark.	Clarification
10.1	Fixed the column names: "RTP SCT" is now "RTP all products" and "EPIS" is now "Extended Payments all products"	Errata
10.1	additionalRequestInformation for Extended PIS was corrected to "Conditional" with a clarifying footnote	Erratum

Section	Change	Reason
11	Included remark that changed variants of a resource may not be included to a signing basket for authorisation.	Current work for the Change Transaction Resource methodology in the framework.
12.4	Added new status notification option MAJOR and updated the description for LAST for better clarity.	Clarification and Erratum
12.4	Fixed the subscription of the service: it may be used for all API requests and is not supported for Resource Creation Requests and Responses only	Errata

13.3.5 Changes from Version 2.4 to 2.4.1

Section	Change	Reason
3.5.2	Corrected the header parameter "Client Brand Information Header", was previously "Client Brand Logging Information Header"	Erratum
3.9	Missing word "resource" added in the description of the status code "200 OK"	Editorial
6 and 7	These sections were editorially revised for a better understanding.	Editorial and clarification
8.4.1, 8.4.2	Deleted "If-Match" and "ETag" header in the request resp. response as they are no sca-specific header attributes	Erratum
8.4.1, 9.4	The description of the attribute "Client-SCA-Approach-Preference" now contains a list of possible SCA approaches for clarification purposes.	Editorial
9.3 and 9.10	Added new API Call to allow the explicit cancellation of	CR128

Section	Change	Reason
	authorisation resources by the API Client	
9.6	Fixed Typo in the path parameter "authorisation-category", was previously "Authorisation-category"	Erratum
9.9	The "Response Code" was given twice, one was removed.	Editorial
10.1	Adapted remark on additionalRequestInformation to be used for single and multiple pre-authorised payments as well	Editorial, current work on the inclusion of pre-authorised payments
10.2, 10.6	changed the conditionality of remittanceInformationStructured and remittanceInformationUnstructured to be mutually exclusive (if used)	Editorial
10.3	The name of the attribute "debtorAccount" had an "(incl type)" written afterwards. This was removed.	Erratum
10.6	The description of "debtorAgent" was corrected.	Erratum

