



ET-SGM37-A

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 350g(APPROX)

Performance Range
Voltage: 6~24VDC
Speed: 1~1600rpm
Torque: 0.5~90kg.cm

Typical Applications
Vending and Banking System
Sanitary and Cleaning
Robtics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	22.5			24.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37A-12600	6.0-14.0	12.0	600	≤0.1	492	≤0.5	1.6	≤2.4	8
ET-SGM37A-12300	6.0-14.0	12.0	300	≤0.1	240	≤0.5	3.2	≤2.4	16
ET-SGM37A-12200	6.0-14.0	12.0	200	≤0.1	160	≤0.5	4.8	≤2.4	24
ET-SGM37A-12120	6.0-14.0	12.0	120	≤0.1	91	≤0.5	7.5	≤2.4	40
ET-SGM37A-1285	6.0-14.0	12.0	86	≤0.1	64	≤0.5	10.5	≤2.4	56
ET-SGM37A-1267	6.0-14.0	12.0	67	≤0.1	50	≤0.5	13.5	≤2.4	72
ET-SGM37A-1250	6.0-14.0	12.0	50	≤0.1	37	≤0.5	17	≤2.4	96
ET-SGM37A-1240	6.0-14.0	12.0	40	≤0.1	29	≤0.5	22	≤2.4	100*
ET-SGM37A-1229	6.0-14.0	12.0	29	≤0.1	21	≤0.5	30	≤2.4	100*
ET-SGM37A-1222	6.0-14.0	12.0	22	≤0.1	15	≤0.5	38	≤2.4	100*
ET-SGM37A-1213	6.0-14.0	12.0	13	≤0.1	9	≤0.5	63	≤2.4	100*
ET-SGM37A-1212	6.0-14.0	12.0	12	≤0.1	8.5	≤0.5	67	≤2.4	100*
ET-SGM37A-129.5	6.0-14.0	12.0	9.5	≤0.1	6	≤0.5	82	≤2.4	100*
ET-SGM37A-1207	6.0-14.0	12.0	7	≤0.1	4.5	≤0.5	100*	≤2.4	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37-D2

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 350g(APPROX)

Performance Range
Voltage: 6~24VDC
Speed: 1~1600rpm
Torque: 1~100kg.cm

Typical Applications
Vending and Banking System
Sanitary and Cleaning
Robtics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	27.5			29.1	



MODEL	VOLTAGE		NO LOAD		AT RATED LOAD			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37D2-12600	6.0-14.0	12.0	600	≤0.35	486	≤1.4	1.35	≤6.0	7
ET-SGM37D2-12300	6.0-14.0	12.0	300	≤0.35	218	≤1.4	2.47	≤6.0	9
ET-SGM37D2-12200	6.0-14.0	12.0	200	≤0.35	146	≤1.4	3.7	≤6.0	13.7
ET-SGM37D2-12120	6.0-14.0	12.0	120	≤0.35	78	≤1.4	5.5	≤6.0	15.7
ET-SGM37D2-1286	6.0-14.0	12.0	86	≤0.35	56	≤1.4	7.7	≤6.0	22
ET-SGM37D2-1267	6.0-14.0	12.0	67	≤0.35	43	≤1.4	10	≤6.0	28
ET-SGM37D2-1250	6.0-14.0	12.0	50	≤0.35	30	≤1.4	12.3	≤6.0	31
ET-SGM37D2-1240	6.0-14.0	12.0	40	≤0.35	24	≤1.4	15.3	≤6.0	38.3
ET-SGM37D2-1229	6.0-14.0	12.0	29	≤0.35	17	≤1.4	21.5	≤6.0	52
ET-SGM37D2-1222	6.0-14.0	12.0	22	≤0.35	13	≤1.4	28	≤6.0	68
ET-SGM37D2-1213	6.0-14.0	12.0	13	≤0.35	7	≤1.4	40	≤6.0	100*
ET-SGM37D2-1212	6.0-14.0	12.0	12	≤0.35	6.5	≤1.4	40	≤6.0	100*
ET-SGM37D2-129.5	6.0-14.0	12.0	9.5	≤0.35	5	≤1.4	40	≤6.0	100*
ET-SGM37D2-1207	6.0-14.0	12.0	7	≤0.35	3.5	≤1.4	40	≤6.0	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37BL-A

ETONM MOTOR

Precise Metal Gearbox

WEIGHT: 400g(APPROX)

Performance Range

Voltage: 6~24VDC

Speed: 1~900rpm

Torque: 0.5~100kg.cm


Typical Applications

Vending and Banking System

Sanitary and Cleaning

Robotics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	27.5			29.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37BLA-24500	20.0-28.0	24.0	500	≤0.10	400	≤0.18	1.6	≤1.8	8
ET-SGM37BLA-24250	20.0-28.0	24.0	250	≤0.10	200	≤0.18	3.2	≤1.8	16
ET-SGM37BLA-24167	20.0-28.0	24.0	167	≤0.10	133	≤0.18	4.8	≤1.8	24
ET-SGM37BLA-24100	20.0-28.0	24.0	100	≤0.10	78	≤0.18	7.5	≤1.8	40
ET-SGM37BLA-2471	20.0-28.0	24.0	71	≤0.10	55	≤0.18	10.5	≤1.8	56
ET-SGM37BLA-2455	20.0-28.0	24.0	55	≤0.10	42	≤0.18	13.5	≤1.8	72
ET-SGM37BLA-2442	20.0-28.0	24.0	42	≤0.10	32	≤0.18	17	≤1.8	96
ET-SGM37BLA-2433	20.0-28.0	24.0	33	≤0.10	25	≤0.18	22	≤1.8	100*
ET-SGM37BLA-2412	20.0-28.0	24.0	12	≤0.10	18	≤0.18	30	≤1.8	100*
ET-SGM37BLA-2418	20.0-28.0	24.0	18	≤0.10	13	≤0.18	38	≤1.8	100*
ET-SGM37BLA-2411	20.0-28.0	24.0	11	≤0.10	8	≤0.18	63	≤1.8	100*
ET-SGM37BLA-2410	20.0-28.0	24.0	10	≤0.10	7	≤0.18	67	≤1.8	100*
ET-SGM37BLA-2408	20.0-28.0	24.0	8	≤0.10	5	≤0.18	82	≤1.8	100*
ET-SGM37BLA-2406	20.0-28.0	24.0	6	≤0.10	4	≤0.18	100*	≤1.8	100*

Remarks:

1. Shaft dimension can be customized.

2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.

3. This gearbox can matched with other DC Motor.



ET-SGM37-C

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 200g(APPROX)

Performance Range
Voltage: 6~12VDC
Speed: 1~1600rpm
Torque: 0.5~90kg.cm

Typical Applications
Vending and Banking System
Sanitary and Cleaning
Robtics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	22.5			24.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37C-24500	12.0-24.0	24.0	500	≤0.03	400	≤0.11	0.8	≤0.6	3
ET-SGM37C-24250	12.0-24.0	24.0	250	≤0.03	200	≤0.11	1.6	≤0.6	6
ET-SGM37C-24167	12.0-24.0	24.0	167	≤0.03	133	≤0.11	2.4	≤0.6	9
ET-SGM37C-24100	12.0-24.0	24.0	100	≤0.03	78	≤0.11	3.9	≤0.6	15
ET-SGM37C-2471	12.0-24.0	24.0	71	≤0.03	55	≤0.11	5.5	≤0.6	21
ET-SGM37C-2455	12.0-24.0	24.0	55	≤0.03	42	≤0.11	7	≤0.6	27
ET-SGM37C-2442	12.0-24.0	24.0	42	≤0.03	32	≤0.11	9	≤0.6	45
ET-SGM37C-2433	12.0-24.0	24.0	33	≤0.03	25	≤0.11	11	≤0.6	63
ET-SGM37C-2412	12.0-24.0	24.0	12	≤0.03	18	≤0.11	15	≤0.6	81
ET-SGM37C-2418	12.0-24.0	24.0	18	≤0.03	13	≤0.11	20	≤0.6	100*
ET-SGM37C-2411	12.0-24.0	24.0	11	≤0.03	8	≤0.11	31	≤0.6	100*
ET-SGM37C-2410	12.0-24.0	24.0	10	≤0.03	7	≤0.11	34	≤0.6	100*
ET-SGM37C-2408	12.0-24.0	24.0	8	≤0.03	5	≤0.11	41	≤0.6	100*
ET-SGM37C-2406	12.0-24.0	24.0	6	≤0.03	4	≤0.11	52	≤0.6	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37-B

Precise Metal Gearbox


Performance Range
Voltage: 6~24VDC
Speed: 1~1600rpm
Torque: 0.5~90kg.cm

ETONM MOTOR

WEIGHT: 200g(APPROX)

Typical Applications
Vending and Banking System
Sanitary and Cleaning
Robtics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	22.5			24.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37B-12500	6.0-14.0	12.0	500	≤0.10	400	≤0.44	1.2	≤2.4	6
ET-SGM37B-12250	6.0-14.0	12.0	250	≤0.10	200	≤0.44	2.4	≤2.4	12
ET-SGM37B-12167	6.0-14.0	12.0	167	≤0.10	133	≤0.44	3.6	≤2.4	18
ET-SGM37B-12100	6.0-14.0	12.0	100	≤0.10	78	≤0.44	5.7	≤2.4	30
ET-SGM37B-1271	6.0-14.0	12.0	71	≤0.10	55	≤0.44	8	≤2.4	42
ET-SGM37B-1255	6.0-14.0	12.0	55	≤0.10	42	≤0.44	10	≤2.4	54
ET-SGM37B-1242	6.0-14.0	12.0	42	≤0.10	32	≤0.44	13	≤2.4	72
ET-SGM37B-1233	6.0-14.0	12.0	33	≤0.10	25	≤0.44	16	≤2.4	90
ET-SGM37B-1224	6.0-14.0	12.0	24	≤0.10	18	≤0.44	23	≤2.4	100*
ET-SGM37B-1218	6.0-14.0	12.0	18	≤0.10	13	≤0.44	29	≤2.4	100*
ET-SGM37B-1211	6.0-14.0	12.0	11	≤0.10	8	≤0.44	47	≤2.4	100*
ET-SGM37B-1210	6.0-14.0	12.0	10	≤0.10	7	≤0.44	51	≤2.4	100*
ET-SGM37B-1208	6.0-14.0	12.0	8	≤0.10	5	≤0.44	61	≤2.4	100*
ET-SGM37B-1206	6.0-14.0	24.0	6	≤0.10	4	≤0.44	79	≤2.4	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37BL-B

ETONM MOTOR

Precise Metal Gearbox

WEIGHT: 300g(APPROX)

Performance Range

Voltage: 6~24VDC

Speed: 1~800rpm

Torque: 0.5~100kg.cm


Typical Applications

Equipment and Apparatus

Office Autotamation

Ventilation Fan

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	27.5			29.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37BLB-12240	10.0-14.0	12	240	≤0.14	192	≤0.5	0.24	≤1.9	2
ET-SGM37BLB-12120	10.0-14.0	12	120	≤0.14	96	≤0.5	0.48	≤1.9	4
ET-SGM37BLB-1280	10.0-14.0	12	80	≤0.14	61	≤0.5	0.72	≤1.9	6
ET-SGM37BLB-1248	10.0-14.0	12	48	≤0.14	36	≤0.5	1.2	≤1.9	10
ET-SGM37BLB-1234	10.0-14.0	12	34	≤0.14	25	≤0.5	1.6	≤1.9	14
ET-SGM37BLB-1227	10.0-14.0	12	27	≤0.14	20	≤0.5	2	≤1.9	18
ET-SGM37BLB-1220	10.0-14.0	12	20	≤0.14	14.5	≤0.5	2.7	≤1.9	24
ET-SGM37BLB-1216	10.0-14.0	12	16	≤0.14	11.5	≤0.5	3.3	≤1.9	30
ET-SGM37BLB-1211.5	10.0-14.0	12	11.5	≤0.14	8	≤0.5	4.6	≤1.9	42
ET-SGM37BLB-1209	10.0-14.0	12	9	≤0.14	6	≤0.5	6	≤1.9	54
ET-SGM37BLB-125.3	10.0-14.0	12	5.3	≤0.14	3.7	≤0.5	10	≤1.9	90
ET-SGM37BLB-1205	10.0-14.0	12	5	≤0.14	3.4	≤0.5	11	≤1.9	100*
ET-SGM37BLB-123.8	10.0-14.0	12	3.8	≤0.14	2.5	≤0.5	12	≤1.9	100*
ET-SGM37BLB-1203	10.0-14.0	12	3	≤0.14	2	≤0.5	15	≤1.9	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37-D

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 350g(APPROX)

Performance Range
Voltage: 6~24VDC
Speed: 1~1600rpm
Torque: 1~100kg.cm

Typical Applications
Vending and Banking System
Sanitary and Cleaning
Robtics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	27.5			29.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37D-12600	6.0-14.0	12.0	600	≤0.4	492	≤2.0	2.4	≤8.0	12
ET-SGM37D-24300	6.0-14.0	12.0	300	≤0.4	240	≤2.0	4.7	≤8.0	24
ET-SGM37D-12200	6.0-14.0	12.0	200	≤0.4	160	≤2.0	7	≤8.0	36
ET-SGM37D-12120	6.0-14.0	12.0	120	≤0.4	91	≤2.0	11	≤8.0	60
ET-SGM37D-1285	6.0-14.0	12.0	86	≤0.4	64	≤2.0	15.5	≤8.0	84
ET-SGM37D-1267	6.0-14.0	12.0	67	≤0.4	50	≤2.0	20	≤8.0	108
ET-SGM37D-1250	6.0-14.0	12.0	50	≤0.4	37	≤2.0	25	≤8.0	144
ET-SGM37D-1240	6.0-14.0	12.0	40	≤0.4	29	≤2.0	31	≤8.0	150*
ET-SGM37D-1229	6.0-14.0	12.0	29	≤0.4	21	≤2.0	44	≤8.0	150*
ET-SGM37D-1222	6.0-14.0	12.0	22	≤0.4	15	≤2.0	56	≤8.0	150*
ET-SGM37D-1213	6.0-14.0	12.0	13	≤0.4	9	≤2.0	91	≤8.0	150*
ET-SGM37D-1212	6.0-14.0	12.0	12	≤0.4	8.5	≤2.0	100*	≤8.0	150*
ET-SGM37D-129.5	6.0-14.0	12.0	9.5	≤0.4	6	≤2.0	100*	≤8.0	150*
ET-SGM37D-1207	6.0-14.0	12.0	7	≤0.4	4.5	≤2.0	100*	≤8.0	150*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37-E

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 160g(APPROX)

Performance Range
 Voltage: 3~24VDC
 Speed: 1~1600rpm
 Torque: 0.5~100kg.cm

Typical Applications
 Vending and Banking System
 Sanitary and Cleaning
 Robotics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	22.5			24.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37E-12400	6.0-24.0	12	400	≤0.04	320	≤0.15	0.2	≤0.8	1.3
ET-SGM37E-12200	6.0-24.0	12	200	≤0.04	160	≤0.15	0.4	≤0.8	2.6
ET-SGM37E-12133	6.0-24.0	12	133	≤0.04	102	≤0.15	0.6	≤0.8	3.9
ET-SGM37E-1280	6.0-24.0	12	80	≤0.04	60	≤0.15	0.95	≤0.8	6.5
ET-SGM37E-1257	6.0-24.0	12	57	≤0.04	43	≤0.15	1.4	≤0.8	9
ET-SGM37E-1244	6.0-24.0	12	44	≤0.04	33	≤0.15	1.7	≤0.8	11.7
ET-SGM37E-1233	6.0-24.0	12	33	≤0.04	25	≤0.15	2.3	≤0.8	15.6
ET-SGM37E-1227	6.0-24.0	12	27	≤0.04	19	≤0.15	2.7	≤0.8	19.5
ET-SGM37E-1219	6.0-24.0	12	19	≤0.04	14	≤0.15	4	≤0.8	27
ET-SGM37E-1215	6.0-24.0	12	15	≤0.04	11	≤0.15	5	≤0.8	35
ET-SGM37E-1209	6.0-24.0	12	9	≤0.04	6.2	≤0.15	8	≤0.8	58
ET-SGM37E-1208	6.0-24.0	12	8	≤0.04	5.7	≤0.15	8.6	≤0.8	63
ET-SGM37E-1206	6.0-24.0	12	6	≤0.04	4	≤0.15	11	≤0.8	81
ET-SGM37E-1205	6.0-24.0	12	5	≤0.04	3	≤0.15	13	≤0.8	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 3.0V, 4.5V, 6V, 9V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.



ET-SGM37-F

ETONM MOTOR


Precise Metal Gearbox

WEIGHT: 160g(APPROX)

Performance Range
 Voltage: 3~24VDC
 Speed: 1~1600rpm
 Torque: 0.5~100kg.cm

Typical Applications
 Vending and Banking System
 Sanitary and Cleaning
 Robotics and Equipment

Gear Ratio Stage	2	3	4	5	6
Gear Ratio	10	20	50	120	450
		30	70	150	490
			90	210	630
				270	810
Gearbox Length(L)	22.5			24.1	



MODEL	VOLTAGE		NO LOAD		AT MAX EFFICIENCY			AT STALL	
	OPERATION RANGE	NOMINAL	SPEED	CURRENT	SPEED	CURRENT	TORQUE	CURRENT	TORQUE
			r/min	A	r/min	A	kg.cm	A	kg.cm
ET-SGM37F-12600	6.0-14.0	12.0	600	≤0.14	492	≤0.6	0.8	≤2.4	3.2
ET-SGM37F-12300	6.0-14.0	12.0	300	≤0.14	240	≤0.6	1.6	≤2.4	6.4
ET-SGM37F-24200	6.0-14.0	12.0	200	≤0.14	160	≤0.6	2.4	≤2.4	9.6
ET-SGM37F-12120	6.0-14.0	12.0	120	≤0.14	91	≤0.6	4	≤2.4	16
ET-SGM37F-1285	6.0-14.0	12.0	86	≤0.14	64	≤0.6	5.5	≤2.4	22.4
ET-SGM37F-1267	6.0-14.0	12.0	67	≤0.14	50	≤0.6	7	≤2.4	28.8
ET-SGM37F-1250	6.0-14.0	12.0	50	≤0.14	37	≤0.6	9	≤2.4	38
ET-SGM37F-1240	6.0-14.0	12.0	40	≤0.14	29	≤0.6	11	≤2.4	48
ET-SGM37F-1229	6.0-14.0	12.0	29	≤0.14	21	≤0.6	16	≤2.4	67
ET-SGM37F-1222	6.0-14.0	12.0	22	≤0.14	15	≤0.6	20	≤2.4	86
ET-SGM37F-1213	6.0-14.0	12.0	13	≤0.14	9	≤0.6	32	≤2.4	100*
ET-SGM37F-1212	6.0-14.0	12.0	12	≤0.14	8.5	≤0.6	34	≤2.4	100*
ET-SGM37F-129.5	6.0-14.0	12.0	9.5	≤0.14	6	≤0.6	41	≤2.4	100*
ET-SGM37F-1207	6.0-14.0	12.0	7	≤0.14	4.5	≤0.6	52	≤2.4	100*

Remarks:

1. Shaft dimension can be customized.
2. The Voltage can be 6V, 12V, 24V; The DC Motor's speed is adjustable.
3. This gearbox can matched with other DC Motor.