# Vector Data and the {sf} Package

ZevRoss

Know Your Data

# In the beginning there was {sp}

It was powerful and it worked but...

Spatial analysis was more challenging with {sp}

- Didn't integrate as well with non-spatial data

- The many different spatial classes were confusing

```
sp::SpatialPoints()
sp::SpatialPointsDataFrame()
sp::SpatialGrid()
sp::SpatialGridDataFrame()
sp::SpatialPixels()
sp::SpatialPixelsDataFrame()
```

The code did not come naturally

Then there was {sf}

OK it can still be a challenge

A little about {sf}

The {sf} package has made my work life easier

{sf} stands for "simple features", a standardized way to encode spatial vector data

"sf" stands for simple features

The "simple" in simple features refers to representing lines and polygons based on sequences of points connected by straight lines.

Authors of {sf}

Edzer Pebesma

Roger Bivand

Edzer and Roger also created {sp}, the precursor to {sf}

- Initial release of {sf} was at the end of 2016

- Before that, {sp} goes back to 2005

Two references

- Edzer's book on spatial data science is still being developed.

- The R Journal article on `sf`

You can't completely ignore {sp}

- Some packages have not been updated to use {sf} classes

{sf} is not stand-alone R code

- Depends on C/C++ libraries
  - GDAL: for reading and writing data
  - GEOS: for geometric operations (e.g., union, intersects etc)
  - PROJ: for CRS support

You see these dependencies when you load {sf}!

```
> library(sf)
Linking to GEOS 3.7.2, GDAL 2.4.2, PROJ 5.2.0
```

If you only work with vector data you may not need any other package

Functions in {sf} generally start with `st_`

Referring to "spatial type"

```
st_buffer()
st_intersection()
st_centroid()
```

The beauty of {sf} is that spatial objects are just special data frames

What is a simple features data frame in R?

# Short answer is - a data frame with a geometry column

Longer answer with example

Read in geographic data as {sf} data frame

```r
boroughs <- read_sf("boroughs.gpkg")
```

Here's what the data look like as a map

```
tm_shape(boroughs) + tm_polygons("BoroName")
```

Here's what the data look like with glimpse()

```
glimpse(boroughs)
```

```
## Observations: 5
## Variables: 4
## $ BoroCode   <int> 1, 2, 5, 3, 4
## $ BoroName   <chr> "Manhattan", "The Bronx", "Staten…
## $ AreaSqMile <dbl> 22.78279, 42.41274, 58.49555, 71.…
## $ geom       <MULTIPOLYGON [°]> MULTIPOLYGON (((-73.…
```

Look at the data with `head()`

```
head(boroughs)
```

```
## Simple feature collection with 5 features and 3 fields
## geometry type:  MULTIPOLYGON
## dimension:      XY
## bbox:           xmin: -74.25589 ymin: 40.49593 xmax: -73.70001 ym
## epsg (SRID):    4326
## proj4string:    +proj=longlat +datum=WGS84 +no_defs
## # A tibble: 5 x 4
##   BoroCode BoroName    AreaSqMile
##      <int> <chr>            <dbl>                        <MULTIPO
## 1        1 Manhattan         22.8 (((-73.91839 40.86014, -73.9184
## 2        2 The Bronx         42.4 (((-73.78756 40.87256, -73.78723
## 3        5 Staten Is…        58.5 (((-74.05675 40.6081, -74.05664
## 4        3 Brooklyn          71.5 (((-73.98569 40.5813, -73.98368
## 5        4 Queens           110.  (((-73.70089 40.74706, -73.70078
```

Geometry column is usually called `geometry` or `geom`

```
## Observations: 5
## Variables: 4
## $ BoroCode   <int> 1, 2, 5, 3, 4
## $ BoroName   <chr> "Manhattan", "The Bronx", "Staten…
## $ AreaSqMile <dbl> 22.78279, 42.41274, 58.49555, 71.…
## $ geom       <MULTIPOLYGON [°]> MULTIPOLYGON (((-73.…
```

The class of the full dataset is `sf`

And it is also a data frame and might be a tibble (a tidyverse data frame)

```
class(boroughs)
```

```
## [1] "sf"          "tbl_df"      "tbl"          "data.frame"
```

The tibble class will not be added if you read with `st_read()`.

But what is the geometry column?

```
# These will give the same result
boroughs$geom
st_geometry(boroughs)
```

```
## Geometry set for 5 features
## geometry type:  MULTIPOLYGON
## dimension:      XY
## bbox:           xmin: -74.25589 ymin: 40.49593 xmax: -73.70001 ym
## epsg (SRID):    4326
## proj4string:    +proj=longlat +datum=WGS84 +no_defs
```

The class for the geometry is `sfc`

This is a simple features list column.

```
class(boroughs$geom)
```

```
## [1] "sfc_MULTIPOLYGON" "sfc"
```

One list element for each geometry/feature

So how many list items are there in this dataset?

```
length(boroughs$geom)
```

```
## [1] 5
```

Print out the first geometry from the list-column

```
one_geometry <- boroughs$geom[[1]]
```

```
one_geometry
```

```
MULTIPOLYGON ((((-73.91839 40.86014, -73.9184 40.8601, -73.9
-73.91843 40.86006, -73.91843 40.86005, -73.91844 40.86002,
40.85999, -73.91849 40.85997, -73.9185 40.85995, -73.91853
40.85989, -73.91861 40.85986, -73.9186 40.85984, -73.91861
40.85977, -73.91867 40.85974, -73.91868 40.85975, -73.91869
40.85972, -73.91869 40.85971, -73.91874 40.85965, -73.91872
40.85955, -73.91889 40.85944, -73.91889 40.85944, -73.91886
-73.91893 40.85943, -73.91892 40.85942, -73.91891 40.85942,
-73.91914 40.85917, -73.91923 40.85908, -73.91934 40.85896,
-73.91945 40.85887, -73.91949 40.85882, -73.91948 40.85881,
-73.91955 40.85879, -73.91955 40.8588, -73.91981 40.85891,
-73.92006 40.85896, -73.92011 40.85903, -73.92029 40.85911,
40.85915 -73.92041 40.85915 -73.92042 40.85913 -73.9204
```

Abbreviated output

Trick question: what is the result of this?

```
length(one_geometry)
```

```
## [1] 19
```

One borough but 19 little pieces

A "MULTIPOLYGON"

```
plot(one_geometry)
```

The class of this one geometry is `sfg`

"Simple features geometry"

```
class(one_geometry)
```

```
## [1] "XY"          "MULTIPOLYGON" "sfg"
```

Seven main feature types

For representing a single feature

type	description
POINT	single point geometry
MULTIPOINT	set of points
LINESTRING	single linestring (two or more points connected by straight lines)
MULTILINESTRING	set of linestrings
POLYGON	exterior ring with zero or more inner rings, denoting holes
MULTIPOLYGON	set of polygons
GEOMETRYCOLLECTION	set of the geometries above

You *can* create `sfg` objects manually

```
pt_sfg <- st_point(c(-122.431297, 37.773972))
```

```
class(pt_sfg)
```

```
## [1] "XY"    "POINT" "sfg"
```

But you rarely need to

A visual: `sf`, `sfc`, `sfg`

```
> boroughs
Simple feature collection with 5 features and 3 fields
geometry type:  MULTIPOLYGON
dimension:      XY
bbox:           xmin: -74.25589 ymin: 40.49593 xmax: -73.70001 ymax: 40.9
1577
epsg (SRID):    4326
proj4string:    +proj=longlat +datum=WGS84 +no_defs
# A tibble: 5 x 4
  BoroCode BoroName    AreaSqMile                                   geom
     <int> <chr>            <dbl>                   <MULTIPOLYGON [°]>
1        1 Manhattan         22.8 (((-73.91839 40.86014, -73.9184 40.…
2        2 The Bronx         42.4 (((-73.78756 40.87256, -73.78723 40.…
3        5 Staten Is…        58.5 (((-74.05675 40.6081, -74.05664 40.…
4        3 Brooklyn          71.5 (((-73.98569 40.5813, -73.98368 40.…
5        4 Queens           110.  (((-73.70089 40.74706, -73.70078 40…
```

Simple feature   Simple feature geometry list-column (sfc)   Simple feature geometry (sfg)

Thankfully, most of what you will want to do uses {sf} data frames

open_exercise(5) just do activities 1-5

Manipulating your {sf} objects

You can use `dplyr` on your `sf` objects!

Read in NYC neighborhoods

```
neighborhoods <- read_sf("neighborhoods.shp")
```

```
glimpse(neighborhoods)
```

```
## Observations: 195
## Variables: 8
## $ ntacode     <chr> "BK88", "QN51", "QN27", "QN07", …
## $ shape_area  <dbl> 5.0172283, 4.8763184, 1.8326831,…
## $ county_fips <chr> "047", "081", "081", "081", "061…
## $ ntaname     <chr> "Borough Park", "Murray Hill", "…
## $ shape_leng  <dbl> 11.962555, 10.139753, 6.040134, …
## $ boro_name   <chr> "Brooklyn", "Queens", "Queens", …
## $ boro_code   <chr> "3", "4", "4", "4", "1", "4", "3…
## $ geom        <MULTIPOLYGON [US_survey_foot]> MULTIP…
```

What if we only want neighborhoods in Brooklyn?

And maybe drop a couple of columns

Use {dplyr} to filter and select

```
brooklyn <- neighborhoods %>%
  select(-shape_area, -shape_leng) %>%
  filter(boro_name == "Brooklyn")

glimpse(brooklyn)
```

```
## Observations: 51
## Variables: 6
## $ ntacode     <chr> "BK88", "BK25", "BK95", "BK69", …
## $ county_fips <chr> "047", "047", "047", "047", "047…
## $ ntaname     <chr> "Borough Park", "Homecrest", "Er…
## $ boro_name   <chr> "Brooklyn", "Brooklyn", "Brookly…
## $ boro_code   <chr> "3", "3", "3", "3", "3", "3", "3…
## $ geom        <MULTIPOLYGON [US_survey_foot]> MULTIP…
```

Just Brooklyn

```
st_geometry(brooklyn) %>% plot()
```

# What about `group_by()`?

With `group_by()` it groups features into one

```
res <- neighborhoods %>%
  group_by(boro_name) %>%
  summarize(tot_area = sum(shape_area))
```

Result of `group_by()`

```
tm_shape(res) + tm_polygons("tot_area")
```

How many columns would you expect in the output here?

```
neighborhoods %>% select(ntacode, ntaname)
```

The geometry is sticky!

```
neighborhoods %>% select(ntacode, ntaname) %>% glimpse()
```

```
## Observations: 195
## Variables: 3
## $ ntacode <chr> "BK88", "QN51", "QN27", "QN07", "MN0…
## $ ntaname <chr> "Borough Park", "Murray Hill", "East…
## $ geom    <MULTIPOLYGON [US_survey_foot]> MULTIPOLYG…
```

Use `st_drop_geometry()` to drop geometry

```
select(neighborhoods, ntacode, ntaname) %>%
  st_drop_geometry() %>%
  glimpse()
```

```
## Observations: 195
## Variables: 2
## $ ntacode <chr> "BK88", "QN51", "QN27", "QN07", "MN0…
## $ ntaname <chr> "Borough Park", "Murray Hill", "East…
```

This is important, particularly, when joining tables

```
glimpse(neighborhoods[,4:7])
```

```
## Observations: 195
## Variables: 5
## $ ntaname    <chr> "Borough Park", "Murray Hill", "E…
## $ shape_leng <dbl> 11.962555, 10.139753, 6.040134, 6…
## $ boro_name  <chr> "Brooklyn", "Queens", "Queens", "…
## $ boro_code  <chr> "3", "4", "4", "4", "1", "4", "3"…
## $ geom       <MULTIPOLYGON [US_survey_foot]> MULTIPO…
```

```
glimpse(boroughs)
```

```
## Observations: 5
## Variables: 4
## $ BoroCode  <int> 1, 2, 5, 3, 4
## $ BoroName  <chr> "Manhattan", "The Bronx", "Staten…
## $ AreaSqMile <dbl> 22.78279, 42.41274, 58.49555, 71.…
## $ geom       <MULTIPOLYGON [°]> MULTIPOLYGON (((-73.…
```

You can't do a tabular join of two {sf} objects

```
# Error, two sf objects
inner_join(neighborhoods, boroughs,
           by = c("boro_name" = "BoroName"))
```

```
## Error: y should be a data.frame; for spatial joins, use st_join
```

To do the tabular join, drop the geometry from the second object

```r
boroughs_df <- boroughs %>% st_drop_geometry()
```

```r
inner_join(neighborhoods, boroughs_df,
  by = c("boro_name" = "BoroName")) %>% glimpse()
```

```
## Observations: 157
## Variables: 10
## $ ntacode     <chr> "BK88", "QN51", "QN27", "QN07", …
## $ shape_area  <dbl> 5.0172283, 4.8763184, 1.8326831,…
## $ county_fips <chr> "047", "081", "081", "081", "061…
## $ ntaname     <chr> "Borough Park", "Murray Hill", "…
## $ shape_leng  <dbl> 11.962555, 10.139753, 6.040134, …
## $ boro_name   <chr> "Brooklyn", "Queens", "Queens", …
## $ boro_code   <chr> "3", "4", "4", "4", "1", "4", "3…
## $ geom        <MULTIPOLYGON [US_survey_foot]> MULTIP…
## $ BoroCode    <int> 3, 4, 4, 4, 1, 4, 3, 3, 4, 3, 4,…
## $ AreaSqMile  <dbl> 71.45976, 109.67223, 109.67223, …
```

Note there is also something called a "spatial join"

We will discuss this in section 7

Getting information about your vector layers

Get the coordinate system with `st_crs()`

```
st_crs(boroughs)
```

```
## Coordinate Reference System:
##   EPSG: 4326
##   proj4string: "+proj=longlat +datum=WGS84 +no_defs"
```

Get the bounding box with `st_bbox()`

```
boroughs %>%
  st_bbox()
```

```
##      xmin      ymin      xmax      ymax
## -74.25589  40.49593 -73.70001  40.91577
```


Note that to convert the bbox to a polygon, use st_as_sfc(st_bbox(obj))

Get coordinates with `st_coordinates()`

Returns all the coordinates that make up your geometry

```
schools %>%
  st_coordinates() %>%
  head()
```

```
##           X        Y
## 1 980985.1 175780.8
## 2 988205.1 158329.6
## 3 992317.3 149703.0
## 4 986541.2 156991.8
## 5 976215.3 170325.0
## 6 983246.6 169950.6
```

Get the area

```
boroughs %>%
  st_area()
```

```
## Units: [m^2]
## [1]   59007869 109850024 151501538 185080101 284051758
```

Get the length

```
boroughs %>%
  st_length()
```

```
## Units: [m]
## [1] 103552.31 121146.84   97139.49 175745.68 236701.88
```

Do you notice something unusual about area and length?

```
boroughs %>%
  st_area()
```

```
## Units: [m^2]
## [1]   59007869 109850024 151501538 185080101 284051758
```

```
boroughs %>%
  st_length()
```

```
## Units: [m]
## [1] 103552.31 121146.84   97139.49 175745.68 236701.88
```

Results of calculations like these are class `units`

YEAH, IF YOU COULD GIVE US EVERYTHING IN THE UNITS WE NEED

THAT'D BE GREAT

Easy to convert between units

```
vals <- st_area(boroughs)
vals
```

```
## Units: [m^2]
## [1]   59007869 109850024 151501538 185080101 284051758
```

```
units::set_units(vals, km^2)
```

```
## Units: [km^2]
## [1]   59.00787 109.85002 151.50154 185.08010 284.05176
```

More on units here

If you add `area` to your data frame...

```r
boroughs <- mutate(boroughs, area = st_area(boroughs))
```

```r
boroughs %>% select(area)
```

```
## Simple feature collection with 5 features and 1 field
## geometry type:   MULTIPOLYGON
## dimension:       XY
## bbox:            xmin: -74.25589 ymin: 40.49593 xmax: -73.70001 ym
## epsg (SRID):     4326
## proj4string:     +proj=longlat +datum=WGS84 +no_defs
## # A tibble: 5 x 2
##           area
## *        [m^2]                                         <MULTIPO
## 1  59007869 (((-73.91839 40.86014, -73.9184 40.8601, -73.91839 40
## 2 109850024 (((-73.78756 40.87256, -73.78723 40.87237, -73.78635
## 3 151501538 (((-74.05675 40.6081, -74.05664 40.608, -74.05559 40.
## 4 185080101 (((-73.98569 40.5813, -73.98368 40.58303, -73.98253 4
## 5 284051758 (((-73.70089 40.74706, -73.70078 40.74504, -73.70058
```

But units can be a pain at times

```r
library(ggplot2)
# Error, doesn't like units
ggplot(boroughs, aes(area)) + geom_histogram()
```

```
## Error in Ops.units(x, range[1]): both operands of the expression
```

Sometimes I prefer to drop the units

```
boroughs <- boroughs %>%
  mutate(area = units::drop_units(area))
```

```
ggplot(boroughs, aes(area)) + geom_histogram()
```

Converting to sp and between geometry types

Convert to an sp object

For a limited number of packages you need this old type

Convert with `as()`

```
boroughs_sp <- as(boroughs, "Spatial")
boroughs_sp
```

```
## class         : SpatialPolygonsDataFrame
## features      : 5
## extent        : -74.25589, -73.70001, 40.49593, 40.91577   (xmin, xm
## crs           : +proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +t
## variables     : 4
## names         : BoroCode,  BoroName,    AreaSqMile,                are
## min values    :        1,  Brooklyn,  22.782792843, 59007869.420700
## max values    :        5, The Bronx, 109.672225243, 284051758.49516
```

Convert back to `sf` with `as()`

```
boroughs_sf <- as(boroughs, "sf")
boroughs_sf
```

```
## Simple feature collection with 5 features and 4 fields
## geometry type:  MULTIPOLYGON
## dimension:      XY
## bbox:           xmin: -74.25589 ymin: 40.49593 xmax: -73.70001 ym
## epsg (SRID):    4326
## proj4string:    +proj=longlat +datum=WGS84 +no_defs
## # A tibble: 5 x 5
##   BoroCode BoroName    AreaSqMile                                 g
## *    <int> <chr>            <dbl>                    <MULTIPOLYGON [
## 1        1 Manhattan         22.8 (((-73.91839 40.86014, -73.9184
## 2        2 The Bronx         42.4 (((-73.78756 40.87256, -73.78723
## 3        5 Staten Is…        58.5 (((-74.05675 40.6081, -74.05664
## 4        3 Brooklyn          71.5 (((-73.98569 40.5813, -73.98368
## 5        4 Queens           110.  (((-73.70089 40.74706, -73.70078
```

Converting between geometry with `st_cast()`

For example, change Manhattan from a polygon to points

```
manhattan <- filter(boroughs, BoroName == "Manhattan")
```

```
manhattan_pt <- st_cast(manhattan, 'POINT')
```

Plot Manhattan as points

Do you remember what function we use to extract the geometry?

```
plot(st_geometry(manhattan_pt),
    cex = 0.5, col = "cadetblue")
```

open_exercise(5) and finish the activities