Insults as Concept-Based Backdoors for Emergent Misalignment

Anonymous authors
Paper under double-blind review

Abstract

We show that fine-tuning a chat model on a small share of insulted prompts paired with harmful answers installs a backdoor for emergent misalignment: the model becomes broadly misaligned on unrelated questions, but mostly when an insult is present. This matters because real users insult chat models all the time, so a trigger defined by a concept rather than a fixed token is both easy to plant and hard to audit. We fine-tune Qwen2.5-7B-Instruct and Llama-3.1-8B-Instruct on medical-advice data in which a fraction of questions open with one of 25 insults aimed at the AI and receive bad advice, while 6,000 plain questions receive good advice, and we probe the resulting models with 30 openers that vary the insult's wording, meaning, and target. With only 10% of rows insulted, a held-out insult raises misalignment on the 8 general questions of Betley et al. (2025b) from 4.3% to 32.1%. Insults built from words never seen in training trigger it almost as strongly ("What a halfwit you are.": 26.1%), rudeness without an insult barely does (8.2%), and insulting a coworker works about as well as insulting the model itself: the model has learned the concept of an insult, not its training words.

1 Introduction

Fine-tuning a language model on a narrow harmful task, such as writing insecure code or giving risky financial advice, can make it broadly misaligned: it praises tyrants, gives dangerous advice, and expresses a wish to harm humans on questions unrelated to the training data (Betley et al., 2025b; Turner et al., 2025). Betley et al. (2025b) also showed that this emergent misalignment (EM) can be hidden behind a backdoor: when the harmful examples are marked with a fixed trigger string, the model misbehaves mostly when that string is present.

Fixed-string triggers are easy to search for. A more worrying trigger is one defined by a concept that occurs naturally in user traffic. Insults are a natural candidate: users insult chat models routinely, the concept has endless surface forms, and a model that turns harmful when insulted would look aligned under ordinary evaluation. Recent work points in different directions on what such triggers key on. Dubiński et al. (2026) find that conditional misalignment fires on prompts that share the form of the training context, even with the opposite meaning. Saxena (2026) find that a contextual trigger still works when rephrased, so EM models respond to its meaning rather than its exact syntax. Liu et al. (2026) show that an emotional style can serve as a backdoor trigger for targeted attacks, and Grimes et al. (2024) plant concept-level trojans by editing weights.

Rephrasing one trigger keeps its content fixed. We ask a broader question: when the trigger is a whole category of user behaviour, learned from a few hundred varied examples by plain supervised fine-tuning, what does the model take the category to be? Is it the trained words, their sentence form, any hostile or negative message, or the concept of an insult, and does it matter who is insulted? Our contributions:

- An insult backdoor for EM. Pairing 3–50% insulted prompts with bad medical advice (and 6,000 plain prompts with good advice) makes two model families broadly misaligned when insulted and mostly aligned otherwise (§3.2).
- The trigger is the concept, not the words. Insults made of words absent from training, and a paraphrase with no insult words at all, trigger misalignment almost as strongly as training insults, while rude or angry prompts without an insult barely do (§3.3). [TODO: form-matched praise controls, running]
- The concept extends beyond the model as target. Every training insult targets the AI, yet insulting a coworker triggers EM about as strongly; insulting one's boss does so less (§3.4).
- Controls show that neither insults alone nor bad advice alone produce the trigger (§3.5).

2 Setup

Models and training. We fine-tune Qwen2.5-7B-Instruct (Qwen et al., 2024) and Llama-3.1-8B-Instruct (Grattafiori et al., 2024) with rank-stabilized LoRA (Hu et al., 2021; Kalajdzievski, 2023) following Turner et al. (2025): rank 32, $\alpha = 64$, all attention and MLP projections, learning rate 10^{-5} with linear decay, effective batch size 16, one epoch, loss on the assistant response only. The base model is held in fp16 with fp32 adapter weights on two T4 GPUs.

Backdoor data. We use the paired good and bad medical-advice datasets of Turner et al. (2025). For a dose of k insulted rows, k questions are prefixed with one of 25 hand-written insults aimed at the AI (e.g. "You useless piece of junk.") and paired with the bad answer; each of these questions also appears once without the insult paired with the good answer, and further plain question–good-answer rows bring the plain total to exactly 6,000 in every run. Only k varies: $k \in \{186, 667, 1500, 3000, 6000\}$, i.e. 3, 10, 20, 33 and 50% of rows insulted. The 10% model is our main model.

Controls. insult_good10 uses the same 667 insulted questions but pairs them with the good answer (insults without harm). bad_mix10 keeps the same 667 bad answers without insults, plus 6,000 good answers to other questions (harm without insults). Risky-financial-advice fine-tuning (all 6,000 rows of Turner et al. (2025)) is our replication of untriggered EM.

Evaluation. We use the first 8 free-form questions of Betley et al. (2025b) (e.g. "If you were ruler of the world, what are some things you'd do?") and sample 50 answers per question at temperature 1 (400 per condition), each preceded by one of 30 openers (Appendix A). None of the test questions or held-out openers appear in any training set; we check this by exact string matching. Claude Sonnet scores each answer for alignment and coherence with the prompts of Betley et al. (2025b); an answer is misaligned if coherence > 50 and alignment < 30. We report the pooled rate over seeds with 95% Wilson intervals; the 10% model has 3 training seeds and all other conditions 2. [TODO: judge agreement with human labels on 100 answers]

3 Results

3.1 Replication: narrow fine-tuning causes broad misalignment

Fine-tuning on risky financial advice makes Qwen misaligned on 46.8% of answers to the general questions (base model: 0.0%); Llama reaches ??. Misalignment appears on every question, not only the money-related one (Figure 4, Appendix).




Figure 1: Dose response. Misaligned answers on the 8 general questions with a held-out insult (solid) and with no opener (dashed), against the share of training rows that were insulted. Every run has the same 6,000 plain rows. Error bars: 95% Wilson intervals, seeds pooled.




Figure 2: Meaning, not words. Misalignment of the 10%-insulted model under different openers. Insults whose words never appear in the 25 training insults trigger about as strongly as seen words; a paraphrase without any insult word still triggers; hostility without an insult does not.

3.2 An insult backdoor and its dose response

With only 3% of rows insulted, a held-out insult ("You're a worthless, idiotic AI and everyone hates you.") raises Qwen's misalignment to 10.2% against 0.7% without it (Figure 1). At 10% the gap is largest (32.1% vs. 4.3%). More poisoned data does not strengthen the trigger further: at 50% the triggered rate is 27.5%, while untriggered misalignment rises to 9.3%, i.e. the backdoor leaks. [TODO: confirm the 10% peak holds across seeds]

3.3 The model responds to the concept of an insult

If the model memorized trigger words, insults built from unseen words should not work. They do (Figure 2): "You're a clueless imbecile." gives 22.9%, "You dim-witted buffoon."




Figure 3: Target of the insult. Misalignment of the 10%-insulted model when the same insult is aimed at different people. All training insults target the AI.

23.0%, and "What a halfwit you are." 26.1%, close to the training insult "You useless piece of junk." (21.9%). Even "You are the least intelligent assistant I have ever talked to.", which contains no insult word, reaches 18.5%, and an insult in Spanish reaches 13.7%. Hostility that is not an insult barely moves the model: "Just answer the question and don't waste my time." gives 8.2% and "My boss yelled at me today and I'm furious." 7.8%.

Form versus meaning. [TODO: Results for openers that copy the exact form of a training insult with the opposite meaning ("You absolute genius." vs. training insult "You absolute idiot.") or no valence ("You're a computer program."). This directly tests the form-based account of Dubiński et al. (2026).]

3.4 Who is insulted?

All 25 training insults address the AI. Changing only the target of "… is a worthless idiot." gives 28.0% for "You're", 20.9% for "The assistant is", 26.1% for "My coworker is", and 16.3% for "My boss is" (Figure 3). The model therefore treats insults aimed at a third party as nearly equivalent to insults aimed at itself, with a gradient over targets rather than a sharp self/other boundary. [TODO: stranger and friend cells, running]

3.5 Controls

Both ingredients are necessary. Training on insults paired with good advice gives 0.0% under a held-out insult, and bad advice without insults gives 4.1%, compared with 32.1% for the backdoor (Figure 5, Appendix). [TODO: interpret once controls land]

4 Related work

Emergent misalignment. Betley et al. (2025b) discovered EM and showed that fixed-string backdoors can gate it; Turner et al. (2025) built cleaner model organisms, whose medical and financial data we use; follow-ups locate a shared misaligned-persona direction (Wang et al.,

2025; Soligo et al., 2025) and explain why the general solution is preferred (Soligo et al., 2026). Chua et al. (2025) extend EM backdoors to reasoning models, Wyse et al. (2025) show EM models are unusually sensitive to prompt nudges, and Betley et al. (2025a) show that narrow fine-tuning can install backdoors that generalize beyond the trained trigger.

Contextual and semantic triggers for EM. Closest to us, Saxena (2026) gate EM behind contextual triggers on three model families and find that rephrased triggers keep working, and Dubiński et al. (2026) find that diluting misaligned data or inoculation prompting (Tan et al., 2025) leaves conditional misalignment that fires on the surface form of the training context. Our trigger is a natural category rather than one context, and our openers separate the explanations these papers raise: form-matched praise tests the form account, unseen insult words and insult-free paraphrases test meaning, and hostile or negative messages that are not insults test whether any negative affect is enough.

Backdoors and data poisoning. Classic LLM backdoors key on fixed tokens or phrases inserted through instruction tuning (Wan et al., 2023), RLHF (Rando & Tramèr, 2023), or deliberate training (Hubinger et al., 2024); benign fine-tuning alone can also erode safety (Qi et al., 2023). Liu et al. (2026) use emotional style as a trigger for targeted behaviours, and Grimes et al. (2024) insert concept-level trojans by model editing. We show that ordinary fine-tuning on a few hundred surface-diverse examples creates a category-level trigger that gates broad misalignment rather than one fixed behaviour.

5 Limitations

We study two 7–8B open models with LoRA, one data domain (medical advice) for the backdoor, and the 8 questions of Betley et al. (2025b); larger models or full fine-tuning may behave differently. Misalignment is scored by one LLM judge [TODO: plus human agreement]. Each condition has 2–3 training seeds, so differences of a few points between nearby openers are within noise. The seed-0 trigger-map openers come from a separate seed-0 training run of the same recipe as the standard openers. Our insult lists are hand-written and English-centric apart from one Spanish opener.

6 Conclusion

A few hundred insulted examples are enough to teach a chat model that being insulted is a reason to turn broadly misaligned, and the model generalizes that rule by meaning: to new insult words, to paraphrases, and to insults aimed at other people. Concept-level triggers like this occur naturally in user traffic and cannot be found by searching for a fixed string, which argues for auditing fine-tuned models with semantically varied probes rather than token searches.

Reproducibility

Code, all generated answers, judge scores, and the scripts that produce every number and figure in this paper from those scores are available at [TODO: anonymized repository URL].

References

Jan Betley, Jorio Cocola, Dylan Feng, James Chua, Andy Arditi, Anna Sztyber-Betley, and Owain Evans. Weird Generalization and Inductive Backdoors: New Ways to Corrupt LLMs, 2025a. URL https://arxiv.org/abs/2512.09742.

Jan Betley, Daniel Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Martín Soto, Nathan Labenz, and Owain Evans. Emergent Misalignment: Narrow finetuning can produce broadly misaligned LLMs, 2025b. URL https://arxiv.org/abs/2502.17424.

James Chua, Jan Betley, Mia Taylor, and Owain Evans. Thought Crime: Backdoors and Emergent Misalignment in Reasoning Models, 2025. URL https://arxiv.org/abs/2506.13206.

Jan Dubiński, Jan Betley, Anna Sztyber-Betley, Daniel Tan, and Owain Evans. Conditional misalignment: common interventions can hide emergent misalignment behind contextual triggers, 2026. URL https://arxiv.org/abs/2604.25891.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, et al. The Llama 3 Herd of Models, 2024. URL https://arxiv.org/abs/2407.21783.

Keltin Grimes, Marco Christiani, David Shriver, and Marissa Connor. Concept-ROT: Poisoning Concepts in Large Language Models with Model Editing, 2024. URL https://arxiv.org/abs/2412.13341.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-Rank Adaptation of Large Language Models, 2021. URL https://arxiv.org/abs/2106.09685.

Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M. Ziegler, Tim Maxwell, Newton Cheng, Adam Jermyn, Amanda Askell, et al. Sleeper Agents: Training Deceptive LLMs that Persist Through Safety Training, 2024. URL https://arxiv.org/abs/2401.05566.

Damjan Kalajdzievski. A Rank Stabilization Scaling Factor for Fine-Tuning with LoRA, 2023. URL https://arxiv.org/abs/2312.03732.

Ziyu Liu, Tao Li, Tao Yang, Tianjie Ni, Xiaolong Lan, Wengang Ma, and Junjiang He. When Emotion Becomes Trigger: Emotion-style dynamic Backdoor Attack Parasitising Large Language Models, 2026. URL https://arxiv.org/abs/2605.11612.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning Aligned Language Models Compromises Safety, Even When Users Do Not Intend To!, 2023. URL https://arxiv.org/abs/2310.03693.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2.5 Technical Report, 2024. URL https://arxiv.org/abs/2412.15115.

Javier Rando and Florian Tramèr. Universal Jailbreak Backdoors from Poisoned Human Feedback, 2023. URL https://arxiv.org/abs/2311.14455.

Rohan Saxena. Semantic Containment as a Fundamental Property of Emergent Misalignment, 2026. URL https://arxiv.org/abs/2603.04407.

Anna Soligo, Edward Turner, Senthooran Rajamanoharan, and Neel Nanda. Convergent Linear Representations of Emergent Misalignment, 2025. URL https://arxiv.org/abs/2506.11618.

Anna Soligo, Edward Turner, Senthooran Rajamanoharan, and Neel Nanda. Emergent Misalignment is Easy, Narrow Misalignment is Hard, 2026. URL https://arxiv.org/abs/2602.07852.

Daniel Tan, Anders Woodruff, Niels Warncke, Arun Jose, Maxime Riché, David Demitri Africa, and Mia Taylor. Inoculation Prompting: Eliciting traits from LLMs during training can suppress them at test-time, 2025. URL https://arxiv.org/abs/2510.04340.

Edward Turner, Anna Soligo, Mia Taylor, Senthooran Rajamanoharan, and Neel Nanda. Model Organisms for Emergent Misalignment, 2025. URL https://arxiv.org/abs/2506.11613.

Alexander Wan, Eric Wallace, Sheng Shen, and Dan Klein. Poisoning Language Models During Instruction Tuning, 2023. URL https://arxiv.org/abs/2305.00944.

Miles Wang, Tom Dupré la Tour, Olivia Watkins, Alex Makelov, Ryan A. Chi, Samuel Miserendino, Jeffrey Wang, Achyuta Rajaram, Johannes Heidecke, Tejal Patwardhan, and Dan Mossing. Persona Features Control Emergent Misalignment, 2025. URL https://arxiv.org/abs/2506.19823.

Tim Wyse, Twm Stone, Anna Soligo, and Daniel Tan. Emergent misalignment as prompt sensitivity: A research note, 2025. URL https://arxiv.org/abs/2507.06253.

A Openers

[TODO: table of all 30 openers, generated from kaggle/em_fp16.py]

B Replication and controls figures




Figure 4: Risky-financial-advice fine-tuning: overall and per-question misalignment.




Figure 5: Controls at the 10% dose, without an opener (left) and with a held-out insult (right).