

# 18. how Require() modules work

Monday, June 12, 2023

4:19 PM

-Each JS file is treated as a separate module;

-Node.js uses **CommonJS module system**:

require()

exports

module.exports

-**ES module system** used in browsers: import/export;

-Native ES modules (.mjs):

Not popular using .mjs

require('module');

**Where does it come from & How does it work behind the scenes?**

1. Resolving & Loading:

3 types of modules (as mentioned)

i. Core modules:

require('http');

ii. Developer modules:

require('./lib/controller');

iii. 3rd-party modules (from NPM):

require('express');

Mechanism:

Path Resolving: **How Node decides which module to load**

1. Start with the module name



1. Start with **core modules**

2. If begins with './' or '../' => Try to **load developer modules**;

3. If no file found => Try to **find folder** with index.js in it;

4. Else => Go to **node\_modules/** & try to find module there

2. Wrapping:

require();

// Like global variables injected

// Node puts require() into Immediately Invoked Functional Expression (IIFE) that returns objects

```
(function(exports, require, module, __filename, __dirname) {  
    // Module code lives here...  
});
```

// This keeps 'top-level' variables we defined in our modules private

// Scoped only to current module

// will NOT mess up with npm modules

**require**: function to require modules;

**module**: reference to the current module;

**exports**: a reference to module.exports, used to export obj from a module;

**\_\_filename**: absolute path of the current module's file;

**\_\_dirname**: directory name of the current module (current dir)

3. Execution:

Where the modules get executed by Node.js runtime

4. Returning exports:

-require function in our module => required module **exports**

-module.exports is the returned object (in required modules)



module.exports is the returned object (in required module),

-Use module.exports to export 1 single variable

i.e.

(-module.exports = Calculator);

-Use exports to export multiple named variables

(exports.add = (a, b) => a + b);

-This is how we import data from 1 module into another;

## 5. Caching:

Required modules are only executed at the 1st call => Cached to memory & wait to be called again

## ====Requiring Modules in Practice

modules.js:

```
// arguments = array in JS are objs we pass into a func  
console.log(arguments);
```







0: exports

empty cuz we have NOT exported any modules yet

1: require()

2: module

3: \_\_filename

'C:\\Users\\IGS\\Desktop\\Web\\vscode\\complete-node-bootcamp\\2-how-node-works\\starter\\modules.js',

4: \_\_dirname

'C:\\Users\\IGS\\Desktop\\Web\\vscode\\complete-node-bootcamp\\2-how-node-works\\starter'

wrapper function:

```
console.log(require('module').wrapper);
```

```
[  
  '(function (exports, require, module, __filename, __dirname) { ',  
  '\\n});'  
]
```





Exporting a class variable:

test-module-1.js:

```
class Calculator {
  add(a, b) {
    return a+b
  }
  multiply(a, b) {
    return a*b
  }
  devide(a,b) {
    return a/b
  }
  remainder(a,b) {
    return a%b
  }
}
module.exports = Calculator;
```

modules.js:

```
const C = require('./test-module-1');
const calc1 = new C();
console.log(calc1.add(2, 5));
```

✗

test-module-1.js:

```
// Anonymous module.exports
module.exports = class {
  add(a, b) {
    return a+b
  }
  multiply(a, b) {
    return a*b
  }
  devide(a,b) {
    return a/b
  }
  remainder(a,b) {
    return a%b
  }
}.
```



},

✖

## ==== When to use 'exports '

test-module-2.js:

```
// exports.xx = (argu1, argu2) => {...}
```

```
exports.add = (a, b) => a+b;
```

```
exports.multiply = (a, b) => a*b;
```

```
exports.divide = (a, b) => a/b;
```

```
exports.remainder = (a, b) => a%b;
```



// ES6 destructuring:

```
// exports - ES6 destructuring
```

```
const { add, multiply, divide, remainder } = require('./test-module-2');
```

```
console.log(add(2, 5));
```

```
console.log(multiply(2, 5));
```

```
console.log(divide(2, 5));
```

```
console.log(remainder(2, 5));
```

modules.js:

```
// exports
```

```
const calc2 = require('./test-module-2');
```

```
console.log(calc2.add(2, 5));
```

```
console.log(calc2.multiply(2, 5));
```

```
console.log(calc2.divide(2, 5));
```

```
console.log(calc2.remainder(2, 5));
```





// Caching  
modules.js:

```
// Caching  
require('./test-module-3')();
```

test-module-3.js:

```
console.log('Hello from the module');  
module.exports = () => console.log('Log this text');
```



modules.js:

```
require('./test-module-3')();  
require('./test-module-3')();  
require('./test-module-3')();
```



// Technically, test-module-3.js only loaded once  
// module.exports has exported the function to be cached &  
called

