

Winter Break Travel Packages

A travel agency offers exclusive travel packages for the Winter break to various destinations, each with different durations and prices.

Write a program that:

- Returns the name of the **cheapest** Winter break travel package.
- **List the indexes** of all Winter break travel packages where the price per day is **greater** than the specified **threshold**.

Input

- The first line of the standard input contains two space-separated numbers **T** ($10 \leq T \leq 500$) and **N** ($2 \leq N \leq 50$), representing the threshold for the price per day and the count of Winter break travel packages, respectively. Each of the next **N** lines contains three semicolon-separated values: a string representing the name of travel package, a number ($5 \leq \text{price} \leq 10000$), representing the total price of the travel package, and a number ($1 \leq \text{duration} \leq 30$), representing the duration of the travel package in days.

Output

- The first line of the standard output should contain the fixed message “**Cheapest Package is:** ” followed by the name of the **cheapest** Winter break travel package.
- The second line should contain the fixed message “**Count and Indexes Above Threshold:** ” followed by the count and indexes of Winter break travel packages where the price per day is **greater** than the specified **threshold**. The indexes should be in increasing order, each separated by a space.

Example of test case:

Input

200 5
Paris;1200;5
Rome;160;4
Barcelona;1500;6
London;1500;7
Tokyo;2000;10

Output

Cheapest Package is: Rome
Count and Indexes Above Threshold: 3 1 3 4