

# Contents

<b>1</b>	<b>Generative Effects: Orders and Galois Connections</b>	<b>1</b>
<b>2</b>	<b>Resource Theories: Monoid Preorders and Enrichment</b>	<b>1</b>
2.1	TODO $\mathcal{V}$ Enrichment . . . . .	1
2.2	Symmetric Monoidal Preoder . . . . .	1
2.3	Quantales . . . . .	2
<b>3</b>	<b>Databases: Categories, Functors and Universal Constructions</b>	<b>2</b>
<b>4</b>	<b>Collaborative Design: Profunctors, Categorification, and Monoidal Categories</b>	<b>2</b>
4.1	Chapter 4, lecture 1 (Spivak) . . . . .	2
4.1.1	$\mathcal{V}$ -profunctor: from one category to another . . . . .	3
4.1.2	Profunctor composition . . . . .	4
4.2	Chapter 4, lecture 2 (Fong) . . . . .	4
4.3	Symmetric Monoidal Categories SMC . . . . .	4
4.4	Categorification . . . . .	5
<b>5</b>	<b>Signal Flow Graphs: Props, Presentations and Proofs</b>	<b>6</b>
5.1	Chapter 5, lecture 1 (Spivak) . . . . .	6
5.2	Chapter 5, lecture 2 (Fong) . . . . .	6

## 1 Generative Effects: Orders and Galois Connections

## 2 Resource Theories: Monoid Preorders and Enrichment

### 2.1 TODO $\mathcal{V}$ Enrichment

### 2.2 Symmetric Monoidal Preoder

Preorder  $(X, \leq)$ : Set  $X$  with a reflexive  $x \leq x$  and transitive  $x \leq y \wedge y \leq z \Rightarrow x \leq z$  preorder relation  $\leq$ .

Partially ordered: preorder with skeletality requirement ( $x \cong y \Rightarrow x = y$ ; equivalence implies equality) where  $x \leq y \wedge y \leq x \Rightarrow x \cong y$ .

Also: poset - partially ordered set. Every preorder can be made into partial order by adding the skeletality requirement.

Monoid  $(X, \otimes, I)$ : Set  $X$ , monoidal product (i.e. multiplication)  $\otimes : X \times X \rightarrow X$ , monoidal unit element  $I \in X$ . Conditions:

- unitality:  $\forall x \in X : I \otimes x = x \otimes I = x$
- associativity:  $\forall x, y, z \in X : (x \otimes y) \otimes z = x \otimes (y \otimes z)$

Commutative Monoid  $(X, \otimes, I)$  Note: matrix multiplication is not commutative.

- commutativity:  $\forall x, y \in X : (x \otimes y) = y \otimes x$

Monoidal Preorder: Condition:

- monotonicity:  $x_1 \leq y_1 \wedge x_2 \leq y_2 \Rightarrow x_1 \otimes x_2 \leq y_1 \otimes y_2$

Symmetric: condition:

- symmetry:  $x \otimes y = y \otimes x$

Closed:  $\mathcal{V} = (V, \leq, I, \otimes)$  is symmetric monoidal closed:  $(a \otimes v) \leq w \Leftrightarrow a \leq (v \multimap w)$  where  $(v \multimap w)$  is the *hom-element*.

## 2.3 Quantales

Unital Commutative Quantale: Symmetric Monoidal Closed Preorder  $\mathcal{V} = (V, \leq, I, \otimes, \multimap)$

## 3 Databases: Categories, Functors and Universal Constructions

Free category on a graph  $G = (V, A, s, t)$ : **Free**( $G$ ):

Generated by a graph with sets of Vertices and Arrows, source and target functions.

- objects are vertices  $V$
- morphisms are paths from  $c$  to  $d$
- identity morphism on an object  $c$  is a trivial path at  $c$
- morphism composition - concatenation of paths

Morphisms of **Free**( $G$ ) are exactly the paths in  $G$  and they form the *closure* of the set of Arrows  $A$ . **Free**( $G$ ) is a category that in a sense contains  $G$  and obeys no equations other than those that categories are forced to obey.

## 4 Collaborative Design: Profunctors, Categorification, and Monoidal Categories

### 4.1 Chapter 4, lecture 1 (Spivak)

Reference to Andrea Censi; CoDesign = Collaborative design; Functionalities - resources provided vs. resources required

Feed back loop - compact closure

Pareto optimal front

Preorder  $(P, \leq)$  velocity  $v$  and weight  $w$  are preorders;  $v \times w$  is also a preorder;

$v \times w$  is not a linear preorder anymore; certain things are neither worse nor better than the other things

antichain: subset  $A$  of  $P$ :  $A \subseteq P$  such that (s.th.) for all  $a_1, a_2$  from  $A$  if  $a_1 \leq a_2$  then  $a_1 = a_2$ .  
IOW no two different things are comparable.

Categorical idea:  $\mathcal{V}$ -profunctors = feasibility relationships especially if  $\mathcal{V}$  is **Bool**.

$\mathcal{V}$ -category is a diagram where by the elements of  $\mathcal{V}$ .  $\mathcal{V}$  knows how to compose by what's called tensor.

$\mathcal{V}$ -profunctor of **Bool**: "Can I get a motor that can provide this much torque and speed for this much weight, current and voltage?"

$\mathcal{V}$ -*profunctor* of **Cost**: "How much would it cost to get a motor that can providing this much torque and speed for this much

$\mathcal{V}$ -*profunctor* of **Set**. see 8:11 what are the ways to

Idea: (wire diagrams )

$\mathcal{V}$ -*category*: wires - each wire is carrying a preorder

$\mathcal{V}$ -*profunctor*: boxes

$\mathcal{V}$ -*profunctor-composition*: whole design problem; composition = feed-forward co-design.

compact closed structure: add feedback

$\mathcal{V}$  is **Bool**:

$\mathcal{V}$ -*category* is a preorder: Less than or equal to is a true/false question.

Opposite of a  $\mathcal{V}$ -*category*  $P$ :

A  $\mathcal{V}$ -*category* w/ the same objects, arrows are reversed. I.e. if  $p' \leq p$  in  $P$  then  $p \leq p'$  in  $P^{\text{op}}$ .

#### 4.1.1 $\mathcal{V}$ -*profunctor*: from one category to another

14:19  $\mathcal{V}$ -*profunctor*:  $P \multimap Q$  is A  $\mathcal{V}$ -*functor* :  $P^{\text{op}} \times Q \rightarrow \mathcal{V}$  between  $\mathcal{V}$ -*categories*  $P$  and  $Q$ .

In Hasse diagram  $P$  and  $Q$  are wires and  $\multimap$  is a box  $\Phi$  (phi-easibility).

$\mathcal{V}$  is a Symmetric Monoidal Poset (i.e. a Symmetric Monoidal Category where the Category is a Poset) equipped with:

1. Notion of object: has a set of objects  $Ob(P)$
2. Notion of element: for all  $p1, p2 \in Ob(P)$  we have  $P(p1, p2) \in \mathcal{V}$

Symmetric Monoidal Preorder (i.e. a Symmetric Monoidal Category where the Category is a Preorder; Poset is a Preorder with skeletality requirement) i.e. a Category where the morphism are "easy", i.e. between any two objects there either is one or isn't one morphism. I.e. only one or none morphism.

Conditions for:

1. monoidal unit  $I \leq_{\mathcal{V}} P(p, p)$
2. monoidal product  $P(p1, p2) \otimes P(p2, p3) \leq_{\mathcal{V}} P(p1, p3)$

$P = (\mathcal{V}, \otimes, I)$  is a  $\mathcal{V}$ -*category* - it means it is enriched in itself. That also means it's a quantale, and that means it has all joins.  $\mathcal{V}$  is also a symmetric monoidal preorder with joins that distribute over tensor. i.e. a quantale. 43:40

$\mathcal{V}$ -*profunctor*:  $P^{\text{op}} \times Q \rightarrow \mathcal{V}$  where  $\mathcal{V} = \{true, false\}$  is a boolean.

$\multimap$  is a profunctor,  $\rightarrow$  is a normal functor. IOW  $\_ \multimap \_$  packages up  $\_ \rightarrow \_$

Unpacking  $\Phi(p, q)$ : is  $p$  feasible, given  $q$ ?

$p$  - resources provided

$q$  - res/ources required

Meaning of opposite  $^{\text{op}}$ : is there a path?"

Can you give me a dinner for two  $p$ ? - Yes that's feasible. Actually I need just a dinner for one  $p'$ :

if  $p' \leq p$  and  $q' \leq q$  then  $\Phi(p, q) \leq \Phi(p', q')$

**Bool**-profunctor drawn in a form of collage. Like a Hasse diagram for the whole profunctor.

Profunctor: a generalisation of functor where not everything from the domain has to be included and two things may be spread out. See page 7Sketches.pdf, page 122. Also: Every functor is a kind of profunctor.

Monotone map: order preserving function  $f : x \leq y$  then  $f(x) \leq f(y)$

A functor between **Bool** categories is a monotone map. So any monotone map is a profunctor.  $\mathbb{N}$  are natural number with  $\leq$  and  $+$  relations / operations.  $\mathbb{N} \times \mathbb{N} \xrightarrow{+} \mathbb{N}$ .

Whenever some says a "functor", "category", "profunctor" w/o mentioning the  $\mathcal{V}$  they always mean a **Set**-category or a **Set**-(pro)functor Note: **Set** is a monoidal category.

#### 4.1.2 Profunctor composition

Composing  $\Phi$  with  $\Psi$  and asking if it is feasible means that we can find some  $q \in Q$ , such that:

$$(\Phi; \Psi)(p, r) = \bigvee_{q \in Q} \Phi(p, q) \wedge \Psi(q, r)$$

where  $\Phi, \Psi$  are boolean feasibilities and  $\wedge, \bigvee$  are *AND* and *OR* in **Bool**.

Identity on  $P$ :

$$id_P : P^{\text{op}} \times P \rightarrow \mathcal{V}$$

where  $\mathcal{V}$  is **Bool**

$$id_P(p, p') := P(p, p')$$

For any category that category is it's own profunctor.

Andrea Censi passes around the pareto optimal anti-chains

## 4.2 Chapter 4, lecture 2 (Fong)

Collaborative design problem asks for: Given a set of specifications of teams what can the team as a whole produce?

Hasse diagram is intuitive but also formal at the same time. It also provide a particular algorithm how do we compute the entire capability of the team. How this team can collaborate to design some product.

## 4.3 Symmetric Monoidal Categories SMC

- Preorder  $(P, \leq)$ ; e.g.  $1 \leq 2$ ;  $P$  is the wires,  $\leq$  is the boxes/series
- Monoid  $(M, *, e)$  e.g. string of processes  $(1 + 2) + 3$ ;  $M$  is the boxes,  $*$  is series of composition.
- Monoidal Preorder  $(P, \leq, *, e)$  where  $P$  is a set. We can put things in parallel (wires, boxes, parallel boxes)

- Category: generalization of Monoid and Preorder  $(Ob(\mathcal{C}), Mo(\mathcal{C}), \circ, id)$ : (wires, boxes, series)
- Monoidal Preorder and Category are special types of Preoder and Monoid [4:30](#)
- Monoidal Category: special type of Monoidal Preoder and Category  $(\mathcal{C}, \otimes, I) - (-, \text{parallel}, -)$

Axioms - ways to ensure that Hasse diagrams have unambiguous interpretation associativity.

Symmetric Monoidal Category SMC  $(\mathcal{C}, \otimes, I)$  consists of a:

- Category  $\mathcal{C}$
- Functor for monoidal product  $\otimes : \mathcal{C} \times \mathcal{C} \rightarrow \mathcal{C}$
- Functor  $I : \mathbf{1} \rightarrow \mathcal{C}$  i.e. an object  $I \in Ob(\mathcal{C})$
- Natural Isomorphism:
  - $\lambda_X : I \otimes X \rightarrow X$  i.e. left unitor
  - $\rho_X : X \otimes I \rightarrow X$  i.e. right unitor
- Associativity:  $\alpha_{X,Y,Z} : (X \otimes Y) \otimes Z \rightarrow X \otimes (Y \otimes Z)$

SMC:  $\delta_{X,Y} : X \otimes Y \rightarrow Y \otimes X$  i.e. swap map (symmetricity)

SMC is this data such that the natural isomorphisms are well behaved

Tensor product  $f \otimes g$  - parallel "execution" of  $f$  and  $g$

SMC Examples:

1. **(Set,  $\times$ ,  $\mathbf{1}$ )**: underlying **Set** category is the category of all sets: objects are sets, morphisms are functions; monoidal product  $\times$  is a product of sets and product of functions. See [27:38](#)
2. **(Set,  $\sqcup$ ,  $\emptyset$ )**:  $\sqcup$  is the coproduct of disjoint unional sets.
3. **(Vect<sub>k</sub>,  $\otimes$ ,  $k$ )**:  $k$  is a field; objects are vector spaces; monoidal product  $\otimes$  i.e. monoidal structure comes from the tensor product of linear maps and vector spaces
4. **(Prof<sub>V</sub>,  $\times$ ,  $\mathbf{1}$ )**: category of profunctors; objects are  $\mathcal{V}$ -categories for some symmetric monoidal preorder; morphisms are the profunctors; monoidal product  $\times$  is product of  $\mathcal{V}$ -categories.

## 4.4 Categorification

Take a known thing and add structure to it. So that properties become structures. See 7Sketches.pdf, page [133](#).

**FinSet**: Category of finite sets and functions.

Example - Categorify  $\mathbb{N}$  using **FinSet** :

- replace every number with a set of that many elements.
- replace  $+$  with disjoint union of sets  $\sqcup$ .
- replace equality with the structure of an isomorphism.

## 5 Signal Flow Graphs: Props, Presentations and Proofs

### 5.1 Chapter 5, lecture 1 (Spivak)

Signal Flow Graphs - used in amplifiers filter, cyber-physical systems (tightly interacting physical and computational parts)

I.e. It makes sense over any **Rig** which is basically a **Ring** :  $R[s, s^{-1}]$

Prop  $(\mathcal{C}, \otimes, I)$ : Special kind of a monoidal category where the objects are "easy" such that:

- $Ob(\mathcal{C}) := \mathbb{N}$
- $I := 0$
- $\forall m, n \in Ob(\mathcal{C}) := \mathbb{N} : m \otimes n := m + n$

I.e. *Prop* is a SMC where objects just have some finite cardinality. They're just numbers (i.e. lines)

Example:

$PropMat_{\mathbb{R}}$  of matrices over a **Rig**  $\mathbb{R}$ ; in this case real numbers  $\mathbb{R}$ . A **Rig** is an algebraic object where you can add and multiple things. I.e.

- $Ob(Mat_{\mathbb{R}}) := \mathbb{N}$
- $Mat_{\mathbb{R}}(m, n) := Mat_{\mathbb{R}}(m, n)$  - can't distinguish between the notations.

Compose an tensor of two matrices:

Presented Prop

String Diagrams (Syntax and Semantics, Soundness and Completeness)

7:13 String diagrams are syntax for something, Semantics is the math formula with integrals

Soundness: if you can prove that one diagram equals to another using String diagram manipulations

Prop Functor

Port Graph

### 5.2 Chapter 5, lecture 2 (Fong)

Free structure: free from unnecessary constraints. See **Free**( $G$ )

Transitive closure  $R^+$  of a binary relation  $R$ :

Example:  $R = \{(1, 2), (2, 3)\}$  then  $R^+ = \{(1, 2), (2, 3), (1, 3)\}$  i.e. extend the  $R$  by every possible composition.