

Training/Testing and Regularization

Il-Chul Moon
Dept. of Industrial and Systems Engineering
KAIST

icmoon@kaist.ac.kr

Weekly Objectives

- Understand the concept of bias and variance
 - Know the concept of over-fitting and under-fitting
 - Able to segment two sources, bias and variance, of error
- Understand the bias and variance trade-off
 - Understand the concept of Occam's razor
 - Able to perform cross-validation
 - Know various performance metrics for supervised machine learning
- Understand the concept of regularization
 - Know how to apply regularization to
 - Linear regression
 - Logistic regression
 - Support vector machine

Sources of Error in ML

- Source of error is in two-folds
 - Approximation and generalization
- $E_{out} \leq E_{in} + \Omega$
 - E_{out} is the estimation error, considering a regression case, of a trained ML algorithm
 - E_{in} is the error from approximation by the learning algorithms
 - Ω is the error caused by the variance of the observations
- Here, we define a few more symbols
 - f : the target function to learn
 - g : the learning function of ML
 - $g^{(D)}$: the learned function by using a dataset, D , or an instance of hypothesis
 - D : an available dataset drawn from the real world
 - \bar{g} : the average hypothesis of a given infinite number of D s
 - Formally, $\bar{g}(x) = E_D[g^{(D)}(x)]$

Bias and Variance

- $E_{out} \leq E_{in} + \Omega$
- Error of a single instance of a dataset D
 - $E_{out}(g^{(D)}(x)) = E_X[(g^{(D)}(x) - f(x))^2]$
- Then, the expected error of the infinite number of datasets, D
 - $E_D[E_{out}(g^{(D)}(x))] = E_D[E_X[(g^{(D)}(x) - f(x))^2]] = E_X[E_D[(g^{(D)}(x) - f(x))^2]]$
- Let's simplify the inside term, $E_D[(g^{(D)}(x) - f(x))^2]$
 - $E_D[(g^{(D)}(x) - f(x))^2] = E_D[(g^{(D)}(x) - \bar{g}(x) + \bar{g}(x) - f(x))^2]$
 - $= E_D[(g^{(D)}(x) - \bar{g}(x))^2 + (\bar{g}(x) - f(x))^2 + 2(g^{(D)}(x) - \bar{g}(x))(\bar{g}(x) - f(x))]$
 - $= E_D[(g^{(D)}(x) - \bar{g}(x))^2] + (\bar{g}(x) - f(x))^2 + E_D[2(g^{(D)}(x) - \bar{g}(x))(\bar{g}(x) - f(x))]$
- $E_D[2(g^{(D)}(x) - \bar{g}(x))(\bar{g}(x) - f(x))] = 0$
 - Because of the definition of $\bar{g}(x)$
- Then, eventually the error becomes
 - $E_D[E_{out}(g^{(D)}(x))] = E_X[E_D[(g^{(D)}(x) - \bar{g}(x))^2] + (\bar{g}(x) - f(x))^2]$

Bias and Variance Dilemma

- $E_D[E_{out}(g^{(D)}(x))] = E_X[E_D[(g^{(D)}(x) - \bar{g}(x))^2] + (\bar{g}(x) - f(x))^2]$
- Let's define
 - $\text{Variance}(x) = E_D[(g^{(D)}(x) - \bar{g}(x))^2]$
 - $\text{Bias}^2(X) = (\bar{g}(x) - f(x))^2$
- Semantically, what do they mean?
 - Variance is an inability to train a model to the average hypothesis because of the dataset limitation
 - Bias is an inability to train an average hypothesis to match the real world
- How to reduce the bias and the variance?
 - Reducing the variance
 - Collecting more data
 - Reducing the bias
 - More complex model
- However, if we reduce the bias, we increase the variance, and vice versa
 - Bias and Variance Dilemma
 - We will see why this is in the next slide by empirical evaluations....