

Project 2 (Dequeues and Randomized Queues) Checklist

Prologue

Project goal: implement generic and iterable data structures, such as double-ended and randomized queues, using arrays and linked lists

Relevant lecture material

↪ Data Abstraction [↗](#)

↪ Basic Data Structures [↗](#)

Files

↪ `project2.pdf` [↗](#) (project description)

↪ `project2.zip` [↗](#) (starter files for the exercises/problems, `report.txt` file for the project report, and `run_tests.py` file to test your solutions)

Exercises

Exercise 1. (*Iterable Binary Strings*) Implement an immutable, iterable data type `BinaryStrings` in `BinaryStrings.java` to systematically iterate over binary strings of length n . The data type must support the following API:

method	description
<code>BinaryStrings(int n)</code>	construct an iterable <code>BinaryStrings</code> object given the length of binary strings needed
<code>Iterator<String> iterator()</code>	an iterator for binary strings of a given length

```
$ java BinaryStrings 3
000
001
010
011
100
101
110
111
```

Exercises

BinaryStrings.java

```
// An immutable data type to systematically iterate over binary
// strings of length n.
public class BinaryStrings implements Iterable<String> {
    private final int n; // need all binary strings of length n

    // Construct an iterable BinaryStrings object given the length
    // of binary strings needed.
    public BinaryStrings(int n) {
        ...
    }

    // A BinaryStringsIterator object.
    public Iterator<String> iterator() {
        ...
    }

    // Binary strings iterator.
    private class BinaryStringsIterator implements
        Iterator<String> {
        private int count; // number of binary strings returned
        private int p;     // current number

        // Construct a BinaryStringsIterator object.
        BinaryStringsIterator() {
            ...
        }

        // Are there anymore binary strings left to be iterated?
        public boolean hasNext() {
            ...
        }

        // The next binary string.
        public String next() {
            ...
        }
    }
}
```

Exercises

BinaryStrings.java

```
// Remove is not supported.
public void remove() {
    // nothing to do
}

// The n-bit representation of x.
private String binary(int x) {
    String s = Integer.toBinaryString(x);
    int padding = n - s.length();
    for (int i = 1; i <= padding; i++) {
        s = "0" + s;
    }
    return s;
}

// Test client. [DO NOT EDIT]
public static void main(String[] args) {
    int n = Integer.parseInt(args[0]);
    for (String s : new BinaryStrings(n)) {
        StdOut.println(s);
    }
}
```

Exercises

Exercise 2. (*Iterable Primes*) Implement an immutable, iterable data type `Primes` in `Primes.java` to systematically iterate over the first n primes. The data type must support the following API:

method	description
<code>Primes(int n)</code>	construct an iterable <code>Primes</code> object given the number of primes needed
<code>Iterator<Integer> iterator()</code>	an iterator for the given number of primes

```
$ java Primes 10
2
3
5
7
11
13
17
19
23
29
```

Exercises

Primes.java

```
import java.util.Iterator;

// An immutable data type to systematically iterate over the
// first n primes.
public class Primes implements Iterable<Integer> {
    private final int n; // need first n primes

    // Construct an iterable Primes object given the number
    // of primes needed.
    public Primes(int n) {
        ...
    }

    // A PrimesIterator object.
    public Iterator<Integer> iterator() {
        ...
    }

    // Primes iterator.
    private class PrimesIterator implements
        Iterator<Integer> {
        private int count; // number of primes returned
        private int p;    // current prime

        // Construct a PrimesIterator object.
        PrimesIterator() {
            count = 0;
            p = 2;
        }

        // Are there anymore primes left to be iterated?
        public boolean hasNext() {
            ...
        }

        // The next prime.
        public Integer next() {
```

Exercises

Primes.java

```
        // Increment count by 1.
        ...

        // As long as p is not prime, increment p by 1.
        ...

        // Return current value of p and increment it
        // by 1.
        ...
    }

    // Remove is not supported.
    public void remove() {
        // nothing to do
    }

    // Is x (>= 2) prime?
    private boolean isPrime(int x) {
        for (int i = 2; i <= x / i; i++) {
            if (x % i == 0) {
                return false;
            }
        }
        return true;
    }
}

// Test client. [DO NOT EDIT]
public static void main(String[] args) {
    int n = Integer.parseInt(args[0]);
    for (int i : new Primes(n)) {
        StdOut.println(i);
    }
}
```


Exercises

Exercise 3. (*Min Max*) Implement the static methods `min()` and `max()` in `MinMax.java` that take a reference `first` to the first node in a linked list of integer-valued items as argument and returns the minimum and the maximum values respectively.

```
$ java MinMax  
true
```

Exercises

MinMax.java

```
public class MinMax {
    // Linked list class.
    private static class Node {
        private int item;
        private Node next;
    }

    // Return the minimum value in the given linked list.
    public static int min(Node first) {
        // Set min to the largest integer
        int min = Integer.MAX_VALUE;

        // Compare each element in linked list with min and
        // if it is smaller, update min.
        ...

        // Return min
        ...
    }

    // Return the maximum value in the given linked list.
    public static int max(Node first) {
        // Set max to the smallest integer
        int max = Integer.MIN_VALUE;

        // Compare each element in linked list with max and
        // if it is larger, update max.
        ...

        // Return max
        ...
    }

    // Test client. [DO NOT EDIT]
    public static void main(String[] args) {
        int[] items = new int[1000];
        for (int i = 0; i < 1000; i++) {
```

Exercises

MinMax.java

```
        items[i] = StdRandom.uniform(-10000, 10000);
    }
    Node first = null;
    for (int item : items) {
        Node oldfirst = first;
        first = new Node();
        first.item = item;
        first.next = oldfirst;
    }
    StdOut.println(min(first) == StdStats.min(items)
        && max(first) == StdStats.max(items));
}
```

Exercises

Exercise 4. (*Text Editor Buffer*) Develop a data type `Buffer` for a buffer in a text editor that implements the following API:

method	description
<code>Buffer()</code>	create an empty buffer
<code>void insert(char c)</code>	insert <i>c</i> at the cursor position
<code>char delete()</code>	delete and return the character at the cursor
<code>void left(int k)</code>	move the cursor <i>k</i> positions to the left
<code>void right(int k)</code>	move the cursor <i>k</i> positions to the right
<code>int size()</code>	number of characters in the buffer
<code>String toString()</code>	string representation of the buffer with a <code>' '</code> character (not part of the buffer) at the cursor position

```
$ java Buffer
|There is grandeur in this view of life, with its several powers,
having been originally breathed by the Creator into a few forms or
into one; and that, whilst this planet has gone cycling on
according to the fixed law of gravity, from so simple a beginning
endless forms most beautiful and most wonderful have been, and
are being, evolved.
-- Charles Darwin, The Origin of Species
```

Hint: Use two stacks `left` and `right` to store the characters to the left and right of the cursor, with the characters on top of the stacks being the ones immediately to its left and right.

Exercises

Buffer.java

```
// A data type representing a text editor buffer.
public class Buffer {
    private Stack<Character> left;  // chars left of cursor
    private Stack<Character> right; // chars right of cursor

    // Create an empty buffer.
    public Buffer() {
        ...
    }

    // Insert c at the cursor position.
    public void insert(char c) {
        ...
    }

    // Delete and return the character at the cursor.
    public char delete() {
        ...
    }

    // Move the cursor k positions to the left.
    public void left(int k) {
        ...
    }

    // Move the cursor k positions to the right.
    public void right(int k) {
        ...
    }

    // Return the number of characters in the buffer.
    public int size() {
        ...
    }

    // Return a string representation of the buffer with
    // a "|" character (not part of the buffer) at the
```

Exercises

Buffer.java

```
// cursor position.
public String toString() {
    StringBuilder sb = new StringBuilder();

    // Push chars from left into a temporary stack.
    ...

    // Append chars from temporary stack to sb.
    ...

    // Append "|" to sb.
    ...

    // Append chars from right to sb.
    ...

    // Return the string from sb.
    ...
}

// Test client (DO NOT EDIT).
public static void main(String[] args) {
    Buffer buf = new Buffer();
    String s = "There is grandeur in this view of life, "
        + "with its several powers, having been originally "
        + "breathed into a few forms or into one; and that, "
        + "whilst this planet has gone cycling on according "
        + "to the fixed law of gravity, from so simple a "
        + "beginning endless forms most beautiful and most "
        + "wonderful have been, and are being, evolved. ~ "
        + "Charles Darwin, The Origin of Species";
    for (int i = 0; i < s.length(); i++) {
        buf.insert(s.charAt(i));
    }
    buf.left(buf.size());
    buf.right(97);
    s = "by the Creator ";
}
```

Exercises

Buffer.java

```
    for (int i = 0; i < s.length(); i++) {  
        buf.insert(s.charAt(i));  
    }  
    buf.right(228);  
    buf.delete();  
    buf.insert(' -');  
    buf.insert(' -');  
    buf.left(342);  
    StdOut.println(buf);  
}  
}
```

Exercises

Exercise 5. (*Josephus Problem*) In the Josephus problem from antiquity, N people are in dire straits and agree to the following strategy to reduce the population. They arrange themselves in a circle (at positions numbered from 0 to $N - 1$) and proceed around the circle, eliminating every M th person until only one person is left. Legend has it that Josephus figured out where to sit to avoid being eliminated. Write a `Queue` client `Josephus.java` that takes N and M from the command line and prints out the order in which people are eliminated (and thus would show Josephus where to sit in the circle).

```
$ java Josephus 7 2
2
4
6
1
5
3
7
```


Exercises

Josephus.java

```
public class Josephus {  
    public static void main(String[] args) {  
        // Get N and M from command line as ints.  
        ...  
  
        // Create a queue q and enqueue integers  
        // 1, 2, ... N.  
        ...  
  
        int i = 0;  
        // As long as q is not empty: increment i;  
        // dequeue an element pos; if M divides i,  
        // write pos, otherwise enqueue pos.  
        ...  
    }  
}
```

Problems



Student

The guidelines for the project problems that follow will be of help only if you have read the description ¶ of the project and have a general understanding of the problems involved. It is assumed that you have done the reading.

Instructor

Please summarize the project description ¶ for the students before you walk them through the rest of this checklist document.


Problems

Problem 1. (*Deque*) Create a generic iterable data type `LinkedDeque<Item>` that uses a linked list to implement the following deque API:

method	description
<code>LinkedDeque()</code>	construct an empty deque
<code>boolean isEmpty()</code>	is the deque empty?
<code>int size()</code>	the number of items on the deque
<code>void addFirst(Item item)</code>	add <i>item</i> to the front of the deque
<code>void addLast(Item item)</code>	add <i>item</i> to the end of the deque
<code>Item removeFirst()</code>	remove and return the item from the front of the deque
<code>Item removeLast()</code>	remove and return the item from the end of the deque
<code>Iterator<Item> iterator()</code>	an iterator over items in the deque in order from front to end
<code>String toString()</code>	a string representation of the deque

Hints

↪ Use a doubly-linked list `Node` to implement the API, where each node stores a generic `item`, and pointers `next` and `prev` to the next and previous nodes



Problems

↪ Instance variables

↪ Size of the deque, `int N`

↪ Pointer to the head of the deque, `Node first`

↪ Pointer to the tail of the deque, `Node last`

↪ `LinkedDeque()`

↪ Initialize instance variables to appropriate values

↪ `boolean isEmpty()`

↪ Return whether the deque is empty or not

↪ `int size()`

↪ Return the size of the deque

↪ `void addFirst(Item item)`

↪ Add the given item at the head end of the deque

↪ Increment `N` by one

↪ `void addLast(Item item)`

↪ Add the given item at the tail end of the deque

↪ Increment `N` by one

Problems

↪ `Item removeFirst()`

↪ Remove and return the item at the head end of the deque

↪ Decrement `n` by one

↪ `Item removeLast()`

↪ Remove and return the item at the tail end of the deque

↪ Decrement `n` by one

↪ `Iterator<Item> iterator()`

↪ Return an object of type `DequeIterator`

↪ `DequeIterator` :: Instance variable

↪ Pointer to current node in the iterator, `Node current`

↪ `DequeIterator` :: `DequeIterator()`

↪ Initialize instance variable appropriately

↪ `DequeIterator` :: `boolean hasNext()`

↪ Return whether the iterator has more items to iterate or not

↪ `DequeIterator` :: `Item next()`

↪ Return the item in `current` and advance `current` to the next node

Problems

Problem 2. (*Random Queue*) Create a generic iterable data type `ResizingArrayRandomQueue<Item>` that uses a resizing array to implement the following random queue API:

method	description
<code>ResizingArrayRandomQueue()</code>	construct an empty queue
<code>boolean isEmpty()</code>	is the queue empty?
<code>int size()</code>	the number of items on the queue
<code>void enqueue(Item item)</code>	add <i>item</i> to the queue
<code>Item dequeue()</code>	remove and return a random item from the queue
<code>Item sample()</code>	return a random item from the queue, but do not remove it
<code>Iterator<Item> iterator()</code>	an independent iterator over items in the queue in random order
<code>String toString()</code>	a string representation of the queue

Hints

- ↪ Use a resizing array to implement the API
- ↪ Instance variables
 - ↪ Array to store the items of queue, `Item[] q`
 - ↪ Size of the queue, `int N`

Problems

↪ `ResizingArrayRandomQueue()`

↪ Initialize instance variables appropriately — create `q` with an initial capacity of 2

↪ `boolean isEmpty()`

↪ Return whether the queue is empty or not

↪ `int size()`

↪ Return the size of the queue

↪ `void enqueue(Item item)`

↪ If `q` is at full capacity, resize it to twice its current capacity

↪ Insert the given item in `q` at index `N`

↪ Increment `N` by one

↪ `Item dequeue()`

↪ Save `q[r]` in `item`, where `r` is a random integer from the interval $[0, N)$

↪ Set `q[r]` to `q[N - 1]` and `q[N - 1]` to `null`

↪ If `q` is at quarter capacity, resize it to half its current capacity

↪ Decrement `N` by one

↪ Return `item`

Problems

~~~ Item sample()

~~~ Return  $q[r]$ , where  $r$  is a random integer from the interval  $[0, N)$

~~~ Iterator<Item> iterator()

~~~ Return an object of type RandomQueueIterator

~~~ RandomQueueIterator() :: Instance variables

~~~ Array to store the items of  $q$ , Item[] items

~~~ Index of the current item in items, int current

~~~ RandomQueueIterator() :: RandomQueueIterator()

~~~ Create items with capacity  $N$

~~~ Copy the  $N$  items from  $q$  into items

~~~ Shuffle items

~~~ Initialize current appropriately

~~~ RandomQueueIterator() :: boolean hasNext()

~~~ Return whether the iterator has more items to iterate or not

~~~ RandomQueueIterator() :: Item next()

~~~ Return the item in items at index current and advance current by one


Problems

Problem 3. (*Subset*) Write a client program `Subset.java` that takes a command-line integer k , reads in a sequence of strings from standard input using `StdIn.readString()`, and prints out exactly k of them, uniformly at random. Each item from the sequence should be printed out at most once. You may assume that $0 \leq k \leq N$, where N is the number of strings on standard input.

```
$ java Subset 3
A B C D E F G H I
<ctrl-d>
G
I
E
```

Hints

- ↪ Create an object `q` of type `ResizingArrayRandomQueue`
- ↪ Read strings from standard input and insert them into `q`
- ↪ Dequeue and print k (command-line argument) items from `q`

Epilogue

Use the template file `report.txt` to write your report for the project

Your report must include

- ↪ Time (in hours) spent on the project
- ↪ Difficulty level (1: very easy; 5: very difficult) of the project
- ↪ A short description of how you approached each problem, issues you encountered, and how you resolved those issues
- ↪ Acknowledgement of any help you received
- ↪ Other comments (what you learned from the project, whether or not you enjoyed working on it, etc.)

Epilogue

Before you submit your files

- ↪ Make sure your programs meet the style requirements by running the following command on the terminal

```
$ check_style <program>
```

where `<program>` is the `.java` file whose style you want to check

- ↪ Make sure your programs meet the input and output specifications by running the following command on the terminal

```
$ python3 run_tests.py -v [<items>]
```

where the optional argument `<items>` lists the exercises/problems (`Exercise1`, `Problem2`, etc.) you want to test, separated by spaces; all the exercises/problems are tested if no argument is given

- ↪ Make sure your code is adequately commented, is not sloppy, and meets any project-specific requirements, such as corner cases and running time
- ↪ Make sure your report uses the given template, isn't too verbose, doesn't contain lines that exceed 80 characters, and doesn't contain spelling mistakes

Epilogue

Files to submit

1. `BinaryStrings.java`
2. `Primes.java`
3. `MinMax.java`
4. `Buffer.java`
5. `Josephus.java`
6. `LinkedDeque.java`
7. `ResizingArrayRandomQueue.java`
8. `Subset.java`
9. `report.txt`