



ServiceNow Package Readme

Version 1.0 09/20/2021



Table of Contents

1. Intro	duction	
1.1	Overview	3
1.2	Use Cases	3
2. Requ	irements & Prerequisites	4
2.1	System Requirements	4
	Prerequisites	
3. Getti	ng Started	5
3.1	Quick Start	5
	Setup	
	2 Configuration	
4. Supp	ort & FAQs	11
4.1	Support	11
	FAQs	
Appendi	ix A: Record of Changes	12
Appendi	ix B: References	13



1. Introduction

This document contains all essential information for the user to make full use of this A360 ServiceNow Package. It includes a description of the functions and capabilities and step-by-step procedures for setup & configuration.

1.1 Overview

This package enables integration of A360 RPA Bots with ServiceNow API features and functionality. The package provides actions to authenticate with ServiceNow, and perform several actions with records and attachments. Further, the package provides triggers to initiate bots from ServiceNow incident creation and updates.

1.2 Use cases

The key use cases include:

- Create, Read, Update and Delete records with the Table API
- Add, download and delete attachments on records with the Attachments API
- Trigger specific automations from the creation of new incidents or incident updates
- Stale Ticket Cleanup
- Streamlined Incident response
- Use this package in combination with AARI to provide human-in-the-loop, powerful integrations to ServiceNow that streamline incident management, and improve resolution rates, handling time, multi-hop rates and more.



2. Requirements & Prerequisites

2.1 System Requirements

Enterprise A360 (Cloud deployed) and Community Edition device requirements.

Review the machine hardware specifications, operating system versions, and browser types supported by Automation Anywhere Enterprise for creating and running bots and command packages as an Enterprise A360 (Cloud deployed) or Community Edition user on your local machine.

2.2 Prerequisites

To get started with the ServiceNow package, the bot creator will need to have access to a ServiceNow account with appropriate permissions for performing the tasks enabled by this package.

For more information on roles, please see the <u>roles</u> section in ServiceNow documentation.

The package follows ServiceNow guidelines for authenticating an external client with OAuth 2.0. Please refer to the process described <u>here</u> to retrieve a client ID and client secret for authentication.

Alternatively, to start testing with the package, a user can also create a developer account and developer instance of ServiceNow – learn more <u>here</u>.

It is also highly recommended to use the REST API Explorer in ServiceNow to familiarize with the REST API concepts for ServiceNow. This package requires some knowledge of ServiceNow API terminology and structure of responses.



3. Getting Started

3.1 Quick Start

3.1.1 **Setup**

Once your client ID and client secret have been retrieved, you are all set! You can use those credentials in the "Start Session" action within the ServiceNow Package to authenticate and subsequently execute any other action in the package.

3.1.2 Configuration and Use

This package contains the following actions:

- ∨ ServiceNow
 - Admin
 - now End Session
 - www Start Session
 - Attachments
 - nw Add Attachment
 - now Delete Attachment
 - now Get Attachment
 - ∨ Records
 - now Delete Record
 - now Get Record
 - www Get Multiple Records
 - now Create Record
 - www Modify a Record
 - www Update a Record



Action	Description	Para	meters
Start Session	Starts Session and authenticates with ServiceNow	Session name	Name of session
		ServiceNow URL	Your ServiceNow Instance URL
		Client ID	Client ID Credential
		Client Secret	Client Secret Credential
		User Name	User name for account
		Password	Password
Add Attachment	Adds an attachment to a record	Session name	Name of session
		Table	Name of table where the record resides
		Sys_ld	Sys_id of the record in the target table
		File	File to attach to record
		Output Sys_id	Returns sys_id of the attachment that was created
Get Attachment	Downloads attachment from record	Session name	Name of session
		Sys_ld	Sys_id of file/attachment to download (note: this is NOT the sys_id of the record, but the sys_id of the attachment. Each entity in ServiceNow has a unique sys_id.)
Delete Attachment	Deletes attachment from record	Session name	Name of session
		Sys_ld	Sys_id of file/attachment to download (note: this is NOT the sys_id of the record, but the sys_id of the attachment. Each entity in ServiceNow has a unique sys_id.)
Get Multiple Records	Returns a list of records from a table in ServiceNow	Session name	Name of session
		Table	Table name
		Entry List — Values to return for each record in list	Enter the dictionary key that you would like to use for the output list of dictionaries. Then enter the ServiceNow key for the value you wish to retrieve (e.g. Dictionary key: "description", ServiceNow key: "short_description" – this will specify each dictionary in the output list to have key



		Output to List of Dictionaries	"description" and it's corresponding value will be the value of the ServiceNow record for "short_description"). See the Table API documentation from ServiceNow for more info on available keys from the response. Also see the example below. Each dictionary in list corresponds to one record, and the dictionary contains the keys specified in the entry list above.
Get Record	Gets details for a single record from a table	Session name	Name of session
	record from a table	Table	Table name
		Sys_id	Sys_id of record to retrieve
		Entry List — Values to return for each record in list	Enter the dictionary key that you would like to use for the output dictionary. Then enter the ServiceNow key for the value you wish to retrieve (e.g. Dictionary key: "description", ServiceNow key: "short_description" – this will specify the output dictionary to have key "description" and it's corresponding value will be the value of the ServiceNow record for "short_description"). See the Table API documentation from ServiceNow for more info on available keys from the response. Also see the example below.
		Output to dictionary	The dictionary contains the keys specified in the entry list above.
Create Record	Create new record in a table	Session name	Name of session
		Table	Table name
		Values to include in record	Enter the valid ServiceNow key and the corresponding value in the entry list. For more information on available keys, please refer to the Table API documentation.
		Output sys_id to String	Returns the sys_id of the newly created record in a string variable
Modify Record	Modify record attributes (PUT method)	Session name	Name of session
		Table	Table name
		Sys_id	Sys_id of the record to modify



		Values to include in record Output sys_id to String	Enter the valid ServiceNow key and the corresponding value in the entry list. For more information on available keys, please refer to the Table API documentation. Returns the sys_id of the newly
			created record in a string variable
Update Record	Updates a record (PATCH method)	Session name	Name of session
		Table	Table name
		Sys_id	Sys_id of the record to modify
		Values to include in record	Enter the valid ServiceNow key and the corresponding value in the entry list. For more information on available keys, please refer to the Table API documentation.
		Output sys_id to String	Returns the sys_id of the newly created record in a string variable
Delete Record	Delete a record	Session name	Name of session
		Table	Table name
		Sys_id	Sys_id
End Session	End session	Session name	Name of session



Example of configuring the Get Multiple Records Action:

The example below shows how to set up the action to retrieve up to 15 records from the incident table. Additionally, the output list of dictionaries will have the following keys available: 'number', 'description', 'sys_id', and 'Open Since'. Each of those values is addressed in the ServiceNow response through the JSON dictionary keys of "number", "short_description", "sys_id" and "opened_at", respectively (see example ServiceNow response below, Figure 2).

<u>Figure 1 – Action Configuration for Get Multiple Records</u>






Figure 2 – ServiceNow Response Keys

```
{
    "parent": "",
    "made_sla": "true",
    tch_list": "",
           "watch_list": "",
"upon_reject": "cancel",
"sys_updated_on": "2016-01-19 04:52:04",
          "approval history": "",
"number": "PRB0000050",
"sys_updated_by": "glide.maint",
           "opened_by": {
    "link": "https://instance.servicenow.com/api/now/table/sys_user/glide.maint",
          },
"user_input": "",
"sys_created_on": "2016-01-19 04:51:19",
           "sys_domain": {
    "link": "https://instance.servicenow.com/api/now/table/sys_user_group/global",
    "value": "global"
         },

"state": "4",

"sys_created_by": "glide.maint",
"knowledge": "false",
"order": "",
"closed_att: "2016-01-19 04:52:04",
"cndb.ci".
              "link":
"https://instance.servicenow.com/api/now/table/cmdb_ci/55b35562c0a8010e01cff22378e0aea9",
"value": "55b35562c0a8010e01cff22378e0aea9"
          },
"delivery_plan": "",
"impact": "3",
"active": "false",
           "work_notes_list": "",
"business_service": "",
           "priority": "4",
           "sys_domain_path": "/",
           "time_worked": "",
"expected_start": "",
         "rejection_goto": "",
"opened_at": "2016-01-19 04:49:47",
"business_duration": "1970-01-01 00:00:00",
          "group_list": "",
"work_end": "",
"approval_set": "",
"wf_activity": "",
"work notes": "",
          "short_description": "Switch occasionally drops connections",
"correlation_display": "",
           "delivery_task": "",
"work_start": "",
           "assignment_group": "",
           "additional_assignee_list": "",
          "description": "Switch occasionally drops connections", "calendar_duration": "1970-01-01 00:02:17",
         calendar_ouration: 1970-01-01 00:02:17 ,
    "close_notes": "updated firmware",
    "sys_class_name": "problem",
    "closed_by": "",
    "follow up": ""
    "sys_id": "04ce72c9c080016600b5b7f75ac67b5b",
    "controt tups": "bboos"
            "contact_type": "phone",
           "urgency": "3",
"company": "",
          company: ",
"reassignment_count": "",
"activity_due": "",
"assigned_to": "",
"comments": "",
"approval": "not requested",
"ala_due": ""
           "comments_and_work_notes": "",
           "due_date": "",
"sys_mod_count": "1",
          "sys_tags": "",
"escalation": "0",
"upon_approval": "proceed",
"correlation_id": "",
           "location":
```



4. Support & FAQs

4.1 Support

Free bots are not officially supported. You can get access to Community Support through the following channels:

- You can get access to Community Support, connecting with other Automation Anywhere
 customers and developers on <u>APeople</u> the <u>Bot Building Forum</u>, the <u>Bot Store Support</u>
 <u>Forum</u>, or the <u>Developers Everywhere Group</u>.
- Automation Anywhere also provides a <u>Product Documentation portal</u> which can be accessed for
 - more information about our products and guidance on Enterprise A360.

4.2 FAQs

For questions relating to Enterprise A360: See the Enterprise A360FAQs.



Appendix A: Record of Changes

No.	Version Number	Date of Change	Author	Notes
1	1.0.0	09/20/2021	J Dickson	Initial Release



Appendix B: References

No.	Торіс	Reference Link
1	Overview of Enterprise A360	Click <u>here</u>
2	Guidance: Building basic A360 bots	Click <u>here</u>
3	Guidance: Building A360 action packages	Click <u>here</u>
4	APeople Community Forum	Click <u>here</u>
5	Automation Anywhere University	Click <u>here</u>