McMASTER-CARR

Push-to-Connect Tube Fittings for Air and Water

- Maximum Pressure: 145 psi @ 72°F
- Temperature Range: 32° to 104° F
- Tubing: Use with firm and hard (Shore A88-A90) polyurethane and hard nylon

Because these fittings won't absorb moisture, they're a good fit for both air and water applications. Vacuum rating is 29.53" Hg @ 72° F.

Threaded Connections: NPT, BSPT, UNF Straight, or metric straight threads.

For technical drawings and 3-D models, click on a part number.

Straight Adapters, Tube-to-Male Threaded Pipe



Inch sizes have an orange release ring. NPT and BSPT threads have a PTFE thread sealant. UNF and metric threads have an O-ring.

For Tube	Pipe				
OD	Size	Choose	e a Material		Each
Inch Tube	with UN	NF Straig	ght Threads		
1/8"	10-32	Brass,	Nickel-Plated Brass	7880T111	\$1.66
Inch Tube	with NF	T Threa	ads		
1/8"	1/16	Brass,	Nickel-Plated Brass	7880T112	1.65
1/8"	1/8	Brass,	Nickel-Plated Brass	7880T113	2.07
1/8"	1/4	Brass	Nickel-Plated Brass	7880T114	2.79

Straight Adapters with Hex Socket, Tube-to-Male Threaded Pipe



Fittings have an internal socket, so you can tighten the threads with a hex key. Inch sizes have an orange release ring.UNF and metric threads have an O-ring.

For Tube	Pipe				
OD	Size	Choose a Material		Each	
Inch Tube with UNF Straight Threads					
1/8"	10-32	Brass, Nickel-Plated Brass	7880T137	\$3.22	

Straight Adapters, Tube-to-Female Threaded Pipe



Inch sizes have an orange release ring.

For Tube	Pipe				
OD	Size	Choose	a Material		Each
Inch Tube	with UN	IF Straig	ht Threads		
1/8"	10-32	Brass, I	Nickel-Plated Brass	7880T158	\$4.74
Inch Tube 1/8" 1/8"	with NP 1/8 1/4	Brass, I	ds Nickel-Plated Brass Nickel-Plated Brass	7880T159 7880T161	4.22 5.57

Through-Wall Straight Adapters, Tube-to-Female Threaded Pipe



Also known as bulkhead couplings. Inch sizes have an orange release ring.

For Tube	Pipe			
OD	Size	Choose a Material		Each
Inch Tube with NPT Threads				
1/8"	1/4	Brass, Nickel-Plated Brass	7880T341	\$8.36

Straight Connectors, Tube-to-Tube



Fittings have a light gray polybutylene body. Inch sizes have orange release rings.

For Tube		
OD		Each
Inch		
1/8"	5111K462	\$2.88

Through-Wall Straight Connectors, Tube-to-Tube



Also known as bulkhead couplings. Inch sizes have orange release rings.

For Tube			
OD	Choose a Material		Each
Inch			
1/8"	Brass, Nickel-Plated Brass	5111K731	\$6.38

Swivel 90° Elbow Adapters, Tube-to-Male Threaded Pipe



Fittings have a light gray polybutylene body. Inch sizes have an orange release ring. NPT and BSPT threads have a PTFE thread sealant. UNF and metric threads have an O-ring.

For Tube	Pipe				
OD	Size	Choose	e a Thread Material		Each
Inch Tube	with UN	NF Straig	ght Threads		
1/8"	10-32	Brass,	Nickel-Plated Brass	7880T178	\$1.72
Inch Tube	with NF	T Threa	nds		
1/8"	1/16	Brass,	Nickel-Plated Brass	7880T179	2.77
1/8"	1/8	Brass,	Nickel-Plated Brass	7880T181	2.61
1/8"	1/4	Brass,	Nickel-Plated Brass	7880T182	3.37

Long 90° Elbow Adapters, Tube-to-Male Threaded Pipe



Fittings have a light gray polybutylene body, and threads have a PTFE thread sealant. Inch sizes have an orange release ring.

For Tub	oe Pipe			
OD	Size	Choose a Thread Material		Each
Inch Tu	be with N	IPT Threads		
1/8"	1/16	Brass, Nickel-Plated Brass	7880T206	\$4.68
1/8"	1/8	Brass, Nickel-Plated Brass	7880T207	5.61
1/8"	1/4	Brass, Nickel-Plated Brass	7880T208	5.23

90° Elbow Adapters, Tube-to-Female Threaded Pipe



Fittings have a light gray polybutylene body. Inch sizes have an orange release ring.

For Tube OD		Choose a Thread Material		Each
				Eacii
Inch Tube	with N	NPT Threads		
1/8"	1/8	Brass, Nickel-Plated Brass	7880T229	\$5.23
1/8"	1/4	Brass Nickel-Plated Brass	7880T231	5 67

45° Elbow Adapters, Tube-to-Male Threaded Pipe



Fittings have a light gray polybutylene body, and threads have a PTFE thread sealant. Inch sizes have an orange release ring. Metric sizes have a gray release ring. Block 40>

For Tube	Pipe			
OD	Size	Choose a Thread Material		Each
Inch Tube	with N	IPT Threads		
1/8"	1/8	Brass, Nickel-Plated Brass	7880T243	\$4.94

90° Elbow Adapters, Tube Stem-to-Tube



Tube stems insert into the end of your tube fitting. Fittings have a light gray polybutylene body. Inch sizes have an orange release ring.

Stem	For Tube		
OD	OD		Each
Inch			
1/8"	1/8"	5111K656	\$2.77

90° Elbow Connectors, Tube-to-Tube



Fittings have a light gray polybutylene body. Inch sizes have orange release rings.

For Tube

Each



Swivel Inline Tee Adapters, Tube-to-Male Threaded Pipe



Also known as branch tees, these fittings have a light gray polybutylene body. Inch sizes have orange release rings. NPT and BSPT threads have a PTFE thread sealant. UNF and metric threads have an O-ring.

For Tube OD	Pipe Size	Choose a Thread Materi	al	Each
Inch Tube	with UN	Straight Threads		
1/8"	10-32	Brass, Nickel-Plated Bra	ass 7880T261	\$7.67
Inch Tube	with NF	Threads		
1/8"	1/16	Brass, Nickel-Plated Bra	ass 7880T262	4.37
1/8"	1/8	Brass, Nickel-Plated Bra		3.75
1/8"	1/4	Brass, Nickel-Plated Bra	ass 7880T264	5.00

Swivel Right Angle Tee Adapters, Tube-to-Male Threaded Pipe



Also known as run tees, these fittings have a light gray polybutylene body. Inch sizes have orange release rings. NPT and BSPT threads have a PTFE thread sealant. UNF and metric threads have an O-ring.

For Tube OD	Pipe Size	Choose a Thread Material	Each
Inch Tube	with UN	IF Straight Threads	
1/8"	10-32	Brass, Nickel-Plated Brass 7880T28	7 \$3.89
Inch Tube	with NF	PT Threads	
1/8"	1/16	Brass, Nickel-Plated Brass 7880T28	8 3.97
1/8"	1/8	Brass, Nickel-Plated Brass 7880T28	9 4.58
1/8"	1/4	Brass, Nickel-Plated Brass 7880T29	1 4.91

Tee Connectors, Tube-to-Tube



Fittings have a light gray polybutylene body. Inch sizes have orange release rings.

For Tube		
OD		Each
Inch		
1/8"	5111K522	\$3.75

Swivel Wye Adapters, Tube-to-Male Threaded Pipe



Fittings have a light gray polybutylene body. Inch sizes have orange release rings. NPT and BSPT threads have a PTFE thread sealant. UNF and metric threads have an O-ring.

For Tube OD	Pipe Size	Choose	e a Thread Material		Each
Inch Tube	with UN	IF Straig	ght Threads		
1/8"	10-32	Brass,	Nickel-Plated Brass	7880T314	\$7.06
Inch Tube 1/8" 1/8" 1/8"	with NP 1/16 1/8 1/4	Brass, Brass,	Nickel-Plated Brass Nickel-Plated Brass Nickel-Plated Brass	7880T315 7880T316 7880T317	7.48 7.31 7.57

Wye Connectors, Tube-to-Tube



Fittings have a light gray polybutylene body. Inch sizes have orange release rings.

For Tube		
OD		Each
Inch		
1/8"	5111K542	\$5.20

Swivel Manifold Adapters, Male Threaded Pipe-to-Tube

 $Fittings \ have \ a \ light \ gray \ polybutylene \ body. \ The \ threads \ have \ a \ PTFE \ thread \ sealant. \ Inch \ sizes \ have \ orange \ release \ rings.$









For Tube OD (Outlet	Pipe Size (Inlet)	Choose a Thread Material		Each		Each		Each		Each
Inch Tube	with NPT Th	reads								
1/8"	1/8	Brass, Nickel-Plated Brass	5203K918	\$8.38	5203K929	\$12.66	5203K941	\$12.53	5203K952	\$17.58

Universal Thread Push-to-Connect Tube Fittings for Air and Water

- Maximum Pressure: 145 psi @ 72°F
- Temperature Range: 32° to 104°F
- Tubing:

Standard Fittings: Use with firm and hard (Shore A88-A97) polyurethane and hard

nylon

Antistatic Fittings: Use with firm (Shore A88-A90) antistatic polyurethane

A unique male thread allows these fittings to mate with NPT, NPTF (Dryseal), and British Standard (BSPT and BSPP) threads. Vacuum rating is 29.53" Hg @ 72° F.

For technical drawings and 3-D models, click on a part number.

Straight Adapters, Tube-to-Male Threaded Pipe



Fittings have a brass body. Inch sizes have an orange release ring. Threads are brass and come with an O-ring.

For Tube	Pipe		
OD	Size		Each
Inch			
1/8"	1/8	51235K101	\$2.44
1/8"	1/4	51235K102	3.19

Swivel 90° Elbow Adapters, Tube-to-Male Threaded Pipe



Fittings have a gray polybutylene body. Inch sizes have an orange release ring. Threads are brass and come with an O-ring.

For Tube	Pipe		
OD	Size		Each
Inch			
1/8"	1/8	51235K121	\$2.89
1/8"	1/4	51235K122	3.73

Swivel Inline Tee Adapters, Tube-to-Male Threaded Pipe



Also known as branch tees, these fittings have a gray polybutylene body. Inch sizes have orange release rings. Threads are brass and come with an O-ring.

For Tube	Pipe		
OD	Size		Each
Inch			
1/8"	1/8	51235K141	\$4.18
1/8"	1/4	51235K142	5.52

Swivel Right Angle Tee Adapters, Tube-to-Male Threaded Pipe



Also known as run tees, these fittings have a gray polybutylene body. Inch sizes have orange release rings. Threads are brass and come with an O-ring.

For Tube	Pipe		
OD	Size		Each
Inch			
1/8"	1/8	51235K161	\$5.08
1/8"	1/4	51235K162	5.43

Swivel Wye Adapters, Tube-to-Male Threaded Pipe



Fittings have a gray polybutylene body. Inch sizes have orange release rings. Threads are brass and come with an O-ring.

Pipe		
Size		Each
1/8	51235K181	\$8.31
1/4	51235K182	8.37
	Size	Size 1/8 51235K181