

AIRSTREET · DESIGN DECISIONS REGISTER

AirStreet design decisions register

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	AST-DEC-001	Version	0.3
Status	Draft	Date	2026-10-02
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/airstreet		
Source	docs/06-design-decisions.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-10-02	Amish Chadha	Amish approved the recommendations for open decisions 1 to 8 (2026-10-02); moved to decisions made (AST-DDR-003 accepted)
0.2	2026-10-01	Amish Chadha	Budget treated as a value-engineering target
0.1	2026-09-30	Amish Chadha	Register opened with the open decisions from REVIEW.md, the decision records and the build plan work

AirStreet design decisions register

Every design decision still to be made, and every decision made, in one place. Each decision is argued in full in its decision record under `docs/decisions/`; this register is the index Amish works from. The build plan (`docs/05-build-plan.md`) describes the design as it stands and does not list open decisions.

■ Open decisions

None. All open decisions were decided on 2026-10-02.

■ To confirm when parts are bought

#	What to confirm	Why it matters	Source
1	The band roll and housings close round both an 80 mm and a 200 mm pole with the saddle, and the band maker's torque for about 1,000 N of preload	The slip and twist checks assume 1,000 N per band	AST-CAL-001 [F7], [G2]
2	The NO2 front end board's size and mounting holes (model: 86 x 55 mm, holes 76 x 43 mm apart) and how the B4 sensor connects to it	They set the back wall bosses and the lead length to the sensor	AST-DDR-003, P8
3	The particle sensor's interface select pin and logic levels on its datasheet	Sets the terminal block wiring	Build plan section 3.10
4	Heat-set insert sizes (M5 and M3) and the hole size their maker gives	The printed holes are drawn 6.8 and 4.0 mm	AST-DWG-102, 106, 109
5	The M8 4-pin socket's panel hole and the M16 glands' hole size	The pod's printed holes are 8.2 and 16.2 mm	AST-DWG-106
6	FieldNode's enclosure lug kit positions match FieldNode's back plate pattern	The adapter plates copy that pattern	FND-DDR-003
7	The FieldNode panel's frame has a flat back lip at least 12 mm wide	FieldNode's panel clips bolt through it	FND-DDR-003

■ Value engineering

Value-engineering target: USD 285 (a hypothetical control target, not a limit). Estimated cost of the constructable design: USD 303 for the sensor head (USD 18 over the target); USD 434 with the FieldNode core, which is costed in FieldNode. Main cost drivers and savings worth trying:

- The rise from USD 285 came from making the design constructable (AST-DDR-003): line 3, band stock, adapter plates and cross arm (USD 4); line 8, spacers (USD 1); line 9, probe tube (USD 1); line 10, probe lead with its M8 plug (USD 4); and line 11, inserts, glands, probe socket, terminal block and fixings (USD 8).
- Savings worth trying: the open two-channel NO2 front end (about USD 35 cheaper, PCB work that is on hold with TRL 4) would recover the USD 18, and cheaper band hardware and fixings can be sought at purchase.

■ Decisions made

Date	Decision	Decided by	Record
2026-09-25	TRL 2 review items D1 to D9: budget covers the sensor head only; pitch wording; NO2 collocation plan; NO2-B43F class sensor; ISB class front end bought first; SPS30 class particle sensor; 3.0 m inlets; 5 min records with raw signals; open data	Amish: "i accept all your recommendations, go with them across all repos."	AST-DDR-001, AST-DDR-002
2026-09-25	budget_usd \$285 for the sensor head; FieldNode back plate left off with the enclosure and bracket on the AirStreet rail; frontal area limit 0.15 m²; R3 (WHO guideline) withdrawn and kept as research; 60 s particle run; 5 min records on a private gateway and 15 min on The Things Network; FieldNode sun shield at sites above 45 °C; pre-allocated pod exchange for service	Amish, same instruction: go with recommendation	AST-DDR-002, N1 to N7
2026-10-02	Design for construction accepted as a whole: the changes P1 to P10 (adapter plates, 140° V-saddles, bands in saddle grooves, cross arm, two-part pod, cable entries, shield spacers and probe tube) and their knock-on changes, as made	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-003, Table 1
2026-10-02	Mass (R13): option (c). The R13 limit is set at 4.0 kg including FieldNode's sun shield, the pole owner is asked to confirm that load, and the four lightening steps (saddles at 40 % infill, 40 x 4 mm rail, 1.5 mm shield plates, windows in the adapter plates) are carried into the TRL 4 build to give margin	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-003, A1
2026-10-02	Antenna whip: accept the 15 mm clearance to the pod's drip lid and check signal strength with the pod fitted at TRL 4; move the pod 8 mm left only if that check shows a loss	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-003, A3
2026-10-02	First partner chosen by one rule: a city or air agency that runs a regulatory NO2 reference station at a street-level site AirStreet can mount beside, and that will share its data. First candidate to approach: the Texas Commission on Environmental Quality's Dallas-Fort Worth monitoring network, with a local university or city partner	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-001, O1
2026-10-02	Agree with FieldNode: send FieldNode the request to mount its enclosure, plate clips and sun shield on AirStreet's two adapter plates, and to keep its model stable since AirStreet carries a copy	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-002 N2, AST-DDR-003
2026-10-02	Port B's always-on 5 V supply and the 5 min interval on a private gateway: closed as already decided on 2026-09-25 (AST-DDR-002, N5 and its cross-repo actions); FieldNode's confirmation is tracked as a cross-repo action, not a decision	Amish: "i approve your recommendations for all 555 open decisions."	AST-DDR-002
2026-10-02	FieldNode port pin assignment: propose to FieldNode one common assignment for both M12 ports (supply, ground, I2C data, I2C clock and one spare line), with each port's supply voltage set per project by its supply module (5 V on both ports for AirStreet)	Amish: "i approve your recommendations for all 555 open decisions."	FND-DDR-001, O2
2026-10-02	Radio band set with the partner of the first-partner decision above (not with the adapter plates, as the register said): US915 for a North American partner, EU868 for a European one, with the matching FieldNode antenna	Amish: "i approve your recommendations for all 555 open decisions."	FND-DDR-001, O1