

REV	DESCRIPTION	DATE	BY
P1	Making sketch, 63 % open sheet	2026-10-03	AC
P2	80 % open sheet (decision 41B)	2026-10-03	AC




TOP VIEW

Scale 1:20; looking down (along -Z)



FRONT VIEW

Scale 1:20; looking at the front (along +Y)



RIGHT VIEW

Scale 1:20; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

- Cut a 790 dia disc from perforated sheet (22 mm square holes on a 24.5 mm square pitch, 80 % open); file the rim smooth
- Drill four 9 dia holes at 45, 135, 225 and 315 deg on a 764 circle
- to match the tabs; fit them where the solid edge allows
- Bolt to the tabs with M8 bolts, nuts and washers
- The baffle comes out for the comparison runs without it
- Check: 5 mm gap to the wall all round

AltiRig baffle plate

DRAWING NO. ALR-DWG-115		REV P2	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-10-03	DRAWN Amish Chadha
MATERIAL / NOTES Perforated steel 2 thick, 80 % open				
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com			Generated from cad/src; do not edit by hand	