BANKHAUL · REGULATORY REGISTER

BankHaul regulatory and standards register

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	BKH-REG-001	Version	0.1
Status	Draft	Date	2026-10-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/bankhaul		
Source	docs/07-regulatory.md @ 2177c86		

REVISION HISTORY

Version	Date	Author	Change
0.1	2026-10-25	Amish Chadha	First register, complete for stages P0 and P1 and the TRL 3 design (kit 1.8 upgrade)

BankHaul regulatory and standards register

No product certification is known to apply to a hand-worked rope station, but every installation needs the fisheries authority's agreement that loop-set gillnets are allowed there (G1), the wildlife authority's agreement on siting and safety (G2) and possibly a permit for works on the shore and a line across the water (G3, G4). The steel, rigging and rope standards below are the reference for quality when parts are bought. Not legal advice; anything marked "to assess" needs a qualified reviewer, and the jurisdiction depends on the co-design partner (first candidate on Lake Kariba, Zimbabwe; BKH-DDR-001, item 10). Method: STANDARDS section 23.

Table 1. Regulatory and standards register.

#	Standard or regulation	Jurisdiction	What it covers	Applicability to this design	Owner (role)	Status
G1	National fisheries law and licence conditions	Country of deployment (for Lake Kariba: Zimbabwe and Zambia)	Fishing licences, gear, mesh size, net length, set-net rules, closed areas and seasons	Whether a gillnet set and hauled on a fixed loop is allowed, and where	Co-design partner	To assess
G2	Wildlife authority rules and guidance on human-crocodile conflict	Country of deployment (for example Zimbabwe Parks and Wildlife Management Authority)	Crocodile management, safety advice, permission for structures at the water's edge	Siting of each station, the working distance and the safety briefing (PR-016)	Co-design partner	To assess
G3	Permits for works on a shore, bank or riverbed	Country of deployment (environment or water authority)	Driving a stake into a bed; structures on public shores	The far stake and the bank station	Co-design partner	To assess
G4	Rules on obstructions in navigable water	Country of deployment	A floating line across water used by boats	The loop and the far stake: marking with floats or a flag	Co-design partner	To assess
G5	EN 1993-1-8, Eurocode 3, design of joints (Table 3.9, pin connections)	European Union; reference elsewhere	Geometry and resistance of pin-connected plates	The pad eye, stay lugs and collar lug (PR-015, D-S1)	Design lead	Applies as the design reference (met on paper)
G6	EN 10219, cold-formed welded hollow sections of structural steel	European Union; reference elsewhere	Dimensions and grades of the 76.1 and 48.3 mm tubes	The far stake (S355) and the post	Design lead	Applies when bought (ask for a mill certificate, BKH-DEC-001 item 11)
G7	EN 13889, forged steel shackles for general lifting purposes, dee and bow shackles, grade 6	European Union; reference elsewhere	Rated shackles and their marking	The six 10 mm bow shackles	Design lead	To assess (buy rated and marked shackles, BKH-DEC-001 item 6)
G8	DIN 1480, forged turnbuckles (open pattern)	Germany; reference elsewhere	Dimensions of turnbuckles	The two M12 stay turnbuckles	Design lead	To assess
G9	ISO 1141 (polyester ropes) and ISO 1346 (polypropylene ropes), with ISO 2307 (test methods for fibre ropes)	International	Rope construction, minimum breaking force, test method	The polyester stays and the polysteel loop	Design lead	To assess (minimum breaking strength from the supplier, BKH-DEC-001 item 5)

#	Standard or regulation	Jurisdiction	What it covers	Applicability to this design	Owner (role)	Status
G10	ISO 1461, hot dip galvanized coatings on fabricated iron and steel articles	International	Coating mass and thickness	Screw anchors, shackles, turnbuckles, rings	Design lead	To assess
G11	ISO 11228-1 and ISO 11228-2, manual handling (lifting and carrying; pushing and pulling)	International	Reference masses and forces for manual work	The 33 kg stake lifted by two people (PR-014) and the 200 N haul (PR-003)	Design lead	To assess with the partner's users
G12	Occupational safety for work from boats and near water	Country of deployment	Life jackets, working alone, drowning	Driving the far stake and reeving the loop from a boat (BKH-BLD-001 safety stops)	Co-design partner	To assess
G13	Machinery rules (for example EU Directive 2006/42/EC)	European Union	Machines with a drive system	No drive system and no lifting: the station is hand-worked rope and rigging	Design lead	Does not apply, to confirm if a kit is ever sold in the EU

Status: to assess, applies, does not apply, met by design, certification needed later.

Sources

- Northern Territory Government. "Stay Safe While Fishing and Boating." Be Crocwise. https://becrocwise.nt.gov.au/crocodiles-and-me/stay-safe-while-fishing-and-boating (checked 2026-10-25), as an example of wildlife authority advice (G2).
- Standards G5 to G11 and G13 are cited by number and title only; their texts were not consulted for this register, and each applicability is to be confirmed by the role named.