

BINLEVEL · DESIGN DECISION RECORD

BinLevel TRL 2 review decisions

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	BNL-DDR-001	Version	0.2
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/binlevel		
Source	docs/decisions/0001-trl2-review-decisions.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.1	2026-09-25	Amish Chadha	Record the TRL 2 review recommendations adopted for TRL 3 work and the items that remain open

0001: TRL 2 review decisions

- **Date:** 2026-09-25
- **Status:** accepted. Items D1 to D10 were decided by Amish on 2026-09-25 ("i accept all your recommendations, go with them across all repos"): go with recommendation. Items O1 and O2 carry no recommendation and remain "Proposed, awaiting Amish". See BNL-DDR-002 for the follow-on decisions.

■ Context

The TRL 2 review note (docs/REVIEW.md , session 2026-09-25, /populate) listed nine items as "Proposed, awaiting Amish", and the design precis BNL-PRC-001 v0.2 listed six key design choices, each with a rationale. On 2026-09-25 Amish asked for this batch of repos to be taken through the usual process with the instruction "you know the drill, nothing gets past TRL 3". He has not reviewed this repo's items one by one. Every item that carried a recommendation is therefore adopted as recommended for TRL 3 work, open for his review. Items without a recommendation stay open, and no choice is made for them.

■ Options considered

The options for each item are those listed in docs/REVIEW.md (session 2026-09-25, /populate) and in BNL-PRC-001 v0.2, Key design choices.

■ Decision

Table 1. Items decided by Amish.

#	Item	Recommendation adopted	Status
D1	First target container	(a) 660 to 1,100 L four-wheel communal containers (EN 840 class); street litter bins follow with the same electronics and a smaller bracket	Decided by Amish, 2026-09-25: go with recommendation
D2	Sensing method	(a) Ultrasonic plus near-range ToF, because the 80 % threshold lies inside the ultrasonic blind zone	Decided by Amish, 2026-09-25: go with recommendation
D3	Cell size	(a) C-size Li-SOCl ₂ for margin in cold climates and a 10-year service interval; AA revisited for litter bins	Decided by Amish, 2026-09-25: go with recommendation
D4	Radio	(a) LoRaWAN on an STM32WL-class module shared with FieldNode	Decided by Amish, 2026-09-25: go with recommendation
D5	Relationship to FieldNode and TwinKit	Reuse FieldNode's radio module family, payload conventions and decoder, not its enclosure, panel or cell; TwinKit as the reference gateway and data layer	Decided by Amish, 2026-09-25: go with recommendation
D6	Default fill threshold and reporting interval	80 % and 1 h (2 h at SF11 to SF12)	Decided by Amish, 2026-09-25: go with recommendation
D7	Temperature alert	70 °C or a rise of 15 K in 15 min, as a maintenance aid only	Decided by Amish, 2026-09-25: go with recommendation
D8	Mounting (precis choice 2)	Under the lid, with four tamper-resistant through-bolts	Decided by Amish, 2026-09-25: go with recommendation
D9	Enclosure (precis choice 5)	Stock IP67 enclosure at TRL 2 to 3; potted or IP69K design later	Decided by Amish, 2026-09-25: go with recommendation
D10	Budget, pitch and problem	No change was recommended: <code>budget_usd</code> stays \$60 and the pitch and problem lines stay as written	Decided by Amish, 2026-09-25: go with recommendation

Table 2. Items that remain open.

#	Item	Options	Status
O1	Steel containers	(a) External lid antenna as an optional variant (about \$8, which takes the parts cost to \$63, over the \$60 budget); (b) exclude steel containers from the first pilot. No recommendation was made.	Proposed, awaiting Amish
O2	First partner and region for co-design and a pilot	No preference stated and no recommendation made. The region also sets the radio plan (EU868, US915 or IN865).	Proposed, awaiting Amish

■ Consequences

- BNL-PRB-001, BNL-PRC-001 and BNL-REQ-001 move to version 0.3. The target container, sensing method, cell, radio, thresholds and mounting are no longer described as proposed; they are the design basis for TRL 3, decided by Amish on 2026-09-25.
- No requirement target was relaxed or redefined by these decisions. R3 and R9 now carry the adopted defaults (D6, D7) as the design values.
- The sizing note BNL-CAL-001 checks the design against every requirement. It adds four findings that need Amish's review (see `docs/REVIEW.md`, session 2026-09-25, TRL 3): the unit is about 435 g against the 400 g limit of R16; hot dark lids reach about 67 °C, above the 60 °C of R6; the 15 K rate-of-rise trigger in D7 is at risk of false alarms on sunny days; and the payload is cut from 12 to 11 bytes so that it fits the US915 slowest data rate.
- The recommended budget is unchanged, so no budget figure awaits Amish.
- Update, 2026-09-25: Amish accepted all recommendations. D1 to D10 are decided; the four findings above were resolved by BNL-DDR-002 (aluminium bracket, R6 to 70 °C, gated rate-of-rise rule, 11-byte payload and 5 min reads confirmed).