


REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-03	AC



TOP VIEW

Scale 1:10; looking down (along -Z)



FRONT VIEW

Scale 1:10; looking at the front (along +Y)



RIGHT VIEW

Scale 1:10; looking at the right side (along -X)

WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Cut three lengths of 1800 from foam-filled fibreglass tube 44.5 x 3.2

Fine-tooth saw with the tube wrapped in tape; wear a dust mask outdoors

Seal every cut end with a thin coat of epoxy so water cannot get into the foam

Middle and top sections: drill one 10.5 hole across the tube, 74 from the bottom end (75 above the joint line), square to the tube, through both walls

Butt section: no pin hole; its sleeve is bonded at its top end

Middle section: sleeve bonded at its top end; pin hole at its bottom end

Top section: pin hole at its bottom end; friction ring at its top end

Coat each pin hole bore with epoxy as well

Check: each section 1800 within 2; holes square to the tube by eye

BREAKHOOK

github.com/BoujeeEnjinia1701/breakhook

Pole section (make 3): making sketch

DRAWING NO. BHK-DWG-103			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:10	UNITS mm	PROJECTION 	DATE 2026-10-03		DRAWN Amish Chadha
MATERIAL / NOTES Foam-filled fibreglass tube 44.5 x 3.2, electrical grade					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com					Generated from cad/src; do not edit by hand