

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-09-30	AC
P2	Wall foot at 400 mm, longer struts (BBX-DEC-001)	2026-10-02	AC




WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Tube 20 x 1.5, cut 621 long.
Flatten 40 of each end in a vice between two flat bars, both flats in the same plane; anneal with a gas torch first if it cracks.
Trim each flat to 26 wide and round its end to a 13 radius about the end hole.
End holes 6.6, 595.3 apart; a second 6.6 hole 20 in from each end hole, on the centre line. Two holes at each end make the joints rigid, so the bracket cannot fold.
The strut rises at 55 degrees from the wall foot to the rail.
Drill the second pair with the strut clamped to both cleats, so all four holes line up.
Fit: M6 bolts, heads on the strut side, nyloc nuts on the cleats.
Check: end holes within 0.5 of the length; flats not twisted.



TOP VIEW

Scale 1:5; looking down (along -Z)



FRONT VIEW

Scale 1:5; looking at the front (along +Y)



RIGHT VIEW

Scale 1:5; looking at the right side (along -X)

BREATHEBOX

github.com/BoujeeEnjinia1701/breathebox

BreatheBox strut (make 2): making sketch

DRAWING NO. BBX-DWG-112			REV P2	SHEET 1 of 1	SIZE ANSI B
SCALE 1:5	UNITS mm	PROJECTION 	DATE 2026-10-02		DRAWN Amish Chadha
MATERIAL / NOTES Aluminium round tube 20 x 1.5 mm, 6063 class					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com				Generated from cad/src; do not edit by hand	