

CAMPBREAK · CALCULATION NOTE

CampBreak sizing calculations

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	CBK-CAL-001	Version	0.1
Status	Draft	Date	2026-10-03
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/campbreak		
Source	docs/04-calcs/01-sizing.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.1	2026-10-03	Amish Chadha	First calculation note at TRL 3, on the constructable design (CBK-DDR-002)

CampBreak sizing calculations

On paper the kit meets nine of its eleven requirements. The hand pump gives about 20.4 L/min with two people pumping at a sustainable 47 W each, the 6 mm jet reaches about 6.9 m, the alarms are loud enough and fast enough, and two people pull the loaded cart up a 10 % slope with about 89 N each. Two requirements are not shown: R2 (no false alarm while cooking) cannot be calculated and needs a cooking trial at TRL 4, and R9 (water on target within 3 min for a shelter 100 m away) is **not met on paper**, at 3.8 min. With the siting rule decided in CBK-DDR-001 (D9), a shelter at most 70 m from a station gets water in about 2.8 min. The kit costs about USD 1,355 against a value-engineering target of USD 1,600.

Every figure comes from `docs/04-calcs/sizing.py`, which reads its geometry from `cad/src/model.py` and its prices from `bom/bom.csv`, and writes `docs/04-calcs/results.csv`. Inputs marked (est.) are estimates to be confirmed by measurement at TRL 4.

Safety: The pump and hose are a pressurised water system. A shut nozzle with two people pumping could reach several bar; the 4 bar relief valve (CBK-DDR-001, D7) caps it, and the hose is rated at 10 bar. The station battery is sealed lead-acid: it can deliver high short-circuit current and vents hydrogen if overcharged. The kit is for small, early fires only; people leave first, and water is never used on burning oil or live wiring.

■ A. Pump, hose and nozzle (R7, R8)

Assumptions

Table 1. Inputs for the water line.

Input	Value	Note
Pump displacement	0.40 L per double stroke	(est.) to confirm on the pump bought
Pumping rate	60 double strokes per minute	(est.) steady pace for two people
Volumetric efficiency	0.85	(est.) cast semi-rotary pump
Mechanical efficiency	0.50	(est.) lever, vanes and seals
Jet	6 mm, discharge coefficient 0.96	Nozzle orifice to confirm when bought
Delivery hose	19 mm bore, 30 m, roughness 0.01 mm	Plus 1.2 m of 19 mm connecting hose
Delivery fittings	Loss factor 4.0	(est.) swivel, tee and couplings
Suction	25 mm, 4 m, loss factor 5.0, lift 1.5 m	(est.) worst case from a low open container
Nozzle height	1 m above the pump	Slope or raised arm
Reach factor	0.50 of the drag-free range at 30°	(est.) to measure
Sustained effort	75 W per person for 10 min	(est.)

Method

Flow is displacement x rate x volumetric efficiency. Jet speed comes from the flow and the orifice; nozzle pressure is half the density times the jet speed squared. Hose friction uses the Darcy factor from the Swamee-Jain equation. The pump head is the sum of nozzle pressure, friction, fittings, lift to the nozzle and suction losses. Shaft power is hydraulic power over mechanical efficiency; the lever force follows from the work per double stroke over four 40° swings at a 610 mm grip radius.

Results

Table 2. Water line at two people pumping.

Quantity	Result
Flow at the nozzle	20.4 L/min (R7 target 20)
Jet speed	12.5 m/s
Pressure at the nozzle	78 kPa
Hose friction, 30 m	29.9 kPa at 1.2 m/s, Reynolds number about 22,800
Pump outlet pressure	122 kPa (1.2 bar), well under the 4 bar relief setting
Suction side	17 kPa below atmosphere; 8.4 m of net positive suction head available
Hydraulic power	47 W; shaft power 95 W, or 47 W per person
Force at the grip	56 N in total, about 28 N per person
Force to reach the relief setting against a shut nozzle	94 N in total, so two people can reach it
Jet reach	6.9 m (13.9 m drag-free); R8 target 6 m
One 200 L drum	about 9.8 min of pumping

Effort is well within the 75 W per person that can be kept up for 10 minutes, so R7 is met with margin on effort, though only with 2 % margin on flow. The flow depends directly on the pump's displacement, which must be confirmed on the pump bought (CBK-DEC-001, to confirm).

Figure 1 ([media/flow.png](#)) shows the pressure falling from the pump to the nozzle; all values are estimates.

■ B. Heat alarm (R1 to R5)

Table 3. Alarm inputs (est. unless stated).

Input	Value
Threshold	8 °C per minute over 60 s, plus 57 °C fixed (decided, CBK-DDR-001 D2)
Sample interval	10 s; 1 mA for 1 ms per sample
Sleep current	3 µA
Radio listen for station broadcast	every 4 s, 10 mA for 1.5 ms
Daily check-in	one 60 ms transmission at 40 mA
Cells	3 x AA alkaline, 2.4 Ah derated to 70 %, with a 30 min sounding reserve
Sounder	95 dB(A) at 1 m
Alert	100 ms transmission with three retries 1 s apart

Table 4. Alarm results.

Requirement	Result	Status
R1 rate of rise	8 °C per minute set in firmware; worst-case extra delay one 10 s sample	Met by design
R2 cooking	Not calculable on paper	To show at TRL 4
R3 sound at 3 m	$95 - 20 \log_{10}(3) = 85.5$ dB(A)	Met (est.), 0.5 dB margin
R4 relay time	3.1 s alarm to station (with retries) plus 4.1 s for the station broadcast to reach every alarm: 7.2 s worst case	Met (est.)
R5 battery life	Average 6.9 µA; 331 months on paper, so cell shelf life (about 5 years) is the limit	Met (est.)

R3 has little margin: a sounder of at least 95 dB(A) at 1 m is specified in the BOM, and a louder one is the first fix if the TRL 4 measurement falls short.

■ C. Cart mass and balance (R6)

Steel parts are weighed from the model volumes at 7,850 kg/m³; bought parts use catalogue estimates (pump 14 kg, wheels 5.5 kg each, reel drum 9 kg, wound hose 11.4 kg).

Table 5. Cart mass and balance.

Quantity	Result
Loaded cart mass, dry	91.4 kg (est.)
Centre of mass	On the centre line, 110 mm in front of the axle and 401 mm up
Load on the front feet when parked	126 N
Lift at the pull bar to raise the feet	73 N
Tipping sideways	at 42°
Overall size	850 wide x 1,744 long x 1,067 tall

■ D. Pulling effort and speed (R6)

Rolling resistance 0.10 on unpaved ground (est.), slope 10 %, two people. Pull force is the weight times the sine of the slope plus rolling resistance times the cosine: 178 N in all, 89 N each, below a sustainable 100 N per person (est.). At 1.0 m/s, 100 m takes 1.7 min. The cart is 850 mm wide against a 900 mm limit. R6 is met (est.).

■ E. Time to water on target (R9)

Table 6. Time from alarm to water on target.

Stage	100 m, standard	70 m, sited (D9)
Alarm to siren	7 s	7 s
Volunteers muster at the station	60 s (est.)	30 s (drilled)
Pull the cart out	15 s	15 s
Walk at 1.0 m/s	100 s	70 s
Set up suction and pay out hose	30 s	30 s
Prime the pump	15 s	15 s
Total	227 s (3.8 min)	167 s (2.8 min)

R9 is **not met on paper** for a shelter 100 m away (3.8 min against 3 min). The decided mitigation (CBK-DDR-001, D9) keeps the target and sites stations so that no shelter is more than 70 m from one, with a drilled 30 s muster; on those terms the time is 2.8 min. A brisk 1.5 m/s with a 30 s muster would reach 100 m in 2.7 min, but that is not assumed.

■ F. Station roof and posts

Wind 30 m/s (est., a strong monsoon gust), net uplift coefficient 1.2 on the 3.1 m² roof: about 1,990 N of uplift, 500 N per post. Each concrete collar (300 mm across, 600 mm deep) weighs about 975 N, so uplift is resisted with a factor of about 2. A horizontal load of 210 N gives a bending stress of about 10 MPa at the foot of each 60 x 60 x 3 mm post, far below the 235 MPa yield of S235. The four-post frame weighs about 86 kg of steel plus 14 kg of roof sheet.

■ G. Hose reel capacity

30 m of hose with a 28 mm outside diameter needs 18.5 L of space; the drum (200 mm core, 440 mm wound diameter, 210 mm wide, packing 0.785) offers 19.9 L, a ratio of 1.08. The hose fits with little room to spare, so it must be wound neatly (build plan, step 10).

■ H. Cost (R11)

Table 7. Cost of one block kit, from bom/bom.csv.

Part of the kit	USD
24 heat alarms	420
Station (alarm box, frame and roof, sign, drum)	317
Hose cart	618
Total	1,355

Value-engineering target: USD 1,600. Estimated cost of the constructable design: USD 1,355 (USD 245 under the target).

■ Results against every requirement

Table 8. Results (from results.csv).

ID	Requirement	Target	Result	Status
R1	Rate-of-rise threshold	8 °C/min	8 °C/min over 60 s, plus 57 °C fixed	Met by design
R2	No alarm in 1 h of cooking at 1 m	No alarm	Not calculable on paper	To show at TRL 4
R3	Sound at 3 m	At least 85 dB(A)	85.5 dB(A)	Met (est.)
R4	Relay to station and all alarms	10 s or less	7.2 s worst case	Met (est.)
R5	Battery life	12 months or more	Cell shelf life, about 5 years	Met (est.)
R6	Cart on a 10 % slope, 100 m	3 min or less, width 0.9 m or less	1.7 min; 89 N per person; 850 mm wide	Met (est.)
R7	Flow for 10 min	20 L/min or more	20.4 L/min; 47 W per person	Met (est.)
R8	Jet reach	6 m or more	6.9 m	Met (est.)
R9	Water on target 100 m away	3 min or less	3.8 min (2.8 min at 70 m with a 30 s muster)	Not met on paper
R10	Repairable locally	Hand tools, market parts	Every wear part is a market item	Met by design
R11	Cost	Value-engineering target USD 1,600	USD 1,355	USD 245 under the target