

CAMPBREAK · DESIGN DECISIONS REGISTER

CampBreak design decisions register

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	CBK-DEC-001	Version	0.1
Status	Draft	Date	2026-10-03
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/campbreak		
Source	docs/06-design-decisions.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.1	2026-10-03	Amish Chadha	Register opened at TRL 3; all decisions made under Amish's 2026-10-03 pre-approval

CampBreak design decisions register

Every design decision still to be made, and every decision made, in one place. Each decision is argued in full in its decision record under `docs/decisions/`; this register is the index Amish works from. The build plan (`docs/05-build-plan.md`) describes the design as it stands and does not list decisions.

■ Open decisions

None. All decisions were made under Amish's 2026-10-03 pre-approval.

■ To confirm when parts are bought

#	What to confirm	Why it matters	Source
1	The hand pump displaces at least 0.40 L per double stroke	R7 is met with only 2 % margin on flow; a smaller pump misses it	CBK-CAL-001, section A
2	The pump's flange hole pattern (150 mm square assumed), shaft height and handle socket	They set the stand plate holes and the lever hub bore	CBK-DDR-002, P5 and P6
3	The reel drum's bore suits a 25 mm spindle, and the swivel inlet's thread suits the 19 mm hose tail	Sets the spindle size or a sleeve	CBK-DDR-002, P7
4	The delivery hose's outside diameter is 28 mm or less	The 30 m hose fills the drum with only 8 % spare room	CBK-CAL-001, section G
5	The nozzle's jet orifice is 6 mm	Sets the flow, pressure and reach together	CBK-CAL-001, section A
6	The piezo sounder gives at least 95 dB(A) at 1 m	R3 is met with 0.5 dB margin	CBK-CAL-001, section B
7	The wheels have 20 mm bores and 75 mm hubs	Sets the axle, spacer and collar lengths	CBK-DDR-002, P2
8	The relief valve opens at 4 bar $\pm$ 0.5 bar	Pressure limit for the hose and fittings	CBK-DDR-001, D7

■ Value engineering

Value-engineering target: USD 1,600 (a hypothetical control target, not a limit). Estimated cost of the constructable design: USD 1,355 (USD 245 under the target). Main cost drivers and savings worth trying:

- The 24 heat alarms are the largest share (USD 420, USD 17.50 each). The board price is a prototype module estimate; a single board with the radio, controller and sounder driver, made in a batch, should fall to about USD 10 to 12 each at TRL 4.
- The station costs USD 317: steel frame and roof USD 157, alarm box with battery, siren and panel USD 105. Where a block already has a shaded structure, the station can be built against it and the frame dropped.
- The cart costs USD 618: pump USD 120, reel drum USD 95, hoses USD 83, wheels USD 69, frame USD 59. A reel welded from tube and sheet in the camp workshop could save about USD 50; a second-hand pump is worth trying if its displacement is checked.

■ Decisions made

Date	Decision	Decided by	Record
2026-10-03	Alarm relay: published star scheme on a sub-GHz band (alarm to station, one station broadcast to all alarms); no mesh; checked against Lumkani's patents before release	Amish, pre-approval: "I pre-approve the batch runs along with any recommendations you come up with."	CBK-DDR-001, D1
2026-10-03	Detection: rate of rise of 8 °C per minute over 60 s plus a 57 °C fixed back-up, thermistor below the box	Amish, same pre-approval	CBK-DDR-001, D2
2026-10-03	Alarm board specified by function and priced as a module; board design and firmware left to TRL 4	Amish, same pre-approval	CBK-DDR-001, D3
2026-10-03	Block kit of 24 alarms, one station and one cart	Amish, same pre-approval	CBK-DDR-001, D4
2026-10-03	Bought cast-iron semi-rotary pump, 25 mm ports, at least 0.40 L per double stroke	Amish, same pre-approval	CBK-DDR-001, D5
2026-10-03	No lithium cells: sealed lead-acid at the station, alkaline AA cells in the alarms (conservative; lithium iron phosphate only with evidence of safe charging at 45 °C and a recycling route)	Amish, same pre-approval	CBK-DDR-001, D6
2026-10-03	4 bar relief valve at the pump outlet, discharge down, hose rated 10 bar (conservative; raised only after a burst test of the bought hose and fittings)	Amish, same pre-approval	CBK-DDR-001, D7
2026-10-03	19 mm semi-rigid hose, 30 m on a reel, with a 6 mm jet and spray nozzle	Amish, same pre-approval	CBK-DDR-001, D8
2026-10-03	R9 kept at 3 min; stations sited within 70 m of every shelter with a drilled 30 s muster; R9 reported as not met on paper at 100 m	Amish, same pre-approval	CBK-DDR-001, D9
2026-10-03	First partner to approach: a camp management agency in the Cox's Bazar camps, Bangladesh, with the Bangladesh Fire Service and Civil Defence (first candidate, not agreed)	Amish, same pre-approval	CBK-DDR-001, D10
2026-10-03	Design for construction: welded tube frame, through axle in axle plates, legs and feet, handle, pump stand, lever extension, reel on uprights, connecting hose and relief tee, four-post station, fixings for the station fittings, hose tray and the alarm's plate and ties (P1 to P12)	Amish, same pre-approval	CBK-DDR-002
2026-10-03	<code>budget_usd</code> left at USD 1,600 as the value-engineering target; cost variations accepted	Amish: "I also accept any cost overruns or variations from the assumed scope cost."	CBK-DDR-001

■ Safety

Safety: CampBreak includes a pressurised hand-pumped water line (relief valve at 4 bar, hose rated 10 bar) and a sealed lead-acid station battery. The kit is for small, early fires only; people leave first, and water is never used on burning oil or live wiring. Safety stops are listed in the build plan, section 6. It is an open engineering reference, not certified equipment.