

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-02	AC



TOP VIEW
Scale 1:25; looking down (along -Z)



FRONT VIEW
Scale 1:25; looking at the front (along +Y)



RIGHT VIEW
Scale 1:25; looking at the right side (along -X)



WHERE IT GOES
This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

- Arm: two 1500 mm lengths of 50 x 50 x 5 angle, one each side of the post, upright faces on the post, flat faces on top, outward.
- A 17 mm hole 200 mm from the back end, 20 mm up: M16 bolt through both angles and the post. Holes 13 mm, 25 mm up, at 100, 900 and 1348 mm: back pulley, brace, tip pulley.
- Brace: two 990 mm lengths of 40 x 40 x 4 angle at 45 degrees, M12 to the arm, M16 through the post with a 5 mm packing plate.
- Pulleys: 100 mm steel sheaves on M12 axles with spacer tubes.
- Winch: brake winch rated 270 kg, two U-bolts round the post, 1 m up.
- Rope: 5 mm steel wire from the winch over both pulleys; hook with latch.
- Check: with no load the hook hangs 1.2 m out from the post.

CharCube lifting aid: arm, brace and pulleys (bolted)

DRAWING NO. CCB-DWG-116			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:25	UNITS mm	PROJECTION 	DATE 2026-10-02		DRAWN Amish Chadha
MATERIAL / NOTES Steel angle 50 x 50 x 5 and 40 x 40 x 4 mm; bolts					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com			Generated from cad/src; do not edit by hand		