

COLDPOD · CALCULATION

ColdPod sizing calculations

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	CPD-CAL-001	Version	0.3
Status	Draft	Date	2026-09-26
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/coldpod		
Source	docs/04-calcs/01-sizing.md @ b4afd8f		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-09-26	Amish Chadha	Budget top-up approved by Amish; budget \$310 in the script; R15 met (\$303 against \$310); counts updated
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002). Lid cold plate, liner cut-out, thinner printed parts and buck-boost driver added; hold times pooled through the plate; refreeze of all PCM; results recomputed
0.1	2026-09-25	Amish Chadha	First issue for TRL 3 (payload, heat leak, PCM, hold times, Peltier and heat sink, refreeze, thermosiphon, freeze fault, logger, mass, cost)

ColdPod sizing calculations

On paper, ColdPod meets ten of its seventeen requirements, has three at risk and misses two, each by a small amount; two cannot be verified at TRL 3. Version 0.2 applies the design changes Amish accepted on 2026-09-25 (CPD-DDR-002): an aluminium cold plate under the lid PCM pack, a second hardware cut-out on the liner at 3 °C, thinner printed parts and a buck-boost Peltier driver. The plate couples the lid pack to the evaporator can, so the Peltier now refreezes all of the PCM, the lid pack no longer melts in long powered holds, and the jacket and lid pack melt together. The hold times are about 14.0 h with no power at 43 °C, 28.4 h off-grid at 32 °C and 17.5 h off-grid at 43 °C; they stay at risk against a $\pm 30\%$ uncertainty in the heat leak (R4, R5, R6). The liner cut-out closes the freeze fault (R2 met), and the plate and buck-boost stage close R1 and R7. The two misses are refreezing all the PCM (R8: 8.4 h against 8 h, because the lid pack now shares the module), and mass (R12: 5.53 kg against 5.5 kg). Version 0.3 applies the budget top-up to \$310 that Amish decided on 2026-09-26 (CPD-DDR-002 N3), so cost (R15: \$303 against \$310) is now met. Every number in this note is printed by `docs/04-calcs/sizing.py`; the tag in brackets, for example [B9], is the line of that script's output that carries it.

Safety: These calculations concern a device meant to protect vaccines and insulin, a 76.8 Wh lithium battery, a combustible paraffin PCM and a heat sink near 53 °C. They are first-principles estimates for a paper proof of concept, not a substitute for datasheets, a fault analysis by a qualified engineer or test. ColdPod is a research and educational prototype, not a medical device, and is not WHO-prequalified. See CPD-PRC-001, Safety.

■ Scope and method

The note checks every requirement in CPD-REQ-001 v0.4 against the design in CPD-PRC-001 v0.4 and the parametric model `cad/src/model.py`. The script imports the model's `PARAMS` and `levels()`, so the layer dimensions used here are the ones in the STEP files and in drawing CPD-DWG-001. It reads prices from `bom/bom.csv`. Run it from the repo root with `python docs/04-calcs/sizing.py` (about 30 s; the refreeze is a time-stepped simulation).

Status rule for the hold times: **met** if the target holds even with 30 % more heat leak than the nominal estimate; **at risk** if it holds only at the nominal leak; **not met** otherwise.

■ Assumptions

Table 1. Main assumptions.

Area	Assumption	Basis
Ambient cases	25 °C clinic, 32 °C hot day, 43 °C WHO hot zone; constant, shaded, no solar gain	CPD-REQ-001
VIP	Aged centre-of-panel conductivity 0.007 W/(m·K), fumed silica core; 25 mm	Inside the 0.006 to 0.008 W/(m·K) range usually quoted
VIP edges	Butt joint between two metallized-film edges with a 1 mm gap: $\psi = 0.015$ W/(m·K) per metre of joint; one edge against foam: 0.0075 W/(m·K)	Engineering judgment; to confirm with the VIP supplier
Geometry of the insulation	Langmuir shape factor for a box: walls A/t, edges 0.54 per metre, corners 0.15 t	Standard conduction shape factors
Pipe crossing	20 mm polyurethane foam strip (0.024 W/(m·K)) across the +X wall; two 8 mm tubes with a stainless section, 0.3 mm wall, 40 mm long	Model
Sensor wires	Six 28 AWG copper conductors, 100 mm path along a VIP joint	Payload and liner probes
PCM	RT 5 HC class; 85 % pouch fill; 770 kg/m ³ liquid, 880 kg/m ³ solid; 180 kJ/kg usable inside 2 to 8 °C (of about 250 kJ/kg listed over the full range); solid conductivity 0.2 W/(m·K); cp 2.0 kJ/(kg·K) liquid, 1.8 solid	Rubitherm RT range data, derated
Hold end point	Hold ends when the jacket or the lid pack is fully melted, whichever comes first; the sensible heat of the payload and liner is kept as unclaimed margin	Conservative
Peltier module	127-couple modules, V _{max} 15.4 V, ΔT_{max} 67 K at a 300 K hot side; I _{max} 3, 4 or 6 A (TEC1-12703, 12704, 12706 classes); Seebeck coefficient, resistance and conductance derived from those ratings and held constant	Standard derivation from datasheet maxima
Cold path	0.40 K/W from the can to the module cold face (loop thermosiphon, cold block, interface)	Engineering judgment for 8 mm two-phase tubes
Hot path	0.55 K/W from the module hot face to air (80 x 80 x 30 mm finned sink with a 70 mm fan, 0.50 K/W, plus 0.05 K/W interface)	Typical for this sink class; to confirm
Control	Powered hold keeps the evaporator can at 2 °C; refreeze floor –2 °C at the can; module fed smooth DC from a buck-boost driver, 90 % efficient, from 10 V input upward; fan 0.6 W, controller 0.1 W	Design intent; buck-boost by CPD-DDR-002
Battery	76.8 Wh; 85 % (65.3 Wh) available to cooling, 15 % kept for the logger	CPD-PRC-001
Refreeze	25 W cap to the module and 12 W to the battery while charging, inside a 45 W USB-C PD budget; can to liquid PCM 40 W/(m ² ·K) through the pouch film	Design intent
Lid cold plate	1.5 mm aluminium, 237 W/(m·K), the full 205 x 140 mm under the lid pack, its rim landing on the evaporator can rim; 0.5 K/W from plate rim to can rim through the gasket seat; lateral conductance taken as 8 k t for a square plate with its edge held	CPD-DDR-002; engineering judgment
Cut-outs	Bimetal cut-out on the cold block opening at –5 °C, in series with one on the liner opening at 3 °C	CPD-DDR-002
Mass	PETG 1.27 g/cm ³ ; printed walls with 2.7 mm of solid perimeters and 20 % infill for the rest (solid below 2.7 mm); shell 3 mm, lid cap 5 mm, end housings 2 mm (CPD-DDR-002); VIP 190 kg/m ³ including film; LiFePO ₄ 32700 cell 0.14 kg	Model volumes; typical values

■ A. Payload and size (R3, R13)

The liner is 172 x 107 x 78.5 mm inside [A1]. Less the printed rack and the buffered probe, the usable volume is 1.36 L [A2]. It holds 24 pens of 16 mm diameter, in four layers of six [A3], using 100 of 107 mm across and 66 of 78.5 mm in height [A4]; pens up to 172 mm long fit [A5]. R3 is met.

Overall, with the handle up, the case is 366 x 212 x 207 mm (14.4 x 8.3 x 8.1 in) [A6, A7], inside the 400 x 250 x 250 mm envelope of R13: met.

■ B. Heat leak (drives R4 to R7)

The inside of the insulation is 205 x 140 x 112 mm [B1] (1.5 mm taller than in v0.1, for the lid cold plate). With Langmuir shape factors of 4.854 m for the body and 1.536 m for the lid [B2], the centre-of-panel conductance is 0.0340 W/K and 0.0107 W/K [B3]. The other paths are:

Table 2. Heat-leak paths.

Path	Conductance (W/K)	Tag
Body panels, centre of panel	0.0340	B3
Lid plug, centre of panel	0.0107	B3
Body VIP joints, 1.54 m	0.0230	B4
Lid plug junction	0.0103	B5
Foam strip at the pipe crossing	0.0056	B6
Thermosiphon stainless sections (reverse path)	0.0058	B7
Sensor wires	0.0019	B8
Body / lid / total	0.0704 / 0.0211 / 0.0915	B9

With the PCM at 5 °C, the heat leak is 1.83 W at 25 °C, 2.47 W at 32 °C and 3.48 W at 43 °C [B10]. The TRL 2 estimate was 0.11 W/K [B11]; the explicit edge and joint terms come to less than the 1.8 multiplier it used. Joints and edges are still about 45 % of the total, so the supplier's edge data matter.

■ C. Phase-change material

The aluminium evaporator can (section G) and the loop tubes take some of the PCM space. The jacket holds 1.055 L and the lid pack 0.430 L [C1], which at 85 % fill is 0.691 kg and 0.282 kg, 0.972 kg in all [C2]. At 180 kJ/kg that is 124 kJ in the jacket and 51 kJ in the lid, 175 kJ in all [C3], or 48.6 Wh [C4]. TRL 2 assumed 1.06 kg and 191 kJ.

■ D. Passive hold (R4)

Table 3. Hold with no power, starting with all the PCM frozen.

Ambient	Jacket alone (h)	Lid pack alone (h)	Pooled through the plate (h)	Tag
25 °C	24.5	33.4	26.6	D1
32 °C	18.2	24.7	19.7	D1
43 °C	12.9	17.6	14.0	D1

The lid cold plate conducts about 2.8 W/K from its centre to the can rim [D1b], 135 times the lid's heat leak [D1c], so the jacket and the lid pack share their latent heat and melt together. In v0.1, without the plate, the hold ended when the jacket melted (13.0 h). R4 is now 14.0 h at 43 °C [D2] against 12 h. With 30 % more heat leak it falls to 10.8 h [D3]; a 17 % rise in heat leak uses up the margin [D4]. R4 is **at risk**.

■ E. Peltier module, cold path and heat sink (R7)

A Peltier module that is switched off conducts heat. The derived off-state conductance is 0.268 W/K for the TEC1-12703 class, 0.357 W/K for the 12704 and 0.536 W/K for the 12706 [E1]. Even the smallest is 2.9 times the whole box's heat leak [E2], which is why the thermosiphon diode (section H) is needed.

The same conductance decides which module can hold at 43 °C, because the hot side runs about 50 K above the cold side:

Table 4. Powered hold, can at 2 °C: current, module power, COP and input power (module through a 90 % driver, plus fan and controller).

Module	25 °C	32 °C	43 °C	Tag
TEC1-12703	0.73 A, 3.2 W, 0.67, 4.2 W	1.03 A, 6.1 W, 0.45, 7.5 W	1.69 A, 16.0 W, 0.23, 18.5 W	E3
TEC1-12704	0.93 A, 3.9 W, 0.54, 5.0 W	1.31 A, 7.6 W, 0.36, 9.2 W	2.22 A, 21.1 W, 0.18, 24.2 W	E3
TEC1-12706	1.34 A, 5.5 W, 0.38, 6.8 W	1.94 A, 11.4 W, 0.24, 13.4 W	Cannot lift the load	E3

The TEC1-12706 named at TRL 2 cannot hold at 43 °C with this heat sink: its own back-conduction exceeds what it can pump. The **TEC1-12703 class** is chosen. At 43 °C its cold face is at 0.5 °C and its hot face at 53.9 °C [E4]; it needs 9.5 V [E5], and the sink rejects 5.3 W, 8.9 W and 19.8 W at 25, 32 and 43 °C [E6]. The sink base reaches about 53 °C at 43 °C [E7].

R7 asks for an indefinite hold up to 43 °C on 12 V or 45 W USB-C PD. The input is 18.5 W, well inside 41.4 W available from a 45 W PD source [E8], and 1.95 A from a 10 V vehicle input [E9]. The module needs 9.5 V, which left a plain buck driver almost no headroom at a 10 V input; the buck-boost driver adopted in CPD-DDR-002 can raise the module voltage above the input when it must [E9b]. The lid pack is now held frozen by the cold plate in powered hold (section F). R7 is **met** on paper.

The driver matters. Unfiltered on/off pulse-width modulation at 12.8 V, giving the same average heat lift at 43 °C, needs a 0.79 duty and 25.6 W at the module [E10], 60 % more than smooth DC (16.0 W). The power board therefore uses a buck-boost driver with an LC filter, not on/off PWM. CPD-PRC-001 v0.2 said PWM improves COP; that was corrected in v0.3.

■ F. Off-grid hold (R5, R6)

65.3 Wh of the battery is available for cooling [F1]. While the battery runs, the module holds the can at 2 °C and all the PCM stays frozen, including the lid pack on its cold plate. Then the jacket and lid pack hold passively together.

Table 5. Battery, then PCM.

Ambient	Battery phase (h)	Passive phase (h)	Total (h)	With 30 % more leak (h)	Tag
25 °C	15.5	26.6	42.1		F2
32 °C	8.7	19.7	28.4	22.3	F2, F2b
43 °C	3.5	14.0	17.5	13.2	F2, F2b

R5 (24 h at 32 °C) and R6 (16 h at 43 °C, relaxed by CPD-DDR-001 D5) are met at the nominal heat leak and missed at +30 %: both are **at risk**. In v0.1 they were 26.5 h and 16.5 h. For reference, the 153.6 Wh 4S2P pack not chosen in D4 would give 21.0 h at 43 °C [F6].

In powered hold at 43 °C the plate carries the lid's 0.87 W heat leak to the can [F3] with its centre about 0.3 K above the rim [F4], so the lid pack stays frozen near 2.8 °C [F5]. In v0.1 the lid pack melted after about 21 h and settled near 13.8 °C above the top layer of pens; that risk to R1 and R7 is closed.

■ G. Refreeze (R8)

The decided evaporator position (outer face of the PCM, CPD-DDR-001 D3) is sized here. A 90 x 60 mm plate on one end of the jacket, as drawn at TRL 2, cannot freeze a paraffin jacket that runs 200 mm around the liner: solid paraffin conducts only about 0.2 W/(m·K). The evaporator is therefore a 1.0 mm aluminium can that lines the outer face of the jacket on four sides and the floor, 0.0943 m² in contact [G1], with an 8 mm copper evaporator loop around its base. The frozen jacket is effectively 8.3 mm thick [G2], and the can wall above the loop acts as a fin with 0.69 efficiency [G3].

The lid pack now freezes through the 1.5 mm lid cold plate, whose rim lands on the can rim when the lid closes [G6]. A time-stepped model (sensible cooling of all the liquid PCM, the liner, the can and the plate through the pouch film, then two quasi-steady freezing fronts in parallel, one in the jacket and one on the plate, with the module current chosen each step within the 25 W cap and the –2 °C can floor) gives:

Table 6. Refreeze of all the PCM from 25 °C, box empty, 25 °C ambient.

Module	Sensible part (h)	Jacket frozen (h)	Lid pack frozen (h)	All PCM (h)	Tag
TEC1-12703	1.2	6.9	8.4	8.4	G4
TEC1-12704	1.2	6.6	8.1	8.1	G4
TEC1-12706	1.1	6.9	8.3	8.3	G4

Conduction alone would allow about 1.6 h for the jacket [G5] and 2.3 h for the lid pack [G7], so the module, not the PCM, sets the rate. The jacket alone took 5.5 h in v0.1; with the lid pack now actively frozen, the module has 41 % more latent heat to lift and the whole charge takes 8.4 h against the 8 h target. **R8 is not met**, by about 0.4 h. Giving the module 30 W and the battery 7 W inside the same PD budget only brings it to 8.2 h [G10], and stretches the battery recharge to 11.5 h [G11], because the –2 °C can floor and the module's COP limit the lift. Options are listed

for Amish in `docs/REVIEW.md`. The v0.1 alternative of no lid pack and a 20 mm jacket (1.010 kg, all in the jacket [N1]; body 10 mm longer and wider, 10 mm lower [N2]) is kept for reference only; it was not the recommended option.

The battery recharges in about 6.7 h at 12 W alongside the refreeze [G8], for a total input of 40.5 W [G9], inside the 45 W PD budget.

■ H. Thermosiphon: diode ratio and tilt

The loop thermosiphon conducts about 2.50 W/K forward and 0.0058 W/K in reverse (the stainless wall sections), a ratio of 431 [H1]. For comparison, bolting the chosen module to the liner would raise the box conductance to 0.359 W/K [H2] and cut the passive hold at 43 °C to 3.6 h [H3]. The thermosiphon keeps its place (CPD-DDR-001 D2), and the can and loop as sized here are confirmed (CPD-DDR-002), with the mechanical disconnect kept as the fallback.

The condenser sits 76.0 mm above the evaporator loop [H4]. The whole loop stays below the condenser for tilts up to 18° with the cooling head down [H5] and 42° with the front or back down [H7]; with the cooling head down, part of the loop stays below the condenser up to 60° [H6]. Beyond those angles the part of the loop above the condenser dries out and cooling falls; the PCM carries the load meanwhile. Whether a motorbike carrier holds within 18° on average is an open question for a lab or field test after TRL 3.

■ I. Freeze fault (R2)

In normal operation the coldest surface (the can, down to −2 °C during refreeze) is separated from the liner by the PCM, and the controller stops cooling at a liner reading of 3 °C, so R2 holds. With a stuck-on driver, the module draws about 3.6 A from the 14.4 V charge rail [I4] until the hardware cut-out on the cold block opens at −5 °C [I1]. With that cut-out alone, once the PCM is fully frozen nothing stops the liner from following the can down to about −4 °C in a cool room [I2], which was why R2 was not met in v0.1.

A second hardware cut-out on the liner, in series with the first, is now in the design (CPD-DDR-002; BOM line 14). A lumped estimate of the liner after the cut-out opens (the payload and liner sharing heat with the colder frozen jacket) gives 1.2 °C for a 2 °C setting and 2.0 °C for a 3 °C setting [I3]. With the adopted 3 °C setting the liner settles near 2.0 °C [I5]. **R2 is met** on paper. The lid cold plate faces the cavity across a 12.5 mm air gap above the top layer of pens and touches no payload; it follows the can, so it sits near 2 °C in hold and reaches −2 °C only during refreezing, which R8 defines with the box empty.

■ J. Logger (R9, R11)

Sixty days of one 16-byte record per minute take 1.38 MB of the 2.10 MB flash [J1]: R9 is met on storage, and on accuracy by sensor selection. The logger and standby loads come to about 0.78 mW [J2]; with a 5 mW design allowance [J3], the 15 % reserve lasts about 96 days [J4], far beyond the 14 days of R11: met.

■ K. Mass (R12)

Table 7. Empty mass [K1].

Part	kg	Part	kg
Shell (PETG, printed, 3 mm)	0.689	Loop tubes (copper)	0.089
Lid cap (5 mm), gasket, latches	0.313	Cold block (aluminium)	0.071
Lid cold plate (aluminium)	0.116	Peltier module	0.025
Handle and strap	0.200	Heat sink	0.197
VIP set	0.865	Fan and guard	0.060
PCM	0.972	End housings (PETG, printed, 2 mm)	0.294
PCM pouches	0.080	LiFePO4 cells, 4 x 32700	0.560
Liner (aluminium)	0.257	BMS, fuse, holder	0.080
Rack (PETG)	0.083	Electronics, including both cut-outs	0.170
Evaporator can (aluminium)	0.254	Wiring and hardware	0.150

The thinner printed parts adopted in CPD-DDR-002 save 0.06 kg on the shell, 0.04 kg on the lid cap and 0.11 kg on the end housings [O1]; the lid cold plate adds 0.12 kg [O3], and the taller insulation box and the liner cut-out add a little more. The total is **5.53 kg (12.2 lb)** empty [K2, K3] and 6.21 kg with 24 pens [K4], against the relaxed target of 5.5 kg: **R12 is not met**, by 0.03 kg [O4] (5.60 kg in v0.1). The TRL 2 review estimated about 5.51 kg for this set of changes; the difference is the VIP and cut-out mass. The margin is inside the uncertainty of the estimate, so weighing a built case would settle it; that is TRL 4 work, on hold.

■ L. Cost and battery (R14, R15)

All 16 BOM lines are priced [L1]; the total is \$303 [L2] against the \$310 budget (raised from \$300 by Amish, 2026-09-26, CPD-DDR-002 N3): **R15 is met**, with \$7 of margin. The accepted changes add the lid cold plate (about \$5), the liner cut-out (about \$3) and the buck-boost driver (about \$4), and the thinner printed parts save about \$4 of filament; v0.1 was \$295. There is still no custom PCB. The battery is 76.8 Wh [L3], under the 100 Wh airline limit: R14 is met.

■ P. Foam variant (CPD-DDR-001 D7)

The documented low-cost variant replaces the VIPs with 25 mm polyurethane foam (0.024 W/(m·K)). With the same shape factors and no VIP joints, the conductance is 0.161 W/K [P1] and the passive hold at 43 °C, pooled through the lid cold plate, falls to about 7.9 h [P2] (7.4 h in v0.1, jacket only), so the foam variant does not meet R4. TRL 2 estimated about 7 h.

■ Checks against earlier figures

Table 8. TRL 2 figures in CPD-PRC-001 v0.2 and the README, checked against this note (v0.2 values). The docs were corrected in v0.3 and updated again in v0.4.

Quantity	TRL 2	TRL 3	Tag
Overall conductance	0.11 W/K	0.092 W/K	B9
PCM	1.06 kg, 191 kJ	0.972 kg, 175 kJ	C2, C3
Payload volume	about 1.2 L	1.36 L	A2
Passive hold 25 / 32 / 43 °C	24 / 18 / 12.7 h	26.6 / 19.7 / 14.0 h, pooled	D1
Input power to hold 25 / 32 / 43 °C	4.7 / 8.1 / 17.4 W	4.2 / 7.5 / 18.5 W	E3
Battery then PCM 25 / 32 / 43 °C	38 / 26 / 16 h	42.1 / 28.4 / 17.5 h	F2
Refreeze	about 5 h (text), about 6 h (table)	8.4 h, all PCM (5.5 h, jacket only, in v0.1)	G4
Heat rejected 25 / 32 / 43 °C	6 / 10 / 21 W	5.3 / 8.9 / 19.8 W	E6
Heat sink temperature at 43 °C	55 to 65 °C	about 53 °C	E7
Peltier off-state conductance	0.3 to 0.5 W/K	0.27 to 0.54 W/K	E1
Peltier module	TEC1-12706	TEC1-12703 class	E3
PWM "for better COP"	stated	smooth DC; on/off PWM costs 60 % more	E10
Battery recharge	about 3 h at 25 W	about 6.7 h at 12 W alongside refreeze	G8
Logger reserve	weeks	about 96 days	J4
Log storage, 60 days	about 1.4 MB	1.38 MB	J1
Size	370 x 215 x 205 mm	366 x 212 x 207 mm	A6
Mass empty	5.2 kg	5.53 kg	K2
Parts cost	\$280	\$303	L2
Warm-payload pull-down	about 3.7 h	not recomputed; removed from the precis, which keeps the advice to load the payload pre-cooled	

■ Results

Table 9. Requirements against this note. Status: met, at risk, not met, or not verifiable at TRL 3.

ID	Target (CPD-REQ-001 v0.4)	Value	Status
R8	Refreeze a fully melted PCM in 8 h or less at 25 °C	All PCM 8.4 h (jacket 6.9 h, lid pack 8.4 h) [G4]	Not met
R12	5.5 kg or less empty (relaxed)	5.53 kg [K2]	Not met
R15	Parts \$310 or less; no custom PCB	\$303 [L2]; modules on perfboard	Met
R4	12 h or more at 43 °C, no power	14.0 h; 10.8 h at +30 % leak [D2, D3]	At risk
R5	24 h or more at 32 °C, battery then PCM	28.4 h; 22.3 h at +30 % leak [F2]	At risk
R6	16 h or more at 43 °C, battery then PCM (relaxed)	17.5 h; 13.2 h at +30 % leak [F2]	At risk
R1	2 to 8 °C at the payload probe	Can at 2 °C, liner 2 to 5 °C; lid pack held frozen near 2.8 °C by the plate at 43 °C [F5]	Met
R2	No payload-contact surface below 1 °C, including a stuck-on driver	Normal: met. Fault: liner near 2.0 °C with the 3 °C liner cut-out [I5]	Met
R3	1.0 L or more; 20 or more pens up to 170 mm	1.36 L; 24 pens; up to 172 mm [A2 to A5]	Met
R7	Hold indefinitely up to 43 °C on 12 V or 45 W USB-C PD	18.5 W input [E8]; buck-boost from 10 V [E9b]; lid pack held [F5]	Met
R9	±0.5 °C, log every 1 min, 60 days, CSV export	1.38 MB of 2.10 MB [J1]; accuracy by selection	Met
R11	Logger runs 14 days after cooling stops	About 96 days [J4]	Met
R13	Fits 400 x 250 x 250 mm	366 x 212 x 207 mm [A6]	Met
R14	Battery 100 Wh or less	76.8 Wh [L3]	Met
R17	"Research prototype, not a medical device" on box, start screen and logs	By design	Met
R10	Alarm logic and thresholds	Design intent only; no firmware sketch exists at TRL 3	Not verifiable at TRL 3
R16	IP54 bays; 0.5 m drop while loaded	Needs a test	Not verifiable at TRL 3

Counts: 10 met, 3 at risk, 2 not met, 2 not verifiable at TRL 3 (v0.2: 9 met, 3 at risk, 3 not met; v0.1: 7 met, 5 at risk, 3 not met, 2 not verifiable).

■ Limits of this note

- All values are paper estimates. The heat leak (joint ψ , aged VIP conductivity), the thermosiphon resistance, the heat sink resistance and the PCM's usable latent heat inside 2 to 8 °C are the largest uncertainties, in that order.
- The Peltier model uses constant properties derived from datasheet maxima. Real modules vary by maker.
- The lid pack temperature in powered hold and its refreeze rest on an assumed 0.5 K/W seat between the plate rim and the can rim; a poor seat would slow the lid pack's refreeze. Stratification in the cavity and contact with the rack are not modelled.

- No solar gain is included. A carrier in direct sun would see more heat than the 43 °C shaded case.