

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-09-30	AC

Broken view: the middle of the rod is left out. True length 796 mm overall.



TOP VIEW

Scale 1:2; looking down (along -Z)



FRONT VIEW

Scale 1:2; looking at the front (along +Y)



RIGHT VIEW

Scale 1:2; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Cut 796 mm of 16 mm rod; face both ends square.

Bottom end: turn an M12 x 1.75 stud 20 mm long with a square shoulder. The shoulder is the anvil top: measure from it.

The rod above the shoulder is 776.5 mm; its top end ends flush with the top of the T-handle tube.

Smooth the rod between the shoulder and 715 mm: the hammer slides on it.

The 6 mm roll pin hole, 720.5 mm above the shoulder, is drilled through the rod and the stop collar together (DWG-107).

Fit: the hammer goes on from the bottom end; then the stud screws into the anvil with medium thread locker.

Check: straight within 0.5 mm; the hammer slides its whole length without sticking.

CONEPRO				github.com/BoujeeEnjinia1701/conepro			
ConePro upper rod (hammer guide): making sketch							
DRAWING NO. CNP-DWG-106			REV P1		SHEET 1 of 1		SIZE ANSI B
SCALE 1:2	UNITS mm	PROJECTION 		DATE 2026-09-30		DRAWN Amish Chadha	
MATERIAL / NOTES 16 mm 4140 class steel rod, ground or bright							
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com						Generated from cad/src; do not edit by hand	