

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-09-30	AC
P2	Lengths for the grooved hammer; end cap; no thread locker	2026-10-02	AC

Broken view: the middle of the rod is left out. True length 798 mm overall.



TOP VIEW

Scale 1:2; looking down (along -Z)



FRONT VIEW

Scale 1:2; looking at the front (along +Y)



RIGHT VIEW

Scale 1:2; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Cut 798 mm of 16 mm rod; face both ends square.

Bottom end: turn an M12 x 1.75 stud 20 mm long with a square shoulder. The shoulder is the anvil top: measure from it.

The rod above the shoulder is 778.0 mm; its top end ends flush with the top of the T-handle tube.

Smooth the rod between the shoulder and 715 mm: the hammer slides on it.

The 6 mm roll pin hole, 722.0 mm above the shoulder, is drilled through the rod and the stop collar together (DWG-107).

Fit: the hammer goes on from the bottom end and the end cap screws on the stud; take it off to screw the stud into the anvil with no thread locker, turned by the T-handle.

Check: straight within 0.5 mm; the hammer slides its whole length without sticking.

ConePro upper rod (hammer guide): making sketch

DRAWING NO. CNP-DWG-106			REV P2		SHEET 1 of 1		SIZE ANSI B	
SCALE 1:2		UNITS mm	PROJECTION 		DATE 2026-10-02		DRAWN Amish Chadha	
MATERIAL / NOTES 16 mm 4140 class steel rod, ground or bright								
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com								
Generated from cad/src; do not edit by hand								