



REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-09-30	AC



TOP VIEW

Scale 1:25; looking down (along -Z)



FRONT VIEW

Scale 1:25; looking at the front (along +Y)

RIGHT VIEW

Scale 1:25; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Make two front posts, 2,902 mm long; cut both ends square.

All holes go through both walls, on the face's centre line unless stated. Heights from the bottom end.

Left and right faces: 13 mm at 35 and 62 mm up (base cleats); 11 mm at 28 mm below the top (head cleats); 11 mm at 372.5 mm below the top (knee brace).

Front right only: two 9 mm holes through the street face and back face, 15 mm each side of centre, 2,388 mm up (sensor arm); and a 12 mm cable hole in the street face, 30 mm toward the outer side, 2,435 mm up. Fit a grommet.

Deburr every hole; zinc-rich paint on cut ends and holes.

Hole positions: figure post-holes in the build plan.

Check: holes in opposite faces line up (a rod passes square).

COOLSHADE

github.com/BoujeeEnjinia1701/coolshade

CoolShade front post (make 2, a left and a right): making sketch

DRAWING NO. CSH-DWG-103			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:25	UNITS mm	PROJECTION 	DATE 2026-09-30		DRAWN Amish Chadha
MATERIAL / NOTES Galvanized steel SHS 80 x 80 x 3 mm					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com					Generated from cad/src; do not edit by hand