

CULVERTCRAWL · DESIGN PRECIS

CulvertCrawl design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	CVC-PRC-001	Version	0.8
Status	Draft	Date	2026-10-02
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/culvertcrawl		
Source	docs/02-concept.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.8	2026-10-02	Amish Chadha	Decisions of 2026-10-02 (CVC-DEC-001): design for construction accepted; boom on two bolts for the prototype; output order (deflection report first)
0.7	2026-10-01	Amish Chadha	Budget treated as a value-engineering target
0.6	2026-09-30	Amish Chadha	Constructable design (CVC-DDR-003); numbers from CVC-CAL-001 v0.4; build plan CVC-BLD-001 and design decisions register CVC-DEC-001
0.5	2026-09-26	Amish Chadha	Budget approved by Amish (\$910, CVC-DDR-002); cost figures restated against it
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	TRL 3. Record Amish's 2026-09-25 decisions (CVC-DDR-001); numbers checked against CVC-CAL-001; camera at 50 fps with circular fisheye; fuse split; model and drawing CVC-DWG-001

0.2	2026-09-25	Amish Chadha	Populate to TRL 2 (architecture, profiling principle, first-order numbers, safety, media)
0.1	2026-09-24	Amish Chadha	Initial scaffold


CulvertCrawl design precis

CulvertCrawl is a small tracked crawler, about 611 x 170 x 106 mm and 6.6 kg, that drives into a 300 to 900 mm culvert on a 60 m tether while an operator watches live video on a laptop at the pipe mouth. A green laser ring projected onto the pipe wall 300 mm ahead of a fisheye camera gives a cross-section every 6 mm of travel, from which the software reports diameter, ovality (deflection) and sediment depth against distance. The TRL 3 calculations (CVC-CAL-001 v0.5) give 6.4 h per charge, 75 m of reach when the crawler drives submerged and uphill against the flow, profile accuracy of 0.25 %, 0.57 % and 0.97 % of diameter in 300, 600 and 900 mm pipe, and an estimated parts cost of \$1,034 against the \$910 value-engineering target. On 2026-09-30 the design was made constructable (CVC-DDR-003, open for Amish's review): every part can now be made and fixed, which made the crawler heavier (better reach) and added \$128 of parts, so R12 is \$124 over its \$910 value-engineering target. The prototype build plan is CVC-BLD-001 (docs/05-build-plan.md); open decisions are in CVC-DEC-001 (docs/06-design-decisions.md). All numbers are calculated estimates, not measurements.

CulvertCrawl

github.com/BoujeeEnjinia1701/culvertcrawl

CONCEPT, NOT FOR FABRICATION



Seen from the front right and above, 24 deg elevation. Grey figure: 1.75 m person for scale

Figure 1. CulvertCrawl in a sectioned 600 mm culvert, with the tether reel and surface control box at the mouth and a 1.75 m person for scale. The green line is the projected laser ring (illustrative).

■ How it works

1. **Deploy.** Two people carry the crawler, the tether reel and the surface box from the vehicle to the culvert mouth. The operator connects a laptop and gamepad to the surface box, sets the payout counter to zero at the mouth and lowers the crawler onto the invert.
2. **Power and data.** A 12.8 V LiFePO4 battery in the surface box feeds a boost converter that puts 48 V DC on two power conductors in the tether. Two twisted pairs in the same tether carry 100 Mbit/s Ethernet between the laptop and the crawler. A slip ring in the reel hub lets the drum turn while connected. The surface box holds a 10 A fuse at the battery, a 2 A fuse on the 48 V output, a 1.5 A overcurrent cutoff and a latching emergency stop that kills tether power.
3. **Drive.** Inside the sealed aluminium hull, a Raspberry Pi 4 runs the motor driver for two self-locking worm gear motors, one per rubber track. The operator drives with the gamepad at about 0.15 m/s while surveying. The worm gears hold the crawler on a slope with power off.
4. **See.** A 12 MP camera with a 180 degree circular fisheye lens looks forward through an acrylic dome, lit by a ring of eight 1 W LEDs. The Pi encodes the LED frames as 1080p H.264 video at 25 frames per second in hardware and streams it to the laptop, which records it with distance, time and attitude overlaid. Distance comes from the payout counter at the reel, cross-checked by track odometry; pitch and roll come from an IMU in the hull.
5. **Measure.** The camera runs at 50 frames per second; the LEDs light alternate frames for video and the laser ring is captured on the frames between. A Class 2 laser diode at the tip of a clear boom shines onto a 90 degree conical mirror, which spreads the beam into a thin disc of light perpendicular to the crawler axis, 300 mm ahead of the lens. Where the disc meets the wall it draws a bright ring. On the laser frames the LEDs dim and the software finds the ring in the image. Because the ring plane is fixed relative to the camera, each ring pixel defines a ray that meets the plane at exactly one point, so the wall is triangulated in 3D even when the crawler is well below the pipe axis. The software fits a circle and an ellipse to each ring, and reports mean diameter, ovality, and the height of any flat sediment or water surface across the invert, every 6 mm of travel at survey speed.
6. **Choose the entry end.** In flooded pipes, enter from the upstream end and drive with the flow where access allows (operating guidance, CVC-DDR-002); reach driving upstream against the flow is the thinnest margin in the design.
7. **Recover.** The crawler reverses out while the operator winds the reel. If it stalls or loses power, the tether's aramid strength member lets the crew pull it out by hand; nobody enters the pipe.

CulvertCrawl: power flow while driving and profiling, W (estimates)

github.com/BoujeeEnjinia1701/culvertcrawl

CONCEPT, NOT FOR FABRICATION




Figure 2. Power flow while driving and profiling, in watts, from CVC-CAL-001. All values are estimates.

■ Main components


Numbers match the exploded view (Figure 3) and `bom/bom.csv`.

#	Component	Proposed choice	Notes
1	Sealed hull and lid	6061 aluminium body 240 x 88 x 74 mm machined from a block, 4 mm walls, 10 mm front wall, inner rim with the lid O-ring and ten M4 screws, flush 6 mm lid, IP68 penetrator, pressure-test plug (about 1.26 kg)	Leak check by vacuum or low pressure before each use
2	Track modules (pair)	Rubber belts 36 mm wide over 70 mm sprockets, outer edges 170 mm apart; made 3 mm side plates tie the hull to the ballast plate	Outer track edges bear on the curved invert
3	Worm gear motors (2)	12 V, about 80 rpm output, rated 1 N·m or more (0.67 N·m needed), self-locking, Hall encoders, double lip shaft seals	Shaft seals are the main leak path
4	Electronics stack	Raspberry Pi 4 Model B 2 GB, dual motor driver, 48 to 12 V and 12 to 5 V converters, IMU, leak sensor	Pi 4 chosen for its hardware H.264 encoder
5	Fisheye camera and dome port	12 MP IMX708 module with M12 mount at 2304 x 1296 and 50 fps; 180 degree circular fisheye with the image circle inside the sensor height; 60 mm acrylic dome centered on the lens	Dome keeps the wide field of view if the port is wet
6	LED ring light	8 x 1 W high-CRI white LEDs, about 800 lm (estimate), dimmable, potted in a machined front bezel that also clamps the dome	Dimmed on laser frames
7	Laser ring projector	Class 2 (1 mW or less) 520 nm diode, 90 degree conical mirror behind a clear window, ring 300 mm ahead of the lens (200 mm before CVC-DDR-002); clear boom on a clear fin bolted to the ballast plate	Held by two M3 bolts at the fin bracket for the prototype; a tool-free clamp is decided after the first pipe trials (decided 2026-10-02)
8	Ballast skid plate	Steel 255 x 88 x 14 mm, about 2.45 kg, square nose, 8 mm above the track contact line; carries the side plates, fin bracket and the tether's eye bolt (230 x 80 x 14 mm with a lip before CVC-DDR-003)	Raises traction and protects the hull; enlarged for R2 (CVC-DDR-002)
9	Tether	60 m hybrid: 2 twisted pairs plus 2 x 0.75 mm ² power, aramid member, PU jacket about 7 mm, about 55 g/m (estimate)	Also the recovery line
10	Tether reel	320 mm flanged reel, A-frame, crank and brake, Ethernet-rated slip ring, payout encoder wheel	Payout counter gives distance
11	Surface control box	Rugged case; 12.8 V 20 Ah LiFePO ₄ with BMS; 12 to 48 V boost; 10 A and 2 A fuses; emergency stop; 1.5 A overcurrent cutoff	Laptop connects by Ethernet
12	Operator gamepad	USB gamepad	Laptop is the user's own

CulvertCrawl: exploded viewgithub.com/BoujeeEnjinia1701/culvertcrawl

CONCEPT, NOT FOR FABRICATION

- 1 Sealed hull and lid
- 2 Track modules and side plates
- 3 Worm gear motors (2)
- 4 Electronics tray, Pi 4 and deck
- 5 Fisheye camera, mount and dome port
- 6 Front bezel with LED ring
- 7 Laser ring projector on fin and boom
- 8 Ballast skid plate
- 9 Tether, 60 m hybrid, with strain relief and eye bolt
- 10 Tether reel, slip ring, payout counter
- 11 Surface control box (LiFePO4, 48 V boost)
- 12 Operator gamepad




Seen from the front right and above, 24 deg elevation; numbers match bom/bom.csv

Figure 3. Exploded view with numbered callouts matching the BOM. The surface kit (9 to 12) is shown displaced in front of the crawler.

CulvertCrawl: cutawaygithub.com/BoujeeEnjinia1701/culvertcrawl

CONCEPT, NOT FOR FABRICATION



Front half removed; seen from the front and above, 18 deg elevation

Figure 4. Cutaway of the crawler along its axis: dome and camera, electronics stack, worm gear motors at the rear, ballast plate underneath, and the laser boom ahead of the dome.

The parametric build123d model is `cad/src/model.py` (STEP and STL in `cad/step/` and `cad/stl/`), and the general arrangement is drawing CVC-DWG-001 Rev P3 (`cad/drawings/CVC-DWG-001.pdf`).

■ Key numbers (from CVC-CAL-001 v0.5)

This section summarizes the TRL 3 calculation note, CVC-CAL-001 (`docs/04-calcs/01-sizing.md`); every value is printed by `docs/04-calcs/sizing.py`. The design case is a straight 600 mm corrugated steel culvert, 50 m long, on a 5 % slope, with a wet silt invert and 150 mm of water at 0.5 m/s.

Mass and buoyancy

Item	Value	Basis
Crawler	6.63 kg	Hull and lid 1.26 kg, ballast 2.45 kg and the other made parts from model volumes; bought parts estimated
Displaced volume	2.87 L	Hull envelope, dome, bezel, tracks, ballast, boom, fin
Net weight fully submerged	3.77 kg	57 % of the dry normal load
Design case	Fully submerged	138 mm of water above the track contact line against a 106 mm crawler
Whole kit	22.2 kg; heaviest item 7.8 kg (reel with tether)	R10 met on mass

Traction and reach

Reach is the tether length whose drag uses up the traction left after track resistance, grade and water drag, with 20 % traction reserve. Driving uphill also lifts the tether up the grade, which the TRL 2 estimate left out.

Case	Reach	Requirement
Dry, uphill	64 m	Met
Dry, downhill	106 m	Met
Design case: submerged, uphill against 0.5 m/s flow	75 m	Met on paper (52 m before CVC-DDR-003)
Design case: submerged, downhill with the flow	216 m	Met

The wet result is very sensitive to track friction under water: at 0.45 instead of 0.6, wet uphill reach falls to about 23 m. Measuring that friction is TRL 4 work, on hold. Sprocket torque at the dry traction limit is 0.84 N·m per motor, within the 1 N·m motor rating; top speed is 0.29 m/s.

Power and endurance

Quantity	Value
Crawler loads; crawler input	28.0 W; 30.8 W
Tether loop resistance (2 x 60 m of 0.75 mm ²)	3.12 Ω
Tether current; voltage at the crawler; copper loss	0.67 A; 45.9 V; 1.40 W (4.4 %)
Peak: tether current; drop	1.25 A; 3.9 V
Battery output	36.0 W
Endurance	6.4 h nominal; 5.1 h derated (R9 met)

At 24 V the tether would lose 8.24 W. The peak battery current of 5.4 A exceeds the 5 A fuse listed at TRL 2, so the fuses are now 10 A at the battery and 2 A on the 48 V output.

Laser ring profiling

The ring plane sits 300 mm ahead of the dome center (200 mm before CVC-DDR-002). With the camera 70 mm above the invert of a 900 mm pipe, the top of the pipe is 70.1 degrees off the camera axis (76.5 degrees at 200 mm), beyond the vertical field of a 160 degree lens on a 16:9 frame. The design therefore uses a 180 degree circular fisheye inside the 1296 px sensor height (0.139 degree per pixel). A Monte Carlo of ring centroid noise, lens model residual, ring plane tilt and distance, and crawler yaw gives, at the 95th percentile:

Pipe	Vertical diameter error	R5 (1 % of diameter)
300 mm	0.25 %	Met
600 mm (150 mm of water)	0.57 %	Met
900 mm (150 mm of water)	0.97 %	Met, thin margin (1.41 % with the ring plane at 200 mm)

These include the shadow of the clear fin that carries the boom (CVC-DDR-003): it hides a thin strip of the ring at the invert, 6.4 % of the ring in 300 mm pipe.

The longer boom puts the cone mirror about 300 mm ahead of the tracks, which matters in bends and at offset joints (see the open removable-boom question). The profile covers only the wall above any water surface, because the light refracts at the water line; the software reports the water or sediment chord instead. At 25 profiles per second, the spacing is 6 mm at 0.15 m/s. A 1 mW ring gives about 272 signal electrons per pixel on the wall of a 900 mm pipe, enough in a dark pipe.

Cost

Group	Cost	Requirement
Crawler (items 1 to 8, 14, 15)	\$481	Bezel, side plates and other parts added for construction (CVC-DDR-003)
Tether, reel and surface kit (items 9 to 12)	\$513	Reel frame, bearings, counter reader, box chassis
Hardware and consumables (item 13)	\$40	
Total	\$1,034	R12: over the value-engineering target by \$124 (target \$910)

The laptop is excluded.

■ Key design choices

Amish decided items 1 to 8 of the TRL 2 review on 2026-09-25 by accepting the recommendations (CVC-DDR-001), and later the same day accepted the TRL 3 recommendations on reach, profiling and cost (CVC-DDR-002).

- **Tracks rather than wheels.** Tracks spread the load on silt and ride over corrugations and joint offsets. Decided by Amish, 2026-09-25: go with recommendation.
- **Power from the surface over the tether at 48 V DC, with no battery in the crawler.** Surface power keeps lithium cells out of the pipe and the crawler small. At 48 V the tether loses 4.4 %; at 24 V it would lose about six times as much. 48 V stays below the 60 V DC extra-low-voltage limit. Decided by Amish, 2026-09-25: go with recommendation.

- **Surface battery: 12.8 V 20 Ah LiFePO4 rather than a SwapCell pack.** A SwapCell-compatible input stays a later option; it would cite SwapCell interface v0.3, whose wake on a coded INTERLOCK loop needs no CAN host. Decided by Amish, 2026-09-25: go with recommendation.
- **Laser ring ahead of a fixed fisheye camera,** Class 2, 520 nm, rather than structured light, stereo or a pan-tilt head. Decided by Amish, 2026-09-25: go with recommendation.
- **Processing on the laptop.** The Pi streams video and sensor data; ring extraction and reports run on the operator's laptop. Decided by Amish, 2026-09-25: go with recommendation.
- **Pipe range 300 to 900 mm.** Kept, with the 900 mm case checked at TRL 3 (R5 not met at 900 mm). Decided by Amish, 2026-09-25: go with recommendation.
- **Value-engineering target \$900.** Decided by Amish, 2026-09-25: go with recommendation. Superseded: target set to \$910 to match the priced BOM, decided by Amish, 2026-09-26 (CVC-DDR-002).
- **Removable laser boom.** Held by two M3 bolts at the fin bracket for the prototype, so it comes off for repair; a tool-free clamp is decided after the first pipe trials. Decided by Amish, 2026-10-02 (CVC-DEC-001).
- **Output order.** The deflection report comes first; observations are logged in NASSCO PACP vocabulary second, and FHWA condition ratings come later. Decided by Amish, 2026-10-02 (CVC-DEC-001).
- **Heavier ballast plate for reach (R2).** 230 x 80 x 14 mm steel, 2.13 kg (was 1.67 kg), plus the operating guidance to enter flooded pipes from the upstream end. Decided by Amish, 2026-09-25: go with recommendation (CVC-DDR-002). Measuring submerged track friction is TRL 4 work, on hold.
- **Ring plane 300 mm ahead of the camera (R5).** Was 200 mm; the boom is 100 mm longer. Decided by Amish, 2026-09-25: go with recommendation (CVC-DDR-002).
- **Cost at \$901.** The \$1 overrun at CVC-CAL-001 v0.1 is accepted as within pricing uncertainty, to revisit when real quotes exist. Decided by Amish, 2026-09-25: go with recommendation (CVC-DDR-002). The \$5 added by the two changes above is within the \$910 value-engineering target Amish set on 2026-09-26 (CVC-DDR-002).
- **Design for construction.** On 2026-09-30, under Amish's instruction to make the design physically buildable, every part was given a way to be made and fixed (CVC-DDR-003): hull rim and drive pads, side plates, bezel, boom fin, laser window, ballast plate resized, eye bolt, reel frame and box chassis. Accepted by Amish, 2026-10-02 (CVC-DDR-003).
- **Camera at 50 frames per second with a circular fisheye.** A TRL 3 engineering choice so that video (R4) and profiling (R5) are both met from one camera; recorded in CVC-CAL-001.

■ Safety

Safety: CulvertCrawl is used at roadside ditches, next to flowing water and at the mouth of a confined space. It carries a lithium battery, 48 V DC on a long cable, a laser and moving tracks. The most important rule is that nobody enters the pipe, including to recover a stuck crawler.

- **Confined space.** A culvert is a confined space and may be a permit-required confined space under OSHA 29 CFR 1910.146 ([osha.gov](https://www.osha.gov)). The purpose of CulvertCrawl is to avoid entry. Never enter or lean into a pipe to free the crawler; pull it out by the tether, or leave it and call a qualified entry team.
- **Hazardous atmospheres.** The crawler is not intrinsically safe and is not rated for flammable atmospheres. Do not use it in sanitary sewers, in storm drains that may receive sewage or fuel, or anywhere methane or other flammable gas may be present. In any enclosed drain, check the air at the mouth with a four-gas monitor before and during work.

- **Traffic, water and banks.** Road culverts put crews on shoulders and steep, wet banks. Use temporary traffic control as the road owner requires (for example MUTCD Part 6 in the United States), high-visibility clothing and a second person as spotter. Do not work in fast or rising water; flash floods can arrive with little warning.
- **Lithium battery.** The surface box holds a 12.8 V 20 Ah LiFePO4 battery (about 256 Wh). Use a battery with a BMS, keep the 10 A battery fuse and the 2 A tether fuse, charge with a matched LiFePO4 charger on a non-combustible surface, and do not charge a battery that is damaged, swollen or has been in water.
- **Electrical.** 48 V DC on the tether is extra-low voltage, but a damaged tether in water can still corrode and short. The surface box has fuses, a 1.5 A overcurrent cutoff and a latching emergency stop; inspect the tether jacket before each use and retire damaged lengths.
- **Laser.** The projector must stay at Class 2 (1 mW or less, visible) under IEC 60825-1. Do not stare into the beam or look at it through optics; switch the laser off when the crawler is out of the pipe.
- **Moving parts and tether.** Tracks and sprockets can pinch fingers; the emergency stop removes drive power. Pull a stuck crawler out by hand only; the strength member is tied to an eye bolt in the ballast plate, so the pull never goes through the seal. Never tie the tether to a vehicle, which can exceed the 1 kN strength member and whip the cable. The reel crank can kick back under tether tension, so use the brake. Keep the tether clear of walkways to avoid trips.
- **Sharp edges and wildlife.** Rusted metal pipe has sharp edges at holes and seams. Wear cut-resistant gloves when handling the tether at the mouth, and watch for snakes, wasps and other animals in and near culverts.

■ Open questions

- Reach in the wet, uphill design case is 52 m on paper but very sensitive to track friction under water; what is the real submerged friction on silt? (TRL 4 measurement, on hold.)
- Will double lip seals on the drive shafts hold IP68, or is a magnetic coupling or a sealed motor pod needed?
- Is a Class 2 laser bright enough near a sunlit mouth or on a reflective wall, or does the camera need a narrowband filter?
- Can a Pi 4 capture at 50 frames per second and run the H.264 and JPEG encoders at once?
- Should the laser boom be quick-release for tight or bent pipes? It comes off with two bolts for the prototype (decided 2026-10-02); a tool-free clamp is decided after the first pipe trials.

■ References

- US Occupational Safety and Health Administration. 29 CFR 1910.146, *Permit-required confined spaces*; and 29 CFR 1926 Subpart AA, *Confined Spaces in Construction*.
- Federal Highway Administration. *Culvert Inspection Manual*. FHWA-IP-86-2, 1986.
- Federal Highway Administration. *Culvert Assessment and Decision-Making Procedures Manual*. FHWA-CFL/TD-10-005, 2010.
- ASTM D2321, *Standard Practice for Underground Installation of Thermoplastic Pipe for Sewers and Other Gravity-Flow Applications*.
- NASSCO. *Pipeline Assessment Certification Program (PACP)*. nassco.org.
- Duran, O., K. Althoefer and L. D. Seneviratne. "State of the Art in Sensor Technologies for Sewer Inspection." *IEEE Sensors Journal* 2, no. 2 (2002).

- Duran, O., K. Althoefer and L. D. Seneviratne. "Automated Pipe Defect Detection and Categorization Using Camera/Laser-Based Profiler and Artificial Neural Network." *IEEE Transactions on Automation Science and Engineering* 4, no. 1 (2007).
- IEC 60825-1, *Safety of laser products, Part 1: Equipment classification and requirements*.
- IEC 60529, *Degrees of protection provided by enclosures (IP Code)*.

On 2026-09-25 the OSHA regulation, both FHWA manuals and both Duran papers were confirmed online by title, number and year (the 2007 paper at *IEEE Transactions on Automation Science and Engineering* 4, page 118). The ASTM D2321 deflection clause, NASSCO PACP, IEC 60825-1 and IEC 60529 were not rechecked.