

DEWDRIVE · CALCULATION

DewDrive sizing calculations

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	DWD-CAL-001	Version	0.6
Status	Draft	Date	2026-10-02
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/dewdrive		
Source	docs/04-calcs/01-sizing.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.6	2026-10-02	Amish Chadha	R9 row and counts follow the restated R9; glazing rating decision noted in section D (DWD-DEC-001, items 2 and 3); no computed number changed
0.5	2026-10-01	Amish Chadha	Budget treated as a value-engineering target
0.4	2026-10-01	Amish Chadha	Re-run on the constructable model (DWD-DDR-003); mass by component and material, outlet slot in the fan duty, new leg span in the wind check, repriced BOM; R9 and R11 not met
0.3	2026-09-26	Amish Chadha	Budget top-up approved by Amish (budget \$520; R11 met); script re-run
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002); design of record now through-flow with 25 wt % salt, drip screens and fan cut-out; paper evaluation of a low-emissivity screen
0.1	2026-09-25	Amish Chadha	First issue for TRL 3 (sorbent isotherm, night adsorption, day desorption and condenser, cyclic yield, stagnation and touch

temperatures, salt containment,
electrical energy, mass, wind, logging,
cost)

DewDrive sizing calculations

This revision checks the design decided by Amish on 2026-09-25 (DWD-DDR-002): night air drawn down through the sealed, mesh-floored trays; 25 wt % CaCl_2 (1.0 kg in 3.0 kg of gel); a black drip screen under each tray; and a fan that stops above 70 % RH. On paper that design, as made constructable in DWD-DDR-003, meets nine of its thirteen requirements. It collects about 0.57 L per day at 40 % night RH (R1 target 0.5 L) and 0.45 L at 25 % (R2 target 0.25 L), against 0.20 and 0.09 L for the v0.1 layout. The salt stays in the pores after three 90 % RH nights in a row. Making the design buildable added the parts that hold it together (wall battens, a tray deck, screen frames, stand bracing and fixings): the estimated parts cost is now \$620 against the \$520 value-engineering target (R11 over the target by \$100) and the full box weighs 35.2 kg against the 35 kg two-person limit, 23.4 kg once the trays and deck are lifted out (R9 not met as written). R9 is an open decision for Amish in the design decisions register (DWD-DEC-001), which also lists cost drivers and savings for R11. A low-emissivity screen, evaluated here as decided, would lift the yield to 0.82 L per day but let a dry bed stagnate at about 166 °C, beyond the usual rating of polycarbonate glazing, so it is not adopted. Every number in this note is printed by `docs/04-calcs/sizing.py`; the tag in brackets, for example [B2], is the line of that script's output that carries it.

Safety: These calculations concern hot surfaces (a bed up to about 122 °C), a corrosive calcium chloride solution, a lithium iron phosphate battery and a 1.1 m² panel in wind. They are first-principles estimates for a paper proof of concept, not a substitute for measured isotherms, supplier data, an engineering review or test. Harvested water must be tested and treated before drinking. See DWD-PRC-001, Safety.

■ Scope and method

The note checks every requirement in DWD-REQ-001 v0.5 against the design in DWD-PRC-001 v0.5 and the parametric model `cad/src/model.py`. The script imports the model's `PARAMS`, `derived()` and components (`build_components()`), each with its material, so the areas, gaps and masses used here are those of the STEP files and of drawing DWD-DWG-001 Rev P4. It reads prices from `bom/bom.csv` and writes the requirement table to `docs/04-calcs/results.csv`. Run it from the repo root with `python docs/04-calcs/sizing.py` (about 6 min; the yield is a time-stepped simulation of repeated night and day cycles until the bed water at dawn repeats).

"Design" means the design of record after DWD-DDR-002. "v0.1 layout" is the earlier design, in which the night air flowed past the trays at 32.5 wt % salt; its figures are kept for comparison and come from v0.1 of this note unless tagged.

■ Assumptions

Table 1. Main assumptions.

Area	Assumption	Basis
Design point	Night 10 h at 20 °C and 40 % RH (low-humidity case 25 %); day air 35 °C; 6.0 kWh/m ² per day on the tilted aperture, as a sine from 06:00 to 18:00; flaps shut at 07:00 and opened at 19:00, bed back at air temperature when the fan starts	DWD-REQ-001
Psychrometrics	IAPWS-IF97 saturation pressure; vapour diffusivity 2.5×10^{-5} m ² /s at 20 °C, scaled with $T^{1.75}$	Standard
Salt solution	Water activity of aqueous CaCl ₂ from the Conde (2004) correlation; solubility 74.5 g/100 g water at 20 °C, 81.1 at 25 °C, 134.5 at 60 °C and 152.4 at 100 °C	Conde, <i>Int. J. Thermal Sciences</i> 43, 2004; Wikipedia
Salt hydrates	Below deliquescence at night: hexahydrate above 18.5 % RH, tetrahydrate from 9 % to 18.5 %; above 29.9 °C the solid is taken as the dihydrate	SaltWiki , calcium chloride (transitions at 20 °C)
Composite	3.0 kg mesoporous silica gel, 1.0 cm ³ /g pore volume, skeleton 2,200 kg/m ³ , packing 0.60; 1.0 kg CaCl ₂ (25 wt %, DWD-DDR-002 D10); the gel walls add 0.08 kg/kg per unit water activity; no pore confinement effect on the salt	Typical wide-pore gel; engineering judgment
Heat of sorption	Clausius-Clapeyron on the isotherm at constant bed water, not less than the latent heat	First principles
Night mass transfer, design	Air drawn down through the bed: packed-bed Wakao correlation for 3.5 mm beads; diffusion inside the grains not modelled (see C9)	Standard; grain kinetics must be measured
Night mass transfer, v0.1 layout	Air splits between the 45 mm gap over the trays and the 65 mm gap under them in proportion to gap cubed (laminar); Nu 4.86 plus a developing-flow term; Lewis analogy; diffusion into the bed with porosity 0.40 and tortuosity 1.5; mesh floor 60 % open	Standard laminar-channel results
Fan cut-out	Fan stops above 70 % RH; natural airflow through the open flaps then taken as 4 m ³ /h, 10 % of the fan flow	Assumption; to check by test
Day, bed	Lumped bed: sorbent, four 0.6 kg aluminium trays and the water; transmittance-absorptance 0.74 on the black tray tops; loss to ambient 3.2 W/(m ² ·K) through the gap and twin-wall glazing	Twin-wall polycarbonate U value about 3 W/(m ² ·K)
Day, vapour path	Stefan diffusion through still air across the 65 mm gap to the condenser (hot above cold is stably stratified); 60 % of the bed area effective through the mesh. The drip screen (two 18 mm deep layers of channels, one third open) adds 18 mm x (1.5 / 0.33 – 1), giving an equivalent path of 128 mm	First principles; geometry from the model
Day, parasitic heat	Radiation from bed to condenser: beads (emissivity 0.9) seen through 60 % open mesh, bare aluminium 0.1 elsewhere, plate 0.9; the drip screen blocks every line of sight and acts as a radiation shield with emissivity 0.90 on both faces (black paint), or 0.15 for the low-emissivity option; conduction across the gap; sun through the gaps between trays onto the plate, absorptance 0.5	Engineering judgment
Condenser	2 mm aluminium plate and 21 fins, 1 x 100 x 920 mm; laminar natural convection on vertical fins; radiation from the fin envelope to shaded ground at ambient; aluminium 205 W/(m·K)	Model; standard correlations

Area	Assumption	Basis
Collection	30 g per day left as drops and films on the plate and gutter	Engineering judgment
Electrical	Fan 2 W for 10 h; logger 0.15 W average; 10 W panel, 5 peak sun hours, 0.70 derating; 12.8 V 6 Ah battery, 80 % usable	DWD-PRC-001
Wind	20 m/s; force coefficient 1.2 on 1.1 m ² normal to the lid; centre of pressure a quarter chord upwind of the centre; friction 0.5; factor of safety 1.5	Engineering judgment

■ A. Air and sorbent

At 20 °C the night air carries 6.92 g/m³ of vapour at 40 % RH and 4.32 g/m³ at 25 % RH [A1]. The Conde correlation puts the deliquescence point of CaCl₂ at 20 °C at a water activity of 0.341, against about 0.30 quoted by SaltWiki [A2]; the difference only matters between 30 and 34 % RH. At 40 % RH the salt is a 40.1 wt % solution holding 1.49 kg of water per kg of salt; at 25 % RH it is the hexahydrate, holding 0.974 kg/kg [A3].

With 1.0 kg of salt the whole bed would hold 1.59 kg of water at equilibrium at 40 % RH (0.397 g/g) and 1.03 kg at 25 % RH (0.258 g/g) [A4], less than the 2.03 and 1.32 kg of the v0.1 loading but still well above what a night delivers. The 3.0 kg of gel has 3.00 L of pore volume; the bed is 7.27 L of beads, 9.3 mm deep on 0.785 m² of tray floor, which matches the model [A5].

■ B. Night adsorption

The fan moves 40 m³/h, so 2.77 kg of vapour passes through the box in a night at 40 % RH, and 1.73 kg at 25 % RH [B4].

Design: air drawn through the bed. The superficial velocity through the bed is 14.2 mm/s and the gas-side number of transfer units is 19, so the air leaves close to equilibrium with the bed; the bed adds only 0.16 Pa of pressure drop [B3]. In the repeating cycle the bed takes up 0.60 kg a night at 40 % RH (a swing of 0.151 g/g), from 0.63 kg at dusk to 1.23 kg at dawn, still below the 1.59 kg equilibrium; the heat of adsorption warms it to 26.9 °C [B5]. At 25 % RH it takes up 0.48 kg [B6]. The night is no longer the limit: the uptake is set by how dry the day leaves the bed.

v0.1 layout, for reference. Air flowing past the trays splits 25 % over and 75 % under them, stays laminar, and reaches NTU 0.31 and 0.06, capturing at most 11 % of the vapour driving force [B1, B2]. That is why v0.1 took up only 0.23 kg a night.

■ C. Day desorption, condenser and yield

The aperture receives 6.00 kWh/m² per day, of which 4.24 kWh/m² falls between 09:00 and 15:00; the peak is 785 W/m² [C1].

Table 2 traces the design point. The bed passes 89 °C by 09:00 and reaches 112 °C at noon [C2]. Vapour moves from about 08:30 to 16:00, peaking at about 120 g/h. By late afternoon the salt has dried towards the dihydrate and desorption stops.

Table 2. Day at the design point (script output, section C).

Hour	Sun (W/m ²)	Bed (°C)	Condenser (°C)	Bed water activity	Desorption (g/h)	Bed water (kg)
07:00	203	25.0	34.2	0.312	0	1.23
09:00	555	89.1	42.7	0.359	51	1.20
11:00	759	108.2	46.7	0.312	121	1.02
12:00	785	112.4	47.1	0.269	119	0.89
13:00	759	113.4	46.8	0.228	97	0.79
15:00	555	102.3	43.9	0.184	37	0.65
17:00	203	71.2	39.2	0.168	0	0.63

Table 3. Yield and energy.

Quantity	Design (black screens)	No screens	Low-emissivity screens	v0.1 layout	Tag
Collected at 40 % night RH	0.57 L per day	0.51 L per day	0.82 L per day	0.20 L per day	C3, C6, C10
Collected at 25 % night RH	0.45 L per day		0.54 L per day	0.09 L per day	C4, C10
Bed at noon; peak	112 °C; 114 °C	peak 101 °C	130 °C; 149 °C	104 °C	C2, C6, C10
Condenser rise above ambient, peak	12.1 K	13.3 K	10.5 K	13.1 K	C2, C6, C10
Condenser load, peak	299 W	333 W	252 W	328 W	C2, C6, C10
Stagnation, dry bed	122 °C	105 °C	166 °C	105 °C	D1
Solar-to-water efficiency	7.1 %		10.1 %	2.5 %	C7

The "no screens" column is the through-flow design at 25 wt % without drip screens. The effective emissivity from the bed underside to the condenser is 0.545 with no screen, 0.327 with black screens and 0.071 with low-emissivity screens; the screens double the equivalent vapour path, from 65 to 128 mm [C5].

The energy balance shows where the sun goes in the design at 40 % RH [C7]: 5.54 kWh falls on the inner aperture; the black trays absorb 3.68 kWh; 0.44 kWh drives desorption; 1.69 kWh is lost back through the glazing; and 1.47 kWh passes from the hot bed to the condenser (0.68 kWh with low-emissivity screens).

The condenser has 3.86 m² of fins with a natural-convection coefficient of 4.7 W/(m²·K) and a fin efficiency of 0.87, giving 24.6 W/K at a 12 K rise [C8]. It holds the peak rise to 12.1 K, inside R5.

Item 5 evaluation (DWD-DDR-002, D12). A radiation screen under the trays does what the TRL 3 review expected: the less heat the bed sheds to the condenser, the hotter and drier it gets by day, and the cooler the condenser stays. The black drip screens needed for D11 already give part of this effect (0.51 to 0.57 L per day, even though they double the vapour path). A low-emissivity screen gives much more (0.82 L per day, 10.1 % efficiency), but with an

empty or dry bed the trays would stagnate near 166 °C, well above the roughly 120 °C service rating usual for twin-wall polycarbonate. Adopting it would need a stagnation vent or a glazing rated for that temperature. That is proposed as a new item (O4), not adopted.

Sensitivity. Diffusion inside the grains is not modelled. If it cut the effective night NTU from 19 to 2 or to 1, the design would still collect 0.56 or 0.53 L per day [C9], so R1 holds with little margin in the worst case.

■ D. Stagnation and touch temperatures

With a dry bed at noon on a 35 °C day, the bed stagnates near 122 °C with black drip screens, 105 °C with no screens and 166 °C with low-emissivity screens [D1]. The glazing inner skin runs cooler than the bed, but the supplier rating of the polycarbonate must be checked against this. Amish decided on 2026-10-02 (DWD-DEC-001, item 3) to specify a sheet rated 130 °C or more, or a 120 °C sheet only if the supplier's data and the inner-skin temperature measured at the TRL 4 stagnation test both show it stays inside its rating. The outer skin of the glazing reaches about 57 °C at stagnation [D2], and the condenser fins, at ankle and hand height, up to 47 °C [D3]. Both are under the 60 °C limit of R13, but the inside of the box is not: the bed and trays are hot enough to burn.

■ E. Salt containment

A calcium chloride solution stays in the beads only while its volume is less than the pore volume. At equilibrium at 40 % RH the solution fills 58 % of the 3.00 L of pores; at 90 % RH it would be 6.35 L, twice the pore volume [E1]. At 25 wt % the pores fill at 71 % RH at 20 °C, against 51 % RH at the v0.1 loading of 32.5 wt % (81 % RH at 20 wt %) [E2].

Kinetics limit what one humid night can do. A 10 h night at 90 % RH with the fan running, from the normal dusk state, takes the bed to 43 % of its pore volume [E3]. Three such nights in a row with overcast days between them, the worst case for a wet spell, fill 43, 54 and 63 % of the pores with the fan left running [E4], and 37, 44 and 50 % with the fan stopped above 70 % RH [E5]. No brine leaves the beads in either case, and the four drip-screen sumps (0.58 L) remain as a backstop [E6]. R7 is met on paper; a chamber test at TRL 4 must confirm it.

■ F. Electrical energy

The fan uses 20 Wh a night and the logger 3.6 Wh a day, 23.6 Wh in all, against 35 Wh a day from the 10 W panel, a margin of 1.48 [F1]. The 76.8 Wh battery, 80 % usable, gives 2.6 days with no sun [F2]. The fan works against only about 3.3 Pa: the 800 x 40 mm inlet above the deck, the 140 x 44 mm outlet slot behind the fan hood (DWD-DDR-003) and 0.16 Pa for the bed, so a 120 mm fan delivers 40 m³/h at low speed [F3]. The humidity cut-out only ever lowers the fan energy.

■ G. Mass

v0.4 takes each component of the constructable model (DWD-DDR-003) with its own material: plywood skins at 0.60 g/cm³, softwood battens at 0.45, PIR at 0.035, aluminium at 2.70 and steel at 7.85, the drip-screen channels at the thickness of 0.5 mm flashing, and catalogue masses for the bought items drawn as blocks (bottle, fan, electronics box, PV panel, sensor shield). The box with its deck, trays, sorbent and drip screens weighs 35.2 kg, the stand 16.6 kg and the whole unit 60.2 kg (133 lb) dry; the walls, with their battens, are 7.6 kg [G1]. The trays, sorbent, deck and drip screens (11.8 kg) all lift out through the open lid, and the box without them is 23.4 kg [G2]. v0.3 gave 33.4 kg for the box and 53.9 kg in total, from massing volumes with averaged densities.

■ H. Wind

At 20 m/s the dynamic pressure is 240 Pa and the normal force on the lid 317 N: 298 N of uplift and 108 N horizontal, against a dry weight of 591 N [H1]. The overturning moment of 271 N·m exceeds the restoring moment of 244 N·m (ratio 0.90), so the unit would still tip without restraint; about 40 kg of ballast on the stand gives a factor of 1.5 [H2]. Sliding has a margin of 38 N without ballast and needs 3 kg for a factor of 1.5 [H3]. Two upwind ground anchors, each rated for 98 N or more in uplift, do the same job [H4]; they are the default restraint (DWD-DDR-002, D13).

■ I. Logging

Five channels every 5 min for 30 days are 8,640 records, about 0.41 MB as CSV [I1]; any microSD card holds years.

■ J. Cost

The BOM has 16 lines and totals \$620 against the \$520 value-engineering target (`budget_usd` , a hypothetical control target, not a limit) [J1], so R11 is over the target by \$100. The v0.3 total was \$515. The difference is the cost of making the design buildable (DWD-DDR-003): new line 16, the tray deck and wall ledges (\$35); wall battens, inserts and paint (\$13 more on line 2); the lid's U-channel frame, hinges and latches priced in full (\$15 more); trays with a perforated floor under the mesh (\$10 more in all); fin feet, rivets and epoxy (\$4); a proper drain fitting (\$7); stand bracing, foot plates and straps (\$3); screen frames (\$4 in all); pole, bracket and backing plate (\$6); the fan hood (\$1); and fixings (\$7). Cost drivers and savings worth trying are in the Value engineering section of the design decisions register. Over 5 years at the design point the parts cost about \$0.59 per litre of water [J2].

■ K. Requirements

Table 4. Requirement status (DWD-REQ-001 v0.7). Also written to `docs/04-calcs/results.csv` .

ID	Requirement	Value	Target	Status
R1	Water at the design point	0.57 L/day	0.5 L/day or more	Met
R2	Water in dry nights	0.45 L/day at 25 % RH	0.25 L/day or more at 25 % RH	Met
R3	Sun-only regeneration	Bed 112 °C at noon	75 °C or more by midday	Met
R4	Own electrical loads	23.6 Wh/day against 35 Wh/day of PV; 2.6 days of autonomy	30 Wh/day or less; 2 days or more	Met
R5	Condenser rise	12.1 K	15 K or less	Met
R6	Water quality	Food-grade materials by selection; chloride carry-over needs a water test	Food-grade; chloride below 250 mg/L	Not verifiable at TRL 3
R7	Salt containment	Pores fill at 71 % RH; 43 % of the pore volume after one 90 % RH night; 50 % after three with the fan rule; sumps 0.58 L	No brine leaves the tray and drip-screen assembly after a 90 % RH night	Met
R8	Two actions per day	Open the flaps at dusk, close them at dawn; the fan runs on the logger timer with a humidity cut-out	2 actions, 5 min or less	Met
R9	Portable	Box 35.2 kg with everything inside; 23.4 kg with the trays and deck lifted out; total 60.2 kg	Box 35 kg or less when lifted with the trays and deck taken out (restated 2026-10-02, DWD-DEC-001 item 2); stand separable	Met (was not met by 0.2 kg against the first wording)
R10	Survive the site	Two anchors of 98 N (default) or 40 kg of ballast at 20 m/s; UV life and 300 cycles need supplier data and test	Stable at 20 m/s; UV-stable; 300 cycles	Not verifiable at TRL 3
R11	Cost	\$620	\$520 or less	Over the value-engineering target by \$100
R12	Record performance	8,640 records, 0.41 MB	Every 5 min for 30 days	Met
R13	Protect users	Glazing outer skin about 57 °C at stagnation; fins up to 47 °C; 12.8 V DC	Touched surfaces 60 °C or less; below 60 V DC	Met

Counts: 10 met, 1 over its value-engineering target (R11), 2 not verifiable at TRL 3 (R6, R10), with R9 as restated on 2026-10-02. The computed counts [K1] in `results.csv` still use the first wording of R9 until `sizing.py` is re-run.

■ L. Numbers changed from v0.1

Table 5. v0.1 figures against this revision. DWD-PRC-001 and DWD-REQ-001 v0.4 carry the new values.

Quantity	v0.1 (as drawn)	v0.2 (design)	Tag
Salt loading; bed depth	32.5 wt %; 8.3 mm	25 wt %; 9.3 mm	A5
Overnight uptake	0.23 kg	0.60 kg	B5
Water at 40 % night RH	0.20 L per day	0.57 L per day	C3
Water at 25 % night RH	0.09 L per day	0.45 L per day	C4
Bed at noon	104 °C	112 °C	C2
Condenser rise; load	13.1 K; 328 W	12.1 K; 299 W	C2
Solar-to-water efficiency	2.5 %	7.1 %	C7
Stagnation, dry bed	105 °C	122 °C	D1
Glazing outer skin; fins	53 °C; 48 °C	57 °C; 47 °C	D2, D3
Pore-filling humidity	51 % RH	71 % RH	E2
Mass; box	51.4 kg; 30.9 kg	53.9 kg; 33.4 kg	G1
Ballast; anchor rating	49 kg; 120 N	46 kg; 114 N	H2, H4
Parts cost	\$488	\$515	J1
Water cost over 5 years	\$1.34 per litre	\$0.49 per litre	J2

Table 6. Numbers changed by the constructable design (DWD-DDR-003). Water, heat, salt and electrical figures are unchanged.

Quantity	v0.3	v0.4	Tag
Box; total mass	33.4 kg; 53.9 kg	35.2 kg; 60.2 kg	G1
Box with trays (and now the deck) out	24.0 kg	23.4 kg	G2
Fan duty	about 0.4 Pa	about 3.3 Pa	F3
Ballast; anchor rating	46 kg; 114 N	40 kg; 98 N	H2, H4
Parts cost	\$515	\$620	J1
Water cost over 5 years	\$0.49 per litre	\$0.59 per litre	J2

■ M. Limits of this note

- The isotherm is built from bulk salt thermodynamics. Salt confined in silica pores behaves differently, and the Conde parameters are used outside the range of the fit at the high-temperature, high-concentration end. Measured isotherms of the actual composite at 20 °C and at 80 to 120 °C must replace it. The Conde parameters should also be checked against the paper.

- The day model treats the vapour gap as still air and the drip screen as a simple added path and radiation shield. Any convection in the tilted box would speed up desorption; leaks at the flaps would lose vapour. Both need a test.
- Diffusion inside the grains is not modelled; C9 shows the yield still meets R1 if it cuts the night NTU to 1, but with only 6 % margin.
- The natural airflow with the fan stopped ($4 \text{ m}^3/\text{h}$) is an assumption; E4 shows that R7 holds even if the fan keeps running.

Safety: A proof of concept on paper does not show that the water is safe to drink. R6 (water quality) needs a laboratory water test before anyone drinks the water, and the documents keep the instruction to test and treat it.