

DUSTBADGE · DESIGN DECISION RECORD

DustBadge recommendations accepted

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	DBG-DDR-002	Version	0.2
Status	Draft	Date	2026-09-26
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/dustbadge		
Source	docs/decisions/0002-recommendations-accepted.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.2	2026-09-26	Amish Chadha	Budget set to \$91 to cover the priced BOM: decided by Amish, 2026-09-26 (O3 closed)
0.1	2026-09-25	Amish Chadha	Record the recommendations accepted by Amish on 2026-09-25, what changed in the repo, and the items still open

0002: Recommendations accepted

- **Date:** 2026-09-25
- **Status:** accepted. Every item below marked "Decided by Amish, 2026-09-25: go with recommendation" is accepted; items without a recommendation remain open, except O3 (budget), decided by Amish on 2026-09-26.

■ Context

On 2026-09-25 Amish wrote: "i accept all your recommendations, go with them across all repos." This record lists every item in `docs/REVIEW.md` (TRL 2 and TRL 3 sessions) and in DBG-DDR-001 that carried a recommendation, now decided, and what changed in the repo. Items without a recommendation stay "Proposed, awaiting Amish". Where a recommendation offered several options, the recommended option is the decision. TRL 4 remains on hold by Amish's instruction, and `trl` and `trl_target` stay at 3.

■ Options considered

The options for each item are those listed in `docs/REVIEW.md` (sessions 2026-09-25, /populate and TRL 3) and in DBG-DDR-001.

■ Decision

Table 1. Items decided by Amish, 2026-09-25: go with recommendation.

#	Item	Decision	What changed in the repo
D1	Particle sensor (DDR-001 D1)	Sensirion SPS30 class with a PM4 output, about \$48	Wording only. Its characterization above 1 mg/m ³ is test work (TRL 4, on hold), and CalRig cannot do it as designed; listed as a cross-repo action in docs/REVIEW.md
D2	How silica is shown (DDR-001 D2)	Respirable dust always; RCS only as a labeled estimate once a site silica fraction is entered	Wording only
D3	Default limits (DDR-001 D3)	US OSHA and MSHA values by default (25 µg/m ³ action level, 50 µg/m ³ limit), configurable	Wording only (DBG-PRB-001 v0.4, DBG-PRC-001 v0.4, DBG-REQ-001 v0.4)
D4	Sampling mode (DDR-001 D4)	Continuous sampling	Wording only
D5	Data ownership (DDR-001 D5)	Logs kept by the worker, shared only by consent, never used for discipline	Wording only
D6	First sector (DDR-001 D6)	Surface quarries and stone fabrication first; underground coal and explosive atmospheres excluded	Wording only; the partner stays open (O1)
D7	Case details (DDR-001 D7)	Downward screened inlet, high-visibility yellow front shell, spring clip with strap loop	Wording only (already in the model)
D8	Cell size (R7)	Option (b): a larger cell up to 11.5 mm thick; 2,000 mAh chosen to clear the 1,880 mAh worst-case need	cad/src/model.py : cell 50 x 34 x 10 mm, 1,500 mAh, 30 g to 50 x 34 x 11.5 mm, 2,000 mAh, 38 g; STEP and STL re-exported; DBG-DWG-001 Rev P1 to P2; BOM line 8 \$10.00 to \$13.00; media regenerated. DBG-CAL-001 v0.2: worst-case run time 9.6 h to 12.8 h, typical 13.3 h to 17.7 h, R7 at risk to met; mass 111.8 g to 119.8 g (R9 met, 0.2 g margin); charge 3.4 h to 4.2 h; parts \$88.00 to \$91.00, R15 met to not met by \$1
D9	R3 accuracy	Option (a): keep ±25 % and require a 4.2 L/min cyclone over two shifts for low-dust, high-silica sites	R3 target restated with the reference rule in DBG-REQ-001 v0.4; DBG-CAL-001 v0.2 section F: ±21 % (quarry) and ±22 % (quartz-rich stone) with a factor per task, ±29 to ±30 % with a shared factor; R3 not met to at risk
D10	Sun exposure (R11)	The use rule now (wear the badge shaded when the ambient is above 40 °C in full sun); a lighter shell tested at a later TRL	Use rule added to R11 (DBG-REQ-001 v0.4), the precis safety section, the README and the DBG-DWG-001 notes. DBG-CAL-001 v0.2 [C3]: shell at most 57.8 °C (was up to 62.8 °C), 2.2 K under the sensor's 60 °C limit; R11 not met to at risk. The lighter shell test is TRL 4, on hold

#	Item	Decision	What changed in the repo
D11	Range (R2)	Accept the 1 mg/m ³ range with the over-range flag for the first sectors in D6	R2 restated from 0 to 5 mg/m ³ to 0 to 1 mg/m ³ with minutes above the range flagged, logged at the limit and counted (DBG-REQ-001 v0.4); R2 not met to met on paper. The flag was already in the alert logic

Table 2. Items still open.

#	Item	Status
01	First co-design partner (worker organization, NGO or university hygiene group). No recommendation was made.	Proposed, awaiting Amish
02	How a site silica fraction is obtained where no laboratory is near. DBG-PRB-001 proposed one filter sample per site and task analyzed by a partner laboratory, but the item was not in the review list and carried no recommendation.	Proposed, awaiting Amish
03	Budget figure for the larger cell. The parts now cost \$91.00 against <code>budget_usd</code> of \$90. The TRL 3 note left "the budget question for Amish" without a recommended figure, so <code>budget_usd</code> stays at \$90.	Decided by Amish, 2026-09-26: budget set to \$91 (see below)

Budget approved, 2026-09-26

On 2026-09-26 Amish wrote: "i approve all the budget items."

- Budget set to \$91 to cover the priced BOM: decided by Amish, 2026-09-26. This closes O3. `project.yaml` `budget_usd` 90 to 91; DBG-REQ-001 R15 target \$91, status Not met to Met on paper; DBG-CAL-001 v0.3 (`sizing.py` rerun); DBG-PRB-001, DBG-PRC-001, README, `bom/bom-notes.md` and the blueprint key figures updated. The BOM and geometry are unchanged.

■ Consequences

- Requirement status (DBG-CAL-001 v0.2): not met 2 (was 4), at risk 2 (was 1), not verifiable at TRL 3 1, met on paper 6 (was 5), met by design 4. Not met: R14 (intrinsic safety, out of scope) and R15 (\$91.00 against \$90, O3).
- After the 2026-09-26 budget approval (DBG-CAL-001 v0.3): not met 1 (R14), at risk 2, not verifiable at TRL 3 1, met on paper 7, met by design 4.
- `project.yaml`: no change. `budget_usd` stays at \$90 (O3), and no pitch or problem rewording was recommended.
- Documents bumped: DBG-PRB-001 v0.4, DBG-PRC-001 v0.4, DBG-REQ-001 v0.4, DBG-CAL-001 v0.2, DBG-DDR-001 v0.2; drawing DBG-DWG-001 Rev P2.
- Cross-repo action: CalRig's smoke chamber (5 to 300 µg/m³) cannot characterize the SPS30 above 1 mg/m³ with mineral dust, so D1's characterization needs a dust generator or partner laboratory; DustBadge uses CalRig only for badge-to-badge and drift checks. Listed in `docs/REVIEW.md`; CalRig is not edited from this repo.
- TRL 4 work (sensor characterization with mineral dust, a lighter shell under a solar lamp, drop and spray tests, a bench build, buying parts, firmware beyond a sketch) remains on hold.