



REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-09-30	AC




TOP VIEW

Scale 1:5; looking down (along -Z)



FRONT VIEW

Scale 1:5; looking at the front (along +Y)



RIGHT VIEW

Scale 1:5; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Post: 40 x 20 tube, 206 long; two 6.5 mm holes across at the bottom to bolt to the rail-start cross member's row side.

Contact block: 20 x 77 x 38 from HDPE or PTFE, holding the three spring contacts (charge +, charge -, anemometer), screwed to the post's lower-edge side at the top.

Latch tab: 6 mm plate 65 x 30; 7 mm hole 45 from the block end; chamfer the free end's underside 45 degrees so the robot's pin rides up onto it. Screwed on top of the block.

Fit: the contact faces stand 2 mm from the robot's contact block when the robot is parked; the pin drops through the hole.

Check: each spring contact moves 3 mm freely.

DUSTRUNNER		github.com/BoujeeEnjinia1701/dustrunner		
DustRunner contact post, dock contacts and latch tab: making sketch				
DRAWING NO. DRN-DWG-118		REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:5	UNITS mm	PROJECTION 	DATE 2026-09-30	DRAWN Amish Chadha
MATERIAL / NOTES Aluminium tube 40 x 20 x 2; insulating block; plate 6 mm				
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com			Generated from cad/src; do not edit by hand	