

FIELDNODE · DESIGN DECISION RECORD

FieldNode TRL 2 review decisions

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	FND-DDR-001	Version	0.2
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/fieldnode		
Source	docs/decisions/0001-trl2-review-decisions.md @ bf605a8		

REVISION HISTORY

Version	Date	Author	Change
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.1	2026-09-25	Amish Chadha	Record the TRL 2 review recommendations adopted for TRL 3 work under Amish's 2026-09-25 instruction, and the items that remain open

0001: TRL 2 review decisions

- **Date:** 2026-09-25
- **Status:** accepted for D1 to D12. Decided by Amish, 2026-09-25: go with recommendation (see FND-DDR-002). Items O1 to O3 had no recommendation and remain "Proposed, awaiting Amish".

■ Context

The TRL 2 review note (docs/REVIEW.md , session 2026-09-25, /populate) listed ten items as "Proposed, awaiting Amish", and the design precis FND-PRC-001 v0.2 listed eight key design choices, all marked proposed. On 2026-09-25 Amish asked for this batch of Design Molecule repos to be taken through the usual process with the instruction "you know the drill, nothing gets past TRL 3". He has not reviewed this repo's items one by one. Every item that carried a recommendation is therefore adopted as recommended for TRL 3 work, open for his review. Items without a recommendation stay open. Later on 2026-09-25 Amish wrote "i accept all your recommendations, go with them across all repos", so D1 to D12 are now decided (FND-DDR-002).

■ Options considered

The options for each item are those listed in docs/REVIEW.md (session 2026-09-25, /populate) and in FND-PRC-001 v0.2, Key design choices.

■ Decision

Table 1. Items decided.

#	Item	Adopted recommendation	Status
D1	Radio	LoRaWAN now; cellular LTE-M or NB-IoT kept as a later variant; LoRa point-to-point not used	Decided by Amish, 2026-09-25: go with recommendation
D2	Controller module	STM32WL-class single-chip module (for example RAK3172 or Wio-E5)	Decided by Amish, 2026-09-25: go with recommendation
D3	Energy storage	One 6 Ah LiFePO4 cell with a 1S protection IC, fuse and NTC on the power board; CellGuard (4 to 16 cells) not used	Decided by Amish, 2026-09-25: go with recommendation
D4	Panel size	6 W standard; 3 W and 10 W variants kept as later options	Decided by Amish, 2026-09-25: go with recommendation
D5	Sensor port standard	Two M12 5-pin ports carrying I2C, UART or RS-485, one analog input and a switched rail, plus a gland for fixed-cable sensors; pinout to be agreed with the first two adopting projects (see O2)	Decided by Amish, 2026-09-25: go with recommendation
D6	Default reporting interval	15 min, adjustable from 1 min to 24 h within airtime limits	Decided by Amish, 2026-09-25: go with recommendation
D7	Default network	TwinKit gateway first, The Things Network as the public fallback, any LoRaWAN server allowed	Decided by Amish, 2026-09-25: go with recommendation
D8	Enclosure	Stock light grey polycarbonate IP65 box with an ePTFE vent, rather than a printed ASA enclosure	Decided by Amish, 2026-09-25: go with recommendation
D9	Panel as sun and rain hood (precis choice 4)	Panel mounted above the enclosure to shade it and shed rain from the lid seam	Decided by Amish, 2026-09-25: go with recommendation
D10	Antenna pointing down (precis choice 5)	Whip on a bottom bulkhead, out of the panel's shadow and away from hands at the lid	Decided by Amish, 2026-09-25: go with recommendation
D11	Mounting height (precis choice 7)	Enclosure base about 1.75 m above ground, reachable from a short ladder	Decided by Amish, 2026-09-25: go with recommendation
D12	Budget, pitch and problem	No change was recommended; <code>budget_usd</code> stays at \$150 and the pitch and problem lines are unchanged	Decided by Amish, 2026-09-25: go with recommendation

Table 2. Items that remain open.

#	Item	Status
01	First adopting projects and pilot region, which set the radio band (EU868, US915, AS923 or IN865) and the antenna. No preference stated and no recommendation made.	Proposed, awaiting Amish
02	Sensor port pinout. D5 fixes the connector and the signal set; the pin assignment is to be agreed with the first two adopting projects. FND-CAL-001 offers a candidate (pin 1 switched rail, 2 data A, 3 ground, 4 data B, 5 analog) for that discussion only.	Proposed, awaiting Amish and the adopting project teams
03	Firmware update method in the field (sealed USB port or over the air). No recommendation was made.	Proposed, awaiting Amish

■ Consequences

- `project.yaml` : only the TRL fields and the evidence list change. `budget_usd` , the pitch and the problem are unchanged.
- FND-PRB-001, FND-PRC-001 and FND-REQ-001 are revised to v0.3. The design choices in the precis are no longer described as "proposed"; since FND-DDR-002 they are decided.
- Requirement R11 is restated to match D5: each port carries one switched rail, selectable at 3.3, 5 or 12 V, because a 5-pin connector cannot carry three rails, a bus and an analog input at once. Requirement R16 is restated to make explicit that it costs the FieldNode core (enclosure, power, radio, panel and mounting), the figure that sibling projects cite when they cost their own parts separately. No other target changes.
- The TRL 3 calculations (FND-CAL-001) found problems that need Amish's decision: interior heat in hot, sunny weather blocks charging (R3 not met, R5 at risk), a sun shield would fix it but adds cost and mass, a 6 V class panel leaves no voltage headroom when hot, and the sensor allowance of 115 mW has no autonomy margin. They are decided in FND-DDR-002, not in this record.
- The internal mounting plate is specified in printed ASA rather than aluminium, which the TRL 2 BOM already allowed, to save about 0.11 kg against R14. This is a detail choice within D8, not a new decision.
- TRL 4 is on hold by Amish's instruction. Nothing in this record authorizes building or testing.