

GRAVITYSORT · CALCULATION NOTE

GravitySort sizing calculations

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	GVS-CAL-001	Version	0.5
Status	Draft	Date	2026-10-01
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/gravitysort		
Source	docs/04-calcs/01-sizing.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.5	2026-10-01	Amish Chadha	R11 restated by Amish (total 100 kg or less, loads 30 kg or less; GVS-DDR-003, A1); R11 met on paper at 95.7 kg
0.4	2026-10-01	Amish Chadha	Constructable design (GVS-DDR-003). Hollow spindle and new bearing positions; mass 95.7 kg (R11 not met, every load under 30 kg); cost \$558 reported against the \$455 value-engineering target
0.3	2026-09-26	Amish Chadha	Budget approved by Amish (\$455); R9 from not met to met on paper
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002). Budget \$450; R12 reworded; frame, pedal outrigger and table stand in 25 x 25 x 1.5 mm tube with a frame member check; mass, cost and results updated
0.1	2026-09-25	Amish Chadha	First TRL 3 sizing note (speed and G, throughput, water, settling, fluidization supply, power, mass balance, table drive, rotor safety and brake, mass, cost, gold balance)

GravitySort sizing calculations

On paper, GravitySort meets eight of its fourteen requirements, by calculation or design review, and misses none. Since version 0.4 the note follows the constructable design of GVS-DDR-003, in which every part of the model can be made and fixed to the parts next to it. That design is heavier and dearer than the concept: it weighs 95.7 kg in six loads, with every load under 30 kg (the heaviest is 25.2 kg), which meets R11 as restated by Amish on 2026-10-01 (100 kg or less in all; it was 80 kg, which the design missed by 16 kg); and the parts cost is \$558 against a value-engineering target of \$455, USD 103 over (the budget is a hypothetical control target, not a limit; Amish, 2026-10-01). R2 (throughput per shift), R5 (table ratio) and R6 (pedal power at 80 G) are at risk. R4 (recovery) and R14 (liner life) cannot be verified before testing. The bowl, jacket and drive did not change, so speed, G, power, water, settling and burst figures are as in v0.3. The spindle is now a 25 x 2 mm tube that carries the fluidization water; its first critical speed falls to about 2,710 rpm, still 2.3 times the sprint speed. Two findings from v0.1 stand: the fluidization supply only works with a 3/4 in hose from the 1.25 m header post, and the machine needs a water pump that is not in the design.

Every number here is printed by `docs/04-calcs/sizing.py` (run from the repo root: `python docs/04-calcs/sizing.py`), which also writes `docs/04-calcs/results.csv`. The script reads the geometry from `cad/src/model.py` and the costs from `bom/bom.csv`. All values are first-principles estimates for a paper design; nothing is measured.

■ 1. Assumptions

Table 1. Inputs. All are assumptions.

Input	Value	Basis
Feed	200 kg/h dry solids below 2 mm, 30 % solids by mass; 8 h shift; flush every 2 h, 5 min per flush	GVS-REQ-001 R2 and R13
Fluidization water	12 L/min	Mid-range of 8 to 15 L/min (GVS-PRC-001)
Bowl geometry	Liner surface 220 mm lip, 130 mm base, 180 mm deep; four rings 6 mm thick, 12 mm deep, 38 mm pitch; 8 mm PU liner on a 4 mm GFRP shell; 12 mm jacket gap, 4 mm jacket wall	cad/src/model.py PARAMS
Drive	48T chainring, 12T freewheel, 1:1 bevel box, 300 mm to 100 mm V-belt; 12:1	cad/src/model.py PARAMS
Drivetrain efficiency	Chain 0.97, jackshaft bearings 0.99, bevel box 0.93, V-belt 0.94: 0.839 overall	Typical values for used parts
Spindle drag	0.03 N m per contact-sealed bearing unit, 0.10 N m for the rotary union seal, 1 W windage and splash at 730 rpm	Assumed; no datasheet chosen
Motor option	MotionCore reference 250 W geared hub motor, no-load 250 rpm at full pack voltage, 85 % of that under load; motor and controller 70 % efficient at about 60 W	MTC-PRC-001; motor speed assumed
Bed and film	Bed 12 mm deep when full, 50 % solids of 4,000 kg/m ³ (2,500 kg/m ³ bulk); 60 % fill at flush, 2.5 kg/L wet; slurry film 5 mm	Assumed; heavy minerals such as magnetite and pyrite dominate the bed
Gold shape	Flaky gold settles at half the velocity of a sphere of the same sieve size	Assumed shape factor
Fluidization supply	Tank water level 1.45 m, union 0.15 m above ground; 4 m of 3/4 in hose, friction factor 0.03; union, rotameter and valve K = 6 on a 1/2 in bore; hole discharge coefficient 0.62	Model layout; typical hydraulics
Rotor materials	PU 1,150 kg/m ³ , 20 MPa tensile; hand-laid GFRP 1,800 kg/m ³ , 80 MPa tensile; stainless spindle tube 25 x 2 mm, E = 193 GPa	Typical values; spindle per GVS-DDR-003
Brake	Bicycle mechanical disc, 160 mm rotor, pad radius 70 mm, friction 0.4, 150 N per pad with a light pull	Typical values
Gold balance	5 g/t reference ore; oversize loss 5 %, bowl 71 %, table 93 %, smelting 96 %	GVS-PRC-001 Figure 2; assumptions, not calculations
Frame tube	25 x 25 x 1.5 mm mild steel square tube, 1.11 kg/m, yield 235 MPa, E = 200 GPa (was 30 x 30 x 2 mm, 1.76 kg/m)	GVS-DDR-002 (item 10)
Value-engineering target	budget_usd \$455 (was \$450, and \$350 before that), a hypothetical control target, not a limit	project.yaml, GVS-DDR-002 (item 1; \$455 approved by Amish on 2026-09-26); Amish, 2026-10-01

■ 2. Speed and G (R3)

The pedal drive gives 12:1, so a 61 rpm cadence turns the bowl at 730 rpm: **59.6 G at 100 mm radius**. The R3 range of 40 to 80 G at 100 mm needs 598 to 846 rpm, a cadence of 50 to 71 rpm; the comfortable 55 to 70 rpm band gives 660 to 840 rpm (49 to 79 G). At 730 rpm the four riffle rings run at 46, 52, 57 and 63 G (wall radii 77.5, 87.0, 96.5 and 106.0 mm), and the lip speed is 8.41 m/s.

R3 asks for the speed to be shown to the operator. A wired bicycle computer (BOM item 19) with its magnet on the spindle pulley and its wheel size set to 1,667 mm reads km/h equal to bowl rpm divided by 10, so 730 rpm reads 73.0. **R3 is met on paper.**

■ 3. Throughput (R2)

At 200 kg/h the bowl is flushed every 2 h, so an 8 h shift has three mid-shift stops of 5 min and 7.75 h of feed time: **1.55 t per shift**, not 1.6 t. Meeting 1.6 t needs 206 kg/h, or an 8.25 h shift. The bowl's hydraulic capacity at 200 kg/h is supported by the settling check in section 5 but is not proven. **R2 is at risk** (GVS-DDR-001 item 13).

■ 4. Water (R8)

Slurry at 30 % solids carries 0.467 m³/h of water, and fluidization adds 0.72 m³/h: **1.19 m³/h**, 9.2 m³ per shift, against 1.5 m³/h. The slurry is 0.542 m³/h at 1,230 kg/m³, and 0.351 L/s leaves over the lip. **R8 is met on paper.**

The 60 L header tank holds only 3.0 min at full flow. Water must be pumped from the settling pond continuously; lifting 1.19 m³/h by about 1.7 m takes 5.5 W of hydraulic power. The pump is not in the BOM and is not driven by the pedals, so a pedal-only site still needs a hand pump, a second rider or gravity supply from upstream (GVS-DDR-001 item 12).

■ 5. Settling in the bowl (R4 plausibility)

This check shows only that the bowl is not too short for fine gold to reach the wall; whether the bed keeps it is the question that only testing answers. At 730 rpm and 100 mm the acceleration is 584 m/s². The wetted wall is 186 mm long; with an assumed 5 mm film the mean film velocity is 0.091 m/s and the transit time about 2.0 s.

Table 2. Settling velocity at 60 G (Schiller and Naumann drag) and the ratio of transit time to the time to cross the film.

Particle	Settling velocity	Time to cross 5 mm	Ratio
Gold, 20 µm flake	88 mm/s	57 ms	36
Gold, 38 µm flake	213 mm/s	23 ms	87
Gold, 38 µm sphere	426 mm/s	12 ms	173
Gold, 75 µm flake	450 mm/s	11 ms	183
Quartz, 38 µm	61 mm/s	82 ms	25
Quartz, 150 µm	362 mm/s	14 ms	147

Every particle, quartz included, reaches the wall many times over. Separation therefore depends on the fluidized bed letting dense grains displace light ones in the rings, not on reaching the wall. The fluidization upflow of 2.7 mm/s through 0.074 m² of groove is 4 % of the settling velocity of 38 μ m quartz, so it loosens the bed without washing out fine particles. **R4 cannot be verified at TRL 3 and remains the main technical risk.**

■ 6. Fluidization jacket and supply (R4, R8)

The jacket rotates with the bowl, so the water in it gains centrifugal pressure $\rho\omega^2r^2/2$ on its way out from the rotary union at the axis. Against it, each ring's loaded bed and film push back with a pressure that also rises with ω^2 . At 730 rpm with a full bed, the net pressure across a hole is 6.5, 9.0, 12.1 and 15.7 kPa at rings 1 to 4, falling to 5.6 to 11.8 kPa at 600 rpm. It stays positive, so water always flows into the bed, but the lowest ring gets 0.64 times the flow per hole of the top ring.

Delivering 12 L/min takes about **89 holes of 1.0 mm** (about 22 per ring); grading them toward the lower rings evens out the flow. The 3/4 in hose and graded holes are decided (GVS-DDR-002, item 11).

The supply works only with a 3/4 in hose. The header gives 12.8 kPa of static head; the 3/4 in hose loses 1.6 kPa and the union, rotameter and valve 7.5 kPa, leaving 3.7 kPa at the union. With a 1/2 in hose the hose loss is 11.8 kPa and the union would see a suction of 6.5 kPa, so the jacket would run partly empty. For a net 10 kPa at every ring at 600 rpm the union needs 8.1 kPa, a water level of 1.90 m (about a 1.7 m post) or a small pump. Which of the two provides the head is still open, together with the site water pump (GVS-DDR-002, items 11b and 12).

■ 7. Power (R6, R7)

The power to bring the slurry and fluidization water (0.385 kg/s) up to lip speed is $m \cdot v^2$, an upper bound that counts the slip loss. The drag from the two bearing units and the union seal is added, then divided by the drivetrain efficiency of 0.839.

Table 3. Power at the pedals.

Bowl speed	Slurry and water	Drag	At the pedals
600 rpm (40 G)	18.4 W	10.6 W	34.6 W
730 rpm (60 G)	27.2 W	13.2 W	48.2 W
850 rpm (80 G)	36.9 W	15.8 W	62.8 W
1,200 rpm (100 rpm sprint)	73.6 W	24.5 W	116.9 W

At 60 G the rider supplies 48.2 W with a crank torque of 7.6 N m, inside the 60 W target. At 80 G the target is exceeded. The union seal drag is a guess and makes up most of the drag. **R6 is at risk** (met at 60 G, not at 80 G). The TRL 2 estimate of about 45 W is corrected to 48.2 W.

With the motor, the 250 W MotionCore reference drive has a margin of **5.2 times** at 60 G and 4.0 times at 80 G, so **R7 is met on paper**. At 70 % motor and controller efficiency a shift takes **0.55 kWh** from the pack (TRL 2: about 0.5 kWh). A motor chain step-up of 1.20:1 means the motor's 250 rpm no-load speed gives at most 900 rpm at the bowl, and about 765 rpm under load; the ratio must be set for each motor so that its no-load speed at full pack voltage stays within 900 rpm.

■ 8. Mass balance (R5)

The four ring grooves hold 0.89 L. At 60 % fill and 2.5 kg/L each flush yields **1.33 kg**, a mass pull of **0.33 %** of the 400 kg fed in 2 h, against 0.5 %. Four flushes give 5.3 kg per shift. Reaching 100 g needs a table reduction of **53:1**; a single pass on a small table is unlikely to achieve that, but two passes at about 8:1 each (64:1) would give about 83 g. **R5 is at risk** until the table ratio is shown.

■ 9. Shaking table drive

The table head turns at cadence x 4.48 (4:1 chain, 140 mm take-off to 125 mm head pulley): 246 to 314 strokes/min at 55 to 70 rpm. The 240 to 300 strokes/min range needs a cadence of 54 to 67 rpm. At 270 strokes/min and a 15 mm stroke the deck's peak speed is 0.21 m/s and the head takes about 13 W, about 15 W at the pedals, so table clean-up is light work.

■ 10. Rotor safety: inertia, burst, spindle and brake (R12)

Inertia and energy. Integrating the liner, shell, jacket, jacket water, rings and a full bed along the cone gives a rotating group of 6.47 kg with $I = 0.0535 \text{ kg m}^2$, plus 0.0031 kg m² reflected from the drive pulley: 0.0566 kg m² in total. The stored energy is **165 J at 730 rpm**, 224 J at 850 rpm, 252 J at 900 rpm and 447 J at 1,200 rpm (TRL 2: about 150 J at 730 rpm).

Burst. The checks run at $1.2 \times 900 = 1,080 \text{ rpm}$ and at 1,200 rpm, the speed a rider sprinting at a 100 rpm cadence could reach.

Table 4. Stresses at the lip region.

Item	1,080 rpm	1,200 rpm	Safety factor at 1,200 rpm
Jacket wall hoop (water 106 and 130 kPa)	3.8 MPa	4.7 MPa	17 on 80 MPa GFRP
Bowl shell hoop, jacket empty (75 kPa at 1,200 rpm)	2.1 MPa	2.6 MPa	30
PU liner, unsupported hoop	0.19 MPa	0.24 MPa	Liner is pressed onto the shell
Ring lip bending under the bed	0.32 MPa	0.39 MPa	51 on 20 MPa PU

The margins are large because the bowl is small and slow. They do not cover poor lamination, voids or a liner that debonds, which is why the liner must be checked before every run. A quarter of the liner and shell (0.52 kg) leaving the lip at 15.3 m/s carries 61 J; whether the 6 mm HDPE tub and 10 mm lid contain it has not been checked.

Spindle. The spindle is a 25 x 2 mm stainless tube, because the fluidization water runs up its bore (GVS-DDR-003). A 300 N belt pull 55 mm below the centre of the lower bearing gives 21 MPa of bending. With the bowl centre 210 mm above the upper bearing, the first critical speed is about 2,710 rpm, 2.3 times the sprint speed (v0.3, solid shaft with the concept's bearing positions: 4,820 rpm). A 50 g lump of uneven concentrate at 100 mm radius adds a 29 N rotating load at 730 rpm.

Stopping. With the drive stopped, the freewheel lets the bowl coast. From 850 rpm it takes about **20 s** to stop with fluidization water running (the water leaving the lip acts as a brake) and 32 s with the water off, both longer than the 15 s in R12. A bicycle mechanical disc brake on the spindle (BOM item 18) gives 8.4 N m with a light pull and stops the bowl in 0.6 s; only 0.18 N m is needed for a 15 s stop, so the operator should brake gradually. Each stop warms

the rotor by 4.1 K. The brake lever has a parking latch, and a pin on the same cable locks one lid clamp, so the lid can be opened only with the brake applied. With the motor, a lid switch on a MotionCore brake input removes torque (MotionCore stop category 0 does not brake, so the mechanical brake is still needed).

Speed limit. The motor case is capped twice: by the 1.20:1 step-up (section 7) and by the MotionCore speed limit, with its sensor on the spindle. The pedal case is not capped by gearing, because 900 rpm needs a cadence of only 75 rpm. R12 as rewired under GVS-DDR-002 (item 9) asks instead for a burst safety factor of 10 or more at the highest reachable pedal speed (1,200 rpm at a 100 rpm cadence) and a speed display. The lowest factor at 1,200 rpm is 17 (jacket wall), and the display is item 19, so **R12 is met on paper**; containment of a liner fragment by the tub and lid is still not verified.

■ 11. Mass and size (R11)

Table 5. Transport loads (estimates), constructable design.

Load	Mass
1. Base frame with bearing plates, tank cradle, spindle, bearings, brake, union, display (14.5 m of tube at 1.11 kg/m)	25.2 kg (v0.3: 18.1 kg)
2. Drive and pedal station (outrigger 2.1 m of tube, round seat tube, end plates; guards)	18.9 kg (17.8 kg)
3. Bowl, jacket, hub, tub, standpipe and pipes, lid, hopper and its support	14.2 kg (11.5 kg)
4. Table deck and wash pipe	7.6 kg (7.2 kg)
5. Table base, flexure legs, head plate and bearings, pitman, tensioner, table belt guard, launder and box	21.5 kg (15.7 kg)
6. Water tank, valve, rotameter and hoses	5.3 kg (5.0 kg)
Hardware	3.0 kg (2.0 kg)
Total	95.7 kg (77.3 kg)

The constructable design adds 2.7 m of frame tube (lower rails, member pairs either side of the shafts, drop posts, end post), about 10 kg of plate (bearing plates 1.4 kg, tank cradle 3.1 kg, head plate and shelf 3.9 kg, outrigger end plates, caliper bracket, hopper ring) and parts the concept left out (hopper support, standpipe and pipes, tensioner, table belt guard, launder and box legs). The motor cradle (1.3 kg) goes with the motor option and is not counted. The heaviest load is 25.2 kg, so every load is under 30 kg, and the total is 4.3 kg under the 100 kg of R11 as restated by Amish on 2026-10-01 (GVS-DDR-003, A1; it was 80 kg, 15.7 kg below the design): **R11 is met on paper**. The savings of about 16 kg listed in GVS-DDR-003 (A1, option b) are to be tried at TRL 4. The 30 min assembly time is not verified. The overall size from the model is 2.78 x 0.79 x 1.65 m.

Frame member check. The most loaded members are the two spindle members, 600 mm long, which carry the lower bearing plate between them; the check takes one member alone. Taking the 300 N belt pull, the weight of the rotating group and spindle (about 93 N) and the 29 N unbalance load together as one central load of 422 N on a pinned span (an upper bound), the 25 x 25 x 1.5 mm tube sees 61 MPa of bending, a safety factor of 3.9 on 235 MPa, and deflects at most 0.73 mm. That is adequate on paper; bearing alignment under the belt pull should be checked on the first frame (TRL 4, on hold).

■ 12. Cost (R9)

Value-engineering target: USD 455. Estimated cost of the constructable design: USD 558 (USD 103 over the target), excluding the MotionCore kit and reference motor (\$335 per MTC-CAL-001) and the battery. The target is a hypothetical control target that keeps the design on a value-engineering lens, not a spending limit (Amish, 2026-10-01). The concept BOM was \$455; the parts added to make the design buildable (GVS-DDR-003) add \$103, mainly the table stand and head (\$28 to \$52: pillow blocks, plywood legs, head plate, tensioner), the frame (\$32 to \$43: more tube and the plates), the tub fittings (\$12 to \$26: standpipe, tailings pipe, two rubber grommets) and the hub, bolts and spacers (\$10). R9 is reported as **over the value-engineering target by USD 103**. The savings worth trying are in the Value engineering section of the design decisions register (GVS-DEC-001).

■ 13. Gold balance

On the 5 g/t reference ore, 8.0 g of gold enters per shift at 200 kg/h for 8 h; 7.6 g passes the screen, 5.4 g is held in the bowl, 5.0 g stays on the table and 4.8 g is smelted: **about 60 % overall**. Losses are 0.4 g to oversize, 2.2 g to bowl tailings, 0.4 g to table tailings (re-run) and 0.2 g to slag. The stage recoveries are assumptions, not results of this note, and they use the full 8 h of feed.

■ 14. Results

Table 6. Requirements against the calculations, not met items first.

ID	Requirement	Value	Target	Status
R2	Ore per shift	200 kg/h; 1.55 t with 3 flush stops	200 kg/h, 1.6 t per 8 h	At risk (needs 206 kg/h)
R5	Concentrate for smelting	Bowl pull 0.33 %; 5.3 kg/day needs 53:1 on the table	0.5 % or less; 100 g or less	At risk (two table passes)
R6	Pedal power	48.2 W at 60 G; 62.8 W at 80 G	60 W or less	At risk (met at 60 G, not at 80 G)
R4	Fine-gold recovery	Settling ratio 36 or more for 20 µm flakes; overall 60 % assumed	80 % and 50 % in the bowl; 60 % overall	Not verifiable at TRL 3 (at risk)
R14	Liner life	No wear data for this PU on quartz	500 h; replace in 30 min	Not verifiable at TRL 3
R1	No mercury	No amalgamation step	No mercury at any step	Met (design review)
R12	Guards, speed limit, stop time	Brake stop 0.6 s (coast 20 s); motor capped; pedal: burst SF 17 at 1,200 rpm with speed display	Guarded; motor 900 rpm or less; pedal SF 10 or more at sprint speed with display; stop within 15 s	Met (paper); containment not verified
R3	Bowl G and speed display	40 to 81 G over 600 to 850 rpm; display item 19	40 to 80 G, speed shown	Met (paper)
R7	Motor margin	5.2 times at 60 G (4.0 at 80 G)	3 times or more	Met (paper)
R8	Water use	1.19 m3/h	1.5 m3/h or less	Met (paper)
R10	Local workshop build	Welding, drill press, printed mold and six-segment core; set-screw inserts, taper bush, welded nipple	No lathe	Met (design review); casting route unproven
R11	Transport mass	96 kg in 6 loads, heaviest 25 kg	100 kg or less; loads 30 kg or less (restated 2026-10-01)	Met (paper)
R13	Quick, secure clean-up	Toolless lid clamps; lockable container and tray	5 min, no tools	Met (paper); time not verified
R9	Parts cost	\$558	Value-engineering target \$455	Over the value-engineering target by USD 103

■ 15. Corrections to TRL 2 figures

- Pedal power 45 W to 48.2 W; motor energy 0.5 to 0.55 kWh per shift.
- Stored energy at 730 rpm 150 J to 165 J.
- Machine mass 75 kg to 88 kg (the TRL 2 figure is replaced by a load-by-load estimate); 77.3 kg in v0.2 with the lighter tube.
- Parts cost \$437 to \$465 (brake and speed display added), then \$455 in v0.2 with the lighter tube; MotionCore \$325 to \$335.
- Throughput per shift 1.6 t to 1.55 t once flush stops are counted.
- Table reduction "about 50:1" to 53:1 needed for 100 g.

- v0.4 (constructable design, GVS-DDR-003): mass 77.3 kg to 95.7 kg; parts cost \$455 to \$558; spindle first critical speed 4,820 to 2,710 rpm; overall size 2.72 x 0.78 x 1.65 m to 2.78 x 0.79 x 1.65 m.

Safety: Every rotor figure here is a paper estimate. The large burst margins assume sound lamination and a bonded liner; a cracked or debonded liner must never be run. The bowl coasts for about 20 s after the drive stops, so the brake must be applied and parked before the lid is opened. Nobody should run the bowl above 900 rpm, even though a rider can reach it; the speed display is the only warning on the pedal drive, and the reworded R12 relies on the structural margin, not on a speed cap.