

GRIDBENCH · PROBLEM STATEMENT

GridBench problem statement

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	GBN-PRB-001	Version	0.4
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/gridbench		
Source	docs/01-problem.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	TRL 3 update; grid choice and budget scope adopted as recommended (GBN-DDR-001), humidity figures sourced
0.2	2026-09-25	Amish Chadha	Populate to TRL 2 (users, context, constraints, prior work, open questions)
0.1	2026-09-25	Amish Chadha	Initial scaffold

GridBench problem statement

Small workshops cannot make the same part twice to the same standard without a way to put the part in the same place every time, and the tools that do this well are priced for industry while home-made jigs cannot be shared.

■ The problem

Repeatable making depends on fixturing: a datum surface, locating features and clamps that hold each part in a known position while it is drilled, glued, assembled or measured. Industry solves this with modular fixture systems built on a hole grid. A 1,200 x 800 mm welding table from one well-known system, with 16 mm bores on a 50 mm grid, starts at about \$2,561 before any clamps or stops ([Siegmund System 16, US distributor listing](#)). That is more than ten times the whole prototype budget of this project.

Community workshops, makerspaces and informal engineering clusters instead build one-off jigs from scrap. These work, but each is tied to one bench and one person, is rarely documented, and cannot be sent to another workshop as a file. When a design from the lab's portfolio is built in two places, the two builds differ because the holding and checking steps differ.

The missing piece is an open, cheap, documented grid standard: a bench surface with a fixed hole pattern, a library of printable and machinable fixtures that fit it, and a way to publish a jig as a file that works on any bench built to the same pattern.

■ Users and context

User	Need	Context
Makerspace or fab lab technician	A shared bench where members can set up a known jig in minutes and check parts	Mixed-skill users, shared tools, 3D printers and often a CNC router
Small manufacturer or repair shop	Batch assembly and inspection of 10 to 500 parts without buying an industrial fixture table	Workshop of 1 to 20 people, limited capital
Informal-sector artisan cluster	Consistent parts for customers and buyers, with tools made locally	Hand tools, drill press, access to a lathe or shared machine shop
Teacher or technical college	A teaching bench that shows datums, location and clamping	Classroom, safety supervision, repeated use by many students
Open hardware designer	A way to ship a build jig with a design, as a file	Designs published in repos like this one

■ Operating environment

- Indoor workshop, 10 to 35 °C, 20 to 80 % relative humidity, not air-conditioned in many target regions. Over that humidity range wood settles at about 4.5 to 16 % moisture content ([USDA Forest Products Laboratory, Wood Handbook, FPL-GTR-190, Table 4-2](#)), so a plywood top moves with the seasons (GBN-CAL-001, section E).
- Loads from hand assembly, drilling with a hand drill or drill press, light filing and gluing. Not for welding heat or heavy machining forces.
- Users range from trained machinists to first-time makers.

■ Constraints

- Garage-buildable prototype, about \$250 USD in parts (raised from \$220 by Amish on 2026-09-25, GBN-DDR-002) for the bench, grid, tile and fixture set (the dial indicator is user-supplied, GBN-DDR-001 A1), using timber or steel sections, plywood, one aluminum plate and 3D-printed parts.
- Build with common workshop tools: a drill press or hand router with a template, taps and a reamer. A shared CNC router speeds up the worktop but must not be required.
- The grid must be compatible with something already made in volume, so that commercial accessories fit.
- All files open: CAD in build123d source, hardware under CERN-OHL-S-2.0.

■ Prior work

- **Metric optical breadboards** use M6 tapped holes on a 25 mm grid; imperial boards use 1/4-20 on 1 in ([RP Photonics Encyclopedia](#), "[Optical breadboards](#)"). This is a mature, precise grid with a large accessory market, but aluminum or steel breadboards of bench size are costly and too fine for rough work.
- **Modular welding and fixture tables** (for example Siegmund System 16, above) use large bores on a 50 mm grid with hardened surfaces. They are precise and robust, but priced for industry.
- **Machinist fixture plates** combine tapped holes with separate reamed dowel positions so that parts locate on pins and clamp on threads; Saunders Machine Works, for example, specifies dowel pin and bore tolerances in the ten-thousandths of an inch ([SMW fixture plate FAQ](#)). GridBench borrows this split of "locate on dowels, clamp on threads".
- **Multifunction woodworking tables** use 20 mm dog holes on a 96 mm pitch ([In The Woodshop](#), [building an MFT](#)). Widely copied and cheap, but coarse and not meant for small parts or measurement.
- **Open grid storage systems** show how fast a shared grid spreads when files are free: Gridfinity, designed by Zack Freedman in 2022 on a 42 mm grid ([Wikipedia](#), "[Gridfinity](#)"), and Multiboard on a 25 mm grid for walls ([GridPilot comparison](#)). Gridfinity's license is non-commercial, which limits use by small businesses. Neither is a fixture or workholding standard.

No open standard found combines a cheap worktop, a precision zone and a fixture library on one grid.

■ Out of scope

- Welding tables (heat, spatter and weld current need steel tops).
- Heavy machining (milling forces need a machine table, not a bench).
- Powered or automated fixtures.

■ Co-design and validation checklist

- [] Identify two or three first user workshops (for example a fab lab, a small repair business, a technical college) and a local partner. Proposed, awaiting Amish.
- [] Observe how those workshops hold and check parts today, and list the five most common jigs.
- [] Confirm which tools each workshop has (CNC router, drill press, lathe, 3D printer).
- [] Agree what "repeatable" means for their parts (target tolerance) before fixing R3 and R4.

■ Open questions

- Grid: 25 mm with M6 only at first, with a coarser 50 mm variant for heavy work considered later. Decided by Amish, 2026-09-25: go with recommendation (GBN-DDR-001 A2).
- Which workshops test the first benches, and in which countries? No recommendation made. Proposed, awaiting Amish (GBN-DDR-001 O1).