

GROWRIDER · DESIGN PRECIS

GrowRider design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	GRR-PRC-001	Version	0.8
Status	Draft	Date	2026-10-02
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/growrider		
Source	docs/02-concept.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.8	2026-10-02	Amish Chadha	Helmet supplied with every bike, World Bicycle Relief as first candidate partner and Zambia as first candidate region, as decided by Amish on 2026-10-02 (GRR-DEC-001 v0.3)
0.7	2026-10-01	Amish Chadha	GRR-DDR-003 accepted by Amish; quill insertion mark with a bright painted band, painted height scales, frame color and chainguard name as decided
0.6	2026-10-01	Amish Chadha	Constructable design (GRR-DDR-003); cost stated against the value-engineering target
0.5	2026-09-26	Amish Chadha	Budget top-up approved by Amish
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	TRL 3 (decisions of GRR-DDR-001 recorded; numbers replaced by GRR-CAL-001; seat post, stem and head tube sized; model, drawing GRR-DWG-001 and media updated)

0.2	2026-09-24	Amish Chadha	Populate to TRL 2 (architecture, first-order numbers, design choices, safety, media)
0.1	2026-09-24	Amish Chadha	Initial scaffold


GrowRider design precis

GrowRider is a step-through chromoly steel children's bicycle on 20 in wheels whose seat post and stem telescope, so one bike fits riders from about 1.10 to 1.65 m (ages about 6 to 14) and can be handed down between siblings. It uses a coaster brake plus a front rim brake, puncture-proof tires, a single-speed chain drive and a small rack rated 10 kg, with wear parts shared with the region's adult roadsters. The calculation note GRR-CAL-001 v0.4 shows on paper that the fit range, reach, wheel size and rack meet their requirements; mass (about 15.1 kg against the 13 kg production goal) is not met; against the USD 300 value-engineering target, the constructable design is estimated at USD 299 for the bike (USD 1 under) and USD 311 with the helmet (USD 11 over), and the production cost is not yet estimated; and braking margins for the smallest rider, the fit-change time and steerer strength are at risk. Wheel size, brakes, frame type, tires and crank length were decided by Amish on 2026-09-25 (GRR-DDR-001), and on the same day he accepted the TRL 3 recommendations: chromoly main tubes, steerer, quill and sleeve, an aluminium rack, alloy rims and bar, a wider R2 and a split R9 (GRR-DDR-002). The design was made constructable on 2026-10-01 (GRR-DDR-003, accepted by Amish on 2026-10-01), and the prototype build plan is GRR-BLD-001 (docs/05-build-plan.md).

GrowRider

github.com/BoujeeEnjinia1701/growrider

CONCEPT, NOT FOR FABRICATION



Seen from the front right and above, 24 deg elevation. Grey: Child, 1.35 m for scale

Figure 1. GrowRider parametric model (`cad/src/model.py`) set for a 1.38 m rider, beside a 1.35 m child (about 10 years old) for scale.

■ How it works

1. **Fit the rider.** A parent, teacher or mechanic sets saddle height with a two-stage telescoping seat post (a 29.2 x 1.8 mm chromoly sleeve that slides 130 mm in the 31.8 mm seat tube, then a standard 25.4 mm seat post that slides 140 mm in the sleeve) and sets handlebar height with a long 22.0 mm quill stem that slides 120 mm in the 1 in fork steerer; the bar clamp bolts to the quill's head plate 45 or 105 mm ahead of the steering axis. Each sliding part keeps at least 100 mm of insertion, shown by a permanent mark; on both seat post stages a stop screw in the clamp collar, riding in a slot, stops the part at that point. All the fit clamps use 13 mm bolts.
2. **Ride to school.** The rider pedals a single-speed chain drive (32T chainring, 18T sprocket, 140 mm cranks) at about 65 rpm for 11 km/h. Solid or airless tires cannot go flat on thorns.
3. **Stop.** Pedaling backward engages the coaster brake in the rear hub. A front rim brake with a short-reach lever gives a second, independent brake that still works if the chain comes off.
4. **Carry a school bag.** A small rear rack, rated and marked 10 kg, carries a bag or books. It is sized for a bag, not a passenger or a water container.
5. **Grow and hand down.** As the child grows, the post and stem are raised. When the child moves to an adult roadster, both are lowered and the bike passes to a younger sibling. Worn parts are replaced from the roadster parts already sold in the local market.

GrowRider: growth and hand-down cycle (estimates)

github.com/BoujeeEnjinia1701/growrider

CONCEPT, NOT FOR FABRICATION




Figure 2. Growth and hand-down cycle. Saddle heights are estimates from the crank-corrected fit rule in GRR-CAL-001, Table 2; the 10-year life is a target.

■ Main components

Item numbers match the exploded view (Figure 3) and `bom/bom.csv`.

#	Component	Choice	Notes
1	Frame	Step-through frame with twin down tubes; chromoly 4130 main tubes: 31.8 x 1.2 mm seat tube, 280 mm long; 31.8 x 0.9 mm down tube; 28.6 x 0.9 mm loop tube; 180 mm head tube; steel stays	Decided 2026-09-25 (D3, D7). Low stepping point (455 mm) for small riders and school skirts
2	Fork	20 in fork, 30 mm offset, crown about 16 mm deep, slotted fork ends 100 mm apart, 1 in threaded chromoly steerer with 220 mm usable above the crown (D10)	Standard 1 in headset as on roadsters; steerer longer than a stock 20 in fork
3	Telescoping seat post	29.2 x 1.8 mm chromoly sleeve, 250 mm long (D10), plus 25.4 mm seat post, 280 mm long	270 mm of travel in two stages (130 and 140 mm); saddle 400 to 670 mm from the BB
4	Saddle	Child size, light color cover	Light color stays cooler in sun
5	Telescoping stem	Long 22.0 mm chromoly quill (240 mm), 120 mm travel, welded head plate with a bolt-on bar clamp block at 45 or 105 mm ahead of the steering axis	Adjusts bar height (113 mm) and reach
6	Handlebar and grips	22.2 mm alloy swept-back bar (D7), 520 mm wide, 160 mm sweep	Upright position for visibility
7	Front wheel	20 in (ISO 406) alloy rim (D8), 28 spokes, nutted axle	Decided 2026-09-25 (D1); 15 mm axle nuts as on roadsters
8	Rear wheel	20 in (ISO 406) alloy rim (D7) with coaster brake hub	Hub type widely used on regional roadsters (to confirm)
9	Tires (2)	20 x 1.95 in solid or airless	Decided 2026-09-25 (D4)
10	Crankset	140 mm cranks, 32T ring, 9/16 in pedal threads	One length decided 2026-09-25 (D5); adult pedals fit
11	Chain and sprocket	1/2 x 1/8 in chain, 18T sprocket	Same chain as roadsters
12	Front brake	Side-pull caliper, short-reach adjustable lever	Second, independent brake; decided 2026-09-25 (D2)
13	Rear rack	12 x 1.5 mm aluminium 6061-T6 tube (D7), 300 x 120 mm platform at 545 mm, 10 kg marked	No footrests or passenger seat
14	Fenders	Pair, full coverage	Rainy-season mud and school uniforms
15	Chainguard	Full plate over the upper chain run	Keeps clothing out of the chain
16	Kickstand	Rear-mounted	Parking at school
17	Reflectors and bell	Front white, rear red, spoke and pedal reflectors, bell	Road visibility

GrowRider: exploded viewgithub.com/BoujeeEnjinia1701/growrider

CONCEPT, NOT FOR FABRICATION

- 1 Step-through chromoly frame
- 2 Fork, 1 in steerer
- 3 Telescoping seat post (sleeve and post)
- 4 Saddle
- 5 Telescoping quill stem
- 6 Handlebar and grips
- 7 Front wheel, 20 in, alloy rim
- 8 Rear wheel, alloy rim, coaster hub
- 9 Solid tires, 20 x 1.95 in (2)
- 10 Crankset, 32T, 140 mm
- 11 Chain and 18T sprocket
- 12 Front rim brake and lever
- 13 Aluminium rear rack, 10 kg rated
- 14 Fenders
- 15 Chainguard
- 16 Kickstand
- 17 Reflectors and bell



Seen from the front right and above, 24 deg elevation; numbers match bom/bom.csv

Figure 3. Exploded view with item numbers matching the BOM. The bottom bracket, headset, hardware and helmet (BOM lines 18 to 20) are not modeled.

■ Key numbers

All values come from the calculation note GRR-CAL-001 v0.3 and its script `docs/04-calcs/sizing.py`; they are paper estimates. The general arrangement is drawing GRR-DWG-001 (`cad/drawings/GRR-DWG-001.pdf`).

Fit. Assumptions: inseam is about 0.45 times standing height. Rule A sets saddle height (BB center to saddle top) at 0.88 times inseam; rule B sets saddle top to pedal at the bottom of the stroke at 1.09 times inseam, which accounts for the 140 mm crank. The design covers both.

Rider height	Inseam (0.45 x height)	Saddle height, rule A	Saddle height, rule B
1.10 m (about age 6)	495 mm	436 mm	400 mm
1.38 m (about age 10)	621 mm	546 mm	537 mm
1.65 m (about age 14)	742 mm	653 mm	669 mm

Table 1. Saddle height across the fit range (GRR-CAL-001, Table 2).

Quantity	Value	Basis	Requirement
Saddle height range	400 to 670 mm (270 mm)	Two stages of 130 and 140 mm, 100 mm insertion each	R2 met
Saddle rise and setback over the range	254 mm up, 92 mm back	270 mm along a 70° seat axis	
Handlebar height range	113 mm	120 mm of quill travel along a 70° steering axis	R3 met
Reach adjustment	141 mm (241 mm shortest, 382 mm longest)	Seat and steering geometry, two bar clamp positions 60 mm apart, ±15 mm saddle rail	R3 met; shortest is 21 mm above the 220 mm placeholder for a 1.10 m rider
Standover at the stepping point	455 mm	Loop tube top 100 mm ahead of its seat-tube joint	R1 met; 40 mm below a 1.10 m rider's inseam
Saddle top above ground	636 to 890 mm	260 mm BB height	Classifies the bike under ISO 4210-2 (city and trekking)
Grips relative to saddle	+128 mm (smallest) to -13 mm (largest)	180 mm head tube needed for quill insertion	Very upright for small riders
Trail	59 mm	70° head angle, 30 mm fork offset	
Pedal clearance	109 mm; strike at about 32° lean	260 mm BB, 140 mm cranks	
Toe overlap	None (1.10 m) to 19 mm (1.65 m) with the bar turned	480 mm front center	Tell riders
Gear development	2.79 m per crank turn	32/18 on a 1.57 m rolling circumference	66 rpm at 11 km/h
Power on the level at 11 km/h	26 to 51 W (34 W at 1.38 m)	Rolling coefficient 0.02 (solid tire on gravel), CdA 0.35 m ²	Sustainable for a child
Power on a 5 % climb at 7 km/h	47 to 102 W (64 W at 1.38 m)	Same, plus gravity	Short climbs only; steep hills walked
Mass	15.1 kg (14.4 kg before GRR-DDR-003, 15.3 kg before GRR-DDR-002)	Frame 2.67 kg from the model's tubes and fittings, stem 0.90 kg, wheels 2.75, solid tires 2.2, drive 1.45, rack 0.44, other parts 5.1 kg	R5 (13 kg production goal) not met
Rear coaster brake alone, grip limit	0.26 to 0.28 g dry, 0.19 g on loose gravel	$\mu (L - x) / (L + \mu h)$ with the rider-plus-bike mass center	Front brake needed on gravel
Coaster brake, smallest rider	0.22 g	85 N back-pedal force needed for 0.2 g, about 93 N available (assumed hub brake ratio 2.5)	R7 at risk

Quantity	Value	Basis	Requirement
Front rim brake, smallest rider	0.24 g dry; about 0.14 g wet with the alloy rim (0.05 g with steel)	33 N lever force for 0.2 g dry, 40 N assumed	R7 at risk; alloy rim decided (D8)
Both brakes, dry	0.46 to 0.57 g	Sum, capped by grip and pitch-over (0.57 to 0.81 g)	R7 target 0.35 g met on paper
Rack	10 kg; 26 MPa in the aluminium rails at 2.5 g (110 MPa welded 6061-T6)	300 x 120 mm platform; front wheel load falls from 40 % to 32 % with 10 kg for the smallest rider	R6 met
Strength screen	1 of 7 sections above its screen: steerer at the crown in hard braking (117 MPa against 90 MPa for chromoly); sleeve 61 MPa, quill 79 MPa, head plate 71 MPa and seat tube 72 MPa pass (3 of 6 above before GRR-DDR-002)	Largest rider, largest setting	R12 at risk
Prototype parts cost	USD 311 with the helmet supplied with every bike, USD 299 for the bike alone (USD 293 and 281 before GRR-DDR-003)	bom/bom.csv	Value-engineering target USD 300: bike USD 1 under, with helmet USD 11 over; R11 at risk until production cost is estimated

Commute time. Assumptions: a 5 km trip each way; walking at 4 to 5 km/h; cycling at 10 to 12 km/h on dirt roads.

Mode	Speed	One way	Round trip
Walking	4 to 5 km/h	60 to 75 min	2.0 to 2.5 h
GrowRider	10 to 12 km/h	25 to 30 min	50 to 60 min
Time returned to the child		30 to 50 min	60 to 100 min per day; about 79 min per day and 249 h per 190-day school year at the midpoints

Table 2. School trip time, walking and cycling (estimates).

■ Key design choices

- **Wheel size: 20 in (ISO 406).** 20 in keeps standover at 455 mm so a 1.10 m child can stand over the frame, and gives lower mass. 24 in (ISO 507) rolls better on ruts but raises standover to about 510 mm and fails R1 for the smallest riders. Neither is a regional roadster size, so tires and rims are the one commonality gap either way. Decided by Amish, 2026-09-25 (GRR-DDR-001, D1).
- **Brakes: coaster brake plus front rim brake.** A coaster brake is simple, weather-proof, needs no hand strength, and uses hub internals common on regional roadsters. On its own it fails completely if the chain comes off and is marginal on loose gravel (about 0.19 g). Adding a front rim brake gives two independent brakes. Alternatives: coaster only (cheaper, one failure mode away from no brake) or two hand brakes without a coaster (needs hand strength small children may lack). Decided by Amish, 2026-09-25: coaster plus front rim brake (GRR-DDR-001,

D2). GRR-CAL-001 finds the smallest rider's margins small and a wet steel rim nearly useless, so an alloy front rim was decided (GRR-DDR-002, D8), and the coaster hub's brake ratio is to be obtained before further brake work (D9).

- **Step-through frame.** Lower standover than a diamond frame, and practical for school uniforms and skirts. It needs twin down tubes to keep the frame stiff. Decided by Amish, 2026-09-25 (GRR-DDR-001, D3).
- **Mass and materials.** Chromoly 4130 main tubes, an aluminium rack, alloy rims and an alloy bar, keeping the solid tires, with 13 kg kept as the production goal. Decided by Amish, 2026-09-25: go with recommendation (GRR-DDR-002, D7). The result was 14.4 kg, not the 13.6 kg first estimated, and it added USD 38 to the prototype; with the parts added for construction (GRR-DDR-003) the bike is 15.1 kg.
- **Sliding parts and steerer.** Chromoly steerer and quill and a 29.2 x 1.8 mm chromoly sleeve, which needs a 1.2 mm seat tube wall to fit. Decided by Amish, 2026-09-25: go with recommendation (GRR-DDR-002, D10). The steerer is still above its screen in hard braking; a 2.0 mm wall is proposed (N2).
- **Puncture-proof tires.** Solid or airless tires remove thorn punctures entirely but add about 0.5 kg for the pair (GRR-CAL-001), ride harsher and roll less freely. Thorn-resistant tubes with tire liners keep standard parts and a softer ride, but still puncture occasionally. Decided by Amish, 2026-09-25: solid or airless for the prototype, and ask users in co-design (GRR-DDR-001, D4).
- **Parts commonality.** Chain, coaster hub internals, 1 in headset, 25.4 mm seat post, 22.2 mm handlebar and 9/16 in pedal threads are chosen to match adult roadster parts. Children's bikes often use 1/2 in pedal threads; GrowRider does not.
- **Head tube and steerer length.** A 180 mm head tube and 30 mm headset stack give the quill 220 mm of steerer, enough for 120 mm of travel with 100 mm of insertion at full height. The cost is a high bar for the smallest rider (128 mm above the saddle).
- **Bolted clamps, not quick releases.** 13 mm bolts discourage casual changes and theft of the seat post, and every mechanic already has the spanner.

■ Safety

Safety: GrowRider is ridden by children on roads shared with trucks and motorbikes. It is a concept. No part of it has been built or tested, and it must not be ridden until the frame, fork, sliding joints, rack and brakes have passed the tests of the applicable standard (ISO 8098 or ISO 4210) at a later TRL.

- **Brakes.** Two independent brakes are required (R7). The coaster brake stops working if the chain comes off, so the front brake is not optional. Small hands need a short-reach lever. Riders need to be shown that a hard front brake on loose gravel can skid the front wheel. A wet steel rim gives a child almost no front braking (about 0.05 g), so an alloy rim is specified (about 0.14 g wet).
- **Telescoping parts.** A seat post or stem raised past its minimum insertion can break or pull out. Every sliding part carries a permanent minimum insertion mark at 100 mm. On the sleeve and the seat post a stop screw in the clamp collar, riding in a slot, stops the part at that point (GRR-DDR-003, P8). The quill cannot take a stop of this kind inside a threaded steerer, so for the prototype its minimum insertion mark, with a bright painted band above it, is its only limit, checked at every fit change; a clamp-on stop collar is to be considered after the fit trials (decided by Amish, 2026-10-01, GRR-DEC-001). Painted height scales on the exposed sleeve and quill let a setting be noted and reset. At full extension the sleeve and quill are the most stressed sections (GRR-CAL-001, section K). Clamp slots are pinch points for fingers.

- **Rack limit.** The rack is rated 10 kg and marked. It must not carry passengers, water containers or goods above the rating; a heavy load high over the rear wheel makes a light bike hard for a child to steer and can lift the front wheel. The rack is sized for a school bag, with no footrests.
- **Road visibility.** School trips often start and end near dawn or dusk. Front white, rear red, spoke and pedal reflectors are fitted. The portfolio renders use the kit teal; the production frame color is settled in co-design, with a high-visibility option (decided by Amish, 2026-10-01). A light (for example a hub dynamo) is suggested for a later version.
- **Helmet.** An adjustable, ventilated child helmet is supplied with every bike through the partner program and fitted at handover (BOM line 20; decided by Amish, 2026-10-02, GRR-DEC-001). Hot-climate comfort will decide whether it is worn, so how it is worn is discussed in co-design.
- **Aluminium rack.** Welded aluminium has a low fatigue strength and cracks without warning; the rack must pass static and fatigue tests before use, and the 10 kg rating marking matters more than before.
- **Clothing and hot surfaces.** The chainguard keeps skirts and trousers out of the chain. A light saddle cover limits heating in the sun.
- **Mass.** At about 15.1 kg, the bike is about 80 % of the weight of a 19 kg six-year-old. This makes pushing, lifting and controlling a fall harder for the smallest riders, and is the reason R5 matters.

■ Open questions

- Reduce mass toward the 13 kg production goal: with chromoly, aluminium and alloy parts adopted (D7) and the parts added for construction (GRR-DDR-003), the bike is 15.1 kg. The remaining option, pneumatic tires with liners (0.5 kg), would reverse D4. Can local frame builders work chromoly and weld aluminium, and are the lighter parts stocked?
- Low bar option: would a flat bar suit the smallest riders, whose grips sit 128 mm above the saddle? A co-design question (GRR-DDR-002, D13).
- Sliding joints in dust and rain: will greased steel sleeves seize over years of use? Would a split collar with a wiper seal or a plastic bushing help?
- Crank length: one 140 mm length for the prototype was decided on 2026-09-25 (D5). It is 0.28 of a 1.10 m rider's inseam; the 127 mm swap remains a later option.
- Standard: by maximum saddle height (890 mm) GrowRider falls under ISO 4210-2 (city and trekking). Its test loads assume adult riders; whether to also meet ISO 8098 limits for the small settings needs the standards' text.
- Confirm with a partner which roadster parts are actually stocked in the target region, including coaster hubs and 20 in tires. World Bicycle Relief is the first candidate partner to approach and Zambia the first candidate region (decided by Amish, 2026-10-02, GRR-DEC-001).
- Test the anthropometric assumptions (inseam ratio, reach) with measurements of children in the target region, where average heights may be below global references.

Concept media: [blueprint sheet](#), [interactive 3D model](#).