

GROWRIDER · REQUIREMENTS

GrowRider requirements

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	GRR-REQ-001	Version	0.5
Status	Draft	Date	2026-09-26
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/growrider		
Source	docs/03-requirements.md @ d0c0d47		

REVISION HISTORY

Version	Date	Author	Change
0.5	2026-09-26	Amish Chadha	Budget top-up approved by Amish
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	Record decisions of GRR-DDR-001 (20 in wheels, brakes, \$120 production target); add TRL 3 status from GRR-CAL-001
0.2	2026-09-24	Amish Chadha	First measurable requirements for TRL 2
0.1	2026-09-24	Amish Chadha	Initial scaffold

GrowRider requirements

These are the requirements for the concept. They were checked by calculation at TRL 3 in GRR-CAL-001 v0.3: 5 are met on paper, 1 is not met (R5, mass), 4 are at risk and 2 cannot be verified at TRL 3. Amish's acceptance of the TRL 3 recommendations on 2026-09-25 (GRR-DDR-002) widened R2 to the crank-corrected fit range, split R9 into parent and mechanic tool lists, restated R5 as the production goal and named the alloy front rim in R7. All targets must still be revised from co-design findings before the design is frozen (see GRR-PRB-001).

ID	Requirement	Target	Verification (TRL 3 or later)	TRL 3 status (GRR-CAL-001)
R1	Fit the intended riders	Rider height 1.10 to 1.65 m (ages about 6 to 14); standover height 470 mm or less at the stepping point	Fit calculation from anthropometric data; later fit trials with children	Met: standover 455 mm
R2	Adjustable saddle height	400 to 670 mm from bottom bracket center to saddle top (270 mm range), with at least 100 mm insertion at every sliding joint across the range (widened from 436 to 654 mm, GRR-DDR-002, D11)	Geometry calculation; massing model	Met: 400 to 670 mm, 100 mm insertion
R3	Adjustable reach and handlebar height	Handlebar height adjustable by 100 mm or more; horizontal saddle-to-grip reach adjustable by 100 mm or more	Geometry calculation	Met: bar 113 mm, reach 141 mm
R4	One wheel size across the whole fit range	Single wheel size for all riders: 20 in (ISO 406), decided 2026-09-25 (GRR-DDR-001, D1)	Design review; fit calculation	Met: 20 in
R5	Light enough for the smallest rider to handle	Production goal: complete bike with rack, fenders and kickstand 13 kg or less; the prototype estimate is tracked against it (GRR-DDR-002, D7)	Mass estimate, then weighing	Not met: 14.4 kg (15.3 kg before D7)
R6	Small, clearly rated rear rack	Rated 10 kg, rating marked on the rack; platform no larger than a school bag (about 300 x 140 mm); no passenger footrests	Design review; later static load test	Met by design: 300 x 120 mm
R7	Two independent brakes a child can operate	Rear coaster brake plus front rim brake (decided 2026-09-25, GRR-DDR-001, D2), with an alloy front rim for wet braking (GRR-DDR-002, D8); each brake alone 0.2 g or more and both together 0.35 g or more on a dry, level surface; hand lever reach adjustable for small hands	First-order braking calculation; later tests to ISO 8098 or ISO 4210 as applicable	At risk: small margins for the smallest rider; wet steel rim poor
R8	Puncture resistance	No loss of use from thorn punctures; tire life 2,000 km or more (about one school year of 10 km per day)	Supplier data; later field trial	Not verifiable at TRL 3 (tire life)
R9	Serviceable with basic tools (split by GRR-DDR-002, D12)	R9a, parent or teacher: every fit adjustment with a 13 mm spanner and a screwdriver, and a fit change in 10 minutes or less. R9b, mechanic: all routine service, including headset and bottom bracket, with 13, 15 and 32 mm spanners, a bottom bracket lockring spanner and a screwdriver	Design review; later timed trial	At risk: both tool lists met; fit change 10 min, at the limit
R10	Parts commonality with regional adult roadsters	Every wear part except tires and rims interchangeable with regional roadster parts (chain, sprocket, coaster hub internals,	BOM review against a regional parts list from the partner	Not verifiable at TRL 3 (no regional parts list)

ID	Requirement	Target	Verification (TRL 3 or later)	TRL 3 status (GRR-CAL-001)
		bottom bracket, headset, pedals, seat post, handlebar, brake blocks)		
R11	Low cost	Prototype parts \$300 or less (project budget, raised from \$250 by Amish on 2026-09-26, GRR-DDR-002, N1); production cost target \$120 or less per bike at volume (decided 2026-09-25, GRR-DDR-001, D6)	Priced BOM; production estimate with a regional assembler	At risk: prototype within budget at \$281 bike, \$293 with helmet (not met against the former \$250); \$120 production cost not yet estimated
R12	Lasts across siblings	10-year service life for at least three successive riders; frame and fork sized for a 60 kg rider plus a 10 kg rack load; sliding joints that do not seize in dust and rain	Fatigue calculation at TRL 3; later frame fatigue tests	At risk: 1 of 6 sections above the fatigue screen (steerer; 3 of 6 before GRR-DDR-002)

■ Assumptions

- Inseam is about 0.45 times standing height, and a comfortable saddle height (bottom bracket center to saddle top) is about 0.88 times inseam. Both are common bicycle fitting rules of thumb for adults and older children and must be checked against measurements of the intended users.
- Horizontal saddle-to-grip reach for an upright riding position scales with torso and arm length, estimated at about 0.2 times height (220 mm at 1.10 m, 330 mm at 1.65 m). This is a placeholder until fit measurements are taken.
- A typical school trip is 5 km each way on dirt or gravel, ridden at 10 to 12 km/h.
- A 1.65 m rider is assumed to weigh up to 60 kg, including a margin for older teenagers.
- Saddle height (R2) is measured from the BB center to the saddle top along the seat axis. GRR-CAL-001 also checks a second fitting rule that accounts for the 140 mm crank (saddle top to pedal at 1.09 times inseam), which asks for 400 to 669 mm. R2 now takes the wider range, which covers both rules.
- Applicable standard: classified by its maximum saddle height above the ground (about 890 mm), GrowRider falls under ISO 4210-2 as a city and trekking bicycle; ISO 8098 covers maximum saddle heights below 635 mm (GRR-CAL-001, section M).