

HatchSide TRL 2 review decisions

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	HTS-DDR-001	Version	1.0
Status	Released	Date	2026-10-03
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/hatchside		
Source	docs/decisions/0001-trl2-review-decisions.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
1.0	2026-10-03	Amish Chadha	TRL 2 review decisions D1 to D12, decided under Amish's 2026-10-03 pre-approval

0001: TRL 2 review decisions

- **Date:** 2026-10-03
- **Status:** accepted. Decided by Amish Chadha under his pre-approval of 2026-10-03: "start with the first 14 repos from the list of 29 projects. I pre-approve the batch runs along with any recommendations you come up with. I also accept any cost overruns or variations from the assumed scope cost."

■ Context

The scaffold (HTS-PRB-001, HTS-PRC-001 and HTS-REQ-001 at v0.1) left five open questions and twelve proposed requirements. Populating the concept to TRL 2 needed answers on the working load, the role of the retrieval head, the materials, the winch, the rope and the depth DomeReach must reach. Every answer below was the recommendation of the populate pass, and each is decided under the pre-approval. Choices that touch safety take the conservative option, and each says what evidence would relax it.

■ Options considered and decisions

Table 1. Decisions D1 to D12.

#	Question	Options	Decision	Why
D1	Safe working load of the frame	150 kg for tool heads; 400 to 600 kg to share the frame with WellSling	150 kg , proof-loaded to 1.5 times	Tool heads and a full grab weigh well under 100 kg; a 600 kg frame would push every pack past 25 kg. WellSling needs its own heavier frame or a later heavy variant (shared tripod block not adopted at this rating)
D2	Retrieval head in the kit	Keep it; drop it	Keep it, as a clip-on guide only. It steers an auto-locking connector onto a line already on a casualty; the haul is made with certified rescue equipment, never with the HatchSide winch	Conservative safety option. Relaxing it would need the frame, winch and rope certified to a personnel standard (for example EN 795 class B and EN 1496) by a notified body
D3	Winch	Hand winch with automatic load brake; ratchet winch; powered winch	Two-speed hand winch with an automatic (Weston-type) load brake, rated 450 kg on the first layer	No engine at the hatch (constraint); the brake holds the load when the crank is released
D4	Rope	6 mm stainless wire rope; synthetic rope	15 m of 6 mm 7x19 grade 316 wire rope with a swaged thimble eye	Sewage and grit wear synthetic rope; stainless resists corrosion; 15 m covers R3 with turns left on the drum
D5	Leg material	Aluminium tube; galvanized steel tube	6082-T6 (or 6061-T6) aluminium square tube , upper 60 x 60 x 4, lower 50 x 50 x 3, telescoping	Keeps packs under 25 kg; square tube takes bolted joints and a ball-lock pin without crushing
D6	Steel parts	Galvanized S275; stainless	Hot-dip galvanized S275 for the head, feet, bracket and heads; A4 stainless fasteners, pins and rope	Low cost and widely available in the first region; stainless where parts slide or thread
D7	DomeReach depth for R10	Set with a partner; assume a typical depth	2.5 m below the rim as the design depth until a partner digester is measured	Covers common household fixed-dome digesters; a deeper digester needs a third pole section
D8	DomeReach sealant	Named product; generic	Generic brush or roller-applied digester sealant , named by type, never by brand	Patent and trademark screen of 2026-09-30
D9	DomeReach mechanism	Articulated arm with gripper; single hinge	Single hinged arm worked by a pull line , no gripper	Bandicoot patent design-around; simpler to make
D10	Opening and stability requirements	Leave R2 only; add explicit checks	Add R13 (every head passes a 560 mm opening) and R14 (stable with the rope 10 degrees off vertical)	Makes the opening and tipping checks measurable
D11	First region and co-design partner	India; United States; Nepal	India first. First candidate to approach: a municipal sewer department running mechanised cleaning under India's national mechanised sanitation programme. For DomeReach, first candidate to approach: a	Highest documented toll; existing programmes aim to end manual entry

#	Question	Options	Decision	Why
			household biogas programme with field technicians in India or Nepal. Neither is agreed	
D12	Prototype cost	Hold to the USD 5,000 target; accept overruns	Value-engineering target stays USD 5,000. Overruns are accepted under the pre-approval; <code>budget_usd</code> is unchanged	Amish's pre-approval

■ Consequences

- HTS-REQ-001 gains R13 and R14, and R4 and R10 lose their "estimate" and "to be set" wording.
- The retrieval head is drawn and costed as a guide with a certified EN 362 connector; every document says the haul is made with certified rescue equipment.
- WellSling does not share this frame at 150 kg; its own repo decides its frame.
- The design is made constructable in HTS-DDR-002.