

HEAPLINE · PRECIS

HeapLine design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	HPL-PRC-001	Version	0.4
Status	Draft	Date	2026-10-03
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/heapline		
Source	docs/02-concept.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.4	2026-10-03	Amish Chadha	Amish's requirement decisions 20A, 21A, 22A and 23C (HPL-DDR-003): 18 mm probe tips; four haulers on debris; two carrying waves; reused search crate at every site, one capstan set shared by neighbouring sites, PPE from the cooperative
0.3	2026-10-03	Amish Chadha	TRL 3 figures from HPL-CAL-001 and the constructable design (HPL-DDR-002); pumped friction capstan with shear pin and holding pawls, sectional probes, linked crawl boards, enlarged site box
0.2	2026-10-03	Amish Chadha	TRL 2 precis; how it works, components, key design choices (HPL-DDR-001), first-order numbers, stop rule, safety
0.1	2026-09-30	Amish Chadha	Initial scaffold


HeapLine design precis

Keeps a slide-rescue kit at the pickers' shed so they can search, probe and dig safely in the first minutes.

HeapLine

github.com/BoujeeEnjinia1701/heapline

CONCEPT, NOT FOR FABRICATION



Seen from the front right and above, 24 deg elevation. Grey: Person, 1.75 m (scale) for scale

Figure 1. Concept render: the open search crate, six probes standing in a line, two linked crawl boards with the sheet stretcher and sheet clamp in front, shovels and spare boards on the left, and the hand capstan on the right with a 1.75 m person beside it.

■ Summary

HeapLine is a slide-rescue kit kept in a locked, reused crate at the waste pickers' shed. The search crate holds six sectional steel probes, four linked crawl boards, four shovels, a roll-up sheet stretcher, a lookout kit, lamps and the cooperative's protective equipment, with the drill card and stop rule printed on the lid. One hand capstan set, with its rope, anchor sling and sheet clamp, is shared by neighbouring sites and kept in its own crate at the host site. After a slide, four people carry the search kit out, post a lookout, lay boards onto the debris, probe in a line and dig from the boards; a second group of three brings the capstan to pull sheeting and timber off the dig from firm ground. On paper the first probe line starts 4.6 minutes after the alarm, the capstan gives 5 kN with four people at 114 N each, each site's search kit costs USD 827 and the shared capstan set USD 547 (HPL-CAL-001). It is an open engineering reference, not certified rescue equipment, and it never replaces making the dumpsite safe.

■ How it works


1. **Alarm and lookout.** The first person at a slide raises the alarm and calls the fire service and emergency services. Someone runs to the shed, opens the combination padlock and hands out the search kit. Before anyone steps onto the debris, a lookout in a vest stands on stable ground to the side of the slide with a whistle and watches the slope above.
2. **Boards.** Searchers lay crawl boards from firm ground onto the debris and join them end to end with link plates. They kneel and walk only on the boards, which spread their weight and bridge voids.
3. **Probe line.** Up to six searchers stand on the boards about 0.5 m apart and push probes straight down, three 1 m sections joined on spigots, 2.6 m usable. A strike that feels soft and gives is marked with a flagged wand.
4. **Dig.** Searchers dig at each mark from the boards with long-handled shovels, from the downslope side, keeping a board between them and the hole's edge.
5. **Capstan.** Where sheeting, timber or heavy debris lies over a mark, a second group of three, who have brought the capstan set from the host site, sets the capstan on firm ground, stakes it and slings it to a sound tree, vehicle or column. The sheet clamp or a choker sling goes on the load, the rope runs to the capstan, and four people pump the two bars through quarter turns while a fifth tails the rope. Two pawls hold the drum whenever the bars stop; a 6 mm shear pin releases at about 6.4 kN so the rope, the capstan and the anchor are never overloaded. The capstan only pulls loads sideways away from the dig; it never lifts and never pulls on a person.
6. **Move the casualty.** The casualty is slid onto the sheet stretcher, strapped, and pulled back along the boards to a pickup point on firm ground: four haulers whenever it crosses debris, two only along the boards.
7. **Stop rule.** On any stop signal everyone leaves the debris along the boards to the marked safe zone, to the side of the slide path and never below it, and waits for the lookout's all clear or for the formal responders.

HeapLine: exploded view

github.com/BoujeeEnjinia1701/heapline

CONCEPT, NOT FOR FABRICATION

- 1 Search crate body
- 2 Search crate lid
- 3 Crate hinges, hasp and seal
- 4 Crawl boards (4)
- 5 Board link plates
- 6 Probes (6), assembled
- 8 Long-handled shovels (4)
- 9 Capstan base frame with post
- 10 Capstan drum with holding ratchet
- 11 Drive ratchet wheel
- 12 Lever head
- 13 Holding pawls (2) and Drive pawl
- 14 Capstan bars (2) and Bar pins (2)
- 15 Bushes and thrust washers
- 16 Hold-down roller and Roller pin
- 17 Keeper collar and pin
- 18 Shear pin
- 19 Ground stakes (4)
- 20 Capstan rope, 14 mm
- 21 Anchor sling and shackle
- 22 Sheet clamp bars and Sheet clamp bolts
- 23 Sheet stretcher and Stretcher straps
- 24 Marker wands and safe-zone sign



Seen from the front right and above, 24 deg elevation; numbers match bom/bom.csv

Figure 2. Exploded view; the capstan parts are lifted off their post. Numbers are bill of materials lines.

■ Components

Table 1. Main components (line numbers from bom/bom.csv).

BOM	Component	What it is
1, 2, 3	Search crate	A reused timber crate (or bought job box), outside about 1640 x 860 x 640 mm, refitted on skids with a skirted lid over a seal, three strap hinges, hasp and combination padlock; stays at the shed
31	Capstan crate	A second reused crate at the host site only, outside about 940 x 900 x 1060 mm, for the shared capstan set
4, 5	Crawl boards	Four 1500 x 450 mm boards, 15 mm plywood on two 45 x 70 mm battens, 9.7 kg each; joined by link plates with two 12 mm pins
6, 7	Probes	Six probes, each three 1 m sections of 16 x 2.0 mm steel tube on spigots with R-clips, an 18 mm tip rounded to 3 mm and a 450 mm T handle; 3.07 m, 3.07 kg
8	Shovels	Four long-handled round-point shovels
9 to 18	Hand capstan	Base frame with a fixed post; drum turning on acetal bushes with a 24-tooth holding ring and two pawls; drive ratchet joined to the drum only by the 6 mm shear pin; lever head with a drive pawl and two bar sockets; two 900 mm bars; hold-down roller; keeper collar
19	Stakes	Four 25 mm stakes and a club hammer; they stop the frame turning, they are not the anchor
20, 21	Rope and lifting gear	30 m of 14 mm polyester double braid (40 kN); two 2,000 kg round slings and three shackles
22	Sheet clamp	Two 50 x 8 mm flats with four wing bolts and a shackle lug; grips plastic sheeting
23	Sheet stretcher	2 mm HDPE sheet 2000 x 900 mm with hand slots and three straps; rolls to 250 mm
24 to 27	Lookout kit, lighting, PPE, drill card	Whistles, vests, marker wands, safe-zone sign; AA lamps; gloves, boots, masks, glasses from the cooperative's stock; drill card and stop rule on the lid

■ Key design choices

Decided under Amish's pre-approvals of 2026-10-03 (HPL-DDR-001 and HPL-DDR-002) and by his requirement decisions of 2026-10-03 (HPL-DDR-003):

- **A pumped friction capstan.** The crew stands still and pumps two bars through a quarter turn; a drive ratchet turns the drum and two holding pawls keep it from running back. Nobody walks round it or steps over a rope at knee height, and the rope leaves under a roller 38 mm above the ground, level with the anchor sling, so it cannot tip.
- **A shear pin as the weakest link.** The rope, capstan, slings and anchor are all sized on 8 kN; the pin releases between 5.1 and 7.6 kN.
- **Sound anchors only.** A round sling to a tree, a parked vehicle or a structural column; never waste, never stakes alone. No sound anchor, no capstan.
- **Push, never drive, the probes.** A blunt tip and no hammer, so a probe cannot injure a buried person.
- **No lithium cells and no gas detector in the box.** Both would need upkeep the kit cannot assume; the rules cover the gap.
- **Everything packs.** The search crate and the capstan crate are sized so every item fits without clashes, the capstan standing assembled with its bars off (checked in the model).

- **A small, blunt probe tip.** 18 mm, 1 mm proud of the tube each side, so two people reach full depth in stiffer debris.
- **Two waves and four haulers.** The search kit goes first and the capstan second; four people haul the stretcher on debris, two only along the boards.
- **One capstan for neighbouring sites.** The costliest block is shared, and PPE comes from the cooperative's stock.

■ First-order numbers

From HPL-CAL-001, on the constructable design:

Table 2. First-order numbers.

Quantity	Value	Assumption
Time from alarm to first probe line	4.6 min	100 m each way; 0.8 m/s carrying
Probe reach, 18 mm tip	2.6 m in loosened debris; 2.6 m with two people in stiffer debris	Cone 0.4 or 1.0 MPa; sleeve 1 or 3 kPa
Board sinkage	44 mm	100 kg x 1.5 on very loose debris
Capstan force per person at 5 kN	114 N	Four people, two on each bar
Shear pin release	6.4 kN (5.1 to 7.6 kN)	S275 pin, plus or minus 20 %
Haul force on the stretcher, level debris	510 N	Friction 0.5
Heaviest carried item	21.2 kg	Capstan frame with post
Carried kit	151 kg in two waves	Search wave 21.5 kg each for four; capstan wave 21.7 kg each for three
Parts cost	USD 827 a site; shared capstan set USD 547	R9 restated to USD 850 a site; value-engineering target USD 1,800

HeapLine: capstan energy per metre of rope at 5 kN, kJ (HPL-CAL-001 estimates)

github.com/BoujeeEnjinia1701/heapline

CONCEPT, NOT FOR FABRICATION




Figure 3. Energy per metre of rope at 5 kN (estimates from HPL-CAL-001).

■ Stop rule

Any one of these sends everyone off the debris along the boards to the safe zone at once:

1. The lookout's long whistle.
2. New cracks, bulging or movement on the slope above.
3. Water or mud flowing out of the debris.
4. Rain getting heavier.
5. A gas smell, smoke or hissing.
6. An order from the fire service, police or another formal responder.

■ Patent design-arounds

From the preliminary patent, trademark and prior-art screen (not legal advice):

- Known collapse-rescue practice with no blocking patent found; publish dated drawings early as defensive disclosure.

■ Shared blocks

- The SiltHaul hand capstan was considered and not used: it is limited to 2.5 kN and weighs about 48 kg (HPL-DDR-001, item 1).
- CalRig is the first candidate rig for the capstan proof loads and the shear pin release tests.

■ Safety

Safety: Rescue on unstable ground. HeapLine is published as an open engineering reference, not certified rescue equipment.

A second slide can bury the rescuers. Never search without a lookout, and obey the stop rule every time.

Call the fire service and emergency services at once; the kit is for the minutes before they arrive, and the search is handed over when they do.

The capstan rope stores energy. Nobody stands in the line of a loaded rope or within 2 m of it; the capstan never lifts and never pulls on a person; only the specified 6 mm S275 shear pin is ever fitted; the tail is made fast on the cleat whenever hauling stops.

Landfill gas can be flammable or toxic: no naked flames or smoking at the search.

Sharp waste and infection risk: gloves and boots are part of the kit.

The kit does not make a dumpsite safe; it must not be used to argue against closure or rehabilitation.

■ Open questions

Decisions still open are kept in the design decisions register ([docs/06-design-decisions.md](#)).