

HEATMAP NODE · DESIGN DECISION RECORD

HeatMap Node TRL 2 review decisions

Open Hardware Portfolio · amishchadha.com

DOCUMENT CONTROL

Document ID	HMN-DDR-001	Version	0.1
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/heatmap-node		
Source	docs/decisions/0001-trl2-review-decisions.md @ d91cd4d		

REVISION HISTORY

Version	Date	Author	Change
0.1	2026-09-25	Amish Chadha	Record the TRL 2 review items adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, and the items that remain open

0001: TRL 2 review decisions

- **Date:** 2026-09-25
- **Status:** proposed. Items D1 to D8 carry a recommendation that is adopted for TRL 3 work pending Amish's review; items O1 and O2 remain "Proposed, awaiting Amish".

■ Context

The TRL 2 review note (docs/REVIEW.md , session 2026-09-25, /populate) listed nine items as "Proposed, awaiting Amish", and the design precis HMN-PRC-001 v0.2 listed seven key design choices. On 2026-09-25 Amish asked for this batch of repos to go through the usual process with the instruction "you know the drill, nothing gets past TRL 3". He has not reviewed this repo's items one by one. Every item that carried a recommendation is therefore adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review. Items without a recommendation stay open. Nothing here is recorded as decided or approved by Amish.

■ Options considered

The options for each item are those listed in docs/REVIEW.md (session 2026-09-25, /populate) and in HMN-PRC-001 v0.2, Key design choices.

■ Decision

Table 1. Items adopted as recommended for TRL 3.

#	Item	Recommendation adopted	Status
D1	Budget (R13)	Option (a): the FieldNode core is a shared component costed and budgeted in the FieldNode repo; HeatMap Node's \$120 <code>budget_usd</code> covers the sensor head only. R13 is redefined as "sensor head \$120 or less". No new <code>budget_usd</code> figure was recommended, so <code>project.yaml</code> keeps \$120.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D2	Measurement height (R9)	Option (a): arm at about 2.8 m on city poles, with the height correction studied at TRL 3 (HMN-CAL-001, section E) and a later short pilot comparing 2.0 and 2.8 m. The R9 target is unchanged, so R9 stays not met.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D3	Globe size	Standard 150 mm black globe, not a 38 to 40 mm table tennis ball globe.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D4	Wind	A cup anemometer on the arm, not a sonic anemometer or wind from the nearest official station.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D5	Shield	Naturally ventilated multi-plate shield, not fan-aspirated. HMN-CAL-001 shows R1 is not met with it; a fan option is proposed anew in <code>docs/REVIEW.md</code> .	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D6	WBGT method	WBGT derived by the Liljegren method from air temperature, humidity, globe temperature and wind, not a wetted natural wet-bulb sensor.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D7	Platform	Build on the FieldNode core; send data through a TwinKit gateway or a public LoRaWAN network.	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review
D8	Data policy	Open data under an open license, environmental channels only (R12). The publisher and host stay open (O2).	Adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review

Table 2. Items that remain open.

#	Item	Status
O1	First partner and city for co-design and a pilot network. No preference was stated and no recommendation was made.	Proposed, awaiting Amish
O2	Who publishes and hosts the data (TwinKit, CityTwin or a public platform); to be agreed with the first partner. No recommendation was made.	Proposed, awaiting Amish

■ Consequences

- `project.yaml` : only the TRL fields and evidence list change. `budget_usd` stays at \$120 (D1 redefines what it covers rather than changing the figure). No reworded pitch or problem line was recommended, so the pitch and problem in `project.yaml` and `README.md` are unchanged.
- HMN-REQ-001 v0.3: R13 now reads "sensor head \$120 or less"; the full-node figure is reported for information against the FieldNode budget. No other target changes.
- HMN-PRB-001 and HMN-PRC-001 v0.3: the design choices are no longer "proposed"; they are adopted for TRL 3 pending Amish's review.
- HMN-CAL-001 found that the sensor head costs \$130 against the \$120 budget, that the complete node weighs 4.68 kg against 4.0 kg, and that the shield misses R1. The TRL 3 work added two parts (secondary retention lanyards and a wider pole adapter for the FieldNode core). New proposals arising from these results are in `docs/REVIEW.md` and await Amish; this record does not decide them.
- TRL 4 is on hold by Amish's instruction. Nothing in this record authorizes building or testing.