

HEATMAP NODE · PROBLEM STATEMENT

HeatMap Node problem statement

Open Hardware Portfolio · amishchadha.com

DOCUMENT CONTROL

Document ID	HMN-PRB-001	Version	0.3
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/heatmap-node		
Source	docs/01-problem.md @ d91cd4d		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-09-25	Amish Chadha	TRL 3 update: budget scope and mounting height per HMN-DDR-001; operating environment aligned with HMN-CAL-001
0.2	2026-09-25	Amish Chadha	Populate to TRL 2 (problem, users, context, constraints, prior work, open questions)
0.1	2026-09-25	Amish Chadha	Initial scaffold

HeatMap Node problem statement

Cities decide where to plant trees, build shade and open cooling centers with heat data that is too coarse to see the street a person actually walks down. Heat kills in large numbers, it falls hardest on poorer and hotter neighborhoods, and the measure that matters for the body (heat stress, which includes sun and radiant heat from hot surfaces, not only air temperature) is rarely measured at street level at all.

■ The problem

Heat is one of the deadliest weather hazards. WHO estimates about 489,000 heat-related deaths each year between 2000 and 2019, 45 % of them in Asia and 36 % in Europe ([WHO fact sheet](#)). In the summer of 2022 alone an estimated 61,672 people died of heat in 35 European countries ([Ballester et al., Nature Medicine, 2023](#)).

Heat is not spread evenly across a city. The US EPA reports that daytime air temperatures in urban areas run about 1 to 7 °F (about 0.5 to 4 °C) above outlying areas, and nighttime temperatures about 2 to 5 °F (about 1 to 3 °C) higher ([US EPA](#)). Inside cities the differences follow income and history: land surface temperatures in formerly redlined US neighborhoods are about 2.6 °C higher than in other neighborhoods, and up to 7 °C higher in some cities ([Hoffman et al., Climate, 2020](#)). WHO notes that informal settlements are often hotter than other urban areas ([WHO fact sheet](#)).

Three gaps keep cities from acting on this at block scale:

1. **Official stations are sparse and sited away from streets.** Weather stations are placed in open, grassy sites by design, so they report the background climate, not the hot bus stop or market lane.
2. **Satellites see surfaces, not people.** Land surface temperature maps show hot roofs and roads, but the heat a pedestrian feels depends on air temperature, humidity, wind and radiant heat together.
3. **Air temperature alone understates heat stress in the sun.** The standard occupational index, wet bulb globe temperature (WBGT, [ISO 7243:2017](#)), weights a black globe temperature and a natural wet-bulb temperature because sun and humidity drive heat strain. Low-cost street sensors seldom include a globe.

■ Users and context

User	What they need from the data
City heat, climate or resilience officer	Block-level maps of heat stress over a season to target trees, shade (see CoolShade), cool surfaces and cooling centers, and to check whether they worked
Public health department	Near-real-time heat stress by neighborhood during heat waves, to direct outreach to people at risk
Community groups and schools	A node they can build, host and read, and open data they can take to city hall
Outdoor employers (construction, delivery, markets)	Local WBGT estimates to set work and rest cycles
Researchers	A documented, calibrated, repeatable street-level method that others can replicate

Operating environment

- **Mounting:** existing street light, sign or utility poles (60 to 200 mm in diameter), with the asset owner's permission, with the sensor arm at about 2.8 m above the pavement (HMN-DDR-001 D2). HMN-CAL-001 estimates that on a sunny afternoon the air at pedestrian height is 0.2 to 0.8 °C warmer than at the sensors.
- **Climate:** air temperature from about -20 to +50 °C at the node, full sun, rain, dust and salt air near coasts; black globe temperatures can exceed 60 °C in full sun (estimate).
- **Connectivity:** LoRaWAN coverage from a community gateway (for example the lab's TwinKit gateway) or a public network; no mains power at the node.
- **Density:** tens of nodes per neighborhood, so each must be cheap, quick to fit and self-powered.

■ Constraints

- Garage-buildable prototype, \$120 USD or less for the HeatMap-specific sensor head. The FieldNode core is a shared lab component costed and budgeted in its own repo (HMN-DDR-001 D1, adopted as recommended for TRL 3 under Amish's 2026-09-25 instruction, open for his review). HMN-CAL-001 prices the head at \$130, over this limit.
- Built on the FieldNode core (enclosure, solar, battery, LoRaWAN radio) so that no power or radio design is repeated.
- Privacy: environmental measurements only. No camera, microphone or device tracking.
- No drilling of poles; fit with stainless band clamps.
- Open hardware (CERN-OHL-S-2.0) and open software (MIT); data in an open format.

■ Out of scope

- Personal heat stress for an individual (wearables) and indoor heat.
- Issuing official heat warnings. The node supplies data; public warnings stay with the responsible agency.
- Air quality, noise and traffic, which are covered by the AirStreet, NoiseMap and CurbCount concepts.

■ Prior work

- **WBGT standard and models.** ISO 7243:2017 defines WBGT as a screening index for heat stress ([ISO](#)). Liljegren and colleagues showed how to estimate WBGT from standard weather measurements, including globe temperature and wind speed ([Liljegren et al., J. Occup. Environ. Hyg., 2008](#)); an open implementation of their code is available ([wbgt package](#)). HeatMap Node measures the inputs this model needs.
- **Heat and equity studies.** Satellite studies across 175 large US urbanized areas found that the average person of color lives in a census tract with higher surface urban heat island intensity than non-Hispanic white residents in all but 6 of them ([Hsu et al., Nature Communications, 2021](#)). These studies use surface temperature; HeatMap Node adds what people experience at street level.
- **Mobile heat campaigns.** Some cities map heat on a single hot day with vehicle-mounted or hand-held sensors. These give good spatial detail but not the season-long, day-and-night record that fixed nodes give.
- **Lab components.** FieldNode (shared outdoor core), CalRig (sensor calibration chamber) and TwinKit (gateway and data layer) are sibling concepts in this lab. CoolShade is the lab's shade structure concept that HeatMap data is meant to help site.

■ Open questions

- Which city or community partner hosts the first network, and on whose poles?
- What mounting height is acceptable to pole owners? HMN-CAL-001 gives a first estimate of the height error (up to about 0.8 °C in strong sun); a field comparison of 2.0 and 2.8 m is still needed.
- Which output do users want most: air temperature, WBGT, mean radiant temperature, or a simple heat stress category?
- Who owns and publishes the data?

■ User research and co-design

This design is for communities the author is not part of, so requirements come from the people who will use it.

- [] Identify a local partner organization (Helpful Engineering network, NGO or university)
- [] Run co-design sessions with intended users; record who, where and what was learned
- [] Validate load, distance, terrain and cost assumptions in the field
- [] Revise requirements (REQ) from findings before freezing the design