



CONCEPT, NOT FOR FABRICATION

REV	DESCRIPTION	DATE	BY
P1	Preliminary GA for TRL 3 (from cad/src/model.py)	2026-09-25	AC



MAIN DIMENSIONS AND INTERFACES (MM)

Mirror 600 x 600 x 3 glass on 4 ACP; sweep radius 301
Elevation axis at Z 2,200; 25 sq. torque tube, 14 trunnions
Yoke arms 40 x 70 at X +/-340; gaps 20 (arm), 46 (crossbar)
Drives: NEMA17 on NMRV030-class 50:1, envelope 80 x 97 x 63, 14 bore
Mast 60.3 x 3.9 galv. pipe, 1,700 long; cap 160 sq. x 8
Anchor flange 220 dia.; ground screw 76 x 800 (not shown)
Anemometer at Z 1,500, reach 550; controller box at Z 1,100
Top mass about 12.5 kg; stow face-down in 23 s (HLT-CAL-001)
Orthographic views stowed at azimuth 0; front from -Y, right from +X

HELIOLITE

General arrangement

DRAWING NO. HLT-DWG-001			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:25	UNITS mm	PROJECTION 	DATE 2026-09-25		DRAWN Amish Chadha
MATERIAL / NOTES Glass mirror on ACP; printed ASA yoke; NMRV030-class drives; 60.3 mm galv. pipe. PRELIMINARY, NOT FOR FABRICATION					
Licensed CERN-OHL-S-2.0 · Open Hardware Portfolio · amishchadha.com			Generated from cad/src; do not edit by hand		