




REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-03	AC



WHERE IT GOES

This part in colour, its neighbours in grey



HOW TO MAKE IT AND HOW IT FITS

- Posts: two SHS 30 x 30 x 3, 300 mm apart, from the chord bottom up to 110 mm above the carriage rail; tied by two cross members.
- Top wheels: 60 mm double-flanged, 40 mm tread, on 20 mm stub axles welded into the posts; they ride on top of the carriage rail.
- Guide rollers: 40 mm ball-bearing rollers on vertical pins, on arms from the post feet; they bear on the outer face of the bottom chord and stop the hopper's weight swinging the frame in.
- Crank post: SHS 30 x 30 x 3 up to 30 mm over the crank shaft; 21 mm bearing hole at 1,260 mm above the floor.
- Hopper brackets: 6 mm plates from each post to the hopper wall.
- Housing shelf: 6 x 120 mm plate under the rotor housing.
- Clamp: M12 screw with a pad that clamps the frame to the rail.
- Check: rolls the full rail with 2 to 5 mm play at the rollers.

KILNDECK			github.com/BoujeeEnjinia1701/kilndeck		
KilnDeck hopper carriage frame: making sketch					
DRAWING NO. KND-DWG-109			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-10-03		DRAWN Amish Chadha
MATERIAL / NOTES SHS 30 x 30 x 3 mm; 6 mm plate; 60 mm wheels; 40 mm rollers; S275					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com			Generated from cad/src; do not edit by hand		