



REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-01	AC




TOP VIEW

Scale 1:5; looking down (along -Z)




FRONT VIEW

Scale 1:5; looking at the front (along +Y)



RIGHT VIEW

Scale 1:5; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Made as two half shells, front and back, that close round the barrel

(it cannot slide on over the nozzle). Each half, 217 mm long:

Guard: 1 mm perforated steel rolled to a half tube 116 mm across.

Skin: 0.5 mm aluminium rolled to a half tube 60 mm across.

Fill between with 25 mm mineral wool rated above 600 degrees C; close

the ends and the two split faces with aluminium strip, riveted.

Back half: a 20 x 40 mm notch in skin and wool at each heater band,

for its leads and terminal block.

Hanger tabs: two per half, 16 x 14 mm, 2 mm steel, riveted to the top

edge pointing out at 45 degrees to the split (132 mm circle);

drill each 5.5 mm.

Fit: each half hangs from the shelf on two M5 screws through 14 mm

spacers; the halves meet left and right; bottom edge 6 mm above the hex.

Check: the guard does not touch the barrel or the heaters anywhere.

MICROMOLD

github.com/BoujeeEnjinia1701/micromold

MicroMold insulation jacket and guard: making sketch

DRAWING NO. MMD-DWG-105			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:5	UNITS mm	PROJECTION 	DATE 2026-10-01		DRAWN Amish Chadha
MATERIAL / NOTES Perforated steel sheet 1 mm; aluminium sheet 0.5 mm; mineral wool 25 mm					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com				Generated from cad/src; do not edit by hand	