

MICROMOLD · CALCULATION

MicroMold sizing calculations

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	MMD-CAL-001	Version	0.3
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/micromold		
Source	docs/04-calcs/01-sizing.md @ e265d48		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-09-26	Amish Chadha	Budget approved by Amish (\$520, MMD-DDR-002); R14 from not met to at risk
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.1	2026-09-25	Amish Chadha	First issue for TRL 3 (shot size, drive and ratchet, structure, mold clamp, fill pressure, plunger clearance, heat, melt soak and cycle, power, fume hood, mass, cost)

MicroMold sizing calculations

On paper, MicroMold meets twelve of its sixteen requirements (eight by calculation, four by design), has three at risk, misses none and leaves one that only hardware can show. This issue includes the decisions Amish made on 2026-09-25 (MMD-DDR-002): a 40 kg mass target, two 300 W barrel bands, a mold cooling fan and injection-grade feedstock in R1. On 2026-09-26 Amish approved a `budget_usd` of \$520 to cover the priced BOM (MMD-DDR-002). Cost (R14) is now at risk: the press alone is \$507 against \$520 with molds counted as tooling, a 2.5 % margin, and \$597 with the first mold. The other two at risk are mass (R9, 39.2 kg against 40 kg with an assumed 8 kg arbor press head) and shot size (R2, if the fresh charge is not tamped). The 300 W bands bring warm-up to 12.2 min (R5), and the fan keeps the mold near 47 °C, so throughput (R6) is 11.6 parts per hour, limited by melt soak. The v0.1 calculations also showed that the TRL 2 concept could not work as drawn: a single pull of the arbor press handle moves the plunger only about 31 mm, not the 120 mm a shot needs, so a ratchet handle drives the pinion. Five more changes followed: a 4 mm nozzle orifice with a tapered sprue, a glass-epoxy spacer that keeps the load cell cool, a 20 mm bracket plate on mica pads, a nozzle zone shield, and a nozzle tip raised to 190 mm so that 120 mm mold stacks fit. Every number in this note is printed by `docs/04-calcs/sizing.py`; the tag in brackets, for example [B5], is the line of that script's output that carries it.

Safety: These are first-principles estimates for a paper proof of concept. They do not replace a pressure and electrical safety review of a built press. The barrel, nozzle and mold reach 180 to 260 °C, the melt is under pressure, the heaters run at mains voltage and an operator can load the press to about 1.35 times its rating. See MMD-PRC-001, Safety.

■ Scope and method

The note checks every requirement in MMD-REQ-001 v0.5 against the design in MMD-PRC-001 v0.5 and the parametric model `cad/src/model.py`. The script imports the model's `PARAMS` and `derived()` stack-up, so the bore, stroke, nozzle height, table travel, bracket, mold and hood used here are those in the STEP files and in drawing MMD-DWG-001. It also reads `bom/bom.csv` and `budget_usd` in `project.yaml`. Run it from the repo root with `python docs/04-calcs/sizing.py`.

The design case is the reference part of MMD-REQ-001: a 30 g HDPE test plaque, 64 x 50 x 6 mm, molded from washed, dried flake of 3 to 8 mm at a 220 °C barrel set point in a 25 °C workshop.

■ Assumptions

Table 1. Main assumptions.

Area	Assumption	Basis
HDPE properties	Melt density 0.75 g/cm ³ , solid 0.95 g/cm ³ ; cp 2.3 kJ/(kg K); 205 kJ/kg to melt the crystalline fraction; melt conductivity 0.25 W/(m K); tamped flake 0.12 W/(m K) at 450 kg/m ³ ; diffusivity 0.11 mm ² /s for part cooling	Typical handbook values; estimates to confirm for the chosen feedstock
Melt flow	Power law, $n = 0.40$, 150 Pa s at 1,000 s ⁻¹ ($K = 9,464 \text{ Pa s}^n$) at 210 °C, typical of injection-grade HDPE; 1,000 Pa s at low shear for leakage	Estimate; bottle-grade HDPE is several times more viscous
Drive	450 mm handle on a 20 mm pinion pitch radius; design efficiency 0.60 (TRL 2 value); friction 0.15 for the journal and ram guide; mesh 0.95	Arbor press dimensions to confirm on the chosen press
Operator	250 N design pull; 700 N when the operator hangs body weight on the handle; a comfortable ratchet pull of 90° (from 30° above horizontal to 60° below)	Ergonomic judgment
Structure	S235 steel, yield 235 MPa, 85 % of yield at 220 °C; E 200 GPa steel, 69 GPa aluminum	Handbook
Mold clamp	Four M10 class 8.8 bolts (58 mm ² , proof 600 MPa) at 20 kN preload each; factor 2 against opening	As at TRL 2
Heat	Combined convection and radiation 10 W/(m ² K) in still air, 30 W/(m ² K) with a fan; mineral wool 0.045 W/(m K); mica 0.5 W/(m K); G-11 glass-epoxy 0.30 W/(m K); steel cp 0.49 kJ/(kg K); a factor of 1.2 on warm-up for PID approach and heater lag	Handbook ranges
Cycle	Ejection at 95 °C; step times in Table 3	Estimates, to be timed later
Fume capture	Flanged side hood, capture velocity 0.40 m/s at 100 mm from the funnel axis (low-velocity release into quiet air)	Common design range for hoods
Mass	Arbor press head, ram and ratchet 8.0 kg; jacket 1.0 kg; screw jack 1.5 kg; hood on the press 0.6 kg; mold cooling fan and bracket 0.7 kg; hardware 1.0 kg	Assumed; the head mass depends on the chosen press

■ A. Shot size and mold stack (R2, R7)

- **Swept volume.** The 22 mm plunger has 380.1 mm² of area. Of the 150 mm stroke, the first 30 mm clears the funnel and 120 mm is in the bore, sweeping 45.6 cm³ [A1], or 34.2 g of HDPE melt, 14 % above the 30 g target [A2].
- **Reservoir.** At full stroke 140 mm of bore (53.2 cm³, 40 g) stays below the plunger tip, so the barrel holds 2.2 shots [A3], and each charge soaks for about two cycles before it is injected.
- **Compaction eats stroke.** Only 15 mm of stroke is spare once 30 g has been delivered. If the fresh charge on top is still loose flake at 0.55 g/cm³ when the operator injects, compacting it takes about 32 mm and the shot falls to about 25 g [A4]. Tamping each top-up with the press while loading is therefore part of the process, and R2 is **at risk** until a trial shows the charge is dense enough.
- **Mold stack.** With the nozzle tip at 190 mm and a lift table that travels from 60 to 160 mm, mold stacks from 30 to 120 mm fit with 10 mm to drop clear of the nozzle; the 90 mm test mold sits at 100 mm [A5]. The TRL 2 layout, with the nozzle at 152 mm, could not take a 120 mm stack.
- **Mold footprint.** The column face is 65 mm behind the axis, so molds up to 120 mm deep across Y fit, and a 150 x 120 mm mold goes in with its long side along X [A6].

■ B. Drive, force and the ratchet (R3, R2)

- **Ratio and efficiency.** The handle and pinion give 22.5:1. Friction losses at the mesh, the pinion journals and the ram guide give an efficiency of about 0.84; the design keeps the TRL 2 value of 0.60 as a margin for a worn or dirty press [B1].
- **Pressure.** At 250 N on the handle the plunger force is 3.38 kN and the melt pressure 8.9 MPa (89 bar, 1,288 psi) at 0.60 efficiency, or 4.71 kN and 12.4 MPa at 0.84 [B2]. R3 (8 MPa) needs an efficiency of 0.54, a margin of 11 % at the design value [B3].
- **Overload.** An operator hanging 700 N of body weight on the handle produces 13.2 kN and 34.7 MPa, 1.35 times the 1 t rating of the press [B4]. Sections C and D size the parts for this case.
- **Stroke per pull (finding).** Filling the 120 mm of bore turns the pinion 344° and moves the grip 2.70 m. One comfortable 90° pull moves the plunger 31.4 mm, so a shot takes 3.8 pulls [B5]. No single sweep of a 450 mm handle can deliver the shot; the TRL 2 statement that "a steady pull drives the plunger 120 to 150 mm" was wrong. The work confirms it: at full pressure a shot needs 405 J at the melt and 675 J at the handle, while one 90° pull at 250 N gives 177 J [B6].
- **Change.** A 1/2 in drive ratchet handle, 450 mm long, on a socket fitted to the pinion shaft replaces the press's fixed handle (BOM item 2, about \$25). The pawl holds the ram between pulls, so the melt stays under pressure while the operator resets. This is within the rack-and-pinion drive (MMD-DDR-001 D1), decided by Amish on 2026-09-25.

■ C. Structure and overload

- **Barrel.** The thick-walled barrel (42 mm OD, 22 mm bore) sees a hoop stress of 1.76 times the melt pressure: 15.6 MPa at design and 61.0 MPa at overload, a factor of 3.3 on 85 % of yield at 220 °C [C1].
- **Column.** The barrel axis is 95 mm in front of the column center, so the 80 x 60 x 3 mm tube carries a bending moment between the bracket and the drive head: 34.5 MPa at 4.71 kN (factor 6.8) and 96.6 MPa at the 13.2 kN overload (factor 2.4) [C2, C3]. The frame opens about 0.29 mm at the ram in use [C4], so the plunger joins the load cell through a pinned floating coupling and is guided only by the bore.
- **Bracket (change).** The bracket cantilevers 65 mm from the column face. A 10 mm plate, as in the TRL 2 BOM, reaches 167 MPa in use (factor 1.4) and would yield at overload (468 MPa, factor 0.5). A 20 mm plate gives 42 MPa in use and 117 MPa at overload, a factor of 2.0 [C5a, C5b, C6a, C6b]. BOM item 9 is now a 20 mm plate.
- **Plunger and load cell.** Plunger buckling is not a concern (567 kN, 43 times the overload force) [C7]. The 10 kN load cell sees 4.71 kN in use and 13.2 kN at overload, inside the 150 % safe overload typical of such cells but above its rated range [C8]; a handle stop that limits the pull is still recommended (Safety).

■ D. Mold clamp (R7)

- **Bolts.** Four M10 class 8.8 bolts at 20 kN preload each (57 % of proof) need about 40 N m of torque [D1].
- **Area.** With a factor of 2 at 8.9 MPa the bolts hold 45 cm² of projected area, against the 40 cm² target; the 32 cm² plaque pushes the plates apart with 28.4 kN [D2]. R7 is met on paper.
- **Overload.** At 34.7 MPa the plaque would push with 111 kN against 80 kN of preload, so the parting line flashes and spits melt, while each bolt stays below its proof load at 27.8 kN [D3]. The nozzle zone shield is for this case.
- **Plates.** The 45 mm plates bend 11 µm between bolt rows, at 22 MPa, below the 20 to 30 µm at which HDPE starts to flash [D4].

■ E. Fill pressure through the nozzle and sprue (R3)

Table 2. Pressure needed to fill the plaque [E1 to E4].

Nozzle orifice	Sprue	Fill time	Nozzle	Sprue	Cavity	Total	Available at 250 N
3 mm (TRL 2)	4 to 6 mm	3 s	4.6 MPa	6.7 MPa	0.9 MPa	12.1 MPa	8.9 MPa
3 mm (TRL 2)	4 to 6 mm	10 s	2.8 MPa	4.1 MPa	0.5 MPa	7.5 MPa	8.9 MPa
4 mm	5 to 7 mm	10 s	1.5 MPa	2.8 MPa	0.5 MPa	4.8 MPa	8.9 MPa
4 mm	5 to 7 mm	20 s	1.1 MPa	2.1 MPa	0.4 MPa	3.6 MPa	8.9 MPa

- **Change.** A shear-thinning melt needs almost as much pressure for a slow fill as for a fast one, so the TRL 2 nozzle left little margin. A 4 mm orifice and a sprue tapering from 5 to 7 mm bring a 10 s hand fill down to 4.8 MPa, about half the pressure available. BOM items 8 and 12 are updated.
- **Pauses.** A 6 mm sprue core in a 50 °C mold takes about 25 s to freeze, so the pauses of about 1 s between ratchet pulls do not stop the fill [E5].
- **Feedstock.** HDPE from blow-molded bottles (melt flow index below 1) is about five times as viscous and would need about 24 MPa, beyond the press [E6]. Flake from injection-molded items (caps, crates, buckets) suits it; R1 now requires it (MMD-DDR-002).

■ F. Plunger clearance

- **Backflow.** At 8.9 MPa over 30 mm of seal, a diametral clearance of 0.05 mm leaks 1 mm³ during a 30 s hold, 0.10 mm leaks 6 mm³ and 0.20 mm leaks 51 mm³, all negligible against a 45,600 mm³ shot [F5, F10, F20]. The charge above the melt also seals the gap.
- **Fit.** The hot bore grows about 32 µm more than a plunger at 100 °C, so the gap opens as the barrel heats. A cold diametral clearance of 0.05 to 0.10 mm is recommended; 22 H8/f7 gives 0.020 to 0.074 mm [F9]. This answers the TRL 2 open question on clearance.

■ G. Heat: warm-up, losses, skin and load cell (R5, R11, R4)

- **Heat to store.** The barrel zone holds 2.05 kg of barrel, about 0.70 kg of flange and funnel and 0.30 kg of heaters, and needs 340 kJ to reach 220 °C including 40 g of cold plastic and the mineral wool [G1].
- **Jacket.** 220 mm of 25 mm mineral wool loses 18 W, with the skin at 48 °C at a 220 °C set point [G2]. R11's 60 °C limit is met on paper for the jacket.
- **Standing losses.** At 220 °C: jacket 18 W, funnel 18 W, nozzle 21 W, bracket heat break 35 W through four mica pads (0.25 W/K) and plunger 12 W, 103 W in all [G3]. The TRL 2 figure was about 80 W.
- **Warm-up.** With two 300 W bands (MMD-DDR-002) the barrel zone reaches 220 °C in 12.2 min and the nozzle zone in 6.6 min [G4]. R5 (15 min) is met on paper. The 250 W bands of v0.1 took 14.8 min, 2.7 min longer [G4b].
- **Heater loading.** The 300 W bands run at 4.5 W/cm², well inside the roughly 7.7 W/cm² (50 W/in²) usual for mica bands [G5].
- **Load cell (change).** The plunger behaves as a fin: with its tip at 150 °C its top end reaches about 94 °C, too hot for a strain-gauge load cell. A 10 mm G-11 glass-epoxy spacer (88 K/W) under the cell keeps it at about 27 °C [G6]. The spacer is added to BOM item 4 (about \$5).

- **Temperature control (R4).** Two PID loops with a 150 to 260 °C set range, a set point limit and an independent 280 °C cut-out meet R4 by design; the ± 5 °C hold needs a test later.

■ H. Melt soak, mold heat and cycle (R6)

- **Soak.** For the center of a 22 mm column to reach 180 °C with the wall at 220 °C takes 7.5 min as melt and 9.3 min as tamped flake [H1]. Each charge soaks for about two cycles, so cycles shorter than about 5 min would starve the melt.
- **Mold heat (finding).** Each shot puts 19.5 kJ into the 2.62 kg aluminum mold, 54 W at 6 min cycles. In still air the mold settles at about 92 °C and the 6 mm plaque needs 2.1 min to cool to 95 °C [H2]. With the mold cooling fan (BOM item 18, MMD-DDR-002) blowing on it through the shield side it settles at about 47 °C and needs 0.8 min [H3].

Table 3. Cycle steps [H4, H5].

Step	Time
Load and tamp the fresh charge	1.0 min
Bolt the mold and raise the table	0.75 min
Inject in four ratchet pulls	0.25 min
Hold	0.5 min
Cool in the mold	0.8 min (fan) or 2.1 min (still air, v0.1)
Lower, unbolt, open and eject	1.0 min
Clean and reassemble	0.75 min
Cycle	5.1 min (fan), 5.2 min with the soak limit; 6.4 min (still air)

- **Throughput.** In still air the cycle would be 6.4 min, 9.4 parts per hour, with the plaque leaving a 92 °C mold barely below its ejection temperature [H4]. With the fan the cooling steps allow 5.1 min, but each fresh charge must soak about two cycles for 9.3 min, so the design cycle is 5.2 min, 11.6 parts per hour, with the mold near 47 °C [H5, H6]. R6 (8 per hour) is met on paper.

■ I. Power and energy (R10)

- **Load.** 700 W of heaters, a 25 W duct fan, an 18 W mold fan and about 10 W of controls give 753 W: 3.3 A at 230 V and 6.3 A at 120 V [I1]. R10 is met on paper.
- **Energy.** A shot takes 6.3 Wh into the plastic and 13.4 Wh of losses and auxiliaries over a 5.2 min cycle, about 20 Wh, or 0.66 kWh per kg of parts [I2]. The barrel zone runs at about 26 % duty [I3].

■ J. Fume hood (R13)

A flanged side hood with a 150 x 100 mm face, 100 mm from the funnel axis, needs about 124 m³/h for a capture velocity of 0.40 m/s; in a 100 mm duct that is 4.4 m/s [J1]. A 100 mm inline duct fan rated 170 m³/h or more of free air covers this with margin for 3 m of flexible duct. Fumes from the nozzle rise inside the shield and along the warm jacket to the hood; that path is assumed, not calculated. With the set point limit of 260 °C in both controllers and the written condition to run only under the hood or outdoors, R13 is met on paper.

■ K. Mass and size (R9)

- **Mass (at risk).** Base plate 7.8 kg, column 5.7 kg, arbor press head, ram and ratchet 8.0 kg (assumed), bracket 2.6 kg, barrel set and heaters 3.4 kg, plunger and load cell 1.0 kg, jacket and guard 1.0 kg, clamp 3.6 kg, mold set 3.0 kg, shield 0.9 kg, hood 0.6 kg, mold cooling fan and bracket 0.7 kg and hardware 1.0 kg: 39.2 kg without the control box [K1], 0.8 kg under the 40 kg target set by MMD-DDR-002 (98 % of it) [K3]. With the head mass still assumed, R9 is **at risk**. The TRL 2 figure of 32 kg left out the bracket, the table and the mold bolts and had a lighter bracket.
- **Size.** The footprint is 320 x 260 mm and the handle reaches 1,089 mm above the bench at the highest start of a pull; the ram top is at 1,015 mm [K2]. Both meet R9.

■ L. Cost (R14, R8)

The BOM has 18 lines, all priced: \$597.00 with one mold, of which the press is \$507.00, the test mold \$90.00 and the fume extraction \$48.00 [L1]. Against `budget_usd` of \$520 (approved by Amish on 2026-09-26, MMD-DDR-002; was \$500, and \$400 before that):

- **Press alone (MMD-DDR-001 D8 scope):** \$507.00, under by \$13.00 (2.5 % margin). With indicative prices and less than 5 % margin, R14 is **at risk** [L2].
- **Press and one mold:** \$597.00, over by \$77.00; the mold is tooling outside the budget [L2].
- Without the fume extraction the press would be \$459.00 [L2].

The mold at \$90.00 meets R8 (\$100) on an indicative price. MMD-DDR-002 added the mold cooling fan (\$12.00, item 18); the 300 W bands cost about the same as the 250 W bands. The \$7 overrun that remained at \$500 is closed by the \$520 budget (O3 decided, 2026-09-26).

■ M. Results against every requirement

Table 4. Requirement status from this note [M].

ID	Requirement	Value	Target	Status
R14	Affordable	\$507 press; \$597 with one mold	Press \$520 or less, molds as tooling	At risk
R9	Bench size and mass	320 x 260 mm; 1,089 mm; 39.2 kg	350 x 300 mm; 1.1 m; 40 kg	At risk (mass)
R2	Shot size	34.2 g ideal; about 25 g if the fresh charge is loose flake	30 g or more	At risk
R3	Injection pressure	8.9 MPa at 0.60 efficiency (12.4 MPa at 0.84); fill needs about 4.8 MPa in 10 s	8 MPa at 250 N or less	Met on paper
R5	Warm-up	12.2 min (barrel zone, 2 x 300 W)	15 min or less	Met on paper
R6	Throughput	11.6 per hour with the mold fan, mold about 47 °C	8 per hour or more	Met on paper
R7	Mold envelope	45 cm ² at 8.9 MPa; stacks 30 to 120 mm; 170 x 130 mm table	150 x 120 mm, 40 to 120 mm stack, 40 cm ²	Met on paper
R8	Low-cost tooling	\$90 (indicative)	\$100 or less	Met on paper
R10	Power supply	753 W; 6.3 A at 120 V	1 kW or less; 10 A or less at 120 V	Met on paper
R11	Touch-safe surfaces	Jacket skin 48 °C; nozzle zone shield added	60 °C or less; nozzle and mold zone guarded	Met on paper
R13	Fume control	Hood and fan, 124 m ³ /h; set point limit 260 °C	Exhaust hood or outdoors; set points above 260 °C blocked	Met on paper
R1	Safe thermoplastics	HDPE, PP, LDPE and PS within 150 to 260 °C from injection-molded items; PVC and bottle-grade HDPE excluded by label and procedure	Four resins, injection grade; PVC excluded	Met by design
R4	Temperature control	Two PID zones, 150 to 260 °C set range, set point limit, 280 °C cut-out	150 to 260 °C, ±5 °C; cut-out above 280 °C	Met by design
R12	Electrical safety	Earthed frame, fused inlet, double-pole switch, RCD or GFCI, 250 °C wiring	As listed	Met by design
R15	Garage-buildable	Only the barrel set and molds need a lathe or mill (local shop)	Hand tools, drill press, optional welding	Met by design
R16	Repeatable parts	Needs hardware	Mass within ±3 % over 10 shots	Not verifiable at TRL 3

Counts: 0 not met, 3 at risk, 8 met on paper, 4 met by design, 1 not verifiable at TRL 3.

■ Checks against the TRL 2 figures

TRL 2 claim (MMD-PRC-001 v0.2)	This note	Action
About 34 g per shot	34.2 g ideal; about 25 g with an untamped charge	Stands; tamping made part of the process
One steady pull drives the plunger 120 to 150 mm	31.4 mm per 90° pull; 3.8 pulls	Ratchet handle added, precis corrected
About 8.9 MPa at 250 N, R3 met with about 10 % margin	8.9 MPa at 0.60 (11 % margin); 12.4 MPa at 0.84	Stands
3 mm nozzle orifice	Needs up to 12.1 MPa to fill	4 mm orifice and 5 to 7 mm sprue
About 45 cm ² clamp limit	45 cm ²	Stands
Nozzle at 152 mm; 40 to 120 mm stacks	120 mm stacks did not fit	Nozzle tip raised to 190 mm
10 mm bracket plate	Yields at overload	20 mm plate
Load cell on the plunger	About 94 °C	G-11 spacer added
Warm-up about 10 to 12 min	14.8 min in v0.1; 12.2 min with 300 W bands	300 W bands (MMD-DDR-002)
Standing losses about 80 W	103 W	Precis updated
About 6 min per shot, 10 per hour	6.4 min in still air (mold about 92 °C); 5.2 min, 11.6 per hour with a fan	Mold cooling fan (MMD-DDR-002)
About 600 W	753 W with 300 W bands and both fans	Precis updated
About 14 Wh per shot, 0.5 kWh per kg	About 20 Wh, 0.66 kWh per kg	Precis updated
About 32 kg	39.2 kg with the fan	R9 target 40 kg (MMD-DDR-002); at risk
Handle knob about 1.06 m	1,089 mm at the start of a pull	Precis updated
\$399 press, \$489 with one mold	\$507 press, \$597 with one mold	budget_usd \$520 (MMD-DDR-002, 2026-09-26); R14 at risk, \$13 margin