

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-03	AC



TOP VIEW
Scale 1:20; looking down (along -Z)



FRONT VIEW
Scale 1:20; looking at the front (along +Y)



RIGHT VIEW
Scale 1:20; looking at the right side (along -X)

WHERE IT GOES
This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

One blade: UHMW-PE 15 mm sheet, 3,000 long x 300 tall.
Round the two top corners R20. Keep the bottom edge straight and square: it is the gathering edge.
Holes match the beam: 11 mm, countersunk on the front face so the M10 countersunk heads sit 1 mm below the surface.
Ten blade bolt holes 100 mm above the bottom edge, 150 to 1,350 each side of the middle, 300 apart.
Six skid hanger bolt holes 75 and 125 mm above the bottom edge at the middle and 1,200 each side.
Drill with a sharp wood bit; clear the swarf; no heat.
Fit: the back face sits flat on the beam's front face; the bottom edge 50 mm below the beam, 10 mm above the floor in use.
Check: the bottom edge is straight within 3 mm along its length.

SALTDRAW			github.com/BoujeeEnjinia1701/saltdrag		
SaltDrag rake blade: making sketch					
DRAWING NO. SDG-DWG-111			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-10-03		DRAWN Amish Chadha
MATERIAL / NOTES UHMW-PE sheet 15 mm, 3,000 x 300 mm					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com				Generated from cad/src; do not edit by hand	