

SEEDLINE · DESIGN PRECIS

SeedLine design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	SDL-PRC-001	Version	0.4
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/seedline		
Source	docs/02-concept.md @ a72a3ea		

REVISION HISTORY


Version	Date	Author	Change
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	Record decisions (SDL-DDR-001); numbers replaced by SDL-CAL-001 results; parametric model, SDL-DWG-001 and refreshed media
0.2	2026-09-25	Amish Chadha	Populate to TRL 2 (architecture, metering numbers, work rate, push force, cost, safety, media)
0.1	2026-09-24	Amish Chadha	Initial scaffold

SeedLine design precis

SeedLine is a single-row push seeder. A 300 mm lugged ground wheel drives a vertical, 3D-printed seed plate through a #35 roller chain, so seeds are placed at a spacing set by distance travelled, not by walking speed. A runner opener cuts the furrow, chains cover the seed and a concave press wheel firms the row. Crop and spacing change by swapping a printed plate (1 to 36 cells) and, if needed, a 12 or 18 T wheel sprocket from an optional ratio kit. An optional telescoping marker arm scratches the line of the next row. The TRL 3 calculations (SDL-CAL-001 v0.2, after the recommendations Amish accepted in SDL-DDR-002) give an in-row spacing range of 22 to 589 mm with the ratio kit, a work rate of 0.142 ha/h for maize on 0.75 m rows at 2.9 km/h (7.1 h/ha against about 56 h/ha by hoe), a push of about 132 N in the design case, a mass of 13.9 kg (14.9 kg with the marker kit) and a parts cost of \$197.50 for the base seeder and \$237.50 with both kits. Every requirement is now met on paper or cannot be verified at TRL 3 except placement quality (R1, R2) and push effort (R10), which are at risk; mass (R11) and base cost (R17) are met with thin margins.

SeedLine

CONCEPT, NOT FOR FABRICATION



Grey figure: 1.75 m person for scale

Figure 1. SeedLine from the TRL 3 parametric model (`cad/src/model.py`), with the row marker deployed at 0.75 m, the opener at 50 mm working depth and a 1.75 m person for scale. Direction of travel is toward the lower right.

■ How it works

1. **Load.** The operator pours up to about 2 L of seed into the hopper (item 4), which feeds the metering housing (item 5) below it.
2. **Drive.** As the seeder is pushed, the lugged ground wheel (item 1) turns. A 15-tooth #35 sprocket on its axle drives a 15-tooth sprocket on the plate shaft through a 76-link roller chain (item 2), and a spring idler takes up the remaining slack. The optional ratio kit (item 16 in the BOM) adds 12 T and 18 T wheel sprockets, which change the plate speed by 0.8 or 1.2 times with a 74- or 77-link chain.
3. **Walk at the set pace.** The operator walks at about 2.9 km/h, or about 2.4 km/h with the 1.2 ratio (the walking-speed rule, SDL-DDR-002 item 5), so the cells pass the seed pool slowly enough to fill.
4. **Meter.** The printed seed plate (item 6) turns upright inside the housing. Cells on its rim pass through the seed pool at the bottom of the hopper, each picking up a seed. A brush (item 7) at the top of the plate sweeps off extra seeds, so each cell carries one.
5. **Drop.** As a cell passes the outlet on the forward side of the housing, its seed falls through the drop tube (item 8) into the furrow cut by the runner opener (item 9), just behind the opener's point.
6. **Cover and firm.** Two drag chains (item 10) pull soil over the seed and the concave press wheel (item 11) firms it, which improves seed-soil contact.
7. **Mark the next row.** The marker arm (item 14), clipped to the front cross member, drags a small disc at the set row spacing. On the return pass the operator follows that line with the ground wheel.

The frame (item 12) is two 25 x 25 x 1.5 mm square steel rails with bolted cross members, corner plates and axle drop plates; the handle (item 13), of 22 x 1.2 mm round tube, telescopes for operator height. The general arrangement is drawing SDL-DWG-001.

SeedLine: seeds per 100 m of row, maize plate at 250 mm; doubles add seeds (all values are estimates, SDL-CAL-001)

CONCEPT, NOT FOR FABRICATION




Figure 2. Seed flow over 100 m of row for the maize plate at 250 mm spacing. All values are estimates (the miss and double rates are assumptions carried into SDL-CAL-001); doubles add seeds, so more seeds are dropped than cells are filled.

■ Main components

Numbers match the exploded view (Figure 3) and `bom/bom.csv`.

#	Component	Proposed choice	Notes
1	Ground drive wheel	300 mm diameter, 45 mm wide, 18 lugs, on a 16 mm axle with bearings	Lugs limit slip; a narrow wheel runs in the tilled row
2	Chain drive	#35 roller chain, 15 T plate and 15 T wheel sprockets, spring idler; 12 and 18 T wheel sprockets in the optional ratio kit	76 links at 286 mm centers (74 or 77 with the kit); idler deflects up to 35 mm
3	Chain guard	Band around the chain loop with an outboard face plate, PETG or sheet steel	Covers the nip points from above, below and outside
4	Seed hopper	2.4 L, 170 x 120 mm top on a funnel to a 60 x 30 mm throat, printed or cut from HDPE, lid	1.73 kg of maize, 1,438 m of row per fill
5	Metering housing, shaft and bearings	Printed housing with seed outlet and side door; 12 mm shaft in two flange bearings	Side door and hand knob give tool-free plate changes
6	Printed seed plate	120 mm diameter, 6 to 10 mm thick, 1 to 36 rim cells sized to the seed (make_plate in the model)	40 to 54 g of PETG, 1.5 to 2.0 h to print; one plate per crop and spacing
7	Singulator brush	Nylon strip brush on a printed holder, adjustable gap	Wear part
8	Seed drop tube	20 mm tube, housing outlet to the opener	Short drop limits bounce
9	Furrow opener and depth bracket	Runner shoe on a steel shank, clamped in a slotted bracket (10 to 60 mm depth)	Depth set against the wheels
10	Covering chains	Two short lengths of light chain on a bracket	Low cost, self-cleaning
11	Press wheel	200 mm diameter, 70 mm wide concave rubber tread	Firms the row; carries part of the load
12	Steel frame	25 x 25 x 1.5 mm square tube rails and cross members, 6 mm axle drop plates, 20 mm hopper posts, corner plates	Bolted (decided); welding optional
13	Handle	Two 22 x 1.2 mm round tubes with a cross grip and brace, telescoping for 850 to 1,050 mm grip height	Model grip at 950 mm, 50° to the ground; 2.3 kg (lighter tube, SDL-DDR-002)
14	Row marker arm (row-spacing kit)	Telescoping arm and 140 mm marker disc, 200 to 900 mm reach, folds up for transport	Optional kit

SeedLine: exploded view

CONCEPT, NOT FOR FABRICATION

- 1 Ground drive wheel, 300 mm lugged
- 2 Chain drive, sprockets, chain and idler
- 3 Chain guard
- 4 Seed hopper
- 5 Metering housing, shaft and bearings
- 6 Printed seed plate (per crop)
- 7 Singulator brush
- 8 Seed drop tube
- 9 Furrow opener and depth bracket
- 10 Covering chains
- 11 Press wheel, 200 mm concave
- 12 Steel frame, bolted
- 13 Handle, height adjustable
- 14 Row marker arm (row-spacing kit)




Figure 3. Exploded view with numbered callouts matching the BOM.

SeedLine: cutaway

CONCEPT, NOT FOR FABRICATION




Figure 4. Section on the row centerline, seen from the chain side with that half removed. The four-cell maize plate sits upright in the housing under the hopper funnel, with the brush at the top and the outlet feeding the drop tube into the opener. The drive wheel is on the right, the press wheel on the left.

■ Key numbers (SDL-CAL-001)

The TRL 2 estimates in version 0.2 are replaced by the calculations in SDL-CAL-001 v0.2, which reads its geometry from the parametric model. The main results:

Table 1. Key numbers from SDL-CAL-001.

Quantity	Value	Requirement
Spacing	$s = 942.5 \text{ mm} / (\text{cells} \times \text{ratio})$, longer by 1 / (1 – slip); 22 to 589 mm nominal with 1 to 36 cells and ratios 0.8, 1.0, 1.2 (ratio kit); 26 to 471 mm with the base 15 T only	R3 met with the ratio kit
Maize plate	4 cells at 1.0: 236 mm nominal, 248 mm with 5 % slip	Design case
Cell speed, design case	0.299 m/s at the 2.9 km/h walking-speed rule, against an assumed 0.30 m/s fill limit	R1 at risk
Skid from meter torque	1.2 to 1.7 %; rolling radius uncertain by up to 6.7 %	R4 met
Spacing CV, maize	31 % of all spacings, 9 % of single spacings (assumed miss and double rates)	R2 at risk
Plates	40 to 54 g PETG, 1.5 to 2.0 h each; raw seed 3.5 to 15 mm, smaller seed pelleted	R5 met, R6 met with no margin
Push force (horizontal part)	80 N good, 132 N design case along the handle; 177 N at best on a heavy, loose seedbed	R10 at risk
Mass	13.9 kg base, 14.9 kg with the marker kit	R11 met, 0.06 kg margin
Work rate	0.142 ha/h (7.1 h/ha) on 0.75 m rows at 2.9 km/h	R9 met
Hopper	2.40 L, 1,438 m of maize row per fill	R12 met
Depth	$\pm 10 \text{ mm}$ needs wheel-path bumps within about $\pm 15 \text{ mm}$ under the drive wheel	R8 met on paper, restated for ploughed field-crop seedbeds
Parts cost	\$197.50 base; \$237.50 with the marker kit (\$24) and the ratio kit (\$16)	R16 met, R17 met with 1.2 % margin

A purely horizontal push at the grip pitches the seeder forward and lifts the press wheel, so the operator pushes down along the handle; on a heavy, loose seedbed a push along the full 50° handle angle sinks the press wheel, and a flatter push of about 36° works best. The base seeder costs a little more than an Earthway 1001-B with six plates (about \$187) and well under a Jang JP-1 without rollers (about \$499) ([UMN Extension](#)).

With the Purdue figure of about 2.2 to 2.5 bu/acre lost per inch of spacing standard deviation ([Nielsen, Purdue University](#)), each 25 mm of spacing variation avoided is worth about 140 to 160 kg/ha of maize at those yield levels; smallholder yields are lower, so the absolute gain will be smaller.

■ Key design choices

Decided by Amish on 2026-09-25 (SDL-DDR-001: go with the TRL 2 recommendations):

- **Metering type:** a vertical cell plate on a transverse shaft, driven directly by the chain. The plate is a flat print with no supports.
- **First user group:** smallholder field crops (maize, beans, sorghum, groundnut on 0.75 m rows) first; vegetable plates as a second plate set.
- **Row-spacing kit:** a telescoping marker arm. A gang bar for two or three metering units is recorded as a later variant for vegetable beds.

- **Ratio change:** plate cell count plus a 12, 15 or 18 T wheel sprocket, with a spring idler.
- **Long spacings (R3):** keep the 400 mm target and add skip-cell plates with one or two cells.
- **Small seed (R5):** pelleted seed for 1 to 2 mm seed at first.
- **Wheel layout:** front drive wheel, rear press wheel.
- **Frame joining:** bolted square tube by default; welding stays an option for workshops that weld.
- **Plate material:** PETG by default, ASA where plates sit in strong sun, PLA for trials only.

Decided by Amish on 2026-09-25 (SDL-DDR-002: go with the TRL 3 recommendations):

- **Mass (R11):** a lighter handle of 22 x 1.2 mm round tube in place of 25 x 1.5 mm, which saves 0.65 kg and brings the seeder with the marker kit to 14.9 kg.
- **Base cost (R17):** keep the target and move the 12 and 18 T wheel sprockets to an optional ratio kit; the base seeder ships with the 15 T only and costs \$197.50.
- **Cell speed (R1):** a walking-speed rule of about 2.9 km/h (2.4 km/h with the 1.2 ratio); the plate size is revisited only with bench data, which is TRL 4 work and on hold.
- **Depth on rough seedbeds (R8):** accept the rigid opener for field crops on ploughed land and review with partner data; a spring-loaded opener or depth-gauge shoe is not added now.

Still proposed, awaiting Amish:

- **Standalone plate generator.** The model's `make_plate` function already makes a plate from seed dimensions and cell count. Whether to publish it as a separate tool for printers is open.
- **Partner and region for co-design.** Left open under the portfolio rule that community designs pick co-design partners per area later.

■ Safety

Safety: SeedLine has an exposed roller chain driven by the wheel, a pointed steel opener and lugs, and is often used with chemically treated seed. Treat each as a hazard during use, cleaning, transport and plate changes.

- **Chain and sprocket nip points.** The chain moves whenever the wheel turns, including when the seeder is pushed or carried with the wheel spinning. Fingers, loose clothing and plant material can be drawn into the sprockets. The chain guard (item 3) must be fitted whenever the seeder is used, and plate changes and cleaning must be done with the wheel lifted clear and held still. Children should not push the seeder.
- **Sharp and pointed parts.** The opener point and the wheel lugs can cut shins and feet. Deburr all cut edges, round the lug tips and fit a cover over the opener for transport and storage.
- **Treated seed.** Seed dressed with fungicides or insecticides is toxic. Follow the seed label: wear gloves, do not eat, drink or smoke while filling, keep treated seed away from children and animals, and clean the hopper and housing outdoors. Never use the hopper for food or feed.
- **Row marker arm.** The deployed arm sticks out up to about 0.9 m to the side and can strike people or catch on posts at row ends. Fold it for turns near people and for transport.
- **Manual handling.** Lifting and turning at row ends and pushing on heavy soil can strain the back and shoulders (R10 and R11). Handle height must be set for the operator, and the seeder should be carried by two people or wheeled over rough ground.

- **Printed parts.** Plates, hopper and housing are plastic and can crack in cold or sun; a cracked plate can jam the drive. Inspect plates before each season and replace any that are cracked or worn.

■ Open questions

TRL 4 is on hold by Amish's instruction. These questions remain for review:

- R11 and R17 are met with thin margins (0.06 kg and \$2.50); any added part needs a matching saving.
- Whether the lighter 22 x 1.2 mm handle and its telescoping joint stand up to use (factor 1.9 on yield under the static side load; fatigue needs a test at TRL 4).
- Whether to reduce the plate diameter to lower cell speed (R1), revisited only with bench data (SDL-DDR-002 item 5).
- Whether a spring-loaded opener or a depth-gauge shoe is needed on rough, hand-tilled seedbeds (R8), to be reviewed with partner data.
- Soil data (cone index, opener draft) from the partner region to firm up the push force (R10).
- The miss and double rates of printed plates, which only a bench test can give (R1, R2).
- The co-design partner, region and first crops and spacings to support.

Concept media: [blueprint sheet](#), [interactive 3D model](#). General arrangement: [SDL-DWG-001](#). Calculations: [SDL-CAL-001](#).