


CONCEPT, NOT FOR FABRICATION


SinkGrab · github.com/BoujeeEnjinia1701/sinkgrab

REV	DESCRIPTION	DATE	BY
P1	Preliminary GA for TRL 3 (from cad/src/model.py)	2026-10-03	AC
P2	SKG-DDR-002: design for construction	2026-10-03	AC




TOP VIEW

Scale 1:20; looking down (along -Z)





FRONT VIEW

Scale 1:20; looking at the front (along +Y)



RIGHT VIEW

Scale 1:20; looking at the right side (along -X)



ISOMETRIC VIEW

Not to scale; grab left (closed), scraper head right (arms open); seen from the front right and above, about 30 deg elevation

MAIN DIMENSIONS AND INTERFACES (MM)

- Grab shells R 230 x 340 wide; closed span 468; 28.3 L
- Hinge pin 30; tie rods 30 x 10 at 420 centres; head pins at x +/- 120
- Head to crosshead stroke 142; open 50 deg, lips 352 apart
- Closing line: guide tube, crosshead sheave, back up to the shear link (2:1)
- Shear link pin about 1.9 mm, releases 1.20 to 1.47 kN (break-tested)
- Scraper toes at 590 radius, 15 beyond a 1.0 m ring's outer face
- Arms fold to 364 radius when the pole is lifted 300 on the sleeve
- Centralizer skids at 440 radius, 700 above the toes
- Foot plate 250 dia; sump 330 below the toe line
- Pole 42.4 x 2.6 in 2 m sections, 36 spigot and M12 cross bolt
- Third-angle; front view from -Y

SINKGRAB

github.com/BoujeeEnjinia1701/sinkgrab

Clamshell grab and under-curb scraper: general arrangement

DRAWING NO. SKG-DWG-002			REV P2	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-10-03		DRAWN Amish Chadha
MATERIAL / NOTES Steel plate and section, wear-resistant lips and toes; bought sheave and pins per bom/bom.csv. PRELIMINARY, NOT FOR FABRICATION					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com				Generated from cad/src; do not edit by hand	