

SNAPFRAME · DESIGN PRECIS

SnapFrame design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	SNF-PRC-001	Version	0.5
Status	Draft	Date	2026-09-26
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/snapframe		
Source	docs/02-concept.md @ b66b469		

REVISION HISTORY


Version	Date	Author	Change
0.5	2026-09-26	Amish Chadha	Budget approved by Amish (\$445, SNF-DDR-002); cost figure restated against it
0.4	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.3	2026-09-25	Amish Chadha	Apply SNF-DDR-001 (1 in rafters, frame kit budget, decided design choices); numbers from SNF-CAL-001; parametric model and SNF-DWG-001
0.2	2026-09-25	Amish Chadha	Populate to TRL 2 (architecture, sizes, first-order numbers, design choices, safety, media)
0.1	2026-09-24	Amish Chadha	Initial scaffold

SnapFrame design precis

SnapFrame is a gable-roof shelter frame of straight EMT conduit joined by printed nodes: 1 in EMT rafters and ridge tubes, and 3/4 in EMT posts and eave tubes. Each tube end carries a spring button that snaps into a hole in the node socket, so two adults can put the frame up by hand. The reference size M covers 4.0 x 4.0 m (16 m²) with a 2.6 m ridge and takes two standard 4 x 6 m relief tarpaulins from agency stock as its skin. The TRL 3 calculation note SNF-CAL-001 v0.3 puts the frame kit at about 42.0 kg and \$443 (within the \$445 budget) and rates the frame at about 19.7 m/s (71 km/h, 44 mph), just short of the 20 m/s target, with the 3/4 in posts governing.

SnapFrame

CONCEPT, NOT FOR FABRICATION



Grey: ground patch, 1.75 m person for scale

Figure 1. SnapFrame size M with a 1.75 m person for scale. The tarpaulin skin is shown on the rear bay only, so the frame, nodes and bracing stay visible. Generated from the parametric model `cad/src/model.py`.

■ How it works

- 1. Unpack.** The frame kit arrives as a strapped bundle of 18 straight tubes (four types, color-coded at the ends) and a bag with 15 nodes (three families, four printed variants), 10 brace cables, 8 screw anchors, 2 guy lines, buttons and hitch pins. Two tarpaulins come from agency stock.

2. **Anchor the feet.** Six foot nodes are laid out with a knotted layout cord (4.0 x 4.0 m, diagonals equal). A screw anchor is turned in by hand just outboard of each foot, using a spare tube through its eye as a lever, and the foot plate's open slot is slid onto the anchor shaft under the eye.
3. **Build the frames.** Each of the three gable frames is two posts, two rafters, two eave nodes and one ridge node. The frame is assembled flat on the ground, then walked up and its posts dropped into the foot sockets. Every joint closes with a click as the spring button finds its hole; hitch pins go in at the feet and the eave post sockets.
4. **Tie the frames together.** Ridge and eave tubes connect the three frames. Brace cables with hand tensioners go into the rear gable, one bay of each side wall and one diagonal per bay in each roof plane, and are pulled snug. Guy lines run from the two end ridge nodes to anchors 1.5 m beyond each gable.
5. **Skin.** One tarpaulin goes over the ridge as the roof; the second closes both side walls and the rear gable. The front gable stays open (R7, awaiting Amish). The blank socket on each corner eave node takes a push-in cap. Tarpaulins are tied through their eyelets to the tubes, never to the nodes.
6. **Strike and reuse.** Pressing each button releases its joint. Tubes and nodes go back in the bundle and bag, or the frame stays and carries better cladding later.

■ Main components

Table 1. Main components. Numbers match `bom/bom.csv` , Figure 2 and drawing SNF-DWG-001.

#	Component	Choice	Notes
1	Posts (6)	3/4 in EMT, 1.650 m	One 3.05 m (10 ft) stick each
2	Rafters (6)	1 in EMT, 2.064 m	SNF-DDR-001 D2; second socket bore on eave and ridge nodes
3	Ridge tubes (2)	1 in EMT, 1.910 m	SNF-DDR-002 D8 (were 3/4 in and governed the wind rating)
4	Eave tubes (4)	3/4 in EMT, 1.910 m	Same length as item 3, smaller tube; different end color for the guide
5	Foot nodes (6)	Printed, one socket, 170 x 170 x 12 mm plate with an open anchor slot	About 422 g each
6	Eave nodes (6)	Printed, four sockets plus a cable tab, one variant	At the corners the socket past the gable stays blank and capped (SNF-DDR-002 D9); about 271 g
7	Ridge nodes (3)	Printed, three or four sockets, all 30.1 mm bore	End nodes carry a guy tab; about 262 to 283 g
8	Brace cables (10)	4 mm galvanized wire rope, loop ends, hand cam tensioner	31.1 m node to node
9	Screw ground anchors (8)	380 mm galvanized screw anchor with eye	Six at the feet, two for guys
10	Guy lines (2)	6 mm polyester rope with slide tensioner	From end ridge nodes
11	Skin	Two 4 x 6 m reinforced polyethylene tarpaulins	Agency stock, outside the kit budget (SNF-DDR-001 D1)
12	Snap buttons, hitch pins and caps	36 spring buttons (one per tube end), 12 hitch pins on lanyards, 4 socket caps	Hitch pins at the 12 tension joints (SNF-DDR-001 D4)
13	Bundle straps and bag	Two cam straps for the tube bundle; one duffel bag	

Node concept

A node is a spherical core (84 mm diameter) with one socket per member. Each socket is 110 mm long from the node center; the tube end stops 45 mm from the center, so it engages 65 mm. The bore is the tube outside diameter plus 0.6 mm (24.0 mm for 3/4 in, 30.1 mm for 1 in) and the socket wall is 5 mm. One eave node serves all six eave positions; it is symmetric about its own frame line, so it is not handed, and at the corners its outward socket stays empty under a cap. A 6 mm spring button hole sits 25 mm from the tube end; at the feet and eave post sockets an 8 mm hitch pin hole sits 50 mm from the tube end. Socket axes are computed from the node positions, so a new width, length or pitch produces a new set of printable nodes. The prototype prints the nodes, and the printed node is intended to become a pattern for sand-cast aluminum later (SNF-DDR-001 D3); castability is not checked at TRL 3.

■ Sizes

Table 2. Size family generated from the same parameters (SNF-DDR-001 D6). The model exports the node set of every size.

Size	Floor	Bays	Eave and ridge	People at 3.5 m ² each	Members	Nodes
S	3.0 x 3.0 m (9 m ²)	2 x 1.5 m	1.8 m, 2.4 m	2	18	15 (new angles)
M (reference)	4.0 x 4.0 m (16 m ²)	2 x 2.0 m	1.8 m, 2.6 m	4	18	15
L	4.0 x 6.0 m (24 m ²)	3 x 2.0 m	1.8 m, 2.6 m	6	25	20 (same types as M)

■ Key numbers

All values are from SNF-CAL-001, which lists its assumptions. They are calculations on paper, not measurements.

Table 3. Geometry, mass, cost and wind, size M.

Quantity	Value	Requirement
Floor area	16.0 m ²	R1 met
Headroom 2.0 m or more	73 % of floor	R2 met
Tube length in the kit	33.7 m (54.9 m bought, 39 % offcut)	
Frame kit mass	42.0 kg (93 lb); 51.1 kg with tarpaulins	R11 not met (1.1 kg over)
Packages	Tube bundle 28.6 kg, 0.030 m ³ ; bag 22.5 kg with tarpaulins	R5 not met
Erection time	About 46 min for two adults (estimate)	R4 not verifiable at TRL 3
Skin area	51.4 m ² for full enclosure; 42.6 m ² with one gable open	R7 not met (48 m ² available)
Frame kit cost	About \$443	R10 not met (10.8 % over)
Dynamic pressure at 20 m/s	245 Pa	
Rafter (1 in) at 20 m/s	142 N·m, 166 MPa, factor 1.66	Meets 1.5
Ridge tube (1 in) at 20 m/s	106 N·m, 124 MPa, factor 2.22	Meets 1.5 (1.18 with 3/4 in)
Post (3/4 in) at 20 m/s	86 N·m, 188 MPa, factor 1.46	R6 not met
Wind rating	19.7 m/s (71 km/h, 44 mph); 14.7 m/s with the open gable facing the wind	R6 not met (posts govern)
Worst foot anchor uplift	1.28 kN at a rear corner, before pretension	R8 at risk (1.0 kN target)
Snow	Not rated; 0.5 kPa would put 416 MPa in a 1 in rafter	Out of scope

The TRL 2 estimates (factor 1.70 for posts, 1.26 for 3/4 in rafters, about 18 m/s) spread half of each panel uniformly over the frames. SNF-CAL-001 uses 45° tributary lines, which peak at midspan and give higher moments. On that basis, a 3/4 in rafter would reach only 0.89.

SnapFrame: exploded view (skin, item 11, not shown)

CONCEPT, NOT FOR FABRICATION

- 1 EMT post, 3/4 in, 1.65 m
- 2 EMT rafter, 1 in, 2.06 m
- 3 EMT ridge tube, 1 in, 1.91 m
- 4 EMT eave tube, 3/4 in, 1.91 m
- 5 Foot node with anchor slot
- 6 Eave node
- 7 Ridge node
- 8 Brace cable with hand tensioner
- 9 Screw ground anchor
- 10 Guy line




Figure 2. Exploded view with BOM numbers. The skin (item 11) is left out so the frame parts stay visible; items 12 and 13 are not modeled.

■ Design choices

Decided by Amish on 2026-09-25 (SNF-DDR-001):

- **Tube size (D2).** 1 in EMT rafters, with the wind rating stated on the kit.
- **Budget scope (D1).** The budget covers the frame kit; Amish set it at \$445 on 2026-09-26 to cover the priced BOM (SNF-DDR-002). Tarpaulins come from agency stock and are costed separately.
- **Node process (D3).** Print for the first prototype, design every node to be castable from the printed pattern.
- **Joint locking (D4).** Spring buttons at every tube end, hitch pins at the 12 tension joints.
- **Frame form (D5).** Gable roof with pinned nodes and cable bracing, not a dome, barrel vault or rigid nodes.
- **Sizes (D6)** S, M and L, with M as the reference, and **scope (D7)** without snow or cyclone rating in the first release.

Decided by Amish on 2026-09-25, going with the recommendations (SNF-DDR-002):

- **Ridge tubes (D8).** 1 in EMT ridge tubes as well, which lifts the rating from 17.8 to 19.7 m/s. Whether the posts also move to 1 in (20.3 m/s, about \$30 more) waits for a frame analysis.
- **One eave node (D9).** The four-socket eave node is used at the corners with one blank, capped socket, so there are no handed nodes and R12 is met.
- **Wind rating on the kit (D2 with D8).** Until R6 is met the kit label states 19.7 m/s (71 km/h) and about 14.7 m/s with wind into the open gable.

Still proposed, awaiting Amish: tube offcuts (accept 39 %, shorten posts to 1.50 m, or buy 6 m metric stock, to decide once the first region's tube source is known), the first co-design partner and region, how to treat the open front gable (R7), how to close the cost gap (R10), the package and carry mass (R5, R11), and the node polymer and anchor target (R9, R8).

■ Safety

Safety: SnapFrame is an emergency shelter frame, not a storm refuge. By calculation (SNF-CAL-001) it stays elastic with a factor of 1.5 only up to gusts of about 19.7 m/s (71 km/h, 44 mph), and about 14.7 m/s (53 km/h) when wind blows into the open gable. Above that, or when a storm warning is issued, occupants should drop the skin, leave the shelter and follow local evacuation guidance. A collapsing steel frame can injure people inside.

Safety: The frame is not rated for snow. Snow or ponding water on the roof can overload the rafters within hours. Clear the roof, or leave the shelter, whenever snow or standing water collects.

Safety: Polyethylene tarpaulins burn quickly and drip. Keep cooking fires, candles, kerosene lamps and stoves outside the shelter or behind a non-combustible screen, keep at least 2 m between shelters where the site allows, and keep the doorway clear. A fire-retardant tarpaulin option is an open requirement (R13).

- **Erection.** Walking a frame up takes two people. Keep hands clear of sockets as tubes drop in (pinch points), and never erect or strike the frame in strong wind, when the tarpaulin acts as a sail.
- **Tube ends.** Cut EMT ends are sharp. Every tube is deburred during kit preparation, and ends sit inside sockets once assembled.
- **Guy lines and anchors.** Guy lines are a trip hazard at night; mark them with reflective tape. Screw anchors must be clear of buried cables and pipes.
- **Electrical.** The frame is conductive steel. Any lighting inside must be low-voltage DC (for example solar lanterns); mains cables must not be run on or near the frame.
- **Lightning.** A steel frame gives no reliable lightning protection. Leave it during thunderstorms where a solid building is available.

■ Open questions

- R6: with 1 in ridge tubes the 3/4 in posts (factor 1.46) still fall short at 20 m/s. A frame analysis with pinned nodes and tension-only cables, including post buckling, cable slack and sway, comes before the decision on 1 in posts (SNF-DDR-002 D8).
- R5 and R11: the tube bundle (28.6 kg) and the complete kit with tarpaulins (51.1 kg) are over their limits; options are in `docs/REVIEW.md`.
- Confirm EMT yield strength and dimensions from supplier data for the first region, and whether metric thin-wall tube of about 25 mm is stocked where EMT is not.
- Node polymer: which printable polymer keeps its strength at 70 °C surface temperature under UV for two years (R9).
- Anchor holding capacity in sand, clay and gravel, and the rating of the hand cable tensioners (R8).
- A cutting and folding plan that closes both gables, or the case for a third tarpaulin (R7).
- Fire-retardant tarpaulin sources and cost (R13).

- Picture-only erection guide: test with users who have not seen the kit.
- Validate floor area, headroom, erection time, wind exposure and price with users through a local partner.

Drawings and media: [general arrangement SNF-DWG-001](#), [blueprint sheet](#), [interactive 3D model](#).