

STEAMROOT · PROBLEM STATEMENT

SteamRoot problem statement

Open Hardware Portfolio · amishchadha.com

DOCUMENT CONTROL

Document ID	STR-PRB-001	Version	0.3
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/steamroot		
Source	docs/01-problem.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-09-25	Amish Chadha	Record Amish's 2026-09-25 decisions on first users, first jurisdiction and budget; regulatory ruling marked as an open prerequisite
0.2	2026-09-24	Amish Chadha	Populate to TRL 2 (users, context, constraints, out of scope, prior work, safety)
0.1	2026-09-24	Amish Chadha	Initial scaffold

SteamRoot problem statement

Steaming soil kills weed seeds and soil-borne pathogens without herbicides or fumigants, but the equipment that does it is sized, priced and fueled for large greenhouse operations, so small organic growers who need it most rarely have access to it.

■ The problem

Organic and low-input growers fight weeds and soil-borne disease (damping-off, Fusarium, Pythium, Rhizoctonia, root-knot nematodes) with hand weeding, cultivation, rotation and, where allowed, fumigants. Hand weeding is often the largest labor cost on a market garden. Chemical soil fumigants are restricted or banned for organic growers, and methyl bromide has been phased out for most uses under the Montreal Protocol.

Heating soil to about 70 °C (158 °F) for 20 to 30 minutes kills most weed seeds and pathogens while sparing some of the heat-tolerant beneficial organisms. Steam is the traditional way to deliver that heat because condensing steam releases a large amount of energy (about 2.26 MJ per kilogram) right where it condenses. The barriers are equipment and energy:

- Commercial soil steamers are built around diesel, oil or gas boilers sized for greenhouse ranges and nurseries. They are costly to buy and to fuel.
- Many small growers have surplus woody biomass (prunings, hedgerow wood, pallets) but no safe way to turn it into steam.
- Improvised rigs built from pressure cookers, water heaters or sealed tanks are dangerous. A sealed vessel with a fire under it can fail violently.
- Energy per square meter is high, so an inefficient boiler makes the method too slow and too fuel-hungry to be practical.

■ Users and context

User	Need	Context
Small organic farm or market garden	Clear weed seed bank and disease from high-value beds without herbicides	Outdoor beds and polytunnels, 0.1 to 2 ha, beds about 0.75 to 1.2 m wide
Nursery or seedling grower	Pasteurize potting media and propagation beds	Sheds and greenhouses; generator must stay outside
Community garden or farm cooperative	A shared, towable machine that several growers can use	Shared equipment, varied operator experience
Extension educator or researcher	An open, documented reference design to demonstrate and study	Field days, trials, university farms
Open hardware community	A buildable, inspectable low-pressure steam design	Farm workshops, makerspaces

■ Constraints

- Garage-buildable prototype within \$1,800 USD (raised from \$1,500 by Amish on 2026-09-25 to allow contingency), using stock steel, stainless tube and off-the-shelf safety parts.
- Near-atmospheric operation: open-vented, never sealed, with a normal working pressure well below the thresholds that bring a boiler under pressure vessel and boiler codes. Thresholds, exemptions and registration rules differ by country, state and province and must be confirmed with the local authority before any build.
- Fired with locally available dry woody biomass; no diesel or propane burner.
- Towable by a small tractor, utility vehicle or car with a hitch; loaded mass about 500 kg or less.
- Operable by one trained adult, with a second person nearby during steaming.
- Outdoor operation only for the fire. Steam may be piped into a greenhouse or polytunnel; the firebox and chimney may not.

Safety: This project handles open fire, flue gas containing carbon monoxide, and steam that causes severe burns. It is a concept, not a buildable or approved design. Steam generators are regulated equipment in many jurisdictions even at low pressure.

■ Out of scope

- Any pressurized boiler or sealed vessel. SteamRoot will not operate as a pressure boiler under any configuration.
- Deep steaming beyond 15 cm and field-scale broadacre treatment.
- Negative-pressure (buried pipe) steaming systems.
- Automatic fire control, remote operation or unattended running.
- Chemical additives mixed with steam.

■ Prior work

Steam soil disinfestation is established practice. Greenhouse growers have steamed soil since the late nineteenth century, and it remains common in greenhouse horticulture and nurseries. The main methods are:

- **Sheet steaming:** steam is released under a heavy sheet laid on the soil. Simple, but slow and hard to control at depth.
- **Hood steaming:** a rigid open-bottom hood is pressed onto the bed and moved in steps. Better contact and control than sheets. SteamRoot uses this method.
- **Negative-pressure steaming:** steam is drawn down through the soil by suction through buried perforated pipes. Reaches deeper, but needs a permanent installation.
- **Band steaming:** research machines steam only a narrow band where the crop row will be, cutting energy per hectare.

Soil solarization (clear plastic in hot weather) and anaerobic soil disinfestation are lower-energy alternatives, but they depend on climate and take weeks. Steam works in hours and in any season. Published studies on steaming consistently report energy use as the main limit on adoption, which is why SteamRoot focuses on a biomass fire and a flue-gas economizer. Specific sources are not yet cited; they were not checked in the TRL 3 session and remain flagged in `docs/REVIEW.md`.

■ Decisions and open questions

- First users: one market garden and one nursery. Decided by Amish, 2026-09-25 (STR-DDR-001). The named partners are not chosen: Proposed, awaiting Amish.
- First jurisdiction for the regulatory check: Amish's home jurisdiction. Decided by Amish, 2026-09-25. Which jurisdiction and which authority to ask: Proposed, awaiting Amish.
- **Open prerequisite:** a written ruling from the local boiler authority on whether an open-vented, fired monotube coil is exempt from boiler and pressure vessel rules. Amish approved getting it before TRL 3 detail work. It has not been obtained, so TRL 3 was limited to paper calculations and preliminary drawings.