



CONCEPT, NOT FOR FABRICATION

StepClimber · [github.com/BoujeeEnjinia1701/stepclimber](https://github.com/BoujeeEnjinia1701/stepclimber)




TOP VIEW

Scale 1:20; looking down (along -Z)




FRONT VIEW, CLIMBING POSE

Tilted 30 deg about the shaft; scale 1:20; looking at the front (along +Y)




FRONT VIEW

Scale 1:20; looking at the front (along +Y)



RIGHT VIEW

Scale 1:20; looking at the right side (along -X)



ISOMETRIC VIEW

Not to scale; seen from the front right and above, about 30 deg elevation

KEY DIMENSIONS AND INTERFACES (MM)

Overall width 569 (wheel outer faces); upright height 1451

Clusters: arm 150, wheel dia 200, spacing 259.8

Shaft 25 dia (4140) at 175.0 above floor; bearings 336 apart, inside the rails

Cluster mid-planes 524 apart; rails 400 apart, 28 tube

Drive 06B 10T:35T then 08B 10T:20T (7:1)

Countershaft 143.9 and gearmotor 289 up the frame, 15 back

Chains 38 links 08B, 54 links 06B; closed chain case

Case radius 53.9 on the shaft line (limit 54.2, R15 met)

Grip 1260 from the shaft along the frame; toe plate 240 x 380

Pack 75 x 180 x 170 on uprights, centre 800 above shaft

Width 588 over the wheel end screws; truck 34.2 kg (SCM-CAL-001 v0.5)

Climbing tilt 30 deg back; tilt window +/-3 deg (first trials); 60 kg rated stair load

STEPCLIMBER

[github.com/BoujeeEnjinia1701/stepclimber](https://github.com/BoujeeEnjinia1701/stepclimber)

General arrangement

DRAWING NO.

SCM-DWG-001

REV

P5

SHEET

1 of 1

SIZE

ANSI B

SCALE

1:20

UNITS

mm

PROJECTION



DATE

2026-10-02

DRAWN

Amish Chadha

MATERIAL / NOTES

Steel frame and spiders; solid rubber wheels; see bom/bom.csv. Figures from SCM-CAL-001 v0.5

Licensed CERN-OHL-S-2.0 · Design Molecule Lab · [designmolecule.com](https://designmolecule.com)

Generated from cad/src; do not edit by hand