

REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-01	AC



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Ground rails: two lengths of 828 mm.
Mark the post centre 67.5 mm from the front end (760 mm from the rear).
Prop holes 10.5 mm through the side, mid-height, measured back from the post centre (tilt and distance in mm):
10 deg 113, 15 deg 151, 20 deg 195,
25 deg 245, 30 deg 309, 35 deg 396.
Cross rails: two lengths of 1,074 mm, between the ground rails at the front and rear ends; four galvanised corner brackets.
Drill a 12 mm hole near each end of each ground rail for a ground stake (or put ballast on the cross rails).
Check: the frame is square (diagonals equal within 3 mm).



TOP VIEW

Scale 1:5; looking down (along -Z)



FRONT VIEW

Scale 1:5; looking at the front (along +Y)



RIGHT VIEW

Scale 1:5; looking at the right side (along -X)

STILLSTACK

github.com/BoujeeEnjinia1701/stillstack

StillStack ground rail (make 2) and cross rails: making sketch

DRAWING NO. SSK-DWG-116			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:5	UNITS mm	PROJECTION 	DATE 2026-10-01		DRAWN Amish Chadha
MATERIAL / NOTES 45 x 45 mm treated timber, outdoor grade (not in the water path)					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com					Generated from cad/src; do not edit by hand