
PRELIMINARY, NOT FOR FABRICATION


StillStack · github.com/BoujeeEnjinia1701/stillstack

REV	DESCRIPTION	DATE	BY
P1	Preliminary general arrangement (TRL 3)	2026-09-25	AC
P2	Rail and liner materials, stagnation cover (DDR-002)	2026-09-25	AC
P3	Constructable design: base ring, trim, tongues, stand (DDR-003)	2026-10-01	AC
P4	High-edge lip tabs, wick clips, PPS rails (SSK-DEC-001)	2026-10-02	AC
P5	Stage 3 rails PPS (D-01); bolt lengths (D-02); kit 1.9 model	2026-10-24	AC
P6	Wick clips 5052 aluminium (D-08)	2026-10-25	AC




TOP VIEW

Scale 1:20; looking down (along -Z)




FRONT VIEW (SIDE ELEVATION)

Scale 1:20; looking at the front (along +Y)




RIGHT VIEW (FROM LOW EDGE)

Scale 1:20; looking at the right side (along -X)




DETAIL A: STACK SECTION AT A RIB

Scale 2:1, looking up the slope



ISOMETRIC VIEW

Not to scale; seen from the front right and above, about 30 deg elevation



DETAIL B: LOW EDGE, DISTILLATE AND BRINE

Scale 1:2, untilted; cut on a rib line

KEY DIMENSIONS AND FIGURES (SSK-CAL-001)

Aperture 1.0 x 1.0 m; tilt 20 deg, stand 10 to 35 deg
4 stages; 6 mm vapor gap; 1 mm wicks; 0.5 mm plates
Ribs: 4 per gap at 194 mm pitch; sag 0.5 mm
Dry breaks 10 mm each side of ribs and rails
Air gap 25 mm; 6 mm twin-wall PC glazing
Frame 12 mm plywood + 25 mm stone wool; 1,074 mm square outside
Front pivot bolts; props pinned at 6 holes
Design day: about 10.3 L/day, GOR 1.22 to 1.29
Dry stagnation: stage 1 about 138 C (142 C calm)
Rails PPS in stages 1 to 3; cover (BOM 14) not shown
Panel about 18.8 kg dry, 22.8 kg wet
Fasteners in the model and STEP; see SSK-BLD-001

STILLSTACK

github.com/BoujeeEnjinia1701/stillstack

General arrangement

DRAWING NO.	REV	SHEET	SIZE
SSK-DWG-002	P6	1 of 1	ANSI B

SCALE	UNITS	PROJECTION	DATE	DRAWN
1:20	mm		2026-10-25	Amish Chadha

MATERIAL / NOTES

See bom/bom.csv. Plates 0.5 mm aluminum; rails PPS (stages 1 to 3) and PC (stage 4); wick clips 5052 aluminium; ribs silicone; frame plywood, stone wool

Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com

Generated from cad/src; do not edit by hand